

University of Stuttgart
Institute for Computational Physics

Freie Universität



Berlin

SimTech

Simulating Stochastic Processes with Variational Quantum Circuits

Daniel
Fink


Master Thesis

-

Presentation

February 14th, 2022

- University of Stuttgart
 - Prof. Dr. Christian Holm
- Free University of Berlin
 - Prof. Dr. Jens Eisert
 - Dr. Nora Tischler
 - Dr. Ryan Sweke
 - M.Sc. Paul Fährmann



University of Stuttgart
Institute for Computational Physics

Freie Universität



Berlin

Can we predict the future based on past observations?



Can we predict the future based on past observations?




Simulations → show possible futures

Assume linear trend $f(t)$


Add some noise e_t

→ e_t is a stochastic process


Stock Price Trend



Assume data drawn
by a stochastic process



Stock Price Trend







Classical Models \leq Quantum Models

How to get a quantum model?


- Classical **description of the process** \rightarrow q -simulator
 - Binder et al., 10.1103/PhysRevLett.120.240502



- Classical **description of the process** \rightarrow q -simulator
 - Binder et al., 10.1103/PhysRevLett.120.240502




- Data from the process \rightarrow **classical** discovery algorithm
 - Yang et al., arXiv:2105.14434



Goal


Develop a **quantum** learning algorithm for predictive models,
which uses **only data** as input.





- Stochastic Processes
- ϵ -machine
- Quantum Circuits
- q -simulator
- Quantum Learning Algorithm
- Results
- Conclusion





Stochastic Processes


















- Simulating = sampling trajectories
- Trajectory is governed by $P(\vec{X}|\hat{X})$





ϵ -machine















Classical Topological Complexity: $d_c = \log_2 N$

Period- N Uniform Renewal Process





Period = 2

A dark blue circle is centered on a medium blue background. Inside the circle, the words "Quantum" and "Circuits" are written in white, stacked vertically.

Quantum Circuits







q -simulator

Memory Register


Auxiliary Registers






Quantum Topological Complexity: $d_q = \text{\#qubits}$

In general:




For some processes:




Thompson et al.,
10.1103/PhysRevX.8.031013

In general:




Thompson et al.,
10.1103/PhysRevX.8.031013

For some processes:




Approximate models:




Q-Models can have better accuracy
Yang et al., arXiv:2105.14434

In general:




Thompson et al.,
10.1103/PhysRevX.8.031013

For some processes:




Approximate models:




Q-Models can have better accuracy
Yang et al., arXiv:2105.14434


How to get a **quantum representation** of a quantum model?




Variational Quantum Circuits


Machine Learning Model










$$\text{Approximate } P \rightarrow |P - \hat{P}_\theta| < \delta$$



Quantum Learning Algorithm









Kullback-Leibler divergence:
(KL)

$$D_{KL}(P, \hat{P}) = \sum_x P(x) \log_2 \frac{P(x)}{\hat{P}(x)}$$



Kullback-Leibler divergence:
(KL)

$$D_{KL}(P, \hat{P}) = \sum_x P(x) \log_2 \frac{P(x)}{\hat{P}(x)}$$




mean over time steps

average over pasts

Kullback-Leibler divergence:
(KL)

$$D_{KL}(P, \hat{P}) = \sum_x P(x) \log_2 \frac{P(x)}{\hat{P}(x)}$$




mean over time steps

average over pasts


Total Variation Distance:
(TV)

$$D_{TV}(P, \hat{P}) = \frac{1}{2} \sum_x |P(x) - \hat{P}(x)|$$



Kullback-Leibler divergence:
(KL)

$$D_{KL}(P, \hat{P}) = \sum_x P(x) \log_2 \frac{P(x)}{\hat{P}(x)}$$




mean over time steps

average over pasts


Total Variation Distance:
(TV)

$$D_{TV}(P, \hat{P}) = \frac{1}{2} \sum_x |P(x) - \hat{P}(x)|$$



sum up time steps

sum up pasts



Ideally, use validation metric:

$$D_{KL}(P, \hat{P}) = \sum_x P(x) \log_2 \frac{P(x)}{\hat{P}(x)}$$



Ideally, use validation metric:

$$D_{KL}(P, \hat{P}) = \sum_x P(x) \log_2 \frac{P(x)}{\hat{P}(x)}$$

unknown



inefficient

Maximum Mean Discrepancy:
(MMD)




$$\text{MMD}[P, \hat{P}] = 0 \iff P = \hat{P}$$


Maximum Mean Discrepancy:
(MMD)



$$\text{MMD}[P, \hat{P}] = 0 \Leftrightarrow P = \hat{P}$$




$$C(\boldsymbol{\theta}) = \sum_{\tilde{x}} w_{\tilde{x}} \cdot \text{MMD}^2[\mathcal{P}, \hat{\mathcal{P}}_{\boldsymbol{\theta}} | \tilde{x}]$$




$$C(\theta) = \sum_{\tilde{x}} w_{\tilde{x}} \cdot \text{MMD}^2[P, \hat{P}_{\theta}|\tilde{x}]$$



$$C(\theta) = \sum_{\tilde{x}} w_{\tilde{x}} \cdot \text{MMD}^2[P, \hat{P}_{\theta}|\tilde{x}] + R_{\tilde{x}}(\theta)$$





Regularization = penalizes models with a large set of memory states





Results







$$E(\tilde{x}, \theta)$$

\uparrow initial state for $\tilde{x} = 0$
 \uparrow initial state for $\tilde{x} = 1$

$+$ memory states for $x_i = 0$
 $+$ memory states for $x_i = 1$







$$E(\tilde{x}, \theta)$$

\uparrow initial state for $\tilde{x} = 0$
 \uparrow initial state for $\tilde{x} = 1$


$+$ memory states for $x_i = 0$
 $+$ memory states for $x_i = 1$





- Developed a hybrid quantum learning algorithm for predictive models
- Learning algorithm is memory efficient
- Extended MMD for predictive models → Decrease KL and TV
- Regularization → small set of memory states
- Learned models show constantly good simulation performance


- Apply the algorithm to the period-3 uniform renewal process
- Consider processes with outcomes $\subseteq \mathbb{N}$




Thank you
very much!

Questions
are highly
welcome.


ϵ -machine



HMM




unifilar




Analytical solution:


$$|0\rangle \xrightarrow{X} |1\rangle = |\sigma_0\rangle$$

$$|0\rangle \xrightarrow{H} |+\rangle = |\sigma_1\rangle$$



Ansatz:





Kullback-Leibler divergence:
(KL)

$$D_{KL}(P, \hat{P}) = \sum_x P(x) \log_2 \frac{P(x)}{\hat{P}(x)}$$

$$D_{KL}(L, P, \hat{P}) = \sum_{\mathbf{x}_{1:L}} \frac{1}{L} \sum_{\tilde{\mathbf{x}}} P(\tilde{\mathbf{x}}) \cdot P(\mathbf{x}_{1:L} | \tilde{\mathbf{x}}) \log_2 \frac{P(\mathbf{x}_{1:L} | \tilde{\mathbf{x}})}{\hat{P}(\mathbf{x}_{1:L} | \tilde{\mathbf{x}})}$$

Total Variation Distance:
(TV)

$$D_{TV}(P, \hat{P}) = \frac{1}{2} \sum_x |P(x) - \hat{P}(x)|$$

$$D_{TV}(L, P, \hat{P}) = \frac{1}{2} \sum_{\mathbf{x}_{1:L}} \sum_{\tilde{\mathbf{x}}} |P(\mathbf{x}_{1:L} | \tilde{\mathbf{x}}) - \hat{P}(\mathbf{x}_{1:L} | \tilde{\mathbf{x}})|$$


Kernel






$$MMD^2[F, P, \hat{P}] = \mathbb{E}_{x \sim P, x' \sim P}[k(x, x')] - 2 \cdot \mathbb{E}_{x \sim P, y' \sim \hat{P}}[k(x, y)] + \mathbb{E}_{y \sim \hat{P}, y' \sim \hat{P}}[k(y, y')]$$


$$\frac{\partial MMD^2[P, \hat{P}_{\theta}]}{\partial \theta_i} = \sum_{j=1}^m \alpha'_{i,j}(\theta_i) \left[\mathbb{E}_{\substack{x \sim \hat{P}_{\theta_{i,j}^+} \\ y \sim \hat{P}_{\theta}}} [k(x, y)] - \mathbb{E}_{\substack{x \sim \hat{P}_{\theta_{i,j}^-} \\ y \sim \hat{P}_{\theta}}} [k(x, y)] - \mathbb{E}_{\substack{x \sim \hat{P}_{\theta_{i,j}^+} \\ y \sim P}} [k(x, y)] + \mathbb{E}_{\substack{x \sim \hat{P}_{\theta_{i,j}^-} \\ y \sim P}} [k(x, y)] \right]$$

Matrix depending on the ansatz











$$f(\boldsymbol{\theta}) = \langle 0 | U(\boldsymbol{\theta})^\dagger \hat{O} U(\boldsymbol{\theta}) | 0 \rangle$$

$$\frac{\partial f(\boldsymbol{\theta})}{\partial \mu} = \frac{1}{2} \sum_{j=1}^m \alpha'_j(\mu) \left[f_j\left(\alpha_j(\mu), +\frac{\pi}{2}\right) - f_j\left(\alpha_j(\mu), -\frac{\pi}{2}\right) \right]$$





Thank you
very much!

Questions
are highly
welcome.