



Topical Meeting

Machine Learning

Overview:

Simulating Stochastic Processes with Quantum Devices

Part II

June 1st, 2022


Daniel Fink




Agenda



- Last time:
 - Simulation of stochastic processes
 - Why quantum computing is relevant there








Agenda



- Last time:
 - Simulation of stochastic processes
 - Why quantum computing is relevant there
- Today:
 - What is the connection to machine learning?






Agenda




- Part 1: Qubits
- Part 2: Quantum Circuits
- Part 3: Example
- Part 4: Parameterized Quantum Circuits (PQCs)
- Part 5: Issues and open questions

































$$|0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix} \in \mathbb{C}^2$$





$$|0\rangle = \begin{bmatrix} 1\\0 \end{bmatrix} \in \mathbb{C}^2 \qquad |1\rangle =$$

$$|1\rangle = \begin{bmatrix} 0 \\ 1 \end{bmatrix} \in \mathbb{C}^2$$





$$|0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix} \in \mathbb{C}^2$$

$$|1\rangle = \begin{bmatrix} 0 \\ 1 \end{bmatrix} \in \mathbb{C}^2$$

$$|2\rangle = |010\rangle$$





$$|0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix} \in \mathbb{C}^2 \qquad |1\rangle = \begin{bmatrix} 0 \\ 1 \end{bmatrix} \in \mathbb{C}^2$$

$$|2\rangle = |010\rangle = |0\rangle \otimes |1\rangle \otimes |0\rangle$$





$$|0\rangle = \begin{bmatrix} 1\\0 \end{bmatrix} \in \mathbb{C}^2$$
 $|1\rangle = \begin{bmatrix} 0\\1 \end{bmatrix} \in \mathbb{C}^2$

$$|2\rangle = |010\rangle = |0\rangle \otimes |1\rangle \otimes |0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix} \otimes \begin{bmatrix} 0 \\ 1 \end{bmatrix} \otimes \begin{bmatrix} 1 \\ 0 \end{bmatrix}$$





$$|0\rangle = \begin{bmatrix} 1\\0 \end{bmatrix} \in \mathbb{C}^2$$

$$|1\rangle = \begin{bmatrix} 0 \\ 1 \end{bmatrix} \in \mathbb{C}^2$$

$$|2\rangle = |010\rangle = |0\rangle \otimes |1\rangle \otimes |0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix} \otimes \begin{bmatrix} 0 \\ 1 \end{bmatrix} \otimes \begin{bmatrix} 1 \\ 0 \end{bmatrix} = \begin{bmatrix} 0 \\ 0 \\ 1 \\ 0 \\ 0 \\ 0 \end{bmatrix} \in \mathbb{C}^{8}$$





$$|0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix} \in \mathbb{C}^2$$

$$|1\rangle = \begin{bmatrix} 0 \\ 1 \end{bmatrix} \in \mathbb{C}^2$$

$$|2\rangle = |010\rangle = |0\rangle \otimes |1\rangle \otimes |0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix} \otimes \begin{bmatrix} 0 \\ 1 \end{bmatrix} \otimes \begin{bmatrix} 1 \\ 0 \end{bmatrix} = \begin{bmatrix} 0 \\ 0 \\ 0 \\ 0 \\ 0 \end{bmatrix} \in \mathbb{C}^8 = \mathbb{C}^{2^3}$$





nasis states

$$|0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix} \in \mathbb{C}^2$$

$$|1\rangle = \begin{bmatrix} 0 \\ 1 \end{bmatrix} \in \mathbb{C}^2$$

$$|2\rangle = |010\rangle = |0\rangle \otimes |1\rangle \otimes |0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix} \otimes \begin{bmatrix} 0 \\ 1 \\ 0 \end{bmatrix} \otimes \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \\ 0 \end{bmatrix} \in \mathbb{C}^8 = \mathbb{C}^{2^3}$$





Single-qubit state: $|\psi_1\rangle = \alpha |0\rangle + \beta |1\rangle$





Single-qubit state:
$$|\psi_1\rangle = \alpha |0\rangle + \beta |1\rangle = \begin{bmatrix} \alpha \\ \beta \end{bmatrix} \in \mathbb{C}^2$$





$$|\psi_1\rangle = \frac{\alpha}{|0\rangle} + \frac{\beta}{|1\rangle} = \begin{bmatrix} \alpha \\ \beta \end{bmatrix} \in \mathbb{C}^2$$

with
$$|\alpha|^2 + |\beta|^2 = 1$$





$$|\psi_1\rangle = \alpha|0\rangle + \beta|1\rangle = \begin{bmatrix} \alpha \\ \beta \end{bmatrix} \in \mathbb{C}^2$$

with
$$|\alpha|^2 + |\beta|^2 = 1$$

$$|\psi_n\rangle = \sum_{i=0}^{2^n-1} \alpha_i |i\rangle \in \mathbb{C}^{2^n}$$





$$|\psi_1\rangle = \alpha|0\rangle + \beta|1\rangle = \begin{bmatrix} \alpha \\ \beta \end{bmatrix} \in \mathbb{C}^2$$

with
$$|\alpha|^2 + |\beta|^2 = 1$$

$$|\psi_n\rangle = \sum_{i=0}^{2^n-1} \alpha_i |i\rangle \in \mathbb{C}^{2^n}$$

with
$$\sum_{i=0}^{2^n-1} |\alpha_i|^2 = 1$$







$$= \begin{bmatrix} x_0 \\ x_1 \\ x_2 \\ \vdots \\ x_{n-1} \end{bmatrix} \in \mathbb{R}^n$$





















$$= |x\rangle = x_0|0\rangle + \dots + x_{n-1}|n-1\rangle \in \mathbb{C}^{2^d}$$









$$= |x\rangle = x_0|0\rangle + \dots + x_{n-1}|n-1\rangle \in \mathbb{C}^{2^d}$$

O(d) qubits












$$= \begin{bmatrix} x_0 \\ x_1 \\ x_2 \\ \vdots \\ x_{n-1} \end{bmatrix} \in \mathbb{R}^n$$







$$= |x\rangle = x_0|0\rangle + \dots + x_{n-1}|n-1\rangle \in \mathbb{C}^{2^d}$$


O(d) qubits



Part 2:
Quantum
Circuits





















Mathematically:


Gate

 $\rightarrow U: \mathbb{C}^n \rightarrow \mathbb{C}^n$, unitary

$$\rightarrow U|\psi\rangle = |\psi'\rangle$$







Mathematically:

Gate

 $\rightarrow U: \mathbb{C}^n \rightarrow \mathbb{C}^n$, unitary

 $\rightarrow U|\psi\rangle = |\psi'\rangle$

Measurement $\rightarrow \hat{O}: \mathbb{C}^n \rightarrow \mathbb{C}^n$, Hermitian


 $\rightarrow \hat{O} |\psi\rangle \neq |\psi'\rangle$

instead

 $\rightarrow |\psi\rangle \stackrel{\hat{0}}{\rightarrow} |\phi\rangle$







Mathematically:

Output
$$\rightarrow \langle \hat{O} \rangle = \langle \psi | \hat{O} | \psi \rangle = \langle 0 | U^{\dagger} \hat{O} U | 0 \rangle$$





Hadamard gate:

$$H|0\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) = |+\rangle$$





Hadamard gate:

$$H|0\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) = |+\rangle$$

$$H|1\rangle = \frac{1}{\sqrt{2}}(|0\rangle - |1\rangle) = |-\rangle$$





Hadamard gate:

$$H|0\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) = |+\rangle$$

$$H|1\rangle = \frac{1}{\sqrt{2}}(|0\rangle - |1\rangle) = |-\rangle$$

create superposition





create superposition

Hadamard gate:

$$H|0\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) = |+\rangle$$

$$H|1\rangle = \frac{1}{\sqrt{2}}(|0\rangle - |1\rangle) = |-\rangle$$

CNOT:

$$CNOT|a,b\rangle = |a,a \oplus b\rangle$$



Important Gates



Hadamard gate:

$$H|0\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) = |+\rangle$$

$$H|1\rangle = \frac{1}{\sqrt{2}}(|0\rangle - |1\rangle) = |-\rangle$$

create superposition

CNOT:

$$CNOT|a,b\rangle = |a,a \oplus b\rangle$$

e.g.
$$CNOT|1,1\rangle = |1,1 \oplus 1\rangle = |1,0\rangle$$



Important Gates



Hadamard gate:

$$H|0\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) = |+\rangle$$

$$H|1\rangle = \frac{1}{\sqrt{2}}(|0\rangle - |1\rangle) = |-\rangle$$

create superposition

CNOT:

$$CNOT|a,b\rangle = |a,a \oplus b\rangle$$

"IF" operation

e.g.
$$CNOT|1,1\rangle = |1,1 \oplus 1\rangle = |1,0\rangle$$



Important Gates



Hadamard gate:

$$H|0\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) = |+\rangle$$

$$H|1\rangle = \frac{1}{\sqrt{2}}(|0\rangle - |1\rangle) = |-\rangle$$

create superposition

CNOT:

$$CNOT|a,b\rangle = |a,a \oplus b\rangle$$

"IF" operation

e.g.
$$CNOT|1,1\rangle = |1,1 \oplus 1\rangle = |1,0\rangle$$


$$(H \otimes I)CNOT|00\rangle = \frac{1}{\sqrt{2}}(|00\rangle + |11\rangle)$$


create entanglement

Part 3: Example














• Given training data set: $T = \{(x^p, c^p)\}_{p=1,...,N}$








• Given training data set: $T = \{(x^p, c^p)\}_{p=1,...,N}$

• Given new data point: $x' \in \mathbb{R}^n$








• Given training data set: $T = \{(x^p, c^p)\}_{p=1,...,N}$

• Given new data point: $x' \in \mathbb{R}^n$

Goal:

Find class c' of x'







1. Step: Construct $|\phi_0\rangle = \sum_p |p\rangle (|0\rangle |\psi_{x'}\rangle + |1\rangle |\psi_{x^p}\rangle) |c^p\rangle$





1. Step: Construct $|\phi_0\rangle = \sum_p |p\rangle (|0\rangle |\psi_{x'}\rangle + |1\rangle |\psi_{x^p}\rangle) |c^p\rangle$

 $|0\rangle$ —

 $|0\rangle$ —

 $|0\rangle$ —


 $|0\rangle$ —





marker

$$|\phi_0\rangle = \sum_{p} |p\rangle (|0\rangle |\psi_{x'}\rangle + |1\rangle |\psi_{x^p}\rangle) |c^p\rangle$$




$$|0\rangle$$
 —


$$|0\rangle$$
 —


$$|0\rangle$$
 —













$$|0\rangle$$
 —


$$|0\rangle$$
 —














$$|0\rangle$$
 –











$$(|0\rangle -)$$

$$(|0\rangle -$$





1. Step: Construct
$$|\phi_0\rangle = \sum_p |p\rangle (|0\rangle |\psi_{x'}\rangle + |1\rangle |\psi_{x^p}\rangle) |c^p\rangle$$

2. Step: Applying one gate and one partial measurement...






1. Step: Construct
$$|\phi_0\rangle=\sum_p|p\rangle(|0\rangle|\psi_{x'}\rangle+|1\rangle|\psi_{x^p}\rangle)|c^p\rangle$$
 class

- 2. Step: Applying one gate and one partial measurement...
- Measure class qubit $P(|c\rangle = 0) = \sum_{p|c^p=0} d(x', x^p)^{-1}$ 3. Step:





$$P(|c\rangle = 0) = \sum_{p|c^p=0} d(x', x^p)^{-1}$$







1. Step: Construct
$$|\phi_0\rangle=\sum_p|p\rangle(|0\rangle|\psi_{x'}\rangle+|1\rangle|\psi_{x^p}\rangle)|c^p\rangle$$

- 2. Step: Applying one gate and one partial measurement...
- 3. Step: Measure class qubit $P(|c\rangle = 0) = \sum_{p|c^p=0} d(x', x^p)^{-1}$
- 4. Step: Take *c* with higher probability





1. Step: Construct $|\phi_0\rangle = \sum_p |p\rangle (|0\rangle |\psi_{x'}\rangle + |1\rangle |\psi_{x^p}\rangle) |c^p\rangle$

2. Step: Applying one gate and one partial measurement...

3. Step: Measure class qubit

4. Step: Take *c* with higher probability







1. Step: Construct $|\phi_0\rangle = \sum_p |p\rangle (|0\rangle |\psi_{x'}\rangle + |1\rangle |\psi_{x^p}\rangle) |c^p\rangle$

2. Step: Applying one gate and one partial measurement...

 $(1) \quad \bigodot$

3. Step: Measure class qubit

O(1)

4. Step: Take *c* with higher probability





1. Step: Construct
$$|\phi_0\rangle = \sum_p |p\rangle (|0\rangle |\psi_{x'}\rangle + |1\rangle |\psi_{x^p}\rangle) |c^p\rangle$$
 $O(2^N)$

- 2. Step: Applying one gate and one partial measurement...
- 3. Step: Measure class qubit
- 4. Step: Take *c* with higher probability

 $(1) \quad \bigodot$



1. Generation QML Algorithms



- Promised exponential speed-up
- Need "Quantum Random Access Memory" (QRAM)

$$|\psi_x\rangle = \sum_{i=0}^{2^{n}-1} \frac{x_i}{|i\rangle}$$

- QRAM needs exponentially many steps
- No physical implementation so far



1. Generation QML Algorithms




- Promised exponential speed-up
- Need "Quantum Random Access Memory" (QRAM)

$$|\psi_x\rangle = \sum_{i=0}^{2^{n-1}} \frac{x_i}{|i\rangle}$$


- QRAM needs exponentially many steps
- No physical implementation so far
- → "Learn" the quantum states

$$\left|\tilde{\psi}_{x}\right\rangle = \sum_{i=0}^{2^{n}-1} \frac{\tilde{\chi}_{i}}{\left|i\right\rangle}$$
























$$f(\boldsymbol{\theta}) = \langle \psi(\boldsymbol{\theta}) | \hat{O} | \psi(\boldsymbol{\theta}) \rangle = \langle 0 | U(\boldsymbol{\theta})^{\dagger} \hat{O} U(\boldsymbol{\theta}) | 0 \rangle$$

can be used within a cost function






Machine Learning Model








Machine Learning Model




















































Part 5:
Open
Questions






How to avoid Barren Plateaus?







- How to avoid Barren Plateaus?
- Is there a Quantum Advantage?







- How to avoid Barren Plateaus?
- Is there a Quantum Advantage?
- How to define cost functions?

$$C(\boldsymbol{\theta}) = \langle \psi(\boldsymbol{\theta}) | \hat{O} | \psi(\boldsymbol{\theta}) \rangle + \cdots ?$$





- How to avoid Barren Plateaus?
- Is there a Quantum Advantage?
- How to define cost functions?

How to implement constraints?


minimize $C(\theta)$


subject to ???





- How to avoid Barren Plateaus?
- Is there a Quantum Advantage?
- How to define cost functions?





Thanks! A discussion is highly welcome.