



# **Anthos with NetApp**

## **NetApp Solutions**

NetApp  
June 03, 2022

This PDF was generated from [https://docs.netapp.com/us-en/netapp-solutions/containers/anthos-with-netapp/a-w-n\\_anthos\\_VMW.html](https://docs.netapp.com/us-en/netapp-solutions/containers/anthos-with-netapp/a-w-n_anthos_VMW.html) on June 03, 2022. Always check docs.netapp.com for the latest.

# Table of Contents

- NVA-1165: Anthos with NetApp ..... 1
  - Use cases ..... 1
  - Business value ..... 1
  - Technology overview ..... 1
  - Advanced configuration options ..... 2
  - Current support matrix for validated releases ..... 2
  - Anthos Overview ..... 2
  - NetApp Storage Overview: Anthos with NetApp ..... 11
  - NetApp Storage Integration Overview ..... 17
  - Advanced Configuration Options For Anthos ..... 33
  - Solution Validation and Use Cases: Anthos with NetApp ..... 41
  - Videos and Demos: Anthos with NetApp ..... 41
  - Additional Information: Anthos with NetApp ..... 41

# NVA-1165: Anthos with NetApp

Alan Cowles and Nikhil Kulkarni, NetApp

This reference document provides deployment validation of the Anthos with NetApp solution by NetApp and our engineering partners, when it is deployed in multiple data center environments.

It also details storage integration with NetApp storage systems by making use of the Astra Trident storage orchestrator for the management of persistent storage.

Lastly, a number of solution validations and real world use cases are explored and documented.

## Use cases

The Anthos with NetApp solution is architected to deliver exceptional value for customers with the following use cases:

- Easy to deploy and manage Anthos environment deployed using the provided 'bmctl' tool on bare metal or the 'gkectl' tool on VMware vSphere.
- Combined power of enterprise container and virtualized workloads with Anthos deployed virtually on vSphere or on bare metal with [kubevirt](#).
- Real-world configuration and use cases highlighting Anthos features when used with NetApp storage and Astra Trident, the open-source storage orchestrator for Kubernetes.

## Business value

Enterprises are increasingly adopting DevOps practices to create new products, shorten release cycles, and rapidly add new features. Because of their innate agile nature, containers and microservices play a crucial role in supporting DevOps practices. However, practicing DevOps at a production scale in an enterprise environment presents its own challenges and imposes certain requirements on the underlying infrastructure, such as the following:

- High availability at all layers in the stack
- Ease of deployment procedures
- Nondisruptive operations and upgrades
- API-driven and programmable infrastructure to keep up with microservices agility
- Multitenancy with performance guarantees
- Ability to run virtualized and containerized workloads simultaneously
- Ability to scale infrastructure independently based on workload demands

The Anthos with NetApp solution acknowledges these challenges and presents a solution that helps address each concern by implementing the fully automated deployment of Anthos On Prem in the customers data center environment of choice.

## Technology overview

The Anthos with NetApp solution is comprised of the following major components:

## Anthos On Prem

Anthos On Prem is a fully supported enterprise Kubernetes platform that can be deployed in the VMware vSphere hypervisor, or on a bare metal infrastructure of your choosing.

For more information about Anthos, see the Anthos website located [here](#).

## NetApp storage systems

NetApp has several storage systems perfect for enterprise data centers and hybrid cloud deployments. The NetApp portfolio includes NetApp ONTAP, NetApp Element, and NetApp e-Series storage systems, all of which can provide persistent storage for containerized applications.

For more information visit the NetApp website [here](#).

## NetApp storage integrations

Astra Trident is an open-source and fully-supported storage orchestrator for containers and Kubernetes distributions, including Anthos.

For more information, visit the Astra Trident website [here](#).

## Advanced configuration options

This section is dedicated to customizations that real world users would likely need to perform when deploying this solution into production, such as creating a dedicated private image registry or deploying custom load balancer instances.

## Current support matrix for validated releases

Technology	Purpose	Software version
NetApp ONTAP	Storage	9.8, 9.9.1
NetApp Element	Storage	12.3
NetApp Astra Trident	Storage Orchestration	22.01.0
Anthos Clusters on VMware	Container orchestration	1.10
Anthos on bare metal	Container Orchestration	1.10
VMware vSphere	Data center virtualization	6.7U3, 7.0U3

Next: [Anthos Overview: Anthos with NetApp](#).

## Anthos Overview

Anthos with NetApp is a verified, best-practice hybrid cloud architecture for the deployment of an on-premises Google Kubernetes Engine (GKE) environment in a reliable and dependable manner. This NetApp Verified Architecture reference document serves as both a design guide and a deployment validation of the Anthos with NetApp solution deployed to bare metal and virtual environments. The architecture described in this document has been validated by subject matter experts at NetApp and Google Cloud to provide the advantages of running Anthos within your enterprise data-center environment.

## Anthos

Anthos is a hybrid-cloud Kubernetes data center solution that enables organizations to construct and manage modern hybrid-cloud infrastructures while adopting agile workflows focused on application development.


Anthos on VMware, a solution built on open-source technologies, runs on-premises in a VMware vSphere-based infrastructure, which can connect and interoperate with Anthos GKE in Google Cloud.

Adopting containers, service mesh, and other transformational technologies enables organizations to experience consistent application development cycles and production-ready workloads in local and cloud-based environments. The following figure depicts the Anthos solution and how a deployment in an on-premises data center interconnects with infrastructure in the cloud.

For more information about Anthos, see the Anthos website located [here](#).

Anthos provides the following features:

- **Anthos configuration management.** Automates the policy and security of hybrid Kubernetes deployments.
- **Anthos Service Mesh.** Enhances application observability, security, and control with an Istio-powered service mesh.
- **Google Cloud Marketplace for Kubernetes Applications.** A catalog of curated container applications available for easy deployment.
- **Migrate for Anthos.** Automatic migration of physical services and VMs from on-premises to the cloud.
- **Stackdriver.** Management service offered by Google for logging and monitoring cloud instances.



## Deployment methods for Anthos

## Anthos clusters on VMware

Anthos clusters deployed to VMware vSphere environments are easy to deploy, maintain, and scale rapidly for most end-user Kubernetes workloads.

For more information about Anthos clusters on VMware, deployed with NetApp, please visit the page [here](#).

## Anthos on bare metal

Anthos clusters deployed on bare metal servers are hardware agnostic and allow you to select a compute platform optimized for your personalized use case.

For more information about Anthos on bare metal clusters deployed with NetApp, please visit the page [here](#).

[Next: NetApp Storage Overview: Anthos with NetApp.](#)

## Anthos Clusters on VMware: Anthos with NetApp

Anthos clusters on VMware is an extension of Google Kubernetes Engine that is deployed in an end user's private data center. An organization can deploy the same applications designed to run in containers in Google Cloud in Kubernetes clusters on-premises.

Anthos clusters on VMware can be deployed into an existing VMware vSphere environment in your data center, which can save on capital expenses and enable more rapid deployment and scaling operations.

The deployment of Anthos clusters on VMware includes the following components:

- **Anthos Admin Workstation.** A deployment host from which gkectl and kubectl commands can be run to deploy and interact with Anthos deployments.
- **Admin Cluster.** The initial cluster deployed when setting up Anthos clusters on VMware. This cluster manages all subordinate user cluster actions, including deployment, scaling, and upgrade.
- **User Cluster.** Each user cluster is deployed with its own load balancer instance or partition, allowing it to act as a standalone Kubernetes cluster for individual users or groups, helping to achieve full multitenancy.

The following graphic is a description of an Anthos clusters on VMware deployment.



## Benefits

Anthos clusters on VMware offers the following benefits:

- **Advanced multitenancy.** Each end user can be assigned their own user cluster, deployed with the virtual resources necessary for their own development environment.
- **Cost savings.** End users can realize significant cost savings by deploying multiple user clusters to the same physical environment, utilizing their own physical resources for their application deployments instead of provisioning resources in their Google Cloud environment or on large bare metal clusters.
- **Develop then publish.** On-premises deployments can be used while applications are in development, which allows for testing of applications in the privacy of a local data center before being made publicly available in the cloud.
- **Security requirements.** Customers with increased security concerns or sensitive data sets that cannot be stored in the public cloud are able to run their applications from the security of their own data centers,

thereby meeting organizational requirements.

## VMware vSphere

VMware vSphere is a virtualization platform for centrally managing a large number of virtualized servers and networks running on the ESXi hypervisor.

For more information about VMware vSphere, see the [VMware vSphere website](#).

VMware vSphere provides the following features:

- **VMware vCenter Server.** VMware vCenter Server provides unified management of all hosts and VMs from a single console and aggregates performance monitoring of clusters, hosts, and VMs.
- **VMware vSphere vMotion.** VMware vCenter allows you to hot migrate VMs between nodes in the cluster upon request in a nondisruptive manner.
- **vSphere High Availability.** To avoid disruption in the event of host failures, VMware vSphere allows hosts to be clustered and configured for high availability. VMs that are disrupted by host failure are rebooted shortly on other hosts in the cluster, restoring services.
- **Distributed Resource Scheduler (DRS).** A VMware vSphere cluster can be configured to load balance the resource needs of the VMs it is hosting. VMs with resource contentions can be hot migrated to other nodes in the cluster to make sure that enough resources are available.

## Hardware requirements

### Compute

Google Cloud periodically requests updated validation of partner server platforms with new releases of Anthos through their Anthos Ready platform partner program. A listing of currently validated server platforms, and the versions of Anthos supported can be found [here](#).

The following table contains server platforms that have been tested by NetApp and NetApp partner engineers for the validation of Anthos clusters on VMware deployments. These include solutions such as the [NetApp FlexPod](#) with Cisco UCS servers and the [NetApp HCI](#) hybrid cloud infrastructure platform.

Manufacturer	Make	Model
Cisco	UCS	B200 M5
NetApp	HCI	C410

### Operating system

Anthos clusters on VMware can be deployed to both vSphere 6 and 7 environments as chosen by the customer to help match their current datacenter infrastructure.

The following table contains a list of Linux operating systems that have been used by NetApp and our partners to validate the solution.

Operating System	Release	Anthos Versions
VMware vSphere	6.7U3	1.10
VMware vSphere	7.0U3	1.10



### Additional hardware

To complete the deployment of Anthos with NetApp as a fully validated solution, additional data center components for networking and storage have been tested by NetApp and our partner engineers.

The following table includes information about these additional infrastructure components.

Manufacturer	Hardware Name	Model
Mellanox	SN	2010
NetApp	AFF	A250
NetApp	HCI	S410

### Additional software

The following table includes a list of software versions deployed in the validation environment.

Manufacturer	Software Name	Version
Cisco	UCS	4.1(3e)
NetApp	Element	12
NetApp	HCI	1.8
NetApp	ONTAP	9.9.1
NetApp	Astra Trident	22.01

During the Anthos Ready platform validation performed by NetApp, the lab environment was built based on the following diagram, which allowed us to test multiple deployed user clusters alongside multiple NetApp Storage systems and storage backends.



## Network infrastructure support resources

The following infrastructure should be in place prior to the deployment of Anthos:

- At least one DNS server providing full host-name resolution that is accessible from the in-band management network and the VM network.
- At least one NTP server that is accessible from the in-band management network and the VM network.
- A DHCP server available to provide network address leases on demand should clusters need to scale dynamically.
- (Optional) Outbound internet connectivity for both the in-band management network and the VM network.

## Best practices for production deployments

This section lists several best practices that an organization should take into consideration before deploying this solution into production.

### Deploy Anthos to an ESXi cluster of at least three nodes

Although it is possible to install Anthos in a vSphere cluster of less than three nodes for demonstration or evaluation purposes, this is not recommended for production workloads. While two nodes allow for basic HA and fault tolerance, an Anthos cluster configuration must be modified to disable default host affinity, and this deployment method is not supported by Google Cloud.

## Configure virtual machine and host affinity

Distributing Anthos cluster nodes across multiple hypervisor nodes can be achieved by enabling VM and host affinity.

Affinity or anti-affinity is a way to define rules for a set of VMs and/or hosts that determine whether the VMs run together on the same host or hosts in the group or on different hosts. It is applied to VMs by creating affinity groups that consist of VMs and/or hosts with a set of identical parameters and conditions. Depending on whether the VMs in an affinity group run on the same host or hosts in the group or separately on different hosts, the parameters of the affinity group can define either positive affinity or negative affinity.

To configure affinity groups, see the appropriate link below for your version of VMWare vSphere.

[vSphere 6.7 Documentation: Using DRS Affinity Rules.](#)

[vSphere 7.0 Documentation: Using DRS Affinity Rules.](#)

[Next: NetApp Storage Overview: Anthos with Netapp.](#)

## Anthos on bare metal: Anthos with NetApp

### Benefits

The hardware-agnostic capabilities of Anthos on bare metal allow you to select a compute platform optimized for your personalized use case and also provide many additional benefits.

Examples include:

- **Bring your own server.** You can use servers that match your existing infrastructure to reduce capital expenditure and management costs.
- **Bring your own Linux OS.** By choosing the Linux OS that you wish to deploy your Anthos on bare metal environment to, you can ensure that the Anthos environment fits neatly into your existing infrastructure and management schemes.
- **Improved performance and lowered cost.** Without the requirement of a hypervisor, Anthos on bare metal clusters call for direct access to server hardware resources, including performance-optimized hardware devices like GPUs.
- **Improved network performance and lowered latency.** Because the Anthos on bare metal server nodes are directly connected to your network without a virtualized abstraction layer, they can be optimized for low latency and performance.

### Hardware requirements

#### Compute

Google Cloud periodically requests updated validation of partner server platforms with new releases of Anthos through their Anthos Ready platform partner program. A listing of currently validated server platforms and the versions of Anthos supported can be found [here](#).

The following table contains server platforms that have been tested by NetApp and NetApp partner engineers for the validation of Anthos on bare metal deployments.

Manufacturer	Make	Model
Cisco	UCS	B200 M5

HPE	Proliant	DL360
-----	----------	-------

### Operating System

Anthos on bare metal nodes can be configured with several different Linux distributions as chosen by the customer to help match their current datacenter infrastructure.

The following table contains a list of Linux operating systems that have been used by NetApp and our partners to validate the solution.

Operating System	Release	Anthos Versions
CentOS	8.4	1.10
Red Hat Enterprise Linux	8.4	1.10
Ubuntu	18.04 LTS	1.10
Ubuntu	20.04 LTS	1.10

### Additional hardware

To complete the deployment of Anthos on bare metal as a fully validated solution, additional data center components for networking and storage have been tested by NetApp and our partner engineers.

The following table includes information about these additional infrastructure components.

Manufacturer	Hardware Name	Model
Cisco	Nexus	C9336C-FX2
NetApp	AFF	A250

### Additional software

The following table includes a list of additional software versions deployed in the validation environment.

Manufacturer	Software name	Version
Cisco	NXOS	9.3(5)
NetApp	ONTAP	9.9.1
NetApp	Astra Trident	22.01

During the Anthos Ready platform validation performed by NetApp and our partner team at World Wide Technology (WWT), the lab environment was built based on the following diagram, which allowed us to test the functionality of each server type, operating system, the network devices, and storage systems deployed in the solution.

## Anthos BareMetal Physical Hardware Diagram



This multi-OS environment shows interoperability with supported OS versions for the Anthos on bare metal solution. We anticipate that customers will standardize on one or a subset of operating systems for their own deployment.

### Infrastructure support resources

The following infrastructure should be in place prior to the deployment of Anthos on bare metal:

- At least one DNS server that provides a full host-name resolution accessible from the in-band management network and the VM network.
- At least one NTP server that is accessible from the in-band management network and the VM network.
- (Optional) Outbound internet connectivity for both the in-band management network and the VM network.

[Next: NetApp storage overview: Anthos with Netapp.](#)

## NetApp Storage Overview: Anthos with NetApp

NetApp has several storage platforms that are qualified with our Astra Trident Storage Orchestrator to provision storage for applications deployed on Anthos.



- AFF and FAS systems run NetApp ONTAP and provide storage for both file-based (NFS) and block-based (iSCSI) use cases.
- Cloud Volumes ONTAP and ONTAP Select provide the same benefits in the cloud and virtual space respectively.
- NetApp Cloud Volumes Service (AWS/GCP) and Azure NetApp Files provide file-based storage in the cloud.
- NetApp Element storage systems provide for block-based (iSCSI) use cases in a highly scalable environment.



Each storage system in the NetApp portfolio can ease both data management and movement between on-premises sites and the cloud, ensuring that your data is where your applications are.

The following pages have additional information about the NetApp storage systems validated in the Anthos with NetApp solution:

- [NetApp ONTAP](#)
- [NetApp Element](#)

[Next: NetApp Storage Integrations Overview: Anthos with NetApp.](#)

## NetApp ONTAP: Anthos with NetApp

NetApp ONTAP is a powerful storage-software tool with capabilities such as an intuitive GUI, REST APIs with automation integration, AI-informed predictive analytics and corrective action, nondisruptive hardware upgrades, and cross-storage import.

For more information about the NetApp ONTAP storage system, visit the [NetApp ONTAP website](#).

ONTAP provides the following features:

- A unified storage system with simultaneous data access and management of NFS, CIFS, iSCSI, FC, FCoE, and FC-NVMe protocols.
- Different deployment models include on-premises on all-flash, hybrid, and all-HDD hardware configurations; VM-based storage platforms on a supported hypervisor such as ONTAP Select; and in the cloud as Cloud Volumes ONTAP.
- Increased data storage efficiency on ONTAP systems with support for automatic data tiering, inline data compression, deduplication, and compaction.
- Workload-based, QoS-controlled storage.
- Seamless integration with a public cloud for tiering and protection of data. ONTAP also provides robust data protection capabilities that sets it apart in any environment:
  - **NetApp Snapshot copies.** A fast, point-in-time backup of data using a minimal amount of disk space with no additional performance overhead.
  - **NetApp SnapMirror.** Mirrors the Snapshot copies of data from one storage system to another. ONTAP supports mirroring data to other physical platforms and cloud-native services as well.
  - **NetApp SnapLock.** Efficiently administration of nonrewritable data by writing it to special volumes that cannot be overwritten or erased for a designated period.
  - **NetApp SnapVault.** Backs up data from multiple storage systems to a central Snapshot copy that serves as a backup to all designated systems.
  - **NetApp SyncMirror.** Provides real-time, RAID-level mirroring of data to two different plexes of disks that are connected physically to the same controller.
  - **NetApp SnapRestore.** Provides fast restoration of backed-up data on demand from Snapshot copies.
  - **NetApp FlexClone.** Provides instantaneous provisioning of a fully readable and writeable copy of a NetApp volume based on a Snapshot copy.

For more information about ONTAP, see the [ONTAP 9 Documentation Center](#).



NetApp ONTAP is available on-premises, virtualized, or in the cloud.



## NetApp platforms

### NetApp AFF/FAS

NetApp provides robust all-flash (AFF) and scale-out hybrid (FAS) storage platforms that are tailor-made with low-latency performance, integrated data protection, and multiprotocol support.

Both systems are powered by NetApp ONTAP data management software, the industry's most advanced data-management software for highly-available, cloud-integrated, simplified storage management to deliver the enterprise-class speed, efficiency, and security your data fabric needs.

For more information about NETAPP AFF and FAS platforms, click [here](#).

### ONTAP Select

ONTAP Select is a software-defined deployment of NetApp ONTAP that can be deployed onto a hypervisor in your environment. It can be installed on VMware vSphere or on KVM and provides the full functionality and experience of a hardware-based ONTAP system.

For more information about ONTAP Select, click [here](#).

### Cloud Volumes ONTAP

NetApp Cloud Volumes ONTAP is a cloud-deployed version of NetApp ONTAP available to be deployed in a number of public clouds, including: Amazon AWS, Microsoft Azure, and Google Cloud.



For more information about Cloud Volumes ONTAP, click [here](#).

Next: [NetApp Storage Integrations Overview: Anthos with NetApp](#).

## NetApp Element: Anthos with NetApp

NetApp Element software provides modular, scalable performance, with each storage node delivering guaranteed capacity and throughput to the environment. NetApp Element systems can scale from 4 to 100 nodes in a single cluster and offer a number of advanced storage management features.



For more information about NetApp Element storage systems, visit the [NetApp Solidfire website](#).

### iSCSI login redirection and self-healing capabilities

NetApp Element software leverages the iSCSI storage protocol, a standard way to encapsulate SCSI commands on a traditional TCP/IP network. When SCSI standards change or when the performance of Ethernet networks improves, the iSCSI storage protocol benefits without the need for any changes.

Although all storage nodes have a management IP and a storage IP, NetApp Element software advertises a single storage virtual IP address (SVIP address) for all storage traffic in the cluster. As a part of the iSCSI login process, storage can respond that the target volume has been moved to a different address and therefore it cannot proceed with the negotiation process. The host then reissues the login request to the new address in a process that requires no host-side reconfiguration. This process is known as iSCSI login redirection.

iSCSI login redirection is a key part of the NetApp Element software cluster. When a host login request is received, the node decides which member of the cluster should handle the traffic based on the IOPS and the capacity requirements for the volume. Volumes are distributed across the NetApp Element software cluster and are redistributed if a single node is handling too much traffic for its volumes or if a new node is added. Multiple copies of a given volume are allocated across the array.

In this manner, if a node failure is followed by volume redistribution, there is no effect on host connectivity beyond a logout and login with redirection to the new location. With iSCSI login redirection, a NetApp Element software cluster is a self-healing, scale-out architecture that is capable of nondisruptive upgrades and operations.

### NetApp Element software cluster QoS

A NetApp Element software cluster allows QoS to be dynamically configured on a per-volume basis. You can use per-volume QoS settings to control storage performance based on SLAs that you define. The following three configurable parameters define the QoS:

- **Minimum IOPS.** The minimum number of sustained IOPS that the NetApp Element software cluster provides to a volume. The minimum IOPS configured for a volume is the guaranteed level of performance for a volume. Per-volume performance does not drop below this level.

- **Maximum IOPS.** The maximum number of sustained IOPS that the NetApp Element software cluster provides to a particular volume.
- **Burst IOPS.** The maximum number of IOPS allowed in a short burst scenario. The burst duration setting is configurable, with a default of 1 minute. If a volume has been running below the maximum IOPS level, burst credits are accumulated. When performance levels become very high and are pushed, short bursts of IOPS beyond the maximum IOPS are allowed on the volume.

## Multitenancy

Secure multitenancy is achieved with the following features:

- **Secure authentication.** The Challenge-Handshake Authentication Protocol (CHAP) is used for secure volume access. The Lightweight Directory Access Protocol (LDAP) is used for secure access to the cluster for management and reporting.
- **Volume access groups (VAGs).** Optionally, VAGs can be used in lieu of authentication, mapping any number of iSCSI initiator-specific iSCSI Qualified Names (IQNs) to one or more volumes. To access a volume in a VAG, the initiator's IQN must be in the allowed IQN list for the group of volumes.
- **Tenant virtual LANs (VLANs).** At the network level, end-to-end network security between iSCSI initiators and the NetApp Element software cluster is facilitated by using VLANs. For any VLAN that is created to isolate a workload or a tenant, NetApp Element Software creates a separate iSCSI target SVIP address that is accessible only through the specific VLAN.
- **VRF-enabled VLANs.** To further support security and scalability in the data center, NetApp Element software allows you to enable any tenant VLAN for VRF-like functionality. This feature adds these two key capabilities:
  - **L3 routing to a tenant SVIP address.** This feature allows you to situate iSCSI initiators on a separate network or VLAN from that of the NetApp Element software cluster.
  - **Overlapping or duplicate IP subnets.** This feature enables you to add a template to tenant environments, allowing each respective tenant VLAN to be assigned IP addresses from the same IP subnet. This capability can be useful for in-service provider environments where scale and preservation of IPspace are important.

## Enterprise storage efficiencies

The NetApp Element software cluster increases overall storage efficiency and performance. The following features are performed inline, are always on, and require no manual configuration by the user:

- **Deduplication.** The system only stores unique 4K blocks. Any duplicate 4K blocks are automatically associated to an already stored version of the data. Data is on block drives and is mirrored by using the NetApp Element software Helix data protection. This system significantly reduces capacity consumption and write operations within the system.
- **Compression.** Compression is performed inline before data is written to NVRAM. Data is compressed, stored in 4K blocks, and remains compressed in the system. This compression significantly reduces capacity consumption, write operations, and bandwidth consumption across the cluster.
- **Thin-provisioning.** This capability provides the right amount of storage at the time that you need it, eliminating capacity consumption that caused by overprovisioned volumes or underutilized volumes.
- **Helix.** The metadata for an individual volume is stored on a metadata drive and is replicated to a secondary metadata drive for redundancy.



Element was designed for automation. All the storage features are available through APIs. These APIs are the only method that the UI uses to control the system.

## NetApp Storage Integration Overview

### Anthos Ready storage partner program.

Google Cloud periodically requests updated validation of partner storage integrations with new releases of Anthos through their Anthos Ready storage partner program. A listing of currently validated storage solutions, CSI drivers, available features, and the versions of Anthos supported can be found [here](#).

NetApp has maintained regular compliance with the requests to validate our Astra Trident CSI-compliant storage orchestrator, and our ONTAP and Element storage systems with versions of Anthos on a quarterly basis.

The following table contains the Anthos versions that have been tested by NetApp and NetApp partner engineers for the validation NetApp Astra Trident CSI drivers, and feature sets, as a part of the Anthos Ready storage partner program:

Deployment Type	Version	Storage System	Astra Trident Version	Protocol	Features
VMware	1.10	ONTAP	22.01	NAS	Multiwriter, Volume Expansion, SnapShots
VMware	1.10	ONTAP	22.01	SAN	Raw Block, Volume Expansion, SnapShots
VMware	1.10	Element	22.01	SAN	Raw Block, Volume Expansion, SnapShots
bare metal	1.10	ONTAP	22.01	NAS	Multiwriter, Volume Expansion, SnapShots
bare metal	1.10	ONTAP	22.01	SAN	Raw Block, Volume Expansion, SnapShots

### NetApp Storage Integrations

NetApp provides a number of products to help you with orchestrating and managing persistent data in container based environments, such as Anthos.

NetApp Astra Trident is an open-source and fully-supported storage orchestrator for containers and Kubernetes distributions, including Anthos. For more information, visit the Astra Trident website [here](#).

The following pages have additional information about the NetApp products that have been validated for

application and persistent storage management in the Anthos with NetApp solution:

- [NetApp Astra Trident](#)

[Next: Advanced Configuration Options: Anthos with NetApp.](#)

## Astra Trident Overview

Astra Trident is an open-source and fully supported storage orchestrator for containers and Kubernetes distributions, including Anthos. Trident works with the entire NetApp storage portfolio, including the NetApp ONTAP and Element storage systems, and it also supports NFS and iSCSI connections. Trident accelerates the DevOps workflow by allowing end users to provision and manage storage from their NetApp storage systems without requiring intervention from a storage administrator.

An administrator can configure a number of storage backends based on project needs and storage system models that enable advanced storage features, including compression, specific disk types, or QoS levels that guarantee a certain level of performance. After they are defined, these backends can be used by developers in their projects to create persistent volume claims (PVCs) and to attach persistent storage to their containers on demand.

[Error: Missing Graphic Image]

Astra Trident has a rapid development cycle and, like Kubernetes, is released four times a year.

The latest version of Astra Trident, 22.01, was released in January 2022. A support matrix for what version of Trident has been tested with which Kubernetes distribution can be found [here](#).

Starting with the 20.04 release, Trident setup is performed by the Trident operator. The operator makes large scale deployments easier and provides additional support including self healing for pods that are deployed as a part of the Trident install.

With the 21.01 release, a Helm chart was made available to ease the installation of the Trident Operator.

## Download Astra Trident

To install Trident on the deployed user cluster and provision a persistent volume, complete the following steps:

1. Download the installation archive to the admin workstation and extract the contents. The current version of Trident is 22.01, which can be downloaded [here](#).

```
[ubuntu@gke-admin-ws-2021-07-15 ~]$ wget
https://github.com/NetApp/trident/releases/download/v22.01.0/trident-
installer-22.01.0.tar.gz
--2021-05-06 15:17:30--
https://github.com/NetApp/trident/releases/download/v22.01.0/trident-
installer-22.01.0.tar.gz
Resolving github.com (github.com)... 140.82.114.3
Connecting to github.com (github.com)|140.82.114.3|:443... connected.
HTTP request sent, awaiting response... 302 Found
Location: https://github-
releases.githubusercontent.com/77179634/a4fa9f00-a9f2-11eb-9053-
98e8e573d4ae?X-Amz-Algorithm=AWS4-HMAC-SHA256&X-Amz-
```

```

Credential=AKIAIWNJYAX4CSVEH53A%2F20210506%2Fus-east-
1%2Fs3%2Faws4_request&X-Amz-Date=20210506T191643Z&X-Amz-Expires=300&X-
Amz-
Signature=8a49a2a1e08c147d1ddd8149ce45a5714f9853fee19bb1c507989b9543eb36
30&X-Amz-
SignedHeaders=host&actor_id=0&key_id=0&repo_id=77179634&response-
content-disposition=attachment%3B%20filename%3Dtrident-installer-
22.01.0.tar.gz&response-content-type=application%2Foctet-stream
[following]
--2021-05-06 15:17:30--  https://github-
releases.githubusercontent.com/77179634/a4fa9f00-a9f2-11eb-9053-
98e8e573d4ae?X-Amz-Algorithm=AWS4-HMAC-SHA256&X-Amz-
Credential=AKIAIWNJYAX4CSVEH53A%2F20210506%2Fus-east-
1%2Fs3%2Faws4_request&X-Amz-Date=20210506T191643Z&X-Amz-Expires=300&X-
Amz-
Signature=8a49a2a1e08c147d1ddd8149ce45a5714f9853fee19bb1c507989b9543eb36
30&X-Amz-
SignedHeaders=host&actor_id=0&key_id=0&repo_id=77179634&response-
content-disposition=attachment%3B%20filename%3Dtrident-installer-
22.01.0.tar.gz&response-content-type=application%2Foctet-stream
Resolving github-releases.githubusercontent.com (github-
releases.githubusercontent.com)... 185.199.108.154, 185.199.109.154,
185.199.110.154, ...
Connecting to github-releases.githubusercontent.com (github-
releases.githubusercontent.com)|185.199.108.154|:443... connected.
HTTP request sent, awaiting response... 200 OK
Length: 38349341 (37M) [application/octet-stream]
Saving to: `trident-installer-22.01.0.tar.gz'

100%[=====
=====>] 38,349,341  88.5MB/s
in 0.4s

2021-05-06 15:17:30 (88.5 MB/s) - `trident-installer-22.01.0.tar.gz'
saved [38349341/38349341]

```

## 2. Extract the Trident install from the downloaded bundle.

```

[ubuntu@gke-admin-ws-2021-07-15 ~]$ tar -xzf trident-installer-
22.01.0.tar.gz
[ubuntu@gke-admin-ws-2021-07-15 ~]$ cd trident-installer/
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$

```

## Install the Trident Operator with Helm



Helm is not installed by default on the GKE-Admin workstation. You can easily install it using the apt tool available in Ubuntu.

1. First, set the location of the user cluster's kubeconfig file as an environment variable so that you don't have to reference it, because Trident has no option to pass this file.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ export
KUBECONFIG=~/.user-cluster-1/user-cluster-1-kubeconfig
```

2. Run the Helm command to install the Trident operator from the tarball in the helm directory while creating the trident namespace in your user cluster.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ helm install trident
helm/trident-operator-22.01.0.tgz --create-namespace --namespace trident
NAME: trident
LAST DEPLOYED: Fri May  7 12:54:25 2021
NAMESPACE: trident
STATUS: deployed
REVISION: 1
TEST SUITE: None
NOTES:
Thank you for installing trident-operator, which will deploy and manage
NetApp's Trident CSI
storage provisioner for Kubernetes.

Your release is named 'trident' and is installed into the 'trident'
namespace.
Please note that there must be only one instance of Trident (and
trident-operator) in a Kubernetes cluster.

To configure Trident to manage storage resources, you will need a copy
of tridentctl, which is
available in pre-packaged Trident releases. You may find all Trident
releases and source code
online at https://github.com/NetApp/trident.

To learn more about the release, try:

$ helm status trident
$ helm get all trident
```

3. You can verify that Trident is successfully installed by checking the pods that are running in the namespace or by using the tridentctl binary to check the installed version.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ oc get pods -n
trident
NAME                                READY   STATUS    RESTARTS   AGE
trident-csi-5z45l                   1/2     Running   2           30s
trident-csi-696b685cf8-htdb2       6/6     Running   0           30s
trident-csi-b74p2                   2/2     Running   0           30s
trident-csi-lrw4n                   2/2     Running   0           30s
trident-operator-7c748d957-gr2gw    1/1     Running   0           36s
```

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ ./tridentctl -n
trident version
+-----+-----+
| SERVER VERSION | CLIENT VERSION |
+-----+-----+
| 22.01.0        | 22.01.0        |
+-----+-----+
```



In some cases, customer environments might require the customization of the Trident deployment. In these cases, it is also possible to manually install the Trident operator and update the included manifests to customize the deployment.

## Manually install the Trident Operator

1. First, set the location of the user cluster's kubeconfig file as an environment variable so that you don't have to reference it, because Trident has no option to pass this file.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ KUBECONFIG=~/.user-
cluster-1/user-cluster-1-kubeconfig
```

2. The trident-installer directory contains manifests for defining all the required resources. Using the appropriate manifests, create the TridentOrchestrator custom resource definition.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ kubectl create -f
deploy/crds/trident.netapp.io_tridentorchestrators_crd_post1.16.yaml
customresourcedefinition.apiextensions.k8s.io/tridentorchestrators.tride
nt.netapp.io created
```

3. If one does not exist, create a Trident namespace in your cluster using the provided manifest.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ kubectl apply -f
deploy/namespace.yaml
namespace/trident created
```

4. Create the resources required for the Trident operator deployment, such as a ServiceAccount for the operator, a ClusterRole and ClusterRoleBinding to the ServiceAccount, a dedicated PodSecurityPolicy, or the operator itself.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ kubectl create -f
deploy/bundle.yaml
serviceaccount/trident-operator created
clusterrole.rbac.authorization.k8s.io/trident-operator created
clusterrolebinding.rbac.authorization.k8s.io/trident-operator created
deployment.apps/trident-operator created
podsecuritypolicy.policy/tridentoperatorpods created
```

5. You can check the status of the operator after it's deployed with the following commands:

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ kubectl get
deployment -n trident
NAME                READY    UP-TO-DATE    AVAILABLE    AGE
trident-operator    1/1      1              1             23s
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ kubectl get pods -n
trident
NAME                                READY    STATUS    RESTARTS    AGE
trident-operator-66f48895cc-lzczk    1/1      Running   0            41s
```

6. With the operator deployed, we can now use it to install Trident. This requires creating a TridentOrchestrator.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ kubectl create -f
deploy/crds/tridentorchestrator_cr.yaml
tridentorchestrator.trident.netapp.io/trident created
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ kubectl describe
torc trident
Name:                trident
Namespace:
Labels:               <none>
Annotations:          <none>
API Version:          trident.netapp.io/v1
Kind:                 TridentOrchestrator
Metadata:
  Creation Timestamp:  2021-05-07T17:00:28Z
  Generation:          1
  Managed Fields:
    API Version:        trident.netapp.io/v1
    Fields Type:        FieldsV1
    fieldsV1:
```



```

f:spec:
  ..
  f:debug:
  f:namespace:
Manager:      kubect1-create
Operation:    Update
Time:         2021-05-07T17:00:28Z
API Version:  trident.netapp.io/v1
Fields Type:  FieldsV1
fieldsV1:
  f:status:
    ..
    f:currentInstallationParams:
      ..
      f:IPv6:
      f:autosupportHostname:
      f:autosupportImage:
      f:autosupportProxy:
      f:autosupportSerialNumber:
      f:debug:
      f:enableNodePrep:
      f:imagePullSecrets:
      f:imageRegistry:
      f:k8sTimeout:
      f:kubeletDir:
      f:logFormat:
      f:silenceAutosupport:
      f:tridentImage:
    f:message:
    f:namespace:
    f:status:
    f:version:
Manager:      trident-operator
Operation:    Update
Time:         2021-05-07T17:00:28Z
Resource Version: 931421
Self Link:
/apis/trident.netapp.io/v1/tridentorchestrators/trident
UID:          8a26a7a6-dde8-4d55-9b66-a7126754d81f
Spec:
  Debug:      true
  Namespace:  trident
Status:
  Current Installation Params:
    IPv6:          false
    Autosupport Hostname:

```

```

Autosupport Image:      netapp/trident-autosupport:21.01
Autosupport Proxy:
Autosupport Serial Number:
Debug:                  true
Enable Node Prep:       false
Image Pull Secrets:
Image Registry:
k8sTimeout:             30
Kubelet Dir:             /var/lib/kubelet
Log Format:              text
Silence Autosupport:    false
Trident Image:          netapp/trident:22.01.0
Message:                 Trident installed
Namespace:               trident
Status:                  Installed
Version:                 v22.01.0
Events:
  Type      Reason      Age   From                      Message
  ----      -
  Normal    Installing  80s   trident-operator.netapp.io Installing
Trident
  Normal    Installed  68s   trident-operator.netapp.io Trident
installed

```

7. You can verify that Trident is successfully installed by checking the pods that are running in the namespace or by using the tridentctl binary to check the installed version.

```

[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ kubectl get pods -n
trident
NAME                                READY   STATUS    RESTARTS   AGE
trident-csi-bb64c6cb4-lmd6h         6/6     Running   0           82s
trident-csi-gn59q                    2/2     Running   0           82s
trident-csi-m4szj                    2/2     Running   0           82s
trident-csi-sb9k9                    2/2     Running   0           82s
trident-operator-66f48895cc-lzczk    1/1     Running   0           2m39s

[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ ./tridentctl -n
trident version
+-----+-----+
| SERVER VERSION | CLIENT VERSION |
+-----+-----+
| 22.01.0       | 22.01.0       |
+-----+-----+

```

## Create storage-system backends

After completing the Astra Trident Operator install, you must configure the backend for the specific NetApp storage platform you are using. Follow the links below in order to continue the setup and configuration of Astra Trident.

- [NetApp ONTAP NFS](#)
- [NetApp ONTAP iSCSI](#)
- [NetApp Element iSCSI](#)

Next: [Advanced Configuration Options: Anthos with NetApp](#).

### NetApp ONTAP NFS configuration: Anthos with NetApp

To enable Trident integration with the NetApp ONTAP storage system, you must create a backend that enables communication with the storage system.

1. There are sample backend files available in the downloaded installation archive in the `sample-input` folder hierarchy. For NetApp ONTAP systems serving NFS, copy the `backend-ontap-nas.json` file to your working directory and edit the file.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ cp sample-  
input/backends-samples/ontap-nas/backend-ontap-nas.json ./  
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ vi backend-ontap-  
nas.json
```

2. Edit the `backendName`, `managementLIF`, `dataLIF`, `svm`, `username`, and `password` values in this file.

```
{  
  "version": 1,  
  "storageDriverName": "ontap-nas",  
  "backendName": "ontap-nas+10.61.181.221",  
  "managementLIF": "172.21.224.201",  
  "dataLIF": "10.61.181.221",  
  "svm": "trident_svm",  
  "username": "cluster-admin",  
  "password": "password"  
}
```



It is a best practice to define the custom `backendName` value as a combination of the `storageDriverName` and the `dataLIF` that is serving NFS for easy identification.

3. With this backend file in place, run the following command to create your first backend.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ ./tridentctl -n
trident create backend -f backend-ontap-nas.json
+-----+-----+
+-----+-----+-----+
|          NAME          | STORAGE DRIVER |          UUID          |
| STATE | VOLUMES | |
+-----+-----+-----+
+-----+-----+-----+
| ontap-nas+10.61.181.221 | ontap-nas      | be7a619d-c81d-445c-b80c-5c87a73c5b1e |
| online |         0 | |
+-----+-----+-----+
+-----+-----+-----+
```

4. With the backend created, you must next create a storage class. Just as with the backend, there is a sample storage class file that can be edited for the environment available in the sample-inputs folder. Copy it to the working directory and make necessary edits to reflect the backend created.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ cp sample-
input/storage-class-samples/storage-class-csi.yaml.templ ./storage-
class-basic.yaml
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ vi storage-class-
basic.yaml
```

5. The only edit that must be made to this file is to define the `backendType` value to the name of the storage driver from the newly created backend. Also note the `name-field` value, which must be referenced in a later step.

```
apiVersion: storage.k8s.io/v1
kind: StorageClass
metadata:
  name: basic-csi
provisioner: csi.trident.netapp.io
parameters:
  backendType: "ontap-nas"
```



There is an optional field called `fsType` that is defined in this file. This line can be deleted in NFS backends.

6. Run the `kubectl` command to create the storage class.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ kubectl create -f
storage-class-basic.yaml
storageclass.storage.k8s.io/basic-csi created
```

7. With the storage class created, you must then create the first persistent volume claim (PVC). There is a sample `pvc-basic.yaml` file that can be used to perform this action located in `sample-inputs` as well.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ cp sample-input/pvc-
samples/pvc-basic.yaml ./
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ vi pvc-basic.yaml
```

8. The only edit that must be made to this file is ensuring that the `storageClassName` field matches the one just created. The PVC definition can be further customized as required by the workload to be provisioned.

```
kind: PersistentVolumeClaim
apiVersion: v1
metadata:
  name: basic
spec:
  accessModes:
    - ReadWriteOnce
  resources:
    requests:
      storage: 1Gi
  storageClassName: basic-csi
```

9. Create the PVC by issuing the `kubectl` command. Creation can take some time depending on the size of the backing volume being created, so you can watch the process as it completes.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ kubectl create -f
pvc-basic.yaml
persistentvolumeclaim/basic created

[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ kubectl get pvc
NAME      STATUS    VOLUME                                     CAPACITY
ACCESS MODES  STORAGECLASS  AGE
basic      Bound       pvc-b4370d37-0fa4-4c17-bd86-94f96c94b42d  1Gi
RWO                basic-csi          7s
```

[Next: Advanced Configuration Options: Anthos with NetApp.](#)

## NetApp ONTAP iSCSI configuration: Anthos with NetApp

To enable Trident integration with the NetApp ONTAP storage system, you must create a backend that enables communication with the storage system.

1. There are sample backend files available in the downloaded installation archive in the `sample-input` folder hierarchy. For NetApp ONTAP systems serving iSCSI, copy the `backend-ontap-san.json` file to your working directory and edit the file.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ cp sample-  
input/backends-samples/ontap-san/backend-ontap-san.json ./  
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ vi backend-ontap-  
san.json
```

2. Edit the `managementLIF`, `dataLIF`, `svm`, `username`, and `password` values in this file.

```
{  
  "version": 1,  
  "storageDriverName": "ontap-san",  
  "managementLIF": "172.21.224.201",  
  "dataLIF": "10.61.181.240",  
  "svm": "trident_svm",  
  "username": "admin",  
  "password": "password"  
}
```

3. With this backend file in place, run the following command to create your first backend.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ ./tridentctl -n  
trident create backend -f backend-ontap-san.json  
+-----+-----+-----+  
+-----+-----+-----+  
|          NAME          | STORAGE DRIVER |          UUID          |  
| STATE | VOLUMES |  
+-----+-----+-----+  
+-----+-----+-----+  
| ontapsan_10.61.181.241 | ontap-san      | 6788533c-7fea-4a35-b797-  
fb9bb3322b91 | online |      0 |  
+-----+-----+-----+  
+-----+-----+-----+
```

4. With the backend created, you must next create a storage class. Just as with the backend, there is a sample storage class file that can be edited for the environment available in the `sample-inputs` folder. Copy it to the working directory and make necessary edits to reflect the backend created.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ cp sample-  
input/storage-class-samples/storage-class-csi.yaml.templ ./storage-  
class-basic.yaml  
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ vi storage-class-  
basic.yaml
```

5. The only edit that must be made to this file is to define the `backendType` value to the name of the storage driver from the newly created backend. Also note the `name-field` value, which must be referenced in a later step.

```
apiVersion: storage.k8s.io/v1  
kind: StorageClass  
metadata:  
  name: basic-csi  
provisioner: csi.trident.netapp.io  
parameters:  
  backendType: "ontap-san"
```



There is an optional field called `fsType` that is defined in this file. In iSCSI backends, this value can be set to a specific Linux filesystem type (XFS, ext4, and so on) or can be deleted to allow OpenShift to decide what filesystem to use.

6. Run the `kubectl` command to create the storage class.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ kubectl create -f  
storage-class-basic.yaml  
storageclass.storage.k8s.io/basic-csi created
```

7. With the storage class created, you must then create the first persistent volume claim (PVC). There is a sample `pvc-basic.yaml` file that can be used to perform this action located in `sample-inputs` as well.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ cp sample-input/pvc-  
samples/pvc-basic.yaml ./  
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ vi pvc-basic.yaml
```

8. The only edit that must be made to this file is ensuring that the `storageClassName` field matches the one just created. The PVC definition can be further customized as required by the workload to be provisioned.

```
kind: PersistentVolumeClaim
apiVersion: v1
metadata:
  name: basic
spec:
  accessModes:
    - ReadWriteOnce
  resources:
    requests:
      storage: 1Gi
  storageClassName: basic-csi
```

9. Create the PVC by issuing the `kubectl` command. Creation can take some time depending on the size of the backing volume being created, so you can watch the process as it completes.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ kubectl create -f
pvc-basic.yaml
persistentvolumeclaim/basic created

[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ kubectl get pvc
NAME      STATUS    VOLUME                                     CAPACITY
ACCESS MODES  STORAGECLASS  AGE
basic      Bound      pvc-7ceac1ba-0189-43c7-8f98-094719f7956c  1Gi
RWO                                     basic-csi      3s
```

[Next: Advanced Configuration Options: Anthos with NetApp.](#)

### NetApp Element iSCSI configuration: Anthos with NetApp

To enable Trident integration with the NetApp Element storage system, you must create a backend that enables communication with the storage system using the iSCSI protocol.

1. There are sample backend files available in the downloaded installation archive in the `sample-input` folder hierarchy. For NetApp Element systems serving iSCSI, copy the `backend-solidfire.json` file to your working directory and edit the file.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ cp sample-
input/backends-samples/solidfire/backend-solidfire.json ./
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ vi ./backend-
solidfire.json
```

- a. Edit the user, password, and MVIP value on the `EndPoint` line.
- b. Edit the `SVIP` value.



```
{
  "version": 1,
  "storageDriverName": "solidfire-san",
  "Endpoint": "https://trident:password@172.21.224.150/json-rpc/8.0",
  "SVIP": "10.61.180.200:3260",
  "TenantName": "trident",
  "Types": [{"Type": "Bronze", "Qos": {"minIOPS": 1000, "maxIOPS": 2000, "burstIOPS": 4000}},
            {"Type": "Silver", "Qos": {"minIOPS": 4000, "maxIOPS": 6000, "burstIOPS": 8000}},
            {"Type": "Gold", "Qos": {"minIOPS": 6000, "maxIOPS": 8000, "burstIOPS": 10000}}]
}
```

2. With this back-end file in place, run the following command to create your first backend.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ ./tridentctl -n
trident create backend -f backend-solidfire.json
+-----+-----+
+-----+-----+-----+-----+
|          NAME          | STORAGE DRIVER |          UUID          |
| STATE | VOLUMES | |          |
+-----+-----+-----+-----+
+-----+-----+-----+-----+
| solidfire_10.61.180.200 | solidfire-san  | b90783ee-e0c9-49af-8d26-3ea87ce2efdf |
| online |          0 | |          |
+-----+-----+-----+-----+
+-----+-----+-----+-----+
```

3. With the backend created, you must next create a storage class. Just as with the backend, there is a sample storage class file that can be edited for the environment available in the sample-inputs folder. Copy it to the working directory and make necessary edits to reflect the backend created.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ cp sample-
input/storage-class-samples/storage-class-csi.yaml.templ ./storage-
class-basic.yaml
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ vi storage-class-
basic.yaml
```

4. The only edit that must be made to this file is to define the `backendType` value to the name of the storage driver from the newly created backend. Also note the `name-field` value, which must be referenced in a later step.

```

apiVersion: storage.k8s.io/v1
kind: StorageClass
metadata:
  name: basic-csi
provisioner: csi.trident.netapp.io
parameters:
  backendType: "solidfire-san"

```



There is an optional field called `fsType` that is defined in this file. In iSCSI backends, this value can be set to a specific Linux filesystem type (XFS, ext4, and so on), or it can be deleted to allow OpenShift to decide what filesystem to use.

5. Run the `kubectl` command to create the storage class.

```

[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ kubectl create -f
storage-class-basic.yaml
storageclass.storage.k8s.io/basic-csi created

```

6. With the storage class created, you must then create the first persistent volume claim (PVC). There is a sample `pvc-basic.yaml` file that can be used to perform this action located in `sample-inputs` as well.

```

[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ cp sample-input/pvc-
samples/pvc-basic.yaml ./
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ vi pvc-basic.yaml

```

7. The only edit that must be made to this file is ensuring that the `storageClassName` field matches the one just created. The PVC definition can be further customized as required by the workload to be provisioned.

```

kind: PersistentVolumeClaim
apiVersion: v1
metadata:
  name: basic
spec:
  accessModes:
    - ReadWriteOnce
  resources:
    requests:
      storage: 1Gi
  storageClassName: basic-csi

```

8. Create the PVC by issuing the `kubectl` command. Creation can take some time depending on the size of the backing volume being created, so you can watch the process as it completes.

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ kubectl create -f
pvc-basic.yaml
persistentvolumeclaim/basic created
```

```
[ubuntu@gke-admin-ws-2021-07-15 trident-installer]$ kubectl get pvc
NAME      STATUS    VOLUME                                     CAPACITY
ACCESS MODES  STORAGECLASS  AGE
basic      Bound      pvc-3445b5cc-df24-453d-a1e6-b484e874349d  1Gi
RWO                                     basic-csi  5s
```

[Next: Advanced Configuration Options: Anthos with NetApp.](#)

## Advanced Configuration Options For Anthos

### Exploring load balancer options: Anthos with NetApp

An application deployed in Anthos is exposed to the world by a service, delivered by a load balancer deployed in the Anthos On Prem environment.

The following pages have additional information about load balancer options validated in the Anthos with NetApp solution:

- [F5 BIG-IP](#)
- [SeeSaw](#)

[Next: Solution validation/use cases: Anthos with NetApp.](#)

### Installing F5 BIG-IP load balancers: Anthos with NetApp

F5 BIG-IP is an Application Delivery Controller (ADC) that offers a broad set of advanced, production-grade traffic management and security services like L4-L7 load balancing, SSL/TLS offload, DNS, firewall, and many more. These services drastically increase the availability, security, and performance of your applications.

F5 BIG-IP can be deployed and consumed in various ways, including on dedicated hardware, in the cloud, or as a virtual appliance on-premises. Refer to the documentation here to explore and deploy F5 BIG-IP as per requirement.

F5 BIG-IP was the first of the bundled load balancer solutions available with Anthos On-Prem and was used in a number of the early Anthos Ready partner validations for the Anthos with NetApp solution.



F5 BIG-IP can be deployed in standalone or cluster mode. For the purpose of this validation, F5 BIG-IP was deployed in standalone mode, but, for production purposes, it is preferred to have a cluster of BIG-IPs to avoid a single point of failure.



An F5 BIG-IP system can be deployed on dedicated hardware, in the cloud, or as a virtual appliance on-premises with versions greater than 12.x for it to be integrated with F5 CIS. For the purpose of this document, the F5 BIG-IP system was validated as a virtual appliance, for example using the BIG-IP VE edition.

## Validated releases

This solution makes use of the virtual appliance deployed in VMware vSphere. Networking for the F5 Big-IP virtual appliance can be configured in a two-armed or three-armed configuration based on your network environment. The deployment in this document is based on the two-armed configuration. Additional details on configuring the virtual appliance for use with Anthos can be found [here](#).

The solutions engineering team at NetApp have validated the releases in the following table in our lab to work with deployments of Anthos On-Prem:

Make	Type	Version
F5	BIG-IP VE	15.0.1-0.0.11
F5	BIG-IP VE	16.1.0-0.0.19

## Installation

To install F5 BIG-IP, complete the following steps:

1. Download the virtual application Open Virtual Appliance (OVA) file from F5 [here](#).



To download the appliance, a user must register with F5. They provide a 30-day demo license for the Big-IP Virtual Edition Load Balancer. NetApp recommends a permanent 10Gbps license for the production deployment of an appliance.

2. Right-click the Infrastructure Resource Pool and select Deploy OVF Template. A wizard launches that allows you to select the OVA file that you just downloaded in Step 1. Click Next.

## Deploy OVF Template

### 1 Select an OVF template

2 Select a name and folder

3 Select a compute resource

4 Review details

5 Select storage

6 Ready to complete

### Select an OVF template

Select an OVF template from remote URL or local file system

Enter a URL to download and install the OVF package from the Internet, or browse to a location accessible from your computer, such as a local hard drive, a network share, or a CD/DVD drive.

☐ URL

http | https://remoteserver-address/filetodeploy.ovf | .ova

☒ Local file

Choose Files

BIGIP-15.0.1-0.....ALL-vmware.ova

CANCEL

BACK

NEXT

- Click Next to continue through each step and accept the default values for each screen presented until you reach the storage selection screen. Select the VM\_Datastore that was created earlier, and then click Next.
- The next screen presented by the wizard allows you to customize the virtual networks for use in the environment. Select VM\_Network for the External field and select Management\_Network for the Management field. Internal and HA are used for advanced configurations for the F5 Big-IP appliance and are not configured. These parameters can be left alone, or they can be configured to connect to non-infrastructure, distributed port groups. Click Next.
- Review the summary screen for the appliance, and, if all the information is correct, click Finish to start the deployment.
- After the virtual appliance is deployed, right-click it and power it up. It should receive a DHCP address on the management network. The appliance is Linux-based, and it has VMware Tools deployed, so you can view the DHCP address it receives in the vSphere client.
- Open a web browser and connect to the appliance at the IP address from the previous step. The default login is admin/admin, and, after the first login, the appliance immediately prompts you to change the admin password. It then returns you to a screen where you must log in with the new credentials.

**BIG-IP Configuration Utility**  
F5 Networks, Inc.

**Hostname**  
bigip1

**IP Address**  
172.21.224.20

**Username**  
admin

**Password**  
\*\*\*\*\*

**Log in**

Welcome to the BIG-IP Configuration Utility.

Log in with your username and password using the fields on the left.

(c) Copyright 1996-2019, F5 Networks, Inc., Seattle, Washington. All rights reserved.  
[F5 Networks, Inc. Legal Notices](#)

8. The first screen prompts the user to complete the Setup Utility. Begin the utility by clicking Next.

9. The next screen prompts for activation of the license for the appliance. Click Activate to begin. When prompted on the next page, paste either the 30-day evaluation license key you received when you registered for the download or the permanent license you acquired when you purchased the appliance. Click Next.



For the device to perform activation, the network defined on the management interface must be able to reach the internet.

10. On the next screen, the End User License Agreement (EULA) is presented. If the terms in the license are acceptable, click Accept.
11. The next screen counts the elapsed time as it verifies the configuration changes that have been made so far. Click Continue to resume with the initial configuration.
12. The Configuration Change window closes, and the Setup Utility displays the Resource Provisioning menu. This window lists the features that are currently licensed and the current resource allocations for the virtual appliance and each running service.
13. Clicking the Platform menu option on the left enables additional modification of the platform. Modifications include setting the management IP address configured with DHCP, setting the host name and the time zone the appliance is installed in, and securing the appliance from SSH accessibility.

14. Next click the Network menu, which enables you to configure standard networking features. Click Next to begin the Standard Network Configuration wizard.
15. The first page of the wizard configures redundancy; leave the defaults and click Next. The next page enables you to configure an internal interface on the load balancer. Interface 1.1 maps to the vmnic labeled Internal in the OVF deployment wizard.

[Big-IP Configuration] | *big-IP\_config\_8.png*



The spaces in this page for Self IP Address, Netmask, and Floating IP address can be filled with a non-routable IP for use as a placeholder. They can also be filled with an internal network that has been configured as a distributed port group for virtual guests if you are deploying the three-armed configuration. They must be completed to continue with the wizard.

16. The next page enables you to configure an external network that is used to map services to the pods deployed in Kubernetes. Select a static IP from the VM\_Network range, the appropriate subnet mask, and a floating IP from that same range. Interface 1.2 maps to the vmnic labeled External in the OVF deployment wizard.


[Big-IP Configuration] | *big-IP\_config\_9.png*

17. On the next page, you can configure an internal-HA network if you are deploying multiple virtual appliances in the environment. To proceed, you must fill the Self-IP Address and the Netmask fields, and you must select interface 1.3 as the VLAN Interface, which maps to the HA network defined by the OVF template wizard.
18. The next page enables you to configure the NTP servers. Then click Next to continue to the DNS setup. The DNS servers and domain search list should already be populated by the DHCP server. Click Next to accept the defaults and continue.
19. For the remainder of the wizard, click Next to continue through the advanced peering setup, the configuration of which is beyond the scope of this document. Then click Finish to exit the wizard.
20. Create individual partitions for the Anthos admin cluster and each user cluster deployed in the environment. Click System in the menu on the left, navigate to Users, and click Partition List.
21. The displayed screen only shows the current common partition. Click Create on the right to create the first additional partition, and name it GKE-Admin. Then click Repeat, and name the partition User-Cluster-1, and click the Repeat button again to name the next partition User-Cluster-2. Finally click Finished to complete the wizard. The Partition list screen returns with all the partitions now listed.

## Integration with Anthos

There is a section in each configuration file, respectively for the admin cluster, and each user cluster that you choose to deploy to configure the load balancer so that it will be managed by Anthos On Prem.

The following is a sample from the configuration of the partition for the GKE-Admin cluster, the values that need to be uncommented and modified are placed in bold text below:



```

# (Required) Load balancer configuration
loadBalancer:
# (Required) The VIPs to use for load balancing
vips:
# Used to connect to the Kubernetes API
controlPlaneVIP: "10.61.181.230"
# # (Optional) Used for admin cluster addons (needed for multi cluster
features). Must
# # be the same across clusters
# # addonsVIP: ""
# (Required) Which load balancer to use "F5BigIP" "Seesaw" or
"ManualLB". Uncomment
# the corresponding field below to provide the detailed spec
kind: F5BigIP
# # (Required when using "ManualLB" kind) Specify pre-defined nodeports
# manualLB:
# # NodePort for ingress service's http (only needed for user cluster)
# ingressHTTPTNodePort: 0
# # NodePort for ingress service's https (only needed for user
cluster)
# ingressHTTPSNodePort: 0
# # NodePort for control plane service
# controlPlaneNodePort: 30968
# # NodePort for addon service (only needed for admin cluster)
# addonsNodePort: 31405
# # (Required when using "F5BigIP" kind) Specify the already-existing
partition and
# # credentials
f5BigIP:
address: "172.21.224.21"
credentials:
username: "admin"
password: "admin-password"
partition: "GKE-Admin"
# # # (Optional) Specify a pool name if using SNAT
# # snatPoolName: ""
# (Required when using "Seesaw" kind) Specify the Seesaw configs
# seesaw:
# (Required) The absolute or relative path to the yaml file to use for
IP allocation
# for LB VMs. Must contain one or two IPs.
# ipBlockFilePath: ""
# (Required) The Virtual Router Identifier of VRRP for the Seesaw
group. Must
# be between 1-255 and unique in a VLAN.
# vrid: 0

```



```

# (Required) The IP announced by the master of Seesaw group
# masterIP: ""
# (Required) The number CPUs per machine
# cpus: 4
# (Required) Memory size in MB per machine
# memoryMB: 8192
# (Optional) Network that the LB interface of Seesaw runs in (default:
cluster
# network)
# vCenter:
# vSphere network name
# networkName: VM_Network
# (Optional) Run two LB VMs to achieve high availability (default:
false)
# enableHA: false

```

[Next: Solution Validation/Use Cases: Anthos with NetApp.](#)

## Installing SeeSaw load balancers: Anthos with NetApp

This page lists the installation and configuration instructions for the SeeSaw managed load balancer.

Seesaw is the default managed network load balancer installed in an Anthos Clusters on VMware environment.

### Installing The SeeSaw Load Balancer

The SeeSaw load balancer is fully integrated with Anthos Clusters on VMware and has automated deployment performed as part of the Admin and User cluster setups. There are blocks of text in the `cluster.yaml` configuration files that must be modified to provide load balancer info, and then there is an additional step prior to cluster deployment to deploy the load balancer using the built in 'gkectl' tool.



SeeSaw load balancers can be deployed in HA or Non-HA mode. For the purpose of this validation, the SeeSaw load balancer was deployed in Non-HA mode, which is the default setting. For production purposes, NetApp recommends deploying SeeSaw in an HA configuration for fault tolerance and reliability.

### Integration with Anthos

There is a section in each configuration file, respectively for the admin cluster, and each user cluster that you choose to deploy to configure the load balancer so that it is managed by Anthos On-Prem.

The following text is a sample from the configuration of the partition for the GKE-Admin cluster. The values that need to be uncommented and modified are placed in bold text below:

```

loadBalancer:
# (Required) The VIPs to use for load balancing
vips:
# Used to connect to the Kubernetes API

```

```

controlPlaneVIP: "10.61.181.230"
# # (Optional) Used for admin cluster addons (needed for multi cluster
features). Must
# # be the same across clusters
# # addonsVIP: ""
# (Required) Which load balancer to use "F5BigIP" "Seesaw" or
"ManualLB". Uncomment
# the corresponding field below to provide the detailed spec
kind: Seesaw
# # (Required when using "ManualLB" kind) Specify pre-defined nodeports
# manualLB:
# # NodePort for ingress service's http (only needed for user cluster)
# ingressHTTPNodePort: 0
# # NodePort for ingress service's https (only needed for user
cluster)
# ingressHTTPSNodePort: 0
# # NodePort for control plane service
# controlPlaneNodePort: 30968
# # NodePort for addon service (only needed for admin cluster)
# addonsNodePort: 31405
# # (Required when using "F5BigIP" kind) Specify the already-existing
partition and
# # credentials
# f5BigIP:
# address:
# credentials:
# username:
# password:
# partition:
# # # (Optional) Specify a pool name if using SNAT
# # snatPoolName: ""
# (Required when using "Seesaw" kind) Specify the Seesaw configs
seesaw:
# (Required) The absolute or relative path to the yaml file to use for
IP allocation
# for LB VMs. Must contain one or two IPs.
ipBlockFilePath: "admin-seesaw-block.yaml"
# (Required) The Virtual Router Identifier of VRRP for the Seesaw
group. Must
# be between 1-255 and unique in a VLAN.
vrid: 100
# (Required) The IP announced by the master of Seesaw group
masterIP: "10.61.181.236"
# (Required) The number CPUs per machine
cpus: 1
# (Required) Memory size in MB per machine

```

```

memoryMB: 2048
#   (Optional) Network that the LB interface of Seesaw runs in (default:
cluster
#   network)
vCenter:
#   vSphere network name
networkName: VM_Network
#   (Optional) Run two LB VMs to achieve high availability (default:
false)
enableHA: false

```

The SeeSaw load balancer also has a separate static 'seesaw-block.yaml' file that must be provided for each cluster deployment. This file must be located in the same directory relative to the cluster.yaml deployment file, or the full path must be specified in the section above.

A sample of the admin-seesaw-block.yaml file looks like the following:

```

blocks:
- netmask: "255.255.255.0"
  gateway: "10.63.172.1"
  ips:
- ip: "10.63.172.152"
  hostname: "admin-seesaw-vm"

```



This file provides the gateway and netmask for the network that the load balancer provides to the underlying cluster, as well as the management IP and hostname for the virtual machine that is deployed to run the load balancer.

[Next: Solution validation/use cases: Anthos with NetApp.](#)

## Solution Validation and Use Cases: Anthos with NetApp

The examples provided on this page are solution validations and use cases for Anthos with NetApp.

[Next: Videos and Demos: Anthos with NetApp.](#)

## Videos and Demos: Anthos with NetApp

The following video demonstrate some of the capabilities documented in this document:

[Next: Additional Information: Anthos with NetApp.](#)

## Additional Information: Anthos with NetApp

To learn more about the information described in this document, review the following websites:

- [NetApp Documentation](#)

<https://docs.netapp.com/>

- NetApp Astra Trident Documentation

<https://docs.netapp.com/us-en/trident/index.html>

- NetApp Astra Control Center Documentation

<https://docs.netapp.com/us-en/astra-control-center/>

- Anthos Clusters on VMware Documentation

<https://cloud.google.com/anthos/clusters/docs/on-prem/1.10/overview>

- Anthos on bare metal Documentation

<https://cloud.google.com/anthos/clusters/docs/bare-metal/latest>

- VMware vSphere Documentation

<https://docs.vmware.com/>

## Copyright Information

Copyright © 2022 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

## Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.