■ NetApp

Customer scenarios

NetApp Solutions

NetApp July 25, 2022

This PDF was generated from https://docs.netapp.com/us-en/netapp-solutions/xcp/xcp-bp-customer-scenarios-overview.html on July 25, 2022. Always check docs.netapp.com for the latest.

Table of Contents

C	Sustomer scenarios	. 1
	Overview	. 1
	Data lake to ONTAP NFS	. 1
	High-performance computing to ONTAP NFS	. 2
	Using the XCP Data Mover to migrate millions of small files to flexible storage	. 2
	Using the XCP Data Mover to migrate large files.	. 3
	Duplicate files	. 3
	Specific date-based scan and copy of data	. 5
	Creating a CSV file from SMB/CIFS share	. 6
	Data migration from 7-Mode to ONTAP	. 7
	CIFS data migration with ACLs from a source storage box to ONTAP	45

Customer scenarios

Overview

Previous: Performance tuning.

This section describes customer scenarios and their architectures.

Next: Data lake to ONTAP NFS.

Data lake to ONTAP NFS

Previous: Customer scenarios.

This use case is based on the largest financial customer proof of concept (CPOC) that we have done. Historically, we used the NetApp In-Place Analytics Module (NIPAM) to move analytics data to NetApp ONTAP AI. However, because of recent enhancements and the improved performance of NetApp XCP as well as the unique NetApp data mover solution approach, we reran the data migration using NetApp XCP.

Customer challenges and requirements

Customer challenges and requirements that are worth noting include the following:

- Customers have different types of data, including structured, unstructured, and semistructured data, logs, and machine-to-machine data in data lakes. All systems require all these types of data to process for prediction operations. When data is in a data lake-native file system, it is difficult to process.
- The customer's Al architecture is not able to access data from Hadoop Distributed File System (HDFS) and Hadoop Compatible File System (HCFS), so the data is not available to Al operations. Al requires data in an understandable file system format such as NFS.
- Some special processes are required to move data from the data lake because of the large amount of data and high-throughput, and a cost-effective method is required to move the data to the AI system.

Data mover solution

In this solution, the MapR File System (MapR-FS) is created from local disks in the MapR cluster. The MapR NFS Gateway is configured on each data node with virtual IPs. The file server service stores and manages the MapR-FS data. NFS Gateway makes Map-FS data accessible from the NFS client through the virtual IP. An XCP instance is running on each MapR data node to transfer the data from the Map NFS Gateway to NetApp ONTAP NFS. Each XCP instance transfers a specific set of source folders to the destination location.

The following figure illustrates the NetApp data mover solution for MapR cluster using XCP.



For detailed customer use cases, recorded demos, and test results, see the Using XCP to Move Data from a Data Lake and High-Performance Computing to ONTAP NFS blog.

For detailed steps on moving MapR-FS data into ONTAP NFS by using NetApp XCP, see Appendix B in TR-4732: Big Data Analytics Data to Artificial Intelligence.

Next: High-performance computing to ONTAP NFS.

High-performance computing to ONTAP NFS

Previous: Data lake to ONTAP NFS.

This use case is based on requests from field organizations. Some NetApp customers have their data in a high-performance computing environment, which provides data analytics for training models and enables research organizations to gain insight and understanding of large amount of digital data. NetApp field engineers need a detailed procedure to extract the data from IBM's GPFS to NFS. We used NetApp XCP to migrate the data from GPFS to NFS so that GPUs can process the data. All typically processes data from a network file system.

For more information about the high-performance computing to ONTAP NFS use case, a recorded demo, and test results, see the Using XCP to Move Data from a Data Lake and High-Performance Computing to ONTAP NFS blog.

For detailed steps on moving MapR-FS data into ONTAP NFS by using NetApp XCP, see Appendix A: GPFS to NFS—Detailed Steps in TR-4732: Big Data Analytics Data to Artificial Intelligence.

Next: Using the XCP Data Mover to migrate millions of small files to flexible storage.

Using the XCP Data Mover to migrate millions of small files to flexible storage

Previous: High-performance computing to ONTAP NFS.

This use case is based on the largest NetApp tourism industry customer for on-premises-to-cloud data migration. Because COVID-19 has reduced demand in the travel industry, customers want to save capital expenses on high-end storage in their on-premises environment for the demand pricing application. This customer has a tight SLA to migrate millions of small files to the cloud.

The following figure depicts data migration from on-premises to Azure NetApp Files for small files.



For more information, see the NetApp XCP Data Mover Solution: On Premises to Cloud blog.

Next: Using the XCP Data Mover to migrate large files.

Using the XCP Data Mover to migrate large files

Previous: Using the XCP Data Mover to migrate millions of small files to flexible storage.

This use case is based on a television network customer. The customer wanted to migrate Oracle Recovery Manager (RMAN) backup files to the cloud and run the Oracle E-Business Suite (EBS) application by using Azure NetApp Files with Pacemaker software. The customer also wanted to migrate their database backup files to on-demand cloud storage and transfer large files (in the range of 25GB to 50GB each) to Azure.

The following figure illustrates the data migration from on-premises to Azure NetApp Files for large files.

For more information, see the NetApp XCP Data Mover Solution: On Premises to Cloud blog.

Next: Duplicate files.

Duplicate files

Previous: Using the XCP Data Mover to migrate large files.

NetApp received a request to find duplicate files from a single volume or multiple volumes. NetApp provided the following solution.

For single volume, run the following commands:

```
[root@mastr-51 linux] # ./xcp -md5 -match 'type==f and nlinks==1 and size
!= 0' 10.63.150.213:/common volume/nfsconnector hw cert/ | sort | uniq -cd
--check-chars=32
XCP 1.5; (c) 2020 NetApp, Inc.; Licensed to Calin Salagean [NetApp Inc]
until Mon Dec 31 00:00:00 2029
176,380 scanned, 138,116 matched, 138,115 summed, 10 giants, 61.1 GiB in
(763 MiB/s), 172 MiB out (2.57 MiB/s), 1m5s
Filtered: 38264 did not match
176,380 scanned, 138,116 matched, 138,116 summed, 10 giants, 62.1 GiB in
(918 MiB/s), 174 MiB out (2.51 MiB/s), 1m9s.
      3 00004964ca155eca1a71d0949c82e37e
nfsconnector hw cert/grid 01082017 174316/0/hadoopqe/accumulo/shell/pom.xm
      2 000103fbed06d8071410c59047738389
nfsconnector hw cert/usr hdp/2.5.3.0-37/hive2/doc/examples/files/dim-
data.txt
      2 000131053a46d67557d27bb678d5d4a1
nfsconnector hw cert/grid 01082017 174316/0/log/cluster/mahout 1/artifacts
/classifier/20news reduceddata/20news-bydate-test/alt.atheism/53265
```

For multiple volumes, run the following commands:

```
[root@mastr-51 linux]# cat multiplevolume_duplicate.sh
#! /usr/bin/bash

#user input
JUNCTION_PATHS='/nc_volume1 /nc_volume2 /nc_volume3 /oplogarchivevolume'
NFS_DATA_LIF='10.63.150.213'

#xcp operation
for i in $JUNCTION_PATHS
do
echo "start - $i" >> /tmp/duplicate_results
/usr/src/xcp/linux/xcp -md5 -match 'type==f and nlinks==1 and size != 0'
${NFS_DATA_LIF}:$i | sort | uniq -cd --check-chars=32 | tee -a
/tmp/duplicate_results
echo "end - $i" >> /tmp/duplicate_results
done

[root@mastr-51 linux]# nohup bash +x multiplevolume_duplicate.sh &
[root@mastr-51 linux]# cat /tmp/duplicate_results
```

Specific date-based scan and copy of data

Previous: Duplicate files.

This solution is based on a customer who needs to copy data based on a specific date. Verify the following details:

```
Created a file in Y: and checked the scan command to list them.
c:\XCP>dir Y:\karthik test
Volume in drive Y is from
Volume Serial Number is 80F1-E201
 Directory of Y:\karthik test
05/26/2020 02:51 PM
                       <DIR>
05/26/2020 02:50 PM <DIR>
05/26/2020 02:51 PM
                                2,295 testfile.txt
              1 File(s)
                                 2,295 bytes
              2 Dir(s) 658,747,392 bytes free
c:\XCP>
c:\XCP>xcp scan -match "strftime(ctime,'%Y-%m-%d')>'2020-05-01'" -fmt
"'{},{}'.format(iso(mtime),name)" Y:\
XCP SMB 1.6; (c) 2020 NetApp, Inc.; Licensed to Calin Salagean [NetApp
Inc] until Mon Dec 31 00:00:00 2029
It appears that you are not running XCP as Administrator. To avoid access
issues please run XCP as Administrator.
2020-05-26 14:51:13.132465, testfile.txt
2020-05-26 14:51:00.074216, karthik test
xcp scan -match strftime(ctime,'%Y-%m-%d')>'2020-05-01' -fmt
'{},{}'.format(iso(mtime),name) Y:\ : PASSED
30,205 scanned, 2 matched, 0 errors
Total Time : 4s
STATUS : PASSED
Copy the files based on date (2020 YearMay month first date) from Y: to
c:\XCP>xcp copy -match "strftime(ctime,'%Y-%m-%d')>'2020-05-01'" Y:
Z:\dest karthik
```

```
XCP SMB 1.6; (c) 2020 NetApp, Inc.; Licensed to Calin Salagean [NetApp
Inc] until Mon Dec 31 00:00:00 2029
It appears that you are not running XCP as Administrator. To avoid access
issues please run XCP as Administrator.
30,205 scanned, 3 matched, 0 copied, 0 errors, 5s
xcp copy -match strftime(ctime,'%Y-%m-%d')>'2020-05-01' Y: Z:\dest karthik
30,205 scanned, 3 matched, 2 copied, 0 errors
Total Time : 6s
STATUS : PASSED
c:\XCP>
Check the destination Z:
c:\XCP>dir Z:\dest karthik\karthik test
Volume in drive Z is to
Volume Serial Number is 80F1-E202
 Directory of Z:\dest karthik\karthik test
05/26/2020 02:51 PM <DIR>
05/26/2020 02:50 PM <DIR>
05/26/2020 02:51 PM
                               2,295 testfile.txt
              1 File(s)
                                2,295 bytes
              2 Dir(s) 659,316,736 bytes free
c:\XCP>
```

Next: Creating a CSV file from SMB/CIFS share.

Creating a CSV file from SMB/CIFS share

Previous: Specific date-based scan and copy of data.

The following command dumps data in the CSV format. You can sum up the size column to get the total size of the data.

```
xcp scan -match "((now-x.atime) / 3600) > 31*day" -fmt "'{}, {},
{}'.format(relpath, name, strftime(x.atime, '%y-%m-%d-%H:%M:%S'),
humanize_size(size))" -preserve-atime >file.csv
```

The output should look similar to this example:

```
erase\report_av_fp_cdot_crosstab.csvreport_av_fp_cdot_crosstab.csv20-01-29-10:26:2449.6MiB
```

To scan up to the depth of three subdirectories and provide the result in sorting order, run the xcp -du command and dump the size at each directory level up to the depth of three subdirectories.

```
./xcp scan -du -depth 3 NFS_Server_IP:/source_vol
```

To sort, dump the information to a CSV file and sort the information.

```
xcp scan -match "type == d" -depth 3 -fmt "'{}, {}, {}'.format(name,
relpath, size)" NFS_Server_IP:/share > directory_report.csv
```

This is a custom report that uses the <code>-fmt</code> command. It scans all the directories and dumps the name of the directory, path, and size of directory into a CSV file. You can sort the size column from the spreadsheet application.

Next: Data migration from 7-Mode to ONTAP.

Data migration from 7-Mode to ONTAP

Previous: Creating a CSV file from SMB/CIFS share.

This section provides detailed steps for migrating data from NetApp Data ONTAP operating in 7-Mode to ONTAP.

Transitioning 7-Mode NFSv3 storage to ONTAP for NFS data

This section provides the step-by-step procedure in the following table for transitioning a source 7-Mode NFSv3 export to an ONTAP system.

NetApp assumes that the source 7-Mode NFSv3 volume is exported and mounted on the client system and that XCP is already installed on a Linux system.

1. Verify that the target ONTAP system is healthy.

	uster sh	OW					
Node		Health	Eligibi	lity			
CLUSTER-01							
CLUSTER-02			true				
2 entries wer	e displa	yed.					
CLUSTER::> no	de show						
Node Hea	ılth Elig	ibility	Uptime		Model	Owner	Location
CLUSTER-01							
tru	ie true		78 days	21:01	FAS8060		RTP
CLUSTER-02							
tru	ie true		78 days	20:50	FAS8060		RTP
2 entries wer	e displa	yed.					
CLUSTER::> st	orage fa	ilover s	show				
	_		Takeove	r			
Node	Partne	r	Possibl	e Stat	te Descri	ption	
				_	•		
CLUSTER-01	CLUSTE	R-02	true	Conr	nected to	CLUSTER-02	
CLUSTER-02							

2. Verify that at least one nonroot aggregate exists on the target system. The aggregate is normal.

If there is no data aggregate, create a new one using the storage aggr create command.

3. Create a storage virtual machine (SVM) on the target cluster system.

```
CLUSTER::> vserver create -vserver dest -rootvolume dest root -aggregate
poc -rootvolume-security-style mixed
[Job 647] Job succeeded:
Vserver creation completed
Verify the security style and language settings of the source
Verify that the SVM was successfully created.
CLUSTER::> vserver show -vserver dest
                                    Vserver: dest
                               Vserver Type: data
                            Vserver Subtype: default
                               Vserver UUID: 91f6d786-0063-11e5-b114-
00a09853a969
                                Root Volume: dest root
                                  Aggregate: poc
                                 NIS Domain: -
                 Root Volume Security Style: mixed
                                LDAP Client: -
               Default Volume Language Code: C.UTF-8
                            Snapshot Policy: default
                                    Comment:
                               Quota Policy: default
                List of Aggregates Assigned: -
 Limit on Maximum Number of Volumes allowed: unlimited
                        Vserver Admin State: running
                  Vserver Operational State: running
   Vserver Operational State Stopped Reason: -
                          Allowed Protocols: nfs, cifs, fcp, iscsi, ndmp
                       Disallowed Protocols: -
            Is Vserver with Infinite Volume: false
                           QoS Policy Group: -
                                Confiq Lock: false
                               IPspace Name: Default
```

4. Remove the FCP, iSCSI, NDMP, and CIDS protocols from the target SVM.

```
CLUSTER::> vserver remove-protocols -vserver dest -protocols fcp,iscsi,ndmp,cifs
```

Verify that NFS is the allowed protocol for this SVM.

```
CLUSTER::> vserver show -vserver dest -fields allowed-protocols vserver allowed-protocols ------ dest nfs
```

5. Create a new read-write data volume on the destination SVM. Verify that the security style, language settings, and capacity requirements match the source volume.

```
CLUSTER::> vol create -vserver dest -volume dest_nfs -aggregate poc -size 150g -type RW -state online -security-style mixed [Job 648] Job succeeded: Successful
```

6. Create a data LIF to serve NFS client requests.

```
CLUSTER::> network interface create -vserver dest -lif dest_lif -address 10.61.73.115 -netmask 255.255.255.0 -role data -data-protocol nfs -home -node CLUSTER-01 -home-port e01
```

Verify that the LIF was successfully created.

```
CLUSTER::> network interface show -vserver dest
Logical Status Network Current

Current Is

Vserver Interface Admin/Oper Address/Mask Node Port

Home
------
dest
dest_lif
up/up 10.61.73.113/24 CLUSTER-01 e0i

true
```

7. Create a static route with the SVM, if required.

```
CLUSTER::> network route create -vserver dest -destination 0.0.0.0/0 -gateway 192.168.100.111
```

Verify that the route was successfully created.

```
CLUSTER::> network route show -vserver source

Vserver Destination Gateway Metric

dest

0.0.0.0/0 10.61.73.1 20
```

8. Mount the target NFS data volume in the SVM namespace.

```
CLUSTER::> volume mount -vserver dest -volume dest_nfs -junction-path /dest_nfs -active true
```

Verify that the volume is successfully mounted.

```
CLUSTER::> volume show -vserver dest -fields junction-path
vserver volume junction-path
------
dest dest_nfs /dest_nfs
dest dest_root
/
2 entries were displayed.
```

You can also specify volume mount options (junction path) with the volume create command.

9. Start the NFS service on the target SVM.

```
CLUSTER::> vserver nfs start -vserver dest
```

Verify that the service is started and running.

```
CLUSTER::> vserver nfs status
The NFS server is running on Vserver "dest".

CLUSTER::> nfs show
Vserver: dest

General Access: true

v3: enabled

v4.0: disabled

4.1: disabled

UDP: enabled

TCP: enabled

Default Windows User: -

Default Windows Group: -
```

10. Verify that the default NFS export policy was applied to the target SVM.

11. If required, create a new custom export policy for the target SVM.

```
CLUSTER::> vserver export-policy create -vserver dest -policyname xcpexportpolicy
```

Verify that the new custom export policy was successfully created.

12. Modify the export policy rules to allow access to NFS clients.

```
CLUSTER::> export-policy rule modify -vserver dest -ruleindex 1
-policyname xcpexportpolicy -clientmatch 0.0.0.0/0 -rorule any -rwrule
any -anon 0
Verify the policy rules have modified
CLUSTER::> export-policy rule show -instance
                                    Vserver: dest
                                Policy Name: xcpexportpolicy
                                 Rule Index: 1
                            Access Protocol: nfs3
Client Match Hostname, IP Address, Netgroup, or Domain: 0.0.0.0/0
                             RO Access Rule: none
                             RW Access Rule: none
User ID To Which Anonymous Users Are Mapped: 65534
                   Superuser Security Types: none
               Honor SetUID Bits in SETATTR: true
                  Allow Creation of Devices: true
```

13. Verify that the client is allowed access to the volume.

```
CLUSTER::> export-policy check-access -vserver dest -volume dest nfs
-client-ip 10.61.82.215 -authentication-method none -protocol nfs3
-access-type read-write
                                        Policy
                                                  Policy Rule
Path
                                                  Owner Type Index
                             Policy
                                        Owner
Access
                             xcpexportpolicy
                                        dest root volume
                                                                  1
read
/dest nfs
                             xcpexportpolicy
                                        dest nfs volume
                                                                  1
read-write
2 entries were displayed.
```

14. Connect to the Linux NFS server. Create a mount point for the NFS exported volume.

```
[root@localhost /]# cd /mnt
[root@localhost mnt]# mkdir dest
```

15. Mount the target NFSv3 exported volume at this mount point.



The NFSv3 volumes should be exported but not necessarily mounted by the NFS server. If they can be mounted, the XCP Linux host client mounts these volumes.

```
[root@localhost mnt]# mount -t nfs 10.61.73.115:/dest_nfs /mnt/dest
```

Verify that the mount point was successfully created.

```
[root@ localhost /]# mount | grep nfs
10.61.73.115:/dest_nfs on /mnt/dest type nfs
(rw,relatime,vers=3,rsize=65536,wsize=65536,namlen=255,hard,proto=tcp,ti
meo=600,retrans=2,sec=sys,mountaddr=10.61.82.215,mountvers=3,mountport=4
046,mountproto=udp,local_lock=none,addr=10.61.73.115)
```

16. Create a test file on the NFS exported mount point to enable read-write access.

```
[root@localhost dest]# touch test.txt
Verify the file is created
[root@localhost dest]# ls -l
total 0
-rw-r--r-- 1 root bin 0 Jun 2 03:16 test.txt
```



After the read-write test is complete, delete the file from the target NFS mount point.

17. Connect to the Linux client system in which XCP is installed. Browse to the XCP install path.

```
[root@localhost ~]# cd /linux/
[root@localhost linux]#
```

18. Query the source 7-Mode NFSv3 exports by running the xcp show command on the XCP Linux client host system.

```
[root@localhost]#./xcp show 10.61.82.215
== NFS Exports ==
Mounts Errors Server
     4
          0 10.61.82.215
            Files
                        Space
                               Files
    Space
     Free
             Free
                        Used
                                Used Export
 23.7 GiB 778,134 356 KiB
                                   96 10.61.82.215:/vol/nfsvol1
  17.5 GiB 622,463 1.46 GiB
                                  117 10.61.82.215:/vol/nfsvol
  328 GiB 10.8M 2.86 GiB
                               7,904 10.61.82.215:/vol/vol0/home
                                7,904 10.61.82.215:/vol/vol0
  328 GiB
            10.8M 2.86 GiB
== Attributes of NFS Exports ==
drwxr-xr-x --- root wheel 4KiB 4KiB 2d21h 10.61.82.215:/vol/nfsvol1
drwxr-xr-x --- root wheel 4KiB 4KiB 2d21h 10.61.82.215:/vol/nfsvol
drwxrwxrwx --t root wheel 4KiB 4KiB 9d22h 10.61.82.215:/vol/vol0/home
drwxr-xr-x --- root wheel 4KiB 4KiB 4d0h 10.61.82.215:/vol/vol0
3.89 KiB in (5.70 \text{ KiB/s}), 7.96 KiB out (11.7 \text{ KiB/s}), 0s.
```

19. Scan the source NFSv3 exported paths and print the statistics of their file structure.

NetApp recommends putting the source NFSv3 exports in read-only mode during xcp scan, copy, and sync operations.

```
[root@localhost /]# ./xcp scan 10.61.82.215:/vol/nfsvol
nfsvol
nfsvol/n5000-uk9.5.2.1.N1.1.bin
nfsvol/821_q_image.tgz
nfsvol/822RC2_q_image.tgz
nfsvol/NX5010_12_node_RCF_v1.3.txt
nfsvol/n5000-uk9-kickstart.5.2.1.N1.1.bin
nfsvol/NetApp_CN1610_1.1.0.5.stk
nfsvol/glibc-common-2.7-2.x86_64.rpm
nfsvol/glibc-2.7-2.x86_64.rpm
nfsvol/rhel-server-5.6-x86_64-dvd.iso.filepart
nfsvol/xcp
nfsvol/xcp_source
nfsvol/catalog
23 scanned, 7.79 KiB in (5.52 KiB/s), 1.51 KiB out (1.07 KiB/s), 1s.
```

20. Copy the source 7-Mode NFSv3 exports to NFSv3 exports on the target ONTAP system.

```
[root@localhost /]# ./xcp copy 10.61.82.215:/vol/nfsvol
10.61.73.115:/dest_nfs
44 scanned, 39 copied, 264 MiB in (51.9 MiB/s), 262 MiB out (51.5 MiB/s), 5s
44 scanned, 39 copied, 481 MiB in (43.3 MiB/s), 479 MiB out (43.4 MiB/s), 10s
44 scanned, 40 copied, 748 MiB in (51.2 MiB/s), 747 MiB out (51.3 MiB/s), 16s
44 scanned, 40 copied, 1.00 GiB in (55.9 MiB/s), 1.00 GiB out (55.9 MiB/s), 21s
44 scanned, 40 copied, 1.21 GiB in (42.8 MiB/s), 1.21 GiB out (42.8 MiB/s), 26s
Sending statistics...
44 scanned, 43 copied, 1.46 GiB in (47.6 MiB/s), 1.45 GiB out (47.6 MiB/s), 31s.
```

21. After the copy is finished, verify that the source and destination NFSv3 exports have identical data. Run the xcp verify command.

```
[root@localhost /]# ./xcp verify 10.61.82.215:/vol/nfsvol
10.61.73.115:/dest_nfs
44 scanned, 44 found, 28 compared, 27 same data, 2.41 GiB in (98.4 MiB/s), 6.25 MiB out (255 KiB/s), 26s
44 scanned, 44 found, 30 compared, 29 same data, 2.88 GiB in (96.4 MiB/s), 7.46 MiB out (249 KiB/s), 31s
44 scanned, 100% found (43 have data), 43 compared, 100% verified (data, attrs, mods), 2.90 GiB in (92.6 MiB/s), 7.53 MiB out (240 KiB/s), 32s.
```

If xcp verify finds differences between the source and destination data, then the error no such file or directory is reported in the summary. To fix that issue, run the xcp sync command to copy the source changes to the destination.

22. Before and during the cutover, run <code>verify</code> again. If the source has new or updated data, then perform incremental updates. Run the <code>xcp sync</code> command.

```
For this operation, the previous copy index name or number is required. [root@localhost /]# ./xcp sync -id 3
Index: {source: '10.61.82.215:/vol/nfsvol', target:
'10.61.73.115:/dest_nfs1'}
64 reviewed, 64 checked at source, 6 changes, 6 modifications, 51.7 KiB in (62.5 KiB/s), 22.7 KiB out (27.5 KiB/s), 0s.
xcp: sync '3': Starting search pass for 1 modified directory...
xcp: sync '3': Found 6 indexed files in the 1 changed directory
xcp: sync '3': Rereading the 1 modified directory to find what's new...
xcp: sync '3': Deep scanning the 1 directory that changed...
11 scanned, 11 copied, 12.6KiB in (6.19KiBps), 9.50 KiB out (4.66KiBps),
2s.
```

23. To resume a previously interrupted copy operation, run the xcp resume command.

```
[root@localhost /]# ./xcp resume -id 4
Index: {source: '10.61.82.215:/vol/nfsvol', target:
'10.61.73.115:/dest nfs7'}
xcp: resume '4': WARNING: Incomplete index.
xcp: resume '4': Found 18 completed directories and 1 in progress
106 reviewed, 24.2 KiB in (30.3 KiB/s), 7.23 KiB out (9.06 KiB/s), 0s.
xcp: resume '4': Starting second pass for the in-progress directory...
xcp: resume '4': Found 3 indexed directories and 0 indexed files in the
1 in-progress directory
xcp: resume '4': In progress dirs: unindexed 1, indexed 0
xcp: resume '4': Resuming the 1 in-progress directory...
 20 scanned, 7 copied, 205 MiB in (39.6 MiB/s), 205 MiB out (39.6
MiB/s), 5s
 20 scanned, 14 copied, 425 MiB in (42.1 MiB/s), 423 MiB out (41.8
MiB/s), 11s
 20 scanned, 14 copied, 540 MiB in (23.0 MiB/s), 538 MiB out (23.0
MiB/s), 16s
 20 scanned, 14 copied, 721 MiB in (35.6 MiB/s), 720 MiB out (35.6
MiB/s), 21s
 20 scanned, 15 copied, 835 MiB in (22.7 MiB/s), 833 MiB out (22.7
MiB/s), 26s
 20 scanned, 16 copied, 1007 MiB in (34.3 MiB/s), 1005 MiB out (34.3
MiB/s), 31s
 20 scanned, 17 copied, 1.15 GiB in (33.9 MiB/s), 1.15 GiB out (33.9
MiB/s), 36s
 20 scanned, 17 copied, 1.27 GiB in (25.5 MiB/s), 1.27 GiB out (25.5
MiB/s), 41s
 20 scanned, 17 copied, 1.45 GiB in (36.1 MiB/s), 1.45 GiB out (36.1
 20 scanned, 17 copied, 1.69 GiB in (48.7 MiB/s), 1.69 GiB out (48.7
MiB/s), 51s
Sending statistics...
20 scanned, 20 copied, 21 indexed, 1.77 GiB in (33.5 MiB/s), 1.77 GiB
out (33.4 \text{ MiB/s}), 54s.
```

After resume finishes copying files, run verify again so that the source and destination storage have identical data.

24. The NFSv3 client host needs to unmount the source NFSv3 exports provisioned from the 7-Mode storage and mounts the target NFSv3 exports from ONTAP. Cutover requires an outage.

Transitioning 7-Mode volume Snapshot copies to ONTAP

This section covers the procedure for transitioning a source 7-Mode volume NetApp Snapshot copy to ONTAP.



NetApp assumes that the source 7-Mode volume is exported and mounted on the client system and that XCP is already installed on a Linux system. A Snapshot copy is a point-in-time image of a volume that records incremental changes since the last Snapshot copy. Use the -snap option with a 7-Mode system as the source.

Warning: Keep the base Snapshot copy. Do not delete the base Snapshot copy after the baseline copy is complete. The base Snapshot copy is required for further sync operations.

1. Verify that the target ONTAP system is healthy.

NT1 -		TT 1 + 1-	m12 - 21-21	2 4		
Node		Health	Ellgibli.	1ty 		
CLUSTER-C	1	true	true			
CLUSTER-C	12	true	true			
2 entries	were o	lisplayed.				
CLUSTER::	> node	show				
Node	Health	Eligibility	Uptime	Model	Owner	Location
						-
CLUSTER-C	1					
	true	true	78 days 2	1:01 FAS8060		RTP
CLUSTER-C	12					
	true	true	78 days 2	0:50 FAS8060		RTP
2 entries	were c	lisplayed.				
CLUSTER::	> stora	ge failover :	show			
			Takeover			
Node	E	Partner	Possible	State Descrip	otion	
CLUSTER-C	1 (CLUSTER-02	true	Connected to	CLUSTER-02	
CLUSTER-C	12	CLUSTER-01	true	Connected to	CLUSTER-01	
2 ontrios	ware c	lisplayed.				

2. Verify that at least one nonroot aggregate exists on the target system. The aggregate is normal.

If there is no data aggregate, create a new one using the storage aggr create command.

3. Create an SVM on the target cluster system.

```
CLUSTER::> vserver create -vserver dest -rootvolume dest root -aggregate
poc -rootvolume-security-style mixed
[Job 647] Job succeeded:
Vserver creation completed
Verify the security style and language settings of the source
Verify that the SVM was successfully created.
CLUSTER::> vserver show -vserver dest
                                    Vserver: dest
                               Vserver Type: data
                            Vserver Subtype: default
                               Vserver UUID: 91f6d786-0063-11e5-b114-
00a09853a969
                                Root Volume: dest root
                                  Aggregate: poc
                                 NIS Domain: -
                 Root Volume Security Style: mixed
                                LDAP Client: -
               Default Volume Language Code: C.UTF-8
                            Snapshot Policy: default
                                    Comment:
                               Quota Policy: default
                List of Aggregates Assigned: -
 Limit on Maximum Number of Volumes allowed: unlimited
                        Vserver Admin State: running
                  Vserver Operational State: running
   Vserver Operational State Stopped Reason: -
                          Allowed Protocols: nfs, cifs, fcp, iscsi, ndmp
                       Disallowed Protocols: -
            Is Vserver with Infinite Volume: false
                           QoS Policy Group: -
                                Confiq Lock: false
                               IPspace Name: Default
```

4. Remove the FCP, iSCSI, NDMP, and CIFS protocols from the target SVM.

5. Create a new read-write data volume on the destination SVM. Verify that the security style, language settings, and capacity requirements match the source volume.

```
CLUSTER::> vol create -vserver dest -volume dest_nfs -aggregate poc -size 150g -type RW -state online -security-style mixed [Job 648] Job succeeded: Successful
```

6. Create a data LIF to serve NFS client requests.

```
CLUSTER::> network interface create -vserver dest -lif dest_lif -address 10.61.73.115 -netmask 255.255.255.0 -role data -data-protocol nfs -home -node CLUSTER-01 -home-port e01
```

Verify that the LIF was successfully created.

```
CLUSTER::> network interface show -vserver dest
Logical Status Network Current

Current Is
Vserver Interface Admin/Oper Address/Mask Node Port

Home

dest
dest_lif
up/up 10.61.73.113/24 CLUSTER-01 e0i

true
```

7. If required, create a static route with the SVM.

```
CLUSTER::> network route create -vserver dest -destination 0.0.0.0/0 -gateway 192.168.100.111
```

Verify that the route was successfully created.

```
CLUSTER::> network route show -vserver source

Vserver Destination Gateway Metric

dest

0.0.0.0/0 10.61.73.1 20
```

8. Mount the target NFS data volume in the SVM namespace.

```
CLUSTER::> volume mount -vserver dest -volume dest_nfs -junction-path /dest_nfs -active true
```

Verify that the volume was successfully mounted.

```
CLUSTER::> volume show -vserver dest -fields junction-path
vserver volume junction-path
------
dest dest_nfs /dest_nfs
dest dest_root
/
2 entries were displayed.
```

You can also specify the volume mount options (junction path) with the volume create command.

9. Start the NFS service on the target SVM.

```
CLUSTER::> vserver nfs start -vserver dest
```

Verify that the service is started and running.

```
CLUSTER::> vserver nfs status
The NFS server is running on Vserver "dest".

CLUSTER::> nfs show
Vserver: dest

General Access: true

v3: enabled

v4.0: disabled

4.1: disabled

UDP: enabled

TCP: enabled

Default Windows User: -

Default Windows Group: -
```

10. Verify that the default NFS export policy is applied to the target SVM.

11. If required, create a new custom export policy for the target SVM.

```
CLUSTER::> vserver export-policy create -vserver dest -policyname xcpexportpolicy
```

Verify that the new custom export policy was successfully created.

12. Modify the export policy rules to allow access to NFS clients on the target system.

```
CLUSTER::> export-policy rule modify -vserver dest -ruleindex 1
-policyname xcpexportpolicy -clientmatch 0.0.0.0/0 -rorule any -rwrule
any -anon 0
Verify the policy rules have modified
CLUSTER::> export-policy rule show -instance
                                    Vserver: dest
                                Policy Name: xcpexportpolicy
                                 Rule Index: 1
                            Access Protocol: nfs3
Client Match Hostname, IP Address, Netgroup, or Domain: 0.0.0.0/0
                            RO Access Rule: none
                            RW Access Rule: none
User ID To Which Anonymous Users Are Mapped: 65534
                  Superuser Security Types: none
               Honor SetUID Bits in SETATTR: true
                  Allow Creation of Devices: true
```

13. Verify that the client has access to the target volume.

```
CLUSTER::> export-policy check-access -vserver dest -volume dest nfs
-client-ip 10.61.82.215 -authentication-method none -protocol nfs3
-access-type read-write
                                        Policy
                                                  Policy Rule
Path
                                                  Owner Type Index
                             Policy
                                        Owner
Access
                             xcpexportpolicy
                                        dest root volume
                                                                  1
read
/dest nfs
                             xcpexportpolicy
                                        dest nfs volume
                                                                  1
read-write
2 entries were displayed.
```

14. Connect to the Linux NFS server. Create a mount point for the NFS exported volume.

```
[root@localhost /]# cd /mnt
[root@localhost mnt]# mkdir dest
```

15. Mount the target NFSv3 exported volume at this mount point.



The NFSv3 volumes should be exported but not necessarily mounted by the NFS server. If they can be mounted, the XCP Linux host client mounts these volumes.

```
[root@localhost mnt]# mount -t nfs 10.61.73.115:/dest_nfs /mnt/dest
```

Verify that the mount point was successfully created.

```
[root@ localhost /]# mount | grep nfs
10.61.73.115:/dest_nfs on /mnt/dest type nfs
```

16. Create a test file on the NFS exported mount point to enable read-write access.

```
[root@localhost dest]# touch test.txt
Verify the file is created
[root@localhost dest]# ls -1
total 0
-rw-r--r-- 1 root bin 0 Jun 2 03:16 test.txt
```



17. Connect to the Linux client system in which XCP is installed. Browse to the XCP install path.

```
[root@localhost ~]# cd /linux/
[root@localhost linux]#
```

18. Query the source 7-Mode NFSv3 exports by running the xcp show command on the XCP Linux client host system.

```
[root@localhost]#./xcp show 10.61.82.215
== NFS Exports ==
Mounts Errors Server
           0 10.61.82.215
      4
     Space
            Files
                         Space
                                  Files
      Free
              Free
                         Used
                                 Used Export
  23.7 GiB 778,134
                     356 KiB
                                     96 10.61.82.215:/vol/nfsvol1
  17.5 GiB 622,463 1.46 GiB
                                    117 10.61.82.215:/vol/nfsvol
   328 GiB
             10.8M
                    2.86 GiB
                                  7,904 10.61.82.215:/vol/vol0/home
   328 GiB
           10.8M 2.86 GiB
                                  7,904 10.61.82.215:/vol/vol0
== Attributes of NFS Exports ==
drwxr-xr-x --- root wheel 4KiB 4KiB 2d21h 10.61.82.215:/vol/nfsvol1
drwxr-xr-x --- root wheel 4KiB 4KiB 2d21h 10.61.82.215:/vol/nfsvol
drwxrwxrwx --t root wheel 4KiB 4KiB 9d22h 10.61.82.215:/vol/vol0/home
drwxr-xr-x --- root wheel 4KiB 4KiB 4d0h 10.61.82.215:/vol/vol0
3.89 KiB in (5.70 \text{ KiB/s}), 7.96 KiB out (11.7 \text{ KiB/s}), 0s.
```

19. Scan the source NFSv3 exported paths and print the statistics of their file structure.

NetApp recommends putting the source NFSv3 exports in read-only mode during xcp scan, copy, and sync operations. In sync operation, you must pass the -snap option with a corresponding value.

```
[root@localhost /]# ./xcp scan 10.61.82.215:/vol/nfsvol/.snapshot/snap1
nfsvol
nfsvol/n5000-uk9.5.2.1.N1.1.bin
nfsvol/821_q_image.tgz
nfsvol/822RC2_q_image.tgz
nfsvol/NX5010_12_node_RCF_v1.3.txt
nfsvol/n5000-uk9-kickstart.5.2.1.N1.1.bin
nfsvol/catalog
23 scanned, 7.79 KiB in (5.52 KiB/s), 1.51 KiB out (1.07 KiB/s), 1s.
[root@scspr1202780001 vol_acl4]# ./xcp sync -id 7msnap1 -snap
10.236.66.199:/vol/nfsvol/.snapshot/snap10
(show scan and sync)
```

20. Copy the source 7-Mode NFSv3 snapshot (base) to NFSv3 exports on the target ONTAP system.

```
[root@localhost /]# /xcp copy 10.61.82.215:/vol/nfsvol/.snapshot/snap1
10.61.73.115:/dest_nfs
44 scanned, 39 copied, 264 MiB in (51.9 MiB/s), 262 MiB out (51.5
MiB/s), 5s
44 scanned, 39 copied, 481 MiB in (43.3 MiB/s), 479 MiB out (43.4
MiB/s), 10s
44 scanned, 40 copied, 748 MiB in (51.2 MiB/s), 747 MiB out (51.3
MiB/s), 16s
44 scanned, 40 copied, 1.00 GiB in (55.9 MiB/s), 1.00 GiB out (55.9
MiB/s), 21s
44 scanned, 40 copied, 1.21 GiB in (42.8 MiB/s), 1.21 GiB out (42.8
MiB/s), 26s
Sending statistics...
44 scanned, 43 copied, 1.46 GiB in (47.6 MiB/s), 1.45 GiB out (47.6
MiB/s), 31s.
```

Keep this base snapshot for further sync operations.

21. After copy is complete, verify that the source and destination NFSv3 exports have identical data. Run the xcp verify command.

```
[root@localhost /]# ./xcp verify 10.61.82.215:/vol/nfsvol
10.61.73.115:/dest_nfs
44 scanned, 44 found, 28 compared, 27 same data, 2.41 GiB in (98.4 MiB/s), 6.25 MiB out (255 KiB/s), 26s
44 scanned, 44 found, 30 compared, 29 same data, 2.88 GiB in (96.4 MiB/s), 7.46 MiB out (249 KiB/s), 31s
44 scanned, 100% found (43 have data), 43 compared, 100% verified (data, attrs, mods), 2.90 GiB in (92.6 MiB/s), 7.53 MiB out (240 KiB/s), 32s.
```

If verify finds differences between the source and destination data, then the error no such file or directory `is reported in the summary. To fix that issue, run the `xcp sync command to copy the source changes to the destination.

22. Before and during the cutover, run verify again. If the source has new or updated data, then perform incremental updates. If there are incremental changes, create a new Snapshot copy for these changes and pass that snapshot path with the -snap option for sync operations.

Run the xcp sync command with the -snap option and snapshot path.

```
[root@localhost /]# ./xcp sync -id 3
Index: {source: '10.61.82.215:/vol/nfsvol/.snapshot/snap1', target:
'10.61.73.115:/dest_nfs1'}
64 reviewed, 64 checked at source, 6 changes, 6 modifications, 51.7 KiB
in (62.5
KiB/s), 22.7 KiB out (27.5 KiB/s), 0s.
xcp: sync '3': Starting search pass for 1 modified directory...
xcp: sync '3': Found 6 indexed files in the 1 changed directory
xcp: sync '3': Rereading the 1 modified directory to find what's new...
xcp: sync '3': Deep scanning the 1 directory that changed...
11 scanned, 11 copied, 12.6 KiB in (6.19 KiB/s), 9.50 KiB out (4.66 KiB/s), 2s..
```



For this operation, the base snapshot is required.

23. To resume a previously interrupted copy operation, run the xcp resume command.

```
[root@scspr1202780001 534h dest vol]# ./xcp resume -id 3
XCP <version>; (c) 2020 NetApp, Inc.; Licensed to xxxxx [NetApp Inc]
until Mon Dec 31 00:00:00 2029
xcp: Index: {source: '10.61.82.215:/vol/nfsvol',/.snapshot/snap1,
target: 10.237.160.55:/dest vol}
xcp: resume '7msnap res1': Reviewing the incomplete index...
xcp: diff '7msnap res1': Found 143 completed directories and 230 in
progress
39,688 reviewed, 1.28 MiB in (1.84 MiB/s), 13.3 KiB out (19.1 KiB/s),
xcp: resume '7msnap res1': Starting second pass for the in-progress
directories...
xcp: resume '7msnap res1': Resuming the in-progress directories...
xcp: resume '7msnap res1': Resumed command: copy {-newid:
u'7msnap res1'}
xcp: resume '7msnap res1': Current options: {-id: '7msnap res1'}
xcp: resume '7msnap res1': Merged options: {-id: '7msnap res1', -newid:
u'7msnap res1'}
xcp: resume '7msnap res1': Values marked with a * include operations
before resume
 68,848 scanned*, 54,651 copied*, 39,688 indexed*, 35.6 MiB in (7.04
MiB/s), 28.1 MiB out (5.57 MiB/s), 5s
```

24. The NFSv3 client host must unmount the source NFSv3 exports provisioned from the 7-Mode storage and mount the target NFSv3 exports from ONTAP. This cutover requires an outage.

Migrating ACLv4 from NetApp 7-Mode to a NetApp storage system

This section covers the step-by-step procedure for transitioning a source NFSv4 export to an ONTAP system.



NetApp assumes that the source NFSv4 volume is exported and mounted on the client system and that XCP is already installed on a Linux system. The source should be a NetApp 7-Mode system that support ACLs. ACL migration is supported from NetApp to NetApp only. To copy files with a special character in the name, make sure the source and destination support UTF- 8 encoded language.

Prerequisites for migrating a source NFSv4 export to ONTAP

Before you migrate a source NFSv4 export to ONTAP, the following prerequisites must be met:

- The destination system must have NFSv4 configured.
- The NFSv4 source and target must be mounted on the XCP host. Select NFS v4.0 to match the source and target storage and verify that the ACLs are enabled on the source and target system.
- XCP requires the source/target path to be mounted on the XCP host for ACL processing. In the following example, vol1 (10.63.5.56:/vol1) is mounted on the /mnt/vol1 path:

```
[root@localhost ~]# df -h
Filesystem
                                                            Size Used
Avail Use% Mounted on
10.63.5.56:/vol1
                                                            973M 4.2M
969M 1% /mnt/vol1
[root@localhost ~]# ./xcp scan -l -acl4 10.63.5.56:/vol1/
XCP <version>; (c) 2020 NetApp, Inc.; Licensed to XXX [NetApp Inc] until
Sun Mar 31 00:00:00 2029
drwxr-xr-x --- root root 4KiB 4KiB 23h42m vol1
rw-r--r-- root root 4 0 23h42m vol1/DIR1/FILE
drwxr-xr-x --- root root 4KiB 4KiB 23h42m vol1/DIR1/DIR11
drwxr-xr-x --- root root 4KiB 4KiB 23h42m vol1/DIR1
rw-r--r-- root root 4
                               0 23h42m vol1/DIR1/DIR11/FILE
drwxr-xr-x --- root root 4KiB 4KiB 23h42m vol1/DIR1/DIR11/DIR2
rw-r--r-- root root 4 0 23h42m vol1/DIR1/DIR1/DIR2/FILE
drwxr-xr-x --- root root 4KiB 4KiB 17m43s vol1/DIR1/DIR1/DIR2/DIR22
8 scanned, 8 getacls, 1 v3perm, 7 acls, 3.80 KiB in (3.86 KiB/s), 1.21 KiB
out (1.23 \text{ KiB/s}), 0s.
```

Subdirectories options

The two options to work with subdirectories are as follows:

• For XCP to work on a subdirectory (/vol1/DIR1/DIR11), mount the complete path (10.63.5.56:/vol1/DIR1/DIR11) on the XCP host.

If the complete path is not mounted, XCP reports the following error:

```
[root@localhost ~]# ./xcp scan -l -acl4 10.63.5.56:/vol1/DIR1/DIR11
XCP <version>; (c) 2020 NetApp, Inc.; Licensed to XXX [NetApp Inc] until
Sun Mar 31 00:00:00 2029
xcp: ERROR: For xcp to process ACLs, please mount
10.63.5.56:/vol1/DIR1/DIR11 using the OS nfs4 client.
```

• Use the subdirectory syntax (mount: subdirectory/qtree/.snapshot), as shown in the example below:

Complete the following steps to migrate ACLv4 from NetApp 7-Mode to a NetApp storage system.

1. Verify that the target ONTAP system is healthy.

```
CLUSTER::> cluster show
           Health Eligibility
______
CLUSTER-01
                true
                      true
CLUSTER-02
               true true
2 entries were displayed.
CLUSTER::> node show
Node Health Eligibility Uptime Model Owner Location
CLUSTER-01
      true true 78 days 21:01 FAS8060
                                                RTP
CLUSTER-02
       true true 78 days 20:50 FAS8060
                                                 RTP
2 entries were displayed.
CLUSTER::> storage failover show
                      Takeover
                   Possible State Description
Node
          Partner
-----
CLUSTER-01 CLUSTER-02 true Connected to CLUSTER-02 CLUSTER-01 true Connected to CLUSTER-01
2 entries were displayed.
```

2. Verify that at least one nonroot aggregate exists on the target system. The aggregate is normal.

If there is no data aggregate, create a new one using the storage aggr create command.

3. Create an SVM on the target cluster system.

```
CLUSTER::> vserver create -vserver dest -rootvolume dest_root -aggregate poc -rootvolume-security-style mixed
[Job 647] Job succeeded:
Vserver creation completed
Verify the security style and language settings of the source
```

Verify that the SVM was successfully created.

```
CLUSTER::> vserver show -vserver dest
                                    Vserver: dest
                               Vserver Type: data
                            Vserver Subtype: default
                               Vserver UUID: 91f6d786-0063-11e5-b114-
00a09853a969
                                Root Volume: dest root
                                  Aggregate: poc
                                 NIS Domain: -
                 Root Volume Security Style: mixed
                                LDAP Client: -
               Default Volume Language Code: C.UTF-8
                            Snapshot Policy: default
                                    Comment:
                               Quota Policy: default
               List of Aggregates Assigned: -
Limit on Maximum Number of Volumes allowed: unlimited
                        Vserver Admin State: running
                  Vserver Operational State: running
  Vserver Operational State Stopped Reason: -
                          Allowed Protocols: nfs, cifs, fcp, iscsi, ndmp
                       Disallowed Protocols: -
            Is Vserver with Infinite Volume: false
                           QoS Policy Group: -
                                Confiq Lock: false
                               IPspace Name: Default
```

4. Remove the FCP, iSCSI, NDMP, and CIFS protocols from the target SVM.

```
CLUSTER::> vserver remove-protocols -vserver dest -protocols fcp,iscsi,ndmp,cifs
```

Verify that NFS is the allowed protocol for this SVM.

```
CLUSTER::> vserver show -vserver dest -fields allowed-protocols vserver allowed-protocols ------ dest nfs
```

5. Create a new read-write data volume on the destination SVM. Verify that the security style, language settings, and capacity requirements match the source volume.

CLUSTER::> vol create -vserver dest -volume dest_nfs -aggregate poc -size 150g -type RW -state online -security-style mixed [Job 648] Job succeeded: Successful

6. Create a data LIF to serve NFS client requests.

CLUSTER::> network interface create -vserver dest -lif dest_lif -address 10.61.73.115 -netmask 255.255.255.0 -role data -data-protocol nfs -home -node CLUSTER-01 -home-port e01

Verify that the LIF was successfully created.

```
CLUSTER::> network interface show -vserver dest
Logical Status Network Current

Current Is
Vserver Interface Admin/Oper Address/Mask Node Port

Home

dest
dest_lif
up/up 10.61.73.113/24 CLUSTER-01 e0i

true
```

7. If required, create a static route with the SVM.

```
CLUSTER::> network route create -vserver dest -destination 0.0.0.0/0 -gateway 192.168.100.111
```

Verify that the route was successfully created.

```
CLUSTER::> network route show -vserver source

Vserver Destination Gateway Metric

-----dest

0.0.0.0/0 10.61.73.1 20
```

8. Mount the target NFS data volume in the SVM namespace.

```
CLUSTER::> volume mount -vserver dest -volume dest_nfs -junction-path
/dest_nfs -active true
```

Verify that the volume was successfully mounted.

```
CLUSTER::> volume show -vserver dest -fields junction-path
vserver volume junction-path
------
dest dest_nfs /dest_nfs
dest dest_root
/
2 entries were displayed.
```

You can also specify the volume mount options (junction path) with the volume create command.

9. Start the NFS service on the target SVM.

```
CLUSTER::> vserver nfs start -vserver dest
```

Verify that the service is started and running.

```
CLUSTER::> vserver nfs status
The NFS server is running on Vserver "dest".
CLUSTER::> nfs show
Vserver: dest
General Access: true
v3: enabled
v4.0: enabled
4.1: disabled
UDP: enabled
TCP: enabled
Default Windows User: -
Default Windows Group: -
```

10. Check that the default NFS export policy is applied to the target SVM.

11. If required, create a new custom export policy for the target SVM.

```
CLUSTER::> vserver export-policy create -vserver dest -policyname xcpexportpolicy
```

Verify that the new custom export policy was successfully created.

12. Modify the export policy rules to allow access to NFS clients.

```
CLUSTER::> export-policy rule modify -vserver dest -ruleindex 1 -policyname xcpexportpolicy -clientmatch 0.0.0.0/0 -rorule any -rwrule any -anon 0
```

Verify that the policy rules have been modified.

13. Verify that the client is allowed access to the volume.

```
CLUSTER::> export-policy check-access -vserver dest -volume dest nfs
-client-ip 10.61.82.215 -authentication-method none -protocol nfs3
-access-type read-write
                                        Policy
                                                  Policy Rule
Path
                                                  Owner Type Index
                             Policy
                                        Owner
Access
                             xcpexportpolicy
                                        dest root volume
                                                                  1
read
/dest nfs
                             xcpexportpolicy
                                        dest nfs volume
                                                                  1
read-write
2 entries were displayed.
```

14. Connect to the Linux NFS server. Create a mount point for the NFS exported volume.

```
[root@localhost /]# cd /mnt
[root@localhost mnt]# mkdir dest
```

15. Mount the target NFSv4 exported volume at this mount point.



The NFSv4 volumes should be exported but not necessarily mounted by the NFS server. If they can be mounted, the XCP Linux host client mounts these volumes.

```
[root@localhost mnt]# mount -t nfs4 10.63.5.56:/vol1 /mnt/vol1
```

Verify that the mount point was successfully created.

```
[root@localhost mnt]# mount | grep nfs
10.63.5.56:/vol1 on /mnt/vol1 type nfs4
(rw, relatime, vers=4.0, rsize=65536, wsize=65536, namlen=255, hard, proto=tcp, timeo=600,
retrans=2, sec=sys, clientaddr=10.234.152.84, local_lock=none, addr=10.63.5.
56)
```

16. Create a test file on the NFS exported mount point to enable read-write access.

```
[root@localhost dest]# touch test.txt
```

Verify the file is created.

```
[root@localhost dest]# ls -l
total 0
-rw-r--r- 1 root bin 0 Jun 2 03:16 test.txt
```



After the read-write test is complete, delete the file from the target NFS mount point.

17. Connect to the Linux client system in which XCP is installed. Browse to the XCP install path.

```
[root@localhost ~]# cd /linux/
[root@localhost linux]#
```

18. Query the source NFSv4 exports by running the xcp show command on the XCP Linux client host system.

```
root@localhost]# ./xcp show 10.63.5.56
XCP <version>; (c) 2020 NetApp, Inc.; Licensed to xxx [NetApp Inc] until
Mon Dec 31 00:00:00 2029
getting pmap dump from 10.63.5.56 port 111...
getting export list from 10.63.5.56...
sending 6 mounts and 24 nfs requests to 10.63.5.56...
== RPC Services ==
'10.63.5.56': UDP rpc services: MNT v1/2/3, NFS v3, NLM v4, PMAP v2/3/4,
STATUS v1
'10.63.5.56': TCP rpc services: MNT v1/2/3, NFS v3/4, NLM v4, PMAP
v2/3/4, STATUS v1
== NFS Exports ==
 Mounts Errors Server
            0 10.63.5.56
      6
            Files
     Space
                                Files
                       Space
     Free
             Free
                        Used
                                 Used Export
  94.7 MiB 19,883
                     324 KiB
                                  107 10.63.5.56:/
  971 MiB 31,023 2.19 MiB
                                   99 10.63.5.56:/vol2
  970 MiB 31,024 2.83 MiB
                                   98 10.63.5.56:/vol1
  9.33 GiB 310,697 172 MiB
                                   590 10.63.5.56:/vol 005
            1.10M 4.17 GiB
                                1.00M 10.63.5.56:/vol3
  43.3 GiB
  36.4 GiB 1.10M 11.1 GiB 1.00M 10.63.5.56:/vol4
== Attributes of NFS Exports ==
drwxr-xr-x --- root root 4KiB 4KiB 6d2h 10.63.5.56:/
drwxr-xr-x --- root root 4KiB 4KiB 3d2h 10.63.5.56:/vol2
drwxr-xr-x --- root root 4KiB 4KiB 3d2h 10.63.5.56:/vol1
drwxr-xr-x --- root root 4KiB 4KiB 9d2h 10.63.5.56:/vol 005
drwxr-xr-x --- root root 4KiB 4KiB 9d4h 10.63.5.56:/vol3
drwxr-xr-x --- root root 4KiB 4KiB 9d4h 10.63.5.56:/vol4
6.09 KiB in (9.19 \text{ KiB/s}), 12.2 KiB out (18.3 \text{ KiB/s}), 0s.
```

19. Scan the source NFSv4 exported paths and print the statistics of their file structure.

NetApp recommends putting the source NFSv4 exports in read-only mode during xcp scan, copy, and sync operations.

```
[root@localhost]# ./xcp scan -acl4 10.63.5.56:/vol1
XCP <version>; (c) 2020 NetApp, Inc.; Licensed to xxx [NetApp Inc] until
Mon Dec 31 00:00:00 2029
vol1
vol1/test/f1
vol1/test
3 scanned, 3 getacls, 3 v3perms, 1.59 KiB in (1.72 KiB/s), 696 out (753/s), 0s.
```

20. Copy source NFSv4 exports to NFSv4 exports on the target ONTAP system.

```
[root@localhost]# ./xcp copy -acl4 -newid id1 10.63.5.56:/vol1
10.63.5.56:/vol2
XCP <version>; (c) 2020 NetApp, Inc.; Licensed to xxx [NetApp Inc] until
Mon Dec 31 00:00:00 2029
3 scanned, 2 copied, 3 indexed, 3 getacls, 3 v3perms, 1 setacl, 14.7 KiB
in (11.7 KiB/s), 61 KiB out (48.4 KiB/s), 1s..
```

21. After copy is complete, verify that the source and destination NFSv4 exports have identical data. Run the xcp verify command.

```
[root@localhost]# ./xcp verify -acl4 -noid 10.63.5.56:/vol1
10.63.5.56:/vol2
XCP <version>; (c) 2020 NetApp, Inc.; Licensed to xxx [NetApp Inc] until
Mon Dec 31 00:00:00 2029
3 scanned, 100% found (0 have data), 100% verified (data, attrs, mods,
acls), 6 getacls, 6 v3perms, 2.90 KiB in (4.16 KiB/s), 2.94 KiB out
(4.22 KiB/s), 0s.
```

If verify finds differences between the source and destination data, then the error no such file or directory is reported in the summary. To fix that issue, run the xcp sync command to copy the source changes to the destination.

22. Before and during the cutover, run verify again. If the source has new or updated data, then perform incremental updates. Run the xcp sync command.

```
[root@ root@localhost]# ./xcp sync -id id1
XCP <version>; (c) 2020 NetApp, Inc.; Licensed to xxx [NetApp Inc] until
Mon Dec 31 00:00:00 2029
xcp: Index: {source: 10.63.5.56:/vol1, target: 10.63.5.56:/vol2}
3 reviewed, 3 checked at source, no changes, 3 reindexed, 25.6 KiB in
(32.3 KiB/s), 23.3 KiB out (29.5 KiB/s), 0s.
```

- (i)
- For this operation, the previous copy index name or number is required.
- 23. To resume a previously interrupted copy operation, run the xcp resume command.

```
[root@localhost]# ./xcp resume -id id1
XCP <version>; (c) 2020 NetApp, Inc.; Licensed to xxx [NetApp Inc] until
Mon Dec 31 00:00:00 2029
xcp: Index: {source: 10.63.5.56:/vol3, target: 10.63.5.56:/vol4}
xcp: resume 'idl': Reviewing the incomplete index...
xcp: diff 'id1': Found 0 completed directories and 8 in progress
39,899 reviewed, 1.64 MiB in (1.03 MiB/s), 14.6 KiB out (9.23 KiB/s),
xcp: resume 'id1': Starting second pass for the in-progress
directories...
xcp: resume 'id1': Resuming the in-progress directories...
xcp: resume 'id1': Resumed command: copy {-acl4: True}
xcp: resume 'id1': Current options: {-id: 'id1'}
xcp: resume 'id1': Merged options: {-acl4: True, -id: 'id1'}
xcp: resume 'id1': Values marked with a * include operations before
resume
 86,404 scanned, 39,912 copied, 39,899 indexed, 13.0 MiB in (2.60
MiB/s), 78.4 KiB out (15.6 KiB/s), 5s 86,404 scanned, 39,912 copied,
39,899 indexed, 13.0 MiB in (0/s), 78.4 KiB out (0/s), 10s
1.00M scanned, 100% found (1M have data), 1M compared, 100% verified
(data, attrs, mods, acls), 2.00M getacls, 202 v3perms, 1.00M same acls,
2.56 GiB in (2.76 \text{ MiB/s}), 485 MiB out (524 \text{ KiB/s}), 15m48s.
```

After resume finishes copying files, run verify again so that the source and destination storage have identical data.

Transitioning 7-Mode SMB storage to ONTAP for CIFS data

This section covers the step-by-step procedure for transitioning a source 7-Mode SMB share to an ONTAP system.



NetApp assumes that the 7-Mode and ONTAP systems are SMB licensed. The destination SVM is created, the source and destination SMB shares are exported, and XCP is installed and licensed.

1. Scan the SMB shares for the files and directories.

```
C:\xcp>xcp scan -stats \\10.61.77.189\performance SMB home dirs
XCP SMB 1.6; (c) 2020 NetApp, Inc.; Licensed to xxxx xxxx[NetApp Inc]
until Mon Dec 31 00:00:00 2029
== Maximum Values ==
Size Depth Namelen Dirsize
15.6MiB 2 8 200
== Average Values ==
Size Depth Namelen Dirsize
540KiB 2 7 81
== Top File Extensions ==
.txt .tmp
5601 2200
== Number of files ==
empty <8KiB 8-64KiB 64KiB-1MiB 1-10MiB 10-100MiB >100MiB
46 6301 700 302 200 252
== Space used ==
empty <8KiB 8-64KiB 64KiB-1MiB 1-10MiB 10-100MiB >100MiB
0 6.80MiB 8.04MiB 120MiB 251MiB 3.64GiB 0
== Directory entries ==
empty 1-10 10-100 100-1K 1K-10K >10k
18 1 77 1
== Depth ==
0-5 6-10 11-15 16-20 21-100 >100
7898
== Modified ==
>1 year >1 month 1-31 days 1-24 hrs <1 hour <15 mins future
2167 56 322 5353
== Created ==
>1 year >1 month 1-31 days 1-24 hrs <1 hour <15 mins future
2171 54 373 5300
Total count: 7898
Directories: 97
Regular files: 7801
Symbolic links:
Junctions:
Special files:
Total space for regular files: 4.02GiB
Total space for directories: 0
Total space used: 4.02GiB
7,898 scanned, 0 errors, 0s
```

2. Copy the files (with or without ACL) from the source to the destination SMB share. The following example shows a copy with ACL.

```
C:\xcp>xcp copy -acl -fallback-user "DOMAIN\gabi" -fallback-group
"DOMAIN\Group" \\10.61.77.189\performance SMB home dirs
\\10.61.77.56\performance SMB home dirs
XCP SMB 1.6; (c) 2020 NetApp, Inc.; Licensed to xxxx xxxx[NetApp Inc]
until Mon Dec 31 00:00:00 2029
7,898 scanned, 0 errors, 0 skipped, 184 copied, 96.1MiB (19.2MiB/s), 5s
7,898 scanned, 0 errors, 0 skipped, 333 copied, 519MiB (84.7MiB/s), 10s
7,898 scanned, 0 errors, 0 skipped, 366 copied, 969MiB (89.9MiB/s), 15s
7,898 scanned, 0 errors, 0 skipped, 422 copied, 1.43GiB (99.8MiB/s), 20s
7,898 scanned, 0 errors, 0 skipped, 1,100 copied, 1.69GiB (52.9MiB/s),
25s
7,898 scanned, 0 errors, 0 skipped, 1,834 copied, 1.94GiB (50.4MiB/s),
30s
7,898 scanned, 0 errors, 0 skipped, 1,906 copied, 2.43GiB (100MiB/s),
7,898 scanned, 0 errors, 0 skipped, 2,937 copied, 2.61GiB (36.6MiB/s),
7,898 scanned, 0 errors, 0 skipped, 2,969 copied, 3.09GiB (100.0MiB/s),
7,898 scanned, 0 errors, 0 skipped, 3,001 copied, 3.58GiB (100.0MiB/s),
7,898 scanned, 0 errors, 0 skipped, 3,298 copied, 4.01GiB (88.0MiB/s),
7,898 scanned, 0 errors, 0 skipped, 5,614 copied, 4.01GiB (679KiB/s),
7,898 scanned, 0 errors, 0 skipped, 7,879 copied, 4.02GiB (445KiB/s),
1m5s
7,898 scanned, 0 errors, 0 skipped, 7,897 copied, 4.02GiB (63.2MiB/s),
1m5s
```



If there is no data aggregate, create a new one using the storage aggregate create command.

3. Sync the files on the source and destination.

```
C:\xcp>xcp sync -acl -fallback-user "DOMAIN\gabi" -fallback-group
"DOMAIN\Group" \\10.61.77.189\performance_SMB_home_dirs
\\10.61.77.56\performance_SMB_home_dirs

XCP SMB 1.6; (c) 2020 NetApp, Inc.; Licensed to xxxx xxxx[NetApp Inc]
until Mon Dec 31 00:00:00 2029

10,796 scanned, 4,002 compared, 0 errors, 0 skipped, 0 copied, 0
removed, 5s

15,796 scanned, 8,038 compared, 0 errors, 0 skipped, 0 copied, 0
removed, 10s

15,796 scanned, 8,505 compared, 0 errors, 0 skipped, 0 copied, 0
```

```
removed, 15s
15,796 scanned, 8,707 compared, 0 errors, 0 skipped, 0 copied, 0
removed, 20s
15,796 scanned, 8,730 compared, 0 errors, 0 skipped, 0 copied, 0
removed, 25s
15,796 scanned, 8,749 compared, 0 errors, 0 skipped, 0 copied, 0
removed, 30s
15,796 scanned, 8,765 compared, 0 errors, 0 skipped, 0 copied, 0
removed, 35s
15,796 scanned, 8,786 compared, 0 errors, 0 skipped, 0 copied, 0
removed, 40s
15,796 scanned, 8,956 compared, 0 errors, 0 skipped, 0 copied, 0
removed, 45s
8 XCP v1.6 User Guide © 2020 NetApp, Inc. All rights reserved.
Step Description
15,796 scanned, 9,320 compared, 0 errors, 0 skipped, 0 copied, 0
removed, 50s
15,796 scanned, 9,339 compared, 0 errors, 0 skipped, 0 copied, 0
removed, 55s
15,796 scanned, 9,363 compared, 0 errors, 0 skipped, 0 copied, 0
removed, 1m0s
15,796 scanned, 10,019 compared, 0 errors, 0 skipped, 0 copied, 0
removed, 1m5s
15,796 scanned, 10,042 compared, 0 errors, 0 skipped, 0 copied, 0
removed, 1m10s
15,796 scanned, 10,059 compared, 0 errors, 0 skipped, 0 copied, 0
removed, 1m15s
15,796 scanned, 10,075 compared, 0 errors, 0 skipped, 0 copied, 0
removed, 1m20s
15,796 scanned, 10,091 compared, 0 errors, 0 skipped, 0 copied, 0
removed, 1m25s
15,796 scanned, 10,108 compared, 0 errors, 0 skipped, 0 copied, 0
removed, 1m30s
15,796 scanned, 10,929 compared, 0 errors, 0 skipped, 0 copied, 0
removed, 1m35s
15,796 scanned, 12,443 compared, 0 errors, 0 skipped, 0 copied, 0
removed, 1m40s
15,796 scanned, 13,963 compared, 0 errors, 0 skipped, 0 copied, 0
removed, 1m45s
15,796 scanned, 15,488 compared, 0 errors, 0 skipped, 0 copied, 0
removed, 1m50s
15,796 scanned, 15,796 compared, 0 errors, 0 skipped, 0 copied, 0
removed, 1m51s
```

4. Verify that the files were copied correctly.

```
C:\xcp> xcp verify \\10.61.77.189\performance SMB home dirs
\\10.61.77.56\performance SMB home dir
XCP SMB 1.6; (c) 2020 NetApp, Inc.; Licensed to xxxx xxxx[NetApp Inc]
until Mon Dec 31 00:00:00 2029
8 compared, 8 same, 0 different, 0 missing, 5s
24 compared, 24 same, 0 different, 0 missing, 10s
41 compared, 41 same, 0 different, 0 missing, 15s
63 compared, 63 same, 0 different, 0 missing, 20s
86 compared, 86 same, 0 different, 0 missing, 25s
423 compared, 423 same, 0 different, 0 missing, 30s
691 compared, 691 same, 0 different, 0 missing, 35s
1,226 compared, 1,226 same, 0 different, 0 missing, 40s
1,524 compared, 1,524 same, 0 different, 0 missing, 45s
1,547 compared, 1,547 same, 0 different, 0 missing, 50s
1,564 compared, 1,564 same, 0 different, 0 missing, 55s
2,026 compared, 2,026 same, 0 different, 0 missing, 1m0s
2,045 compared, 2,045 same, 0 different, 0 missing, 1m5s
2,061 compared, 2,061 same, 0 different, 0 missing, 1m10s
2,081 compared, 2,081 same, 0 different, 0 missing, 1m15s
2,098 compared, 2,098 same, 0 different, 0 missing, 1m20s
2,116 compared, 2,116 same, 0 different, 0 missing, 1m25s
3,232 compared, 3,232 same, 0 different, 0 missing, 1m30s
4,817 compared, 4,817 same, 0 different, 0 missing, 1m35s
6,267 compared, 6,267 same, 0 different, 0 missing, 1m40s
7,844 compared, 7,844 same, 0 different, 0 missing, 1m45s
7,898 compared, 7,898 same, 0 different, 0 missing, 1m45s,cifs
```

Next: CIFS data migration with ACLs From a source storage box to ONTAP.

CIFS data migration with ACLs from a source storage box to ONTAP

Previous: Data migration from 7-Mode to ONTAP.

This section covers the step-by-step procedure for migrating CIFS data with security information from a source to a target ONTAP system.

1. Verify that the target ONTAP system is healthy.

```
C1 sti96-vsim-ucs540m cluster::> cluster show
Node
                 Health Eligibility
----- -----
sti96-vsim-ucs540m true true
sti96-vsim-ucs540n true
                      true
2 entries were displayed.
C1 sti96-vsim-ucs540m cluster::> node show
Node Health Eligibility Uptime Model Owner Location
------ ----- -----
_____
sti96-vsim-ucs540m
      true true 15 days 21:17 SIMBOX ahammed sti
sti96-vsim-ucs540n
       true true 15 days 21:17 SIMBOX ahammed sti
2 entries were displayed.
cluster::> storage failover show
                       Takeover
   Partner
                     Possible State Description
-----
sti96-vsim-ucs540m
           sti96-vsim- true Connected to sti96-vsim-ucs540n
           ucs540n
sti96-vsim-ucs540n
           sti96-vsim- true Connected to sti96-vsim-ucs540m
           ucs540m
2 entries were displayed.
C1 sti96-vsim-ucs540m cluster::>
```

2. Verify that at least one nonroot aggregate exists on the target system. The aggregate is normal.

Aggregate	_	e aggregate Available		State	#Vols	Nodes	RAID
Status							
aggr0_sti96	- 	· s 5 1 0 0					
agg10_30190			95%	online	1	sti96-vsim-	
raid_dp,							
_						ucs540o	
normal							
aggr0_sti96			0.50	7.	1		
raid dp,	7.58GB	3/3.3MB	95%	online	Ι	sti96-vsim-	
1a1α_αρ,						ucs540p	
normal						1	
aggr_001	103.7GB	93.63GB	10%	online	1	sti96-vsim-	
raid_dp,							
normal						ucs540p	
sti96 vsim	11085400	aggr1					
	_	='	0%	online	1	sti96-vsim-	
raid_dp,							
						ucs540o	
normal							
sti96_vsim_	_	='	0.0	1	0	a+i0Caim	
raid dp,	23.93GB	23.93GB	08	OULTINE	U	sti96-vsim-	
-a-a_ap/						ucs540p	
normal						-	
5 entries w	ere disp	layed.					



If there is no data aggregate, create a new one using the storage aggr create command.

3. Create an SVM on the target cluster system.

```
cluster::*> vserver create -vserver vs1 -rootvolume root vs1 -aggregate
sti96 vsim ucs540o aggr1 -rootvolume-security-style mixed
Verify that the SVM was successfully created.
C2 sti96-vsim-ucs540o cluster::*> vserver show -vserver vs1
                                    Vserver: vs1
                               Vserver Type: data
                            Vserver Subtype: default
                               Vserver UUID: f8bc54be-d91b-11e9-b99c-
005056a7e57e
                                Root Volume: root vs1
                                  Aggregate: sti96 vsim ucs540o aggr1
                                 NIS Domain: NSQA-RTP-NIS1
                 Root Volume Security Style: mixed
                                LDAP Client: esisconfig
               Default Volume Language Code: C.UTF-8
                            Snapshot Policy: default
                              Data Services: data-nfs, data-cifs,
                                             data-flexcache, data-iscsi
                                    Comment: vs1
                               Quota Policy: default
                List of Aggregates Assigned: -
 Limit on Maximum Number of Volumes allowed: unlimited
                        Vserver Admin State: running
                  Vserver Operational State: running
   Vserver Operational State Stopped Reason: -
                          Allowed Protocols: nfs, cifs, fcp, iscsi, ndmp
                       Disallowed Protocols: -
            Is Vserver with Infinite Volume: false
                           QoS Policy Group: -
                        Caching Policy Name: -
                                Config Lock: false
             Volume Delete Retention Period: 0
                               IPspace Name: Default
                         Foreground Process: -
                   Is Msid Preserved for DR: false
Force start required to start Destination in muliple IDP fan-out case:
false
                    Logical Space Reporting: false
                  Logical Space Enforcement: false
```

4. Create a new read-write data volume on the destination SVM. Verify that the security style, language settings, and capacity requirements match the source volume.

CLUSTER CLUSTER::> vol create -vserver vs1 -volume dest_vol -aggregate aggr_001 -size 150g type RW -state online -security-style ntfs

5. Create a data LIF to serve SMB client requests.

CLUSTER::> network interface create -vserver vs1 -lif sti96-vsim-ucs540o_data1 -address 10.237.165.87 -netmask 255.255.240.0 -role data -data-protocol nfs,cifs -home-node sti96-vsim-ucs540o -home-port e0d

Verify that the LIF was successfully created.

```
cluster::*> network interface show -vserver vs1
Logical Status Network Current

Current Is

Vserver Interface Admin/Oper Address/Mask Node Port

Home

vs1

sti96-vsim-ucs540o_data1

up/up 10.237.165.87/20 sti96-vsim-ucs540o
e0d

true
```

6. If required, create a static route with the SVM.

Network route create -vserver dest -destination 0.0.0.0/0 -gateway 10.237.160.1

Verify that the route was successfully created.

7. Mount the target data volume in the SVM namespace.

```
CLUSTER::> volume mount -vserver vs1 -volume dest_vol -junction-path
/dest_vol -active true
```

Verify that the volume is successfully mounted.

8. Start the CIFs service on the target SVM.

```
cluster::*> vserver cifs start -vserver vs1
Warning: The admin status of the CIFS server for Vserver "vs1" is
already "up".
```

Verify that the service is started and running.

9. Verify that the default export policy is applied to the target SVM.

If required, create a new custom export policy for the target SVM.

CLUSTER::> vserver export-policy create -vserver vs1 -policyname
xcpexport

10. Modify the export policy rules to allow access to CIFs clients.

```
CLUSTER::> export-policy rule modify -vserver dest -ruleindex 1 -policyname xcpexportpolicy -clientmatch 0.0.0.0/0 -rorule any -rwrule any -anon 0
```

Verify that the policy rules are modified.

```
cluster::*> export-policy rule show -instance
                                    Vserver: vs1
                                Policy Name: default
                                 Rule Index: 1
                            Access Protocol: any
List of Client Match Hostnames, IP Addresses, Netgroups, or Domains:
0.0.0.0/0
                             RO Access Rule: any
                             RW Access Rule: any
User ID To Which Anonymous Users Are Mapped: 65534
                   Superuser Security Types: any
               Honor SetUID Bits in SETATTR: true
                  Allow Creation of Devices: true
                 NTFS Unix Security Options: fail
         Vserver NTFS Unix Security Options: use export policy
                      Change Ownership Mode: restricted
              Vserver Change Ownership Mode: use export policy
                                  Policy ID: 12884901889
                                    Vserver: vs1
                                Policy Name: default
                                 Rule Index: 2
                            Access Protocol: any
List of Client Match Hostnames, IP Addresses, Netgroups, or Domains:
0:0:0:0:0:0:0:0/0
                             RO Access Rule: any
                             RW Access Rule: any
User ID To Which Anonymous Users Are Mapped: 65534
                   Superuser Security Types: none
               Honor SetUID Bits in SETATTR: true
                  Allow Creation of Devices: true
                 NTFS Unix Security Options: fail
         Vserver NTFS Unix Security Options: use export policy
                      Change Ownership Mode: restricted
              Vserver Change Ownership Mode: use export policy
                                  Policy ID: 12884901889
2 entries were displayed.
```

11. Verify that the client is allowed access to the volume.

```
cluster::*> export-policy check-access -vserver vs1 -volume dest vol
-client-ip 10.234.17.81 -authentication-method none -protocol cifs
-access-type read-write
                                    Policy Policy Rule
                                   Owner Owner Type Index
Path
                           Policy
Access
                           default root vs1 volume
/
                                                            1
read
                    default dest vol volume
/dest vol
                                                            1
read-write
2 entries were displayed.
```

12. Connect to the Windows client system where XCP is installed. Browse to the XCP install path.

13. Query the source node SMB exports by running the xcp show command on the XCP Windows client host system.

```
C:\WRSHDNT>c:\netapp\xcp\xcp show \\10.237.165.71
c:\netapp\xcp\xcp show \\10.237.165.71
XCP SMB 1.6; (c) 2020 NetApp, Inc.; Licensed to XXX [NetApp Inc] until
Mon Dec 31 00:00:00 2029
 Shares Errors Server
                   10.237.165.71
     6 0
== SMB Shares ==
 Space Space Current
Free Used Connections Share Path
                                                      Folder Path
 9.50GiB 4.57MiB 1
                          \\10.237.165.71\source_share C:\source_vol
94.3MiB 716KiB 0
                          \\10.237.165.71\ROOTSHARE C:\
 0 0 N/A
                          \\10.237.165.71\ipc$
                                                     N/A
 94.3MiB 716KiB 0
                          \\10.237.165.71\c$
                                                     C:\
== Attributes of SMB Shares ==
 Share
                                 Types
Remark
source share
                                 DISKTREE
test share
                                 DISKTREE
                                DISKTREE
test sh
ROOTSHARE
                                DISKTREE
                                                    \"Share mapped
to top of Vserver global namespace, created bydeux init \"
                                PRINTQ, SPECIAL, IPC, DEVICE
 ipc$
С$
                                 SPECIAL
== Permissions of SMB Shares ==
Share
                                Entity
Type
source share
                                Everyone
Allow/Full Control
ROOTSHARE
                               Everyone
Allow/Full Control
ipc$
                               Everyone
Allow/Full Control
                               Administrators
Allow/Full Control/
```

14. Run the help command for copy.

```
C:\WRSHDNT>c:\netapp\xcp\xcp help copy
c:\netapp\xcp\xcp help copy
XCP SMB 1.6; (c) 2020 NetApp, Inc.; Licensed to XXX [NetApp Inc] until
Mon Dec 31 00:00:00 2029
usage: xcp copy [-h] [-v] [-parallel <n>] [-match <filter>] [-preserve-
atime]
                [-acl] [-fallback-user FALLBACK USER]
                [-fallback-group FALLBACK GROUP] [-root]
                source target
positional arguments:
  source
  target
optional arguments:
  -h, --help
                        show this help message and exit
                        increase debug verbosity
  -77
                        number of concurrent processes (default: <cpu-
  -parallel <n>
count>)
  -match <filter>
                       only process files and directories that match
the
                        filter (see `xcp help -match` for details)
                        restore last accessed date on source
  -preserve-atime
                        copy security information
  -acl
  -fallback-user FALLBACK USER
                        the name of the user on the target machine to
receive
                        the permissions of local (non-domain) source
machine
                        users (eg. domain\administrator)
  -fallback-group FALLBACK GROUP
                        the name of the group on the target machine to
receive
                        the permissions of local (non-domain) source
machine
                        groups (eg. domain\administrators)
                        copy acl for root directorytxt
  -root
```

15. On the target ONTAP system, get the list of local user and local group names that you need to provide as values for the fallback-user and fallback-group arguments path.

```
cluster::*> local-user show
 (vserver cifs users-and-groups local-user show)
Vserver User Name
                               Full Name
Description
______
vs1
         D60AB15C2AFC4D6\Administrator
                                               Built-in
administrator account
C2 sti96-vsim-ucs540o cluster::*> local-group show
 (vserver cifs users-and-groups local-group show)
Vserver Group Name
                               Description
_____
_____
          BUILTIN\Administrators Built-in Administrators
group
          BUILTIN\Backup Operators Backup Operators group
BUILTIN\Guests Built-in Guests Group
vs1
vs1
vs1
          BUILTIN\Power Users
                                    Restricted
administrative privileges
vs1 BUILTIN\Users
                                    All users
5 entries were displayed
```

16. To migrate the CIFs data with ACLs from the source to target, run the xcp copy command with the -acl and -fallback-user/group options.

For the fallback-user/group options, specify any user or group that can be found in Active Directory or local user/group to target system.

```
C:\WRSHDNT>c:\netapp\xcp\xcp copy -acl -fallback-user
D60AB15C2AFC4D6\Administrator -fallback-group BUILTIN\Users
\10.237.165.79\ source share \10.237.165.89\ dest share
c:\netapp\xcp\xcp copy -acl -fallback-user D60AB15C2AFC4D6\Administrator
-fallback-group BUILTIN\Users \\10.237.165.79\source share
\\10.237.165.89\dest share
XCP SMB 1.6; (c) 2020 NetApp, Inc.; Licensed to XXX [NetApp Inc] until
Mon Dec 31 00:00:00 2029
753 scanned, 0 errors, 0 skipped, 0 copied, 0 (0/s), 8s
753 scanned, 0 errors, 0 skipped, 0 copied, 0 (0/s), 13s
753 scanned, 0 errors, 0 skipped, 0 copied, 0 (0/s), 18s
ERROR failed to obtain fallback security principal "BUILTIN\Users".
Please check if the principal with the name "BUILTIN\Users" exists on
"D60AB15C2AFC4D6".
ERROR failed to obtain fallback security principal
"D60AB15C2AFC4D6\Administrator". Please check if the principal with the
name "D60AB15C2AFC4D6\Administrator" exists on "D60AB15C2AFC4D6".
ERROR failed to obtain fallback security principal "BUILTIN\Users".
Please check if the principal with the name "BUILTIN\Users" exists on
"D60AB15C2AFC4D6".
ERROR failed to obtain fallback security principal "BUILTIN\Users".
Please check if the principal with the name "BUILTIN\Users" exists on
"D60AB15C2AFC4D6".
ERROR failed to obtain fallback security principal "BUILTIN\Users".
Please check if the principal with the name "BUILTIN\Users" exists on
"D60AB15C2AFC4D6".
753 scanned, 0 errors, 0 skipped, 0 copied, 0 (0/s), 23s
ERROR failed to obtain fallback security principal
"D60AB15C2AFC4D6\Administrator". Please check if the principal with the
name "D60AB15C2AFC4D6\Administrator" exists on "D60AB15C2AFC4D6".
ERROR failed to obtain fallback security principal
"D60AB15C2AFC4D6\Administrator". Please check if the principal with the
name "D60AB15C2AFC4D6\Administrator" exists on "D60AB15C2AFC4D6".
ERROR failed to obtain fallback security principal
"D60AB15C2AFC4D6\Administrator". Please check if the principal with the
name "D60AB15C2AFC4D6\Administrator" exists on "D60AB15C2AFC4D6".
753 scanned, 0 errors, 0 skipped, 0 copied, 0 (0/s), 28s
753 scanned, 0 errors, 0 skipped, 249 copied, 24.0KiB (4.82KiB/s), 33s
753 scanned, 0 errors, 0 skipped, 744 copied, 54.4KiB (6.07KiB/s), 38s
753 scanned, 0 errors, 0 skipped, 746 copied, 54.5KiB (20/s), 43s
753 scanned, 0 errors, 0 skipped, 752 copied, 54.7KiB (1.23KiB/s), 44s
C:\WRSHDNT>
```

^{17.} If xcp copy results in the error message ERROR failed to obtain fallback security principal, add the destination box in the hosts file (C:\Windows\System32\drivers\etc\hosts).

Use the following format for the NetApp storage destination box entry.

<data vserver data interface ip> 1 or more white spaces <cifs server name>

```
cluster::*> cifs show
                        Status Domain/Workgroup Authentication
          Server
                        Admin
                                                Style
Vserver
          Name
                                 Name
D60AB15C2AFC4D6 up
                                 CTL
                                                domain
C2 sti96-vsim-ucs540o cluster::*> network interface show
          Logical Status Network
                                      Current
Current Is
Cluster
          sti96-vsim-ucs540p clus1
                     up/up 192.168.148.136/24 sti96-vsim-ucs540p
                                                          e0a
true
          sti96-vsim-ucs540p clus2
                     up/up 192.168.148.137/24 sti96-vsim-ucs540p
                                                          e0b
true
vs1
          sti96-vsim-ucs540o data1
                     up/up 10.237.165.87/20 sti96-vsim-ucs540o
                                                          e0d
true
          sti96-vsim-ucs540o data1 inet6
                      up/up fd20:8b1e:b255:9155::583/64
                                              sti96-vsim-ucs540o
                                                          e0d
true
          sti96-vsim-ucs540o data2
                     up/up 10.237.165.88/20 sti96-vsim-ucs540o
                                                          e0e
true
10.237.165.87 D60AB15C2AFC4D6 -> destination box entry to be added in
hosts file.
```

^{18.} If you still get the error message ERROR failed to obtain fallback security principal after adding the destination box entry in the hosts files, then the user/group does not exist in the target system.

```
C:\WRSHDNT>c:\netapp\xcp\xcp copy -acl -fallback-user
D60AB15C2AFC4D6\unknown user -fallback-group BUILTIN\Users
\10.237.165.79\ source share \10.237.165.89\ dest share
c:\netapp\xcp\xcp copy -acl -fallback-user D60AB15C2AFC4D6\unknown user
-fallback-group BUILTIN\Users \\10.237.165.79\source share
\10.237.165.89\dest share
XCP SMB 1.6; (c) 2020 NetApp, Inc.; Licensed to XXX [NetApp Inc] until
Mon Dec 31 00:00:00 2029
ERROR failed to obtain fallback security principal
"D60AB15C2AFC4D6\unknown user". Please check if the principal with the
name "D60AB15C2AFC4D6\unknown user" exists on "D60AB15C2AFC4D6".
ERROR failed to obtain fallback security principal
"D60AB15C2AFC4D6\unknown user". Please check if the principal with the
name "D60AB15C2AFC4D6\unknown user" exists on "D60AB15C2AFC4D6".
ERROR failed to obtain fallback security principal
"D60AB15C2AFC4D6\unknown user". Please check if the principal with the
name "D60AB15C2AFC4D6\unknown user" exists on "D60AB15C2AFC4D6".
ERROR failed to obtain fallback security principal
"D60AB15C2AFC4D6\unknown user". Please check if the principal with the
name "D60AB15C2AFC4D6\unknown_user" exists on "D60AB15C2AFC4D6".
753 scanned, 0 errors, 0 skipped, 0 copied, 0 (0/s), 5s
753 scanned, 0 errors, 0 skipped, 0 copied, 0 (0/s), 10s
753 scanned, 0 errors, 0 skipped, 0 copied, 0 (0/s), 15s
753 scanned, 0 errors, 0 skipped, 284 copied, 27.6KiB (5.54KiB/s), 20s
753 scanned, 0 errors, 0 skipped, 752 copied, 54.7KiB (2.44KiB/s), 22s
C:\WRSHDNT>
```

19. Use xcp copy to migrate CIFs data with ACLs (with or without the root folder).

Without the root folder, run the following commands:

```
C:\WRSHDNT>c:\netapp\xcp\xcp copy -acl -fallback-user
D60AB15C2AFC4D6\Administrator -fallback-group BUILTIN\Users
\\10.237.165.79\source_share \\10.237.165.89\dest_share
c:\netapp\xcp\xcp copy -acl -fallback-user
D60AB15C2AFC4D6\Administrator -fallback-group BUILTIN\Users
\\10.237.165.79\source_share \\10.237.165.89\dest_share
XCP SMB 1.6; (c) 2020 NetApp, Inc.; Licensed to XXX [NetApp Inc] until
Mon Dec 31 00:00:00 2029
753 scanned, 0 errors, 0 skipped, 0 copied, 0 (0/s), 5s
753 scanned, 0 errors, 0 skipped, 0 copied, 0 (0/s), 10s
753 scanned, 0 errors, 0 skipped, 0 copied, 0 (0/s), 15s
753 scanned, 0 errors, 0 skipped, 210 copied, 20.4KiB (4.08KiB/s), 20s
753 scanned, 0 errors, 0 skipped, 752 copied, 54.7KiB (2.38KiB/s), 22s
C:\WRSHDNT>
```

With the root folder, run the following commands:

```
C:\WRSHDNT>c:\netapp\xcp\xcp copy -acl -root -fallback-user
D60AB15C2AFC4D6\Administrator -fallback-group BUILTIN\Users
\10.237.165.79\ source share \10.237.165.89\ dest share
c:\netapp\xcp\xcp copy -acl -root -fallback-user
D60AB15C2AFC4D6\Administrator -fallback-group BUILTIN\Users
\10.237.165.79\ source share \10.237.165.89\ dest share
XCP SMB 1.6; (c) 2020 NetApp, Inc.; Licensed to XXX [NetApp Inc] until
Mon Dec 31 00:00:00 2029
753 scanned, 0 errors, 0 skipped, 0 copied, 0 (0/s), 5s
753 scanned, 0 errors, 0 skipped, 0 copied, 0 (0/s), 10s
753 scanned, 0 errors, 0 skipped, 0 copied, 0 (0/s), 15s
753 scanned, 0 errors, 0 skipped, 243 copied, 23.6KiB (4.73KiB/s), 20s
753 scanned, 0 errors, 0 skipped, 752 copied, 54.7KiB (6.21KiB/s), 25s
753 scanned, 0 errors, 0 skipped, 752 copied, 54.7KiB (0/s), 30s
753 scanned, 0 errors, 0 skipped, 752 copied, 54.7KiB (0/s), 35s
753 scanned, 0 errors, 0 skipped, 752 copied, 54.7KiB (0/s), 40s
753 scanned, 0 errors, 0 skipped, 752 copied, 54.7KiB (0/s), 45s
753 scanned, 0 errors, 0 skipped, 752 copied, 54.7KiB (0/s), 50s
753 scanned, 0 errors, 0 skipped, 752 copied, 54.7KiB (0/s), 55s
753 scanned, 0 errors, 0 skipped, 752 copied, 54.7KiB (0/s), 1mOs
753 scanned, 0 errors, 0 skipped, 752 copied, 54.7KiB (0/s), 1m5s
753 scanned, 0 errors, 0 skipped, 752 copied, 54.7KiB (817/s), 1m8s
C:\WRSHDNT>
```

Next: Best practice guidelines and recommendations.

Copyright Information

Copyright © 2022 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.