



# **Disaster Recovery with VMC on AWS (guest connected)**

NetApp Solutions

NetApp  
December 20, 2022

This PDF was generated from <https://docs.netapp.com/us-en/netapp-solutions/ehc/aws/aws-guest-dr-solution-overview.html> on December 20, 2022. Always check docs.netapp.com for the latest.

# Table of Contents

- TR-4931: Disaster Recovery with VMware Cloud on Amazon Web Services and Guest Connect . . . . . 1
  - Overview . . . . . 1
  - Assumptions, pre-requisites and component overview . . . . . 1
  - Performing DR with SnapCenter . . . . . 1
  - Conclusion . . . . . 69
- TR-4931: Disaster Recovery with VMware Cloud on Amazon Web Services and Guest Connect . . . . . 70
  - AWS guest-connected storage disaster recovery . . . . . 139
  - Disaster recovery . . . . . 139

# TR-4931: Disaster Recovery with VMware Cloud on Amazon Web Services and Guest Connect


Authors: Chris Reno, Josh Powell, and Suresh Thoppay - NetApp Solutions Engineering

## Overview

A proven disaster recovery (DR) environment and plan is critical for organizations to ensure that business-critical applications can be rapidly restored in the event of a major outage. This solution focuses on demonstrating DR use cases with a focus on VMware and NetApp technologies, both on-premises and with VMware Cloud on AWS.

NetApp has a long history of integration with VMware as evidenced by the tens of thousands of customers that have chosen NetApp as their storage partner for their virtualized environment. This integration continues with guest-connected options in the cloud and recent integrations with NFS datastores as well. This solution focuses on the use case commonly referred to as guest-connected storage.

In guest-connected storage, the guest VMDK is deployed on a VMware-provisioned datastore, and application data is housed on iSCSI or NFS and mapped directly to the VM. Oracle and MS SQL applications are used to demonstrate a DR scenario, as shown in the following figure.



## Assumptions, pre-requisites and component overview

Before deploying this solution, review the overview of the components, the required pre-requisites to deploy the solution and assumptions made in documenting this solution.

[DR Solution Requirements, Pre-requisites and Planning](#)

## Performing DR with SnapCenter

In this solution, SnapCenter provides application-consistent snapshots for SQL Server and Oracle application data. This configuration, together with SnapMirror technology, provides high-speed data replication between our on-premises AFF and FSx ONTAP cluster. Additionally, Veeam Backup & Replication provides backup and restore capabilities for our virtual machines.

In this section, we cover the configuration of SnapCenter, SnapMirror, and Veeam for both backup and restore.

The following sections cover configuration and the steps needed to complete a failover at the secondary site:

## Configure SnapMirror relationships and retention schedules

SnapCenter can update SnapMirror relationships within the primary storage system (primary > mirror) and to secondary storage systems (primary > vault) for the purpose of long-term archiving and retention. To do so, you must establish and initialize a data replication relationship between a destination volume and a source volume using SnapMirror.

The source and destination ONTAP systems must be in networks that are peered using Amazon VPC peering, a transit gateway, AWS Direct Connect, or an AWS VPN.

The following steps are required for setting up SnapMirror relationships between an on-premises ONTAP system and FSx ONTAP:



Refer to the [FSx for ONTAP – ONTAP User Guide](#) for more information on creating SnapMirror relationships with FSx.

### Record the source and destination Intercluster logical interfaces

For the source ONTAP system residing on-premises, you can retrieve the inter-cluster LIF information from System Manager or from the CLI.

1. In ONTAP System Manager, navigate to the Network Overview page and retrieve the IP addresses of Type: Intercluster that are configured to communicate with the AWS VPC where FSx is installed.

Name	Status	Storage VM	IPspace	Address	Current Node	Current Port	Portset	Protocols	Type	Thr
veeam_repo	✓	Backup	Default	10.61.181.179	E13A300_1	a0a-181		SMB/CIFS, NFS, S3	Data	0
CM01	✓		Default	10.61.181.180	E13A300_1	a0a-181			Cluster/Node Mgmt	0
HC_N1	✓		Default	10.61.181.183	E13A300_1	a0a-181			Intercluster/Cluster/Node Mgmt	0
HC_N2	✓		Default	10.61.181.184	E13A300_2	a0a-181			Intercluster/Cluster/Node Mgmt	0
lif_ora_svm_614	✓	ora_svm	Default	10.61.181.185	E13A300_1	a0a-181		SMB/CIFS, NFS, FL...	Data	0

2. To retrieve the Intercluster IP addresses for FSx, log into the CLI and run the following command:

```
FSx-Dest::> network interface show -role intercluster
```

```
FsxId0ae40e08acc0dea67::> network interface show -role intercluster
Logical      Status      Network      Current      Current      Is
Vserver      Interface   Admin/Oper   Address/Mask  Node         Port         Home
-----
FsxId0ae40e08acc0dea67
inter_1      up/up      172.30.15.42/25  FsxId0ae40e08acc0dea67-01
                                     e0e         true
inter_2      up/up      172.30.14.28/26  FsxId0ae40e08acc0dea67-02
                                     e0e         true
2 entries were displayed.
```

## Establish cluster peering between ONTAP and FSx

To establish cluster peering between ONTAP clusters, a unique passphrase entered at the initiating ONTAP cluster must be confirmed in the other peer cluster.

1. Set up peering on the destination FSx cluster using the `cluster peer create` command. When prompted, enter a unique passphrase that is used later on the source cluster to finalize the creation process.

```
FSx-Dest::> cluster peer create -address-family ipv4 -peer-addr  
source_intercluster_1, source_intercluster_2  
Enter the passphrase:  
Confirm the passphrase:
```

2. At the source cluster, you can establish the cluster peer relationship using either ONTAP System Manager or the CLI. From ONTAP System Manager, navigate to Protection > Overview and select Peer Cluster.

The screenshot shows the ONTAP System Manager interface. The left sidebar contains a navigation menu with sections: DASHBOARD, STORAGE (with sub-items: Overview, Volumes, LUNs, Consistency Groups, NVMe Namespaces, Shares, Buckets, Qtrees, Quotas, Storage VMs, Tiers), NETWORK (with sub-items: Overview, Ethernet Ports, FC Ports), EVENTS & JOBS, PROTECTION (with sub-items: Overview, Relationships), and HOSTS. The 'Overview' item under the PROTECTION section is highlighted with a red box and a red callout bubble labeled '1'. The main content area is titled 'Overview' and contains three sections: 'Intercluster Settings' with a 'Network Interfaces' table, 'Cluster Peers' with a table and a context menu, and 'Mediator' with a 'Configure' button. The 'Storage VM Peers' section is partially visible at the bottom. Red callout bubbles are numbered: '1' points to the 'Overview' link in the sidebar; '2' points to the context menu icon (three dots) in the 'Cluster Peers' section; '3' points to the 'Peer Cluster' button in the same context menu.

**ONTAP System Manager**

**Overview**

**Intercluster Settings**

Network Interfaces

IP ADDRESS
✓ 10.61.181.184
✓ 172.21.146.217
✓ 10.61.181.183
✓ 172.21.146.216

**Cluster Peers**

PEERED CLUSTER NAME
✓ FsxId0ae40e08acc0dea67
✓ OTS02

Peer Cluster  
Generate Passphrase  
Manage Cluster Peers

**Mediator** ⓘ

Not configured.

Configure

**Storage VM Peers**

PEERED STORAGE VMS
✓ 3

3. In the Peer Cluster dialog box, fill out the required information:
  - a. Enter the passphrase that was used to establish the peer cluster relationship on the destination FSx cluster.
  - b. Select **Yes** to establish an encrypted relationship.
  - c. Enter the intercluster LIF IP address(es) of the destination FSx cluster.

d. Click Initiate Cluster Peering to finalize the process.

**Peer Cluster** ✕

Local ————— ————— Remote

STORAGE VM PERMISSIONS

All storage VMs (incl... ✕

Storage VMs created in the future also will be given permissions.

1 PASSPHRASE ?

.....

It cannot be determined from the passphrase whether this relationship was encrypted. Is the relationship encrypted?

2 Yes No

To generate passphrase, [Launch Remote Cluster](#)

3 Intercluster Network Interfaces IP Addresses

172.30.15.42

172.30.14.28

Cancel

+ Add

4 **Initiate Cluster Peering** Cancel

4. Verify the status of the cluster peer relationship from the FSx cluster with the following command:

```
FSx-Dest::> cluster peer show
```

```
FSxId0ae40e08acc0dea67::> cluster peer show
Peer Cluster Name      Cluster Serial Number Availability  Authentication
-----
E13A300                1-80-000011 Available    ok
```

## Establish SVM peering relationship

The next step is to set up an SVM relationship between the destination and source storage virtual machines that contain the volumes that will be in SnapMirror relationships.

1. From the source FSx cluster, use the following command from the CLI to create the SVM peer relationship:

```
FSx-Dest::> vserver peer create -vserver DestSVM -peer-vserver Backup -peer-cluster OnPremSourceSVM -applications snapmirror
```

2. From the source ONTAP cluster, accept the peering relationship with either ONTAP System Manager or the CLI.
3. From ONTAP System Manager, go to Protection > Overview and select Peer Storage VMs under Storage VM Peers.



4. In the Peer Storage VM's dialog box, fill out the required fields:
  - The source storage VM
  - The destination cluster
  - The destination storage VM





5. Click Peer Storage VMs to complete the SVM peering process.

## Create a snapshot retention policy

SnapCenter manages retention schedules for backups that exist as snapshot copies on the primary storage system. This is established when creating a policy in SnapCenter. SnapCenter does not manage retention policies for backups that are retained on secondary storage systems. These policies are managed separately through a SnapMirror policy created on the secondary FSx cluster and associated with the destination volumes that are in a SnapMirror relationship with the source volume.

When creating a SnapCenter policy, you have the option to specify a secondary policy label that is added to the SnapMirror label of each snapshot generated when a SnapCenter backup is taken.



On the secondary storage, these labels are matched to policy rules associated with the destination volume for the purpose of enforcing retention of snapshots.

The following example shows a SnapMirror label that is present on all snapshots generated as part of a policy used for daily backups of our SQL Server database and log volumes.

### Select secondary replication options ⓘ

☐ Update SnapMirror after creating a local Snapshot copy.

☒ Update SnapVault after creating a local Snapshot copy.

Secondary policy label

Custom Label ⓘ

sql-daily

Error retry count

3 ⓘ

For more information on creating SnapCenter policies for a SQL Server database, see the [SnapCenter documentation](#).

You must first create a SnapMirror policy with rules that dictate the number of snapshot copies to retain.

1. Create the SnapMirror Policy on the FSx cluster.

```
FSx-Dest::> snapmirror policy create -vserver DestSVM -policy  
PolicyName -type mirror-vault -restart always
```

2. Add rules to the policy with SnapMirror labels that match the secondary policy labels specified in the SnapCenter policies.

```
FSx-Dest::> snapmirror policy add-rule -vserver DestSVM -policy  
PolicyName -snapmirror-label SnapMirrorLabelName -keep  
#ofSnapshotsToRetain
```

The following script provides an example of a rule that could be added to a policy:

```
FSx-Dest::> snapmirror policy add-rule -vserver sql_svm_dest -policy Async_SnapCenter_SQL -snapmirror-label sql-ondemand -keep 15
```



Create additional rules for each SnapMirror label and the number of snapshots to be retained (retention period).

### Create destination volumes

To create a destination volume on FSx that will be the recipient of snapshot copies from our source volumes, run the following command on FSx ONTAP:

```
FSx-Dest::> volume create -vserver DestSVM -volume DestVolName  
-aggregate DestAggrName -size VolSize -type DP
```

### Create the SnapMirror relationships between source and destination volumes

To create a SnapMirror relationship between a source and destination volume, run the following command on FSx ONTAP:

```
FSx-Dest::> snapmirror create -source-path  
OnPremSourceSVM:OnPremSourceVol -destination-path DestSVM:DestVol -type  
XDP -policy PolicyName
```

### Initialize the SnapMirror relationships

Initialize the SnapMirror relationship. This process initiates a new snapshot generated from the source volume and copies it to the destination volume.

To create a volume, run the following command on FSx ONTAP:

```
FSx-Dest::> volume create -vserver DestSVM -volume DestVolName  
-aggregate DestAggrName -size VolSize -type DP
```

## Deploy and configure Windows SnapCenter server on-premises.

## Deploy Windows SnapCenter Server on premises

This solution uses NetApp SnapCenter to take application-consistent backups of SQL Server and Oracle databases. In conjunction with Veeam Backup & Replication for backing up virtual machine VMDKs, this provides a comprehensive disaster recovery solution for on-premises and cloud-based datacenters.

SnapCenter software is available from the NetApp support site and can be installed on Microsoft Windows systems that reside either in a domain or workgroup. A detailed planning guide and installation instructions can be found at the [NetApp Documentation Center](#).

The SnapCenter software can be obtained at [this link](#).


After it is installed, you can access the SnapCenter console from a web browser using *https://Virtual\_Cluster\_IP\_or\_FQDN:8146*.

After you log into the console, you must configure SnapCenter for backup SQL Server and Oracle databases.

## Add storage controllers to SnapCenter

To add storage controllers to SnapCenter, complete the following steps:

1. From the left menu, select Storage Systems and then click New to begin the process of adding your storage controllers to SnapCenter.



The screenshot shows the NetApp SnapCenter web interface. The left sidebar contains a navigation menu with options: Dashboard, Resources, Monitor, Reports, Hosts, Storage Systems (selected), Settings, and Alerts. The main content area is titled 'ONTAP Storage' and includes a 'Type' dropdown set to 'ONTAP SVMs' and a 'Search by Name' input field. A red box highlights a '+ New' button in the top right corner of the main content area. Below this, a table titled 'ONTAP Storage Connections' displays a list of storage systems.

<input type="checkbox"/>	Name	IP	Cluster Name	User Name	Platform	Controller License
<input type="checkbox"/>	<a href="#">Backup</a>	172.16.13.17	172.16.13.17		AFF	✓
<input type="checkbox"/>	<a href="#">FS02</a>	172.16.13.17	172.16.13.17		AFF	✓
<input type="checkbox"/>	<a href="#">ora_svm</a>	172.16.13.17	172.16.13.17		AFF	✓
<input type="checkbox"/>	<a href="#">ora_svm_dest</a>		172.30.15.42		AFF	Not applicable
<input type="checkbox"/>	<a href="#">sql_svm</a>	172.16.13.17	172.16.13.17		AFF	✓
<input type="checkbox"/>	<a href="#">sql_svm_dest</a>		172.30.15.42		AFF	Not applicable
<input type="checkbox"/>	<a href="#">svm_HCAppls</a>		172.30.15.42		AFF	Not applicable


2. In the Add Storage System dialog box, add the management IP address for the local on-premises ONTAP cluster and the username and password. Then click Submit to begin discovery of the storage system.

## Add Storage System

### Add Storage System

Storage System	<input type="text" value="10.61.181.180"/>
Username	<input type="text" value="admin"/>
Password	<input type="password" value="••••••••"/>

### Event Management System (EMS) & AutoSupport Settings

- ☒ Send AutoSupport notification to storage system
- ☒ Log SnapCenter Server events to syslog
-  **More Options** : Platform, Protocol, Preferred IP etc..

- Repeat this process to add the FSx ONTAP system to SnapCenter. In this case, select More Options at the bottom of the Add Storage System window and click the check box for Secondary to designate the FSx system as the secondary storage system updated with SnapMirror copies or our primary backup snapshots.

## More Options




Platform FAS

☒ Secondary 

Protocol HTTPS

Port 443

Timeout 60 seconds 

☐ Preferred IP 

Save

Cancel

For more information related to adding storage systems to SnapCenter, see the documentation at [this link](#).

## Add hosts to SnapCenter

The next step is adding host application servers to SnapCenter. The process is similar for both SQL Server and Oracle.

1. From the left menu, select Hosts and then click Add to begin the process of adding storage controllers to SnapCenter.
2. In the Add Hosts window, add the Host Type, Hostname, and the host system Credentials. Select the plug-in type. For SQL Server, select the Microsoft Windows and Microsoft SQL Server plug-in.

**NetApp SnapCenter®**

**Managed Hosts**

Search by Name

<input type="checkbox"/>	Name
<input type="checkbox"/>	<a href="#">oraclesrv_01.sddc.netapp.com</a>
<input type="checkbox"/>	<a href="#">oraclesrv_02.sddc.netapp.com</a>
<input type="checkbox"/>	<a href="#">oraclesrv_03.sddc.netapp.com</a>
<input type="checkbox"/>	<a href="#">oraclesrv_04.sddc.netapp.com</a>
<input type="checkbox"/>	<a href="#">oraclesrv_05.sddc.netapp.com</a>
<input type="checkbox"/>	<a href="#">oraclesrv_06.sddc.netapp.com</a>
<input type="checkbox"/>	<a href="#">oraclesrv_07.sddc.netapp.com</a>
<input type="checkbox"/>	<a href="#">oraclesrv_08.sddc.netapp.com</a>
<input type="checkbox"/>	<a href="#">oraclesrv_09.sddc.netapp.com</a>
<input type="checkbox"/>	<a href="#">oraclesrv_10.sddc.netapp.com</a>

**Add Host**

Host Type: Windows

Host Name: sqlsrv-01.sddc.netapp.com

Credentials: sddc-jpowell

**Select Plug-ins to Install** SnapCenter Plug-ins Package 4.6 for Windows

- ☒ Microsoft Windows
- ☒ Microsoft SQL Server
- ☐ Microsoft Exchange Server
- ☐ SAP HANA

[More Options](#) : Port, gMSA, Install Path, Custom Plug-Ins...

**Submit** **Cancel**

3. For Oracle, fill out the required fields in the Add Host dialog box and select the check box for the Oracle Database plug-in. Then click Submit to begin the discovery process and to add the host to SnapCenter.



### Add Host

Host Type Linux ▾

Host Name oraclesrv\_11.sddc.netapp.com

Credentials root ▾



### Select Plug-ins to Install SnapCenter Plug-ins Package 4.6 for Linux

☒ Oracle Database

☐ SAP HANA

 [More Options](#) : Port, Install Path, Custom Plug-Ins...


Submit

Cancel

## Create SnapCenter policies

Policies establish the specific rules to be followed for a backup job. They include, but are not limited to, the backup schedule, replication type, and how SnapCenter handles backing up and truncating transaction logs.

You can access policies in the Settings section of the SnapCenter web client.



For complete information on creating policies for SQL Server backups, see the [SnapCenter documentation](#).

For complete information on creating policies for Oracle backups, see the [SnapCenter documentation](#).

### Notes:

- As you progress through the policy creation wizard, take special note of the Replication section. In this section you stipulate the types of secondary SnapMirror copies that you want taken during the backups process.
- The “Update SnapMirror after creating a local Snapshot copy” setting refers to updating a SnapMirror relationship when that relationship exists between two storage virtual machines residing on the same cluster.
- The “Update SnapVault after creating a local SnapShot copy” setting is used to update a SnapMirror relationship that exists between two separate cluster and between an on-premises ONTAP system and Cloud Volumes ONTAP or FSxN.

The following image shows the preceding options and how they look in the backup policy wizard.

## New SQL Server Backup Policy

1 Name

2 Backup Type

3 Retention

4 Replication

5 Script

### Select secondary replication options ⓘ

☐ Update SnapMirror after creating a local Snapshot copy.

☐ Update SnapVault after creating a local Snapshot copy.

Secondary policy label

Choose

Error retry count

3

## Create SnapCenter Resource Groups

Resource Groups allow you to select the database resources you want to include in your backups and the policies followed for those resources.

1. Go to the Resources section in the left-hand menu.
2. At the top of the window, select the resource type to work with (In this case Microsoft SQL Server) and then click New Resource Group.

Name	Resource Count	Tags	Policies	Last Backup	Overall Status
SQLSRV-01	1		SQL-Daily SQL-Hourly SQL-OnDemand SQL-Weekly	05/11/2022 ...	Completed
SQLSRV-02	1		SQL-Daily SQL-Hourly SQL-OnDemand SQL-Weekly	03/28/2022 ...	Failed
SQLSRV-03	1		SQL-Daily SQL-Hourly	05/11/2022 ...	Completed

The SnapCenter documentation covers step-by-step details for creating Resource Groups for both SQL Server and Oracle databases.

For backing up SQL resources, follow [this link](#).

For Backing up Oracle resources, follow [this link](#).

## Deploy and configure Veeam Backup Server

Veeam Backup & Replication software is used in the solution to back up our application virtual machines and archive a copy of the backups to an Amazon S3 bucket using a Veeam scale-out backup repository (SOBR). Veeam is deployed on a Windows server in this solution. For specific guidance on deploying Veeam, see the [Veeam help Center Technical documentation](#).

## Configure Veeam scale-out backup repository

After you deploy and license the software, you can create a scale-out backup repository (SOBR) as target storage for backup jobs. You should also include an S3 bucket as a backup of VM data offsite for disaster recovery.


See the following prerequisites before getting started.

1. Create an SMB file share on your on-premises ONTAP system as the target storage for backups.
2. Create an Amazon S3 bucket to include in the SOBR. This is a repository for the offsite backups.

## Add ONTAP Storage to Veeam

First, add the ONTAP storage cluster and associated SMB/NFS filesystem as storage infrastructure in Veeam.

1. Open the Veeam console and log in. Navigate to Storage Infrastructure and then select Add Storage.



2. In the Add Storage wizard, select NetApp as the storage vendor and then select Data ONTAP.
3. Enter the management IP address and check the NAS Filer box. Click Next.

## New NetApp Data ONTAP Storage



### Name

Register NetApp Data ONTAP storage by specifying DNS name or IP address.

<b>Name</b>	Management server DNS name or IP address: <input type="text" value="10.61.181.180"/>
Credentials	Description: <input type="text" value="Created by SDDC\jpowell at 5/17/2022 10:34 AM."/>
NAS Filer	Role: <input type="checkbox"/> Block or file storage for VMware vSphere <input type="checkbox"/> Block storage for Microsoft Windows servers <input checked="" type="checkbox"/> NAS filer
Apply	
Summary	

4. Add your credentials to access the ONTAP cluster.

## New NetApp Data ONTAP Storage



### Credentials

Specify account with storage administrator privileges.

<b>Name</b>	Credentials: <input type="text" value="HCIEUC\Admin (HCIEUC\Admin, last edited: 98 days ago)"/>	<input type="button" value="Add..."/>
Credentials	<a href="#">Manage accounts</a>	
NAS Filer	Protocol: <input type="text" value="HTTPS"/>	
Apply	Port: <input type="text" value="443"/>	
Summary		

5. On the NAS Filer page choose the desired protocols to scan and select Next.

New NetApp Data ONTAP Storage ✕


**NAS Filer**

Specify how this storage can be accessed by file backup jobs.

Name	Protocol to use:
Credentials	<input checked="" type="checkbox"/> SMB
<b>NAS Filer</b>	<input type="checkbox"/> NFS
Apply	<input checked="" type="checkbox"/> Create required export rules automatically
Summary	Volumes to scan:
	<input type="text" value="All volumes"/> <span style="float: right;">Choose...</span>
	Backup proxies to use:
	<input type="text" value="Automatic selection"/> <span style="float: right;">Choose...</span>


< Previous
Apply
Finish
Cancel

- Complete the Apply and Summary pages of the wizard and click Finish to begin the storage discovery process. After the scan completes, the ONTAP cluster is added along with the NAS filers as available resources.



- Create a backup repository using the newly discovered NAS shares. From Backup Infrastructure, select Backup Repositories and click the Add Repository menu item.





8. Follow all steps in the New Backup Repository Wizard to create the repository. For detailed information on creating Veeam Backup Repositories, see the [Veeam documentation](#).

## New Backup Repository

**Share**

Type in UNC path to share (mapped drives are not supported), specify share access credentials and how backup jobs should write data to this share.

Name

Shared folder:

Browse...

Share

Use \\server\folder format

Repository

☒ This share requires access credentials:

sddc\administrator (sddc\administrator, last edited: 85 days ago)



Add...

Mount Server

[Manage accounts](#)

Review

Gateway server:

☒ Automatic selection☐ The following server:

Apply

Use this option to improve performance and reliability of backup to a NAS located in a remote site.

Summary

&lt; Previous

Next &gt;


Finish

Cancel

## Add the Amazon S3 bucket as a backup repository

The next step is to add the Amazon S3 storage as a backup repository.

1. Navigate to Backup Infrastructure > Backup Repositories. Click Add Repository.



2. In the Add Backup Repository wizard, select Object Storage and then Amazon S3. This starts the New Object Storage Repository wizard.

## Add Backup Repository

Select the type of backup repository you want to add.



### Direct attached storage

Microsoft Windows or Linux server with internal or direct attached storage. This configuration enables data movers to run directly on the server, allowing for fastest performance.



### Network attached storage

Network share on a file server or a NAS device. When backing up to a remote share, we recommend that you select a gateway server located in the same site with the share.



### Deduplicating storage appliance

Dell EMC Data Domain, ExaGrid, HPE StoreOnce or Quantum DXi. If you are unable to meet the requirements of advanced integration via native appliance API, use the network attached storage option instead.



### Object storage

On-prem object storage system or a cloud object storage provider. Object storage can only be used as a Capacity Tier of scale-out backup repositories, backing up directly to object storage is not currently supported.

3. Provide a name for your object storage repository and click Next.
4. In the next section, provide your credentials. You need an AWS Access Key and Secret Key.

### New Object Storage Repository



#### Account

Specify AWS account to use for connecting to Amazon S3 storage bucket.


Name	Credentials:
Account	<input type="text" value="AKIAH4H43ZT557HXQT2W (last edited: 107 days ago)"/> <a href="#">Add...</a>
	<a href="#">Manage cloud accounts</a>
Bucket	AWS region:
Summary	<input type="text" value="Global"/>
<input type="checkbox"/> Use the following gateway server:	
<input type="text" value="veeam.sddc.netapp.com (Backup server)"/>	
<small>Select a gateway server to proxy access to Amazon S3. If no gateway server is specified, all scale-out backup repository extents must have direct Internet access.</small>	
<div>&lt; Previous    Next &gt;    Finish    Cancel</div>	

5. After the Amazon configuration loads, choose your datacenter, bucket, and folder and click Apply. Finally, click Finish to close out the wizard.

## Create scale-out backup repository

Now that we have added our storage repositories to Veeam, we can create the SOBR to automatically tier backup copies to our offsite Amazon S3 object storage for disaster recovery.

1. From Backup Infrastructure, select Scale-out Repositories and then click the Add Scale-out Repository menu item.



2. In the New Scale-out Backup Repository provide a name for the SOBR and click Next.
3. For the Performance Tier, choose the backup repository that contains the SMB share residing on your local ONTAP cluster.

## New Scale-out Backup Repository



### Performance Tier

Select backup repositories to use as the landing zone and for the short-term retention.

Name	Extents:				
Performance Tier	<table border="1"> <thead> <tr> <th>Name</th> <th></th> </tr> </thead> <tbody> <tr> <td>VBRRepo2</td> <td></td> </tr> </tbody> </table>	Name		VBRRepo2	
Name					
VBRRepo2					
Placement Policy	<div>Add...</div> <div>Remove</div>				

- For the Placement Policy, choose either Data Locality or Performance based your requirements. Select next.
- For Capacity Tier we extend the SOBR with Amazon S3 object storage. For the purposes of disaster recovery, select Copy Backups to Object Storage as Soon as They are Created to ensure timely delivery of our secondary backups.

## New Scale-out Backup Repository



### Capacity Tier

Specify object storage to copy backups to for redundancy and DR purposes. Older backups can be moved to object storage completely to reduce long-term retention costs while preserving the ability to restore directly from offloaded backups.

Name	
Performance Tier	
Placement Policy	
Capacity Tier	<div> <input checked="" type="checkbox"/> Extend scale-out backup repository capacity with object storage:           <div> <div>Amazon S3 Repo</div> <div>Add...</div> </div> </div>
Archive Tier	<div>Define time windows when uploading to capacity tier is allowed</div> <div>Window...</div>
Summary	<div> <input checked="" type="checkbox"/> Copy backups to object storage as soon as they are created            Create additional copy of your backups for added redundancy by having all backups copied to the capacity tier as soon as they are created on the performance tier.         </div> <div> <input checked="" type="checkbox"/> Move backups to object storage as they age out of the operational restore window            Reduce your long-term retention costs by moving older backups to object storage completely while preserving the ability to restore directly from offloaded backups.         </div> <div>           Move backup files older than <input type="text" value="14"/> days (your operational restore window)           <div>Override...</div> </div> <div> <input type="checkbox"/> Encrypt data uploaded to object storage            Password: <div></div> <div>Add...</div> <div>Manage passwords</div> </div>

< Previous

Next >

Finish

Cancel

- Finally, select Apply and Finish to finalize creation of the SOBR.

## Create the scale-out backup repository jobs

The final step to configuring Veeam is to create backup jobs using the newly created SOBR as the backup destination. Creating backup jobs is a normal part of any storage administrator's repertoire and we do not cover the detailed steps here. For more complete information on creating backup jobs in Veeam, see the [Veeam Help Center Technical Documentation](#).

## Cloud backup tools and configuration

To conduct a failover of application VMs and database volumes to VMware Cloud Volume services running in AWS, you must install and configure a running instance of both SnapCenter Server and Veeam Backup and Replication Server. After the failover is complete, you must also configure these tools to resume normal backup operations until a failback to the on-premises datacenter is planned and executed.

### Deploy secondary Windows SnapCenter Server

SnapCenter Server is deployed in the VMware Cloud SDDC or installed on an EC2 instance residing in a VPC with network connectivity to the VMware Cloud environment.

SnapCenter software is available from the NetApp support site and can be installed on Microsoft Windows systems that reside either in a domain or workgroup. A detailed planning guide and installation instructions can be found at the [NetApp documentation center](#).

You can find the SnapCenter software at [this link](#).

### Configure secondary Windows SnapCenter Server

To perform a restore of application data mirrored to FSx ONTAP, you must first perform a full restore of the on-premises SnapCenter database. After this process is complete, communication with the VMs is reestablished and application backups can now resume using FSx ONTAP as the primary storage.

To achieve this, you must complete the following items on the SnapCenter Server:

1. Configure the computer name to be identical to the original on-premises SnapCenter Server.
2. Configure networking to communicate with VMware Cloud and the FSx ONTAP instance.
3. Complete the procedure to restore the SnapCenter database.
4. Confirm that SnapCenter is in Disaster Recovery mode to make sure that FSx is now the primary storage for backups.
5. Confirm that communication is reestablished with the restored virtual machines.

For more information on completing these steps, see to section "[SnapCenter database Restore Process](#)".

### Deploy secondary Veeam Backup & Replication server

You can install the Veeam Backup & Replication server on a Windows server in the VMware Cloud on AWS or on an EC2 instance. For detailed implementation guidance, see the [Veeam Help Center Technical Documentation](#).

## Configure secondary Veeam Backup & Replication server

To perform a restore of virtual machines that have been backed up to Amazon S3 storage, you must install the Veeam Server on a Windows server and configure it to communicate with VMware Cloud, FSx ONTAP, and the S3 bucket that contains the original backup repository. It must also have a new backup repository configured on FSx ONTAP to conduct new backups of the VMs after they are restored.

To perform this process, the following items must be completed:

1. Configure networking to communicate with VMware Cloud, FSx ONTAP, and the S3 bucket containing the original backup repository.
2. Configure an SMB share on FSx ONTAP to be a new backup repository.
3. Mount the original S3 bucket that was used as part of the scale-out backup repository on premises.
4. After restoring the VM, establish new backup jobs to protect SQL and Oracle VMs.

For more information on restoring VMs using Veeam, see the section ["Restore Application VMs with Veeam Full Restore"](#).

## SnapCenter database backup for disaster recovery

SnapCenter allows for the backup and recovery of its underlying MySQL database and configuration data for the purpose of recovering the SnapCenter server in the case of a disaster. For our solution, we recovered the SnapCenter database and configuration on an AWS EC2 instance residing in our VPC. For more information on this step, see [this link](#).

### SnapCenter backup prerequisites

The following prerequisites are required for SnapCenter backup:

- A volume and SMB share created on the on-premises ONTAP system to locate the backed-up database and configuration files.
- A SnapMirror relationship between the on-premises ONTAP system and FSx or CVO in the AWS account. This relationship is used for transporting the snapshot containing the backed-up SnapCenter database and configuration files.
- Windows Server installed in the cloud account, either on an EC2 instance or on a VM in the VMware Cloud SDDC.
- SnapCenter installed on the Windows EC2 instance or VM in VMware Cloud.



## SnapCenter backup and restore process summary

- Create a volume on the on-premises ONTAP system for hosting the backup db and config files.
- Set up a SnapMirror relationship between on-premises and FSx/CVO.
- Mount the SMB share.
- Retrieve the Swagger authorization token for performing API tasks.
- Start the db restore process.
- Use the xcopy utility to copy the db and config file local directory to the SMB share.
- On FSx, create a clone of the ONTAP volume (copied via SnapMirror from on-premises).
- Mount the SMB share from FSx to EC2/VMware Cloud.
- Copy the restore directory from the SMB share to a local directory.
- Run the SQL Server restore process from Swagger.

## Back up the SnapCenter database and configuration

SnapCenter provides a web client interface for executing REST API commands. For information on accessing the REST APIs through Swagger, see the SnapCenter documentation at [this link](#).


## Log into Swagger and obtain authorization token

After you have navigated to the Swagger page, you must retrieve an authorization token to initiate the database restore process.

1. Access the SnapCenter Swagger API web page at *https://<SnapCenter Server IP>:8146/swagger/*.



2. Expand the Auth section and click Try it Out.



3. In the UserOperationContext area, fill in the SnapCenter credentials and role and click Execute.

Name	Description
TokenNeverExpires	Token never expires
boolean (query)	<div>false</div>
<b>UserOperationContext</b> * required	User credentials
object (body)	<div>Edit Value   Model</div> <pre>{   "UserOperationContext": {     "User": {       "Name": "localhost\\scadmin",       "Passphrase": "NetApp321",       "Rolename": "SnapCenterAdmin"     }   } }</pre> <div>Cancel</div> <div>Parameter content type</div> <div>application/json</div> <div>Execute</div>

- In the Response body below, you can see the token. Copy the token text for authentication when executing the backup process.

200 Response body


```
{
  "PluginName": null,
  "HostId": 0,
  "RoleId": null,
  "JobIds": null
},
{
  "User": {
    "Token": "KlYxOg==tsV6EOtdtAmAYpe8q5SG6wcoGaSjwME6jrNy5CsY63HQ5LkoZLIESRNAhpGJJ00UQynENDgtVGDZnvx+I/ZJZIn5MINZrj6CLfGTApplGmcagT08bqb5bMTx07EcdRAidzAXUDb3GyLOKtW0GdwKzSeUwKj3uVupnk1E3lslK6PRBv9RS8j0qHQvo4v4RL0hhThhwPhV9/23nFeJVP/p1Ev4vrV/zeZVTUHFHUM069XRe5cuW9nwyj4b0I5Y5FN3XDkjqQ=",
    "Name": "SCAdmin",
    "TokenHashed": null,
    "Type": "",
    "TokenTime": "2022-03-22T14:21:57.3665661-07:00",
    "Id": "1",
    "FullName": "SCAdmin",
    "Host": null,
    "Author": null,
    "UserName": "",
    "Domain": "",
    "Passphrase": ""
  }
}
```

Download

## Perform a SnapCenter database backup

Next go to the Disaster Recovery area on the Swagger page to begin the SnapCenter backup process.

1. Expand the Disaster Recovery area by clicking it.

**Disaster Recovery** 

GET

/4.6/disasterrecovery/server/backup

Fetch all the existing SnapCenter Server DR Backups.

POST

/4.6/disasterrecovery/server/backup

Starts the SnapCenter Server DR backup.

DELETE

/4.6/disasterrecovery/server/backup

Deletes the existing Snapcenter DR backup.

POST

/4.6/disasterrecovery/server/restore

Starts SnapCenter Server Restore.

POST

/4.6/disasterrecovery/storage

Enable or disable the storage disaster recovery.

2. Expand the /4.6/disasterrecovery/server/backup section and click Try it Out.

POST

/4.6/disasterrecovery/server/backup

Starts the SnapCenter Server DR backup.

Starts and creates a new SnapCenter Server DR backup.

Parameters 

Try it out

3. In the SmDRBackupRequest section, add the correct local target path and select Execute to start the backup of the SnapCenter database and configuration.



The backup process does not allow backing up directly to an NFS or CIFS file share.

Name	Description
<b>Token</b> * required string (header)	User authorization token <div>TUHFHUM069XRe5cuW9nwyj4b0l5Y5FN3XDkjQ==</div>
<b>SmDRBackupRequest</b> * required object (body)	Parameters to take Backup <div><div>Edit Value   Model</div><div><pre>{   "TargetPath": "C:\\\\SnapCenter_Backups\\\\" }</pre></div></div> <div>Cancel</div> <div>Parameter content type application/json</div>

Execute

## Monitor the backup job from SnapCenter

Log into SnapCenter to review log files when starting the database restore process. Under the Monitor section, you can view the details of the SnapCenter server disaster recovery backup.

### Job Details

#### SnapCenter Server disaster recovery backup

- ✓ ▾ SnapCenter Server disaster recovery backup
  - ✓ ▶ Precheck validation
  - ✓ ▶ Disaster recovery backup of 'oraclesrv\_04.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of SnapCenter Server 'SnapCenter.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'oraclesrv\_02.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'oraclesrv\_03.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'oraclesrv\_05.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'oraclesrv\_07.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'sqlsrv-02.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'sqlsrv-03.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'oraclesrv\_10.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'sqlsrv-04.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'sqlsrv-01.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'sqlsrv-05.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'oraclesrv\_09.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'sqlsrv-06.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'sqlsrv-07.sddc.netapp.com'

**i** Task Name: SnapCenter Server disaster recovery backup Start Time: 03/23/2022 10:27:11 AM End Time: 03/23/2022 10:27:47 AM

[View Logs](#)[Cancel Job](#)[Close](#)

### Use XCOPY utility to copy the database backup file to the SMB share

Next you must move the backup from the local drive on the SnapCenter server to the CIFS share that is used to SnapMirror copy the data to the secondary location located on the FSx instance in AWS. Use xcopy with specific options that retain the permissions of the files.

Open a command prompt as Administrator. From the command prompt, enter the following commands:

```
xcopy <Source_Path> \\<Destination_Server_IP>\<Folder_Path> /O /X  
/E /H /K  
xcopy c:\SC_Backups\SnapCenter_DR \\10.61.181.185\snapcenter_dr /O  
/X /E /H /K
```

## Failover

### Disaster occurs at primary site

For a disaster that occurs at the primary on-premises datacenter, our scenario includes failover to a secondary site residing on Amazon Web Services infrastructure using VMware Cloud on AWS. We assume that the virtual machines and our on-premises ONTAP cluster are no longer accessible. In addition, both the SnapCenter and Veeam virtual machines are no longer accessible and must be rebuilt at our secondary site.

This section address failover of our infrastructure to the cloud, and we cover the following topics:

- SnapCenter database restore. After a new SnapCenter server has been established, restore the MySQL database and configuration files and toggle the database into disaster recovery mode in order to allow the secondary FSx storage to become the primary storage device.
- Restore the application virtual machines using Veeam Backup & Replication. Connect the S3 storage that contains the VM backups, import the backups, and restore them to VMware Cloud on AWS.
- Restore the SQL Server application data using SnapCenter.
- Restore the Oracle application data using SnapCenter.



## SnapCenter database restore process


SnapCenter supports disaster recovery scenarios by allowing the backup and restore of its MySQL database and configuration files. This allows an administrator to maintain regular backups of the SnapCenter database at the on-premises datacenter and later restore that database to a secondary SnapCenter database.

To access the SnapCenter backup files on the remote SnapCenter server, complete the following steps:

1. Break the SnapMirror relationship from the FSx cluster, which makes the volume read/write.
2. Create a CIFS server (if necessary) and create a CIFS share pointing to the junction path of the cloned volume.
3. Use xcopy to copy the backup files to a local directory on the secondary SnapCenter system.
4. Install SnapCenter v4.6.
5. Ensure that SnapCenter server has the same FQDN as the original server. This is required for the db restore to be successful.

To start the restore process, complete the following steps:

1. Navigate to the Swagger API web page for the secondary SnapCenter server and follow the previous instructions to obtain an authorization token.
2. Navigate to the Disaster Recovery section of the Swagger page, select `/4.6/disasterrecovery/server/restore`, and click Try it Out.




**POST** `/4.6/disasterrecovery/server/restore` Starts SnapCenter Server Restore.

Starts SnapCenter Server Restore.

Parameters Try it out

3. Paste in your authorization token and, in the SmDRResterRequest section, paste in the name of the backup and the local directory on the secondary SnapCenter server.




Name	Description
<b>Token</b> * required string (header)	User authorization token
<b>SmDRResterRequest</b> * required object (body)	Parameters to take for Restore

[Edit Value](#) [Model](#)

```
{
  "BackupName": "SnapCenter.sddc.netapp.com_03-23-2022_12.38.00.6713",
  "BackupPath": "C:\\SnapCenter\\"
}
```

4. Select the Execute button to start the restore process.

5. From SnapCenter, navigate to the Monitor section to view the progress of the restore job.



The screenshot shows the NetApp SnapCenter web interface. The top navigation bar includes 'Jobs', 'Schedules', 'Events', and 'Logs'. The left sidebar contains links to 'Dashboard', 'Resources', 'Monitor' (selected), 'Reports', 'Hosts', 'Storage Systems', 'Settings', and 'Alerts'. The main content area displays a table of jobs under the heading 'Jobs - Filter'.

ID	Status	Name
20482	✓	SnapCenter Server Disaster Recovery
20481	✓	SnapCenter Server disaster recovery backup
20480	✗	SnapCenter Server disaster recovery backup
20475	✓	Backup of Resource Group 'SQLSRV-09' with policy 'SQL-Hourly'
20474	✓	Backup of Resource Group 'SQLSRV-05' with policy 'SQL-Hourly'
20473	⌚	Backup of Resource Group 'OracleSrv_06' with policy 'Oracle-Hourly'
20472	✗	SnapCenter Server disaster recovery backup

### Job Details

#### SnapCenter Server Disaster Recovery

- ✓ ▼ SnapCenter Server Disaster Recovery
- ✓ ▼ Prepare for restore job
- ✓ ▼ Precheck validation
- ✓ ▼ Saving original server state
- ✓ ▼ Schedule restore
- ✓ ▼ Repository restore
- ✓ ▼ Config restore
- ✓ ▼ Reset MySQL password

6. To enable SQL Server restores from secondary storage, you must toggle the SnapCenter database into Disaster Recovery mode. This is performed as a separate operation and initiated on the Swagger API web page.
- Navigate to the Disaster Recovery section and click `/4.6/disasterrecovery/storage`.
  - Paste in the user authorization token.
  - In the `SmSetDisasterRecoverySettingsRequest` section, change `EnableDisasterRecover` to `true`.
  - Click Execute to enable disaster recovery mode for SQL Server.

Name	Description
<b>Token</b> * required string (header)	User authorization token <div>KlYxOg==rMXzS7EPIGRzTXjfton6Q+JoNGpueQt</div>
<b>SmSetDisasterRecoverySettingsRequest</b> * required object (body)	Parameters to enable or disable the DR mode <div> Edit Value   Model <pre>{   "EnableDisasterRecovery": true }</pre> </div>



See comments regarding additional procedures.


## Restore application VMs with Veeam full restore

## Create a backup repository and import backups from S3

From the secondary Veeam server, import the backups from S3 storage and restore the SQL Server and Oracle VMs to your VMware Cloud cluster.

To import the backups from the S3 object that was part of the on-premises scale-out backup repository, complete the following steps:

1. Go to Backup Repositories and click Add Repository in the top menu to launch the Add Backup Repository wizard. On the first page of the wizard, select Object Storage as the backup repository type.



2. Select Amazon S3 as the Object Storage type.



## Object Storage



Select the type of object storage you want to use as a backup repository.



### S3 Compatible

Adds an on-premises object storage system or a cloud object storage provider.



### Amazon S3

Adds Amazon cloud object storage. Amazon S3, Amazon S3 Glacier (including Deep Archive) and Amazon Snowball Edge are supported.



### Google Cloud Storage

Adds Google Cloud storage. Both Standard and Nearline storage classes are supported.



### IBM Cloud Object Storage

Adds IBM Cloud object storage. S3 compatible versions of both on-premises and IBM Cloud storage offerings are supported.



### Microsoft Azure Storage

Adds Microsoft Azure cloud object storage. Microsoft Azure Blob Storage, Microsoft Azure Archive Storage and Microsoft Azure Data Box are supported.

3. From the list of Amazon Cloud Storage Services, select Amazon S3.



## Amazon Cloud Storage Services



Select the type of Amazon storage you want to use as a backup repository.



### Amazon S3

Adds Amazon S3 storage. Both Standard and Infrequent Access (IA) storage classes are supported.



### Amazon S3 Glacier

Adds Amazon S3 Glacier storage. Both Amazon S3 Glacier and Glacier Deep Archive are supported.




### AWS Snowball Edge

Adds AWS Snowball Edge appliance to enable seeding of backups into Amazon S3 object storage.

4. Select your pre-entered credentials from the drop-down list or add a new credential for accessing the cloud storage resource. Click Next to continue.

New Object Storage Repository ✕


 **Account**  
Specify AWS account to use for connecting to Amazon S3 storage bucket.

Name	
Account	<b>Credentials:</b> <div>AKIA4H43ZT53YJXPY2Y (last edited: 33 days ago) <span>▼</span> <span>Add...</span></div> <div><a href="#">Manage cloud accounts</a></div>
Bucket	<b>AWS region:</b> Global <span>▼</span>
Summary	<div><input type="checkbox"/> Use the following gateway server: EC2AMAZ-3POTKQV (Backup server) <span>▼</span></div> <div>Select a gateway server to proxy access to Amazon S3. If no gateway server is specified, all scale-out backup repository extents must have direct Internet access.</div>

< Previous Next > Finish Cancel

5. On the Bucket page, enter the data center, bucket, folder, and any desired options. Click Apply.

New Object Storage Repository ✕

 **Bucket**  
Specify Amazon S3 bucket to use.

Name	Data center: US East (N. Virginia) <span>▼</span>
Account	Bucket: ehcveeamrepo <span>Browse...</span>
Bucket	Folder: RTP <span>Browse...</span>
Summary	<p><input type="checkbox"/> Limit object storage consumption to: 10 <span>▼</span> TB <span>▼</span> This is a soft limit to help control your object storage spend. If the specified limit is exceeded, already running backup offload tasks will be allowed to complete, but no new tasks will be started.</p> <p><input type="checkbox"/> Make recent backups immutable for: 30 <span>▼</span> days Protects backups from modification or deletion by ransomware, hackers or malicious insiders using native object storage capabilities.</p> <p><input type="checkbox"/> Use infrequent access storage class (may result in higher costs) With lower price per GB but higher retrieval and early deletion fees, this storage class is best suited for long-term storage of GFS full backups. Avoid using it for short-term storage of recent backups.</p> <p><input type="checkbox"/> Store backups in a single availability zone (even lower price per GB, reduced resilience)</p>

< Previous Apply Finish Cancel

6. Finally, select Finish to complete the process and add the repository.



## Import backups from S3 object storage

To import the backups from the S3 repository that was added in the previous section, complete the following steps.

1. From the S3 backup repository, select Import Backups to launch the Import Backups wizard.



2. After the database records for the import have been created, select Next and then Finish at the summary screen to start the import process.



3. After the import is complete, you can restore VMs into the VMware Cloud cluster.



## System



Name: **Configuration Database Resynchr...** Status: **Success**  
Action type: Configuration Resynchronize Start time: 4/6/2022 3:01:30 PM  
Initiated by: EC2AMAZ-3POTKQV\vdadmin End time: 4/6/2022 3:04:57 PM

## Log


Message	Duration
✓ Starting backup repositories synchronization	
✓ Enumerating repositories	
✓ Found 1 repository	
✓ Processing capacity tier extent of S3 Backup Repository 2	0:03:23
✓ S3 Backup Repository: added 2 unencrypted	0:03:20
✓ Importing backup 2 out of 2	0:03:15
✓ Backup repositories synchronization completed successfully	

Close

## Restore application VMs with Veeam full restore to VMware Cloud


To restore SQL and Oracle virtual machines to the VMware Cloud on AWS workload domain/cluster, complete the following steps.

1. From the Veeam Home page, select the object storage containing the imported backups, select the VMs to restore, and then right click and select Restore Entire VM.



2. On the first page of the Full VM Restore wizard, modify the VMs to backup if desired and select Next.

Full VM Restore




**Virtual Machines**  
Select virtual machines to be restored. You can add individual virtual machines from backup files, or containers from live environment (containers will be automatically expanded into plain VM list).

**Virtual Machines**  
Restore Mode  
Secure Restore  
Summary

Virtual machines to restore:

Type in a VM name for instant lookup

Name	Size	Restore point
 SQLSRV-04	62.7 GB	less than a day ago (1:03 AM ...

Add...

Point...

Remove

< Previous


Next >

Finish

Cancel

- On the Restore Mode page, select Restore to a New Location, or with Different Settings.

Full VM Restore



Restore Mode

Specify whether selected VMs should be restored back to the original location, or to a new location or with different settings.

Virtual Machines

Restore Mode

Host

Resource Pool

Datastore

Folder

Network

Secure Restore

Summary

☐ **Restore to the original location**  
 Quickly initiate the restore of selected VM to its original location, with the original name and settings. This option minimizes the chance of user input error.

☒ **Restore to a new location, or with different settings**  
 Customize the restored VM location, and change its settings. The wizard will automatically populate all controls with the original VM settings as the defaults.

☐ **Staged restore**  
 Run the selected VM directly from backup files in the isolated DataLab to make changes to the guest OS or applications prior to placing the VM into production environment.

[Pick proxy to use](#)

☐ **Quick rollback (restore changed blocks only)**  
 Allows for quick VM recovery in case of guest OS software problem, or user error. Do not use this option when recovering from disaster caused by hardware or storage issue, or power loss.


< Previous

Next >

Finish

Cancel

- On the host page, select the Target ESXi host or cluster to restore the VM to.



5. On the Datastores page, select the target datastore location for both the configuration files and hard disk.



×




By default, we will connect the restored VM to the same virtual networks as the original VM. If you are restoring to a different location, specify how networks map between original and new locations.

## Summary

Source	Target
SQLSRV-04	
Management 181 (DSwitch)	Not connected
Data - A - 3374 (DSwitch)	Not connected
Data - B - 3375 (DSwitch)	Not connected

Cancel



7. Select whether to scan the restored VM for malware, review the summary page, and click Finish to start the restore.

## Restore SQL Server application data

The following process provides instructions on how to recover a SQL Server in VMware Cloud Services in AWS in the event of a disaster that renders the on-premises site inoperable.

The following prerequisites are assumed to be complete in order to continue with the recovery steps:

1. The Windows Server VM has been restored to the VMware Cloud SDDC using Veeam Full Restore.
2. A secondary SnapCenter server has been established and SnapCenter database restore and configuration has been completed using the steps outlined in the section ["SnapCenter backup and restore process summary."](#)



## VM: Post restore configuration for SQL Server VM

After the restore of the VM is complete, you must configure networking and other items in preparation for rediscovering the host VM within SnapCenter.

1. Assign new IP addresses for Management and iSCSI or NFS.
2. Join the host to the Windows domain.
3. Add the hostnames to DNS or to the hosts file on the SnapCenter server.



If the SnapCenter plug-in was deployed using domain credentials different than the current domain, you must change the Log On account for the Plug-in for Windows Service on the SQL Server VM. After changing the Log On account, restart the SnapCenter SMCORE, Plug-in for Windows, and Plug-in for SQL Server services.



To automatically rediscover the restored VMs in SnapCenter, the FQDN must be identical to the VM that was originally added to the SnapCenter on premises.

## Configure FSx storage for SQL Server restore

To accomplish the disaster recovery restore process for a SQL Server VM, you must break the existing SnapMirror relationship from the FSx cluster and grant access to the volume. To do so, complete the following steps.

1. To break the existing SnapMirror relationship for the SQL Server database and log volumes, run the following command from the FSx CLI:

```
FSx-Dest::> snapmirror break -destination-path DestSVM:DestVolName
```

2. Grant access to the LUN by creating an initiator group containing the iSCSI IQN of the SQL Server Windows VM:

```
FSx-Dest::> igroup create -vserver DestSVM -igroup groupName  
-protocol iSCSI -ostype windows -initiator IQN
```

3. Finally, map the LUNs to the initiator group that you just created:

```
FSx-Dest::> lun mapping create -vserver DestSVM -path LUNPath igroup  
groupName
```

4. To find the path name, run the `lun show` command.

## Set up the Windows VM for iSCSI access and discover the file systems

1. From the SQL Server VM, set up your iSCSI network adapter to communicate on the VMware Port Group that has been established with connectivity to the iSCSI target interfaces on your FSx instance.
2. Open the iSCSI Initiator Properties utility and clear out the old connectivity settings on the Discovery, Favorite Targets, and Targets tabs.
3. Locate the IP address(es) for accessing the iSCSI logical interface on the FSx instance/cluster. This can be found in the AWS console under Amazon FSx > ONTAP > Storage Virtual Machines.

### Endpoints

Management DNS name

svm-045c077375d3d9799.fs-0ae40e08acc0dea67.fsx.us-east-1.amazonaws.com

NFS DNS name

svm-045c077375d3d9799.fs-0ae40e08acc0dea67.fsx.us-east-1.amazonaws.com

iSCSI DNS name

iscsi.svm-045c077375d3d9799.fs-0ae40e08acc0dea67.fsx.us-east-1.amazonaws.com

Management IP address

198.19.254.53


NFS IP address


198.19.254.53

iSCSI IP addresses

172.30.15.101, 172.30.14.49

4. From the Discovery tab, click Discover Portal and enter the IP addresses for your FSx iSCSI targets.





The image shows a 'Discover Target Portal' dialog box. It has a title bar with a close button (X). The main area contains two paragraphs of text: 'Enter the IP address or DNS name and port number of the portal you want to add.' and 'To change the default settings of the discovery of the target portal, click the Advanced button.' Below the text are two input fields. The first is labeled 'IP address or DNS name:' and contains the text '172.30.14.49'. The second is labeled 'Port: (Default is 3260.)' and contains the text '3260'. At the bottom of the dialog are three buttons: 'Advanced...', 'OK', and 'Cancel'. The 'OK' button is highlighted with a blue border.

Discover Target Portal

Enter the IP address or DNS name and port number of the portal you want to add.


To change the default settings of the discovery of the target portal, click the Advanced button.

IP address or DNS name: 172.30.14.49


Port: (Default is 3260.) 3260

Advanced... OK Cancel

5. On the Target tab, click Connect, select Enable Multi-Path if appropriate for your configuration and then click OK to connect to the target.




6. Open the Computer Management utility and bring the disks online. Verify that they retain the same drive letters that they previously held.




## Attach the SQL Server databases


1. From the SQL Server VM, open Microsoft SQL Server Management Studio and select Attach to start the process of connecting to the database.



2. Click Add and navigate to the folder containing the SQL Server primary database file, select it, and click OK.



3. If the transaction logs are on a separate drive, choose the folder that contains the transaction log.
4. When finished, click OK to attach the database.




## Confirm SnapCenter communication with SQL Server Plug-in

With the SnapCenter database restored to its previous state, it automatically rediscovers the SQL Server hosts. For this to work correctly, keep in mind the following prerequisites:

- SnapCenter must be placed in Disaster Recover mode. This can be accomplished through the Swagger API or in Global Settings under Disaster Recovery.
- The FQDN of the SQL Server must be identical to the instance that was running in the on-premises datacenter.
- The original SnapMirror relationship must be broken.
- The LUNs containing the database must be mounted to the SQL Server instance and the database attached.

To confirm that SnapCenter is in Disaster Recovery mode, navigate to Settings from within the SnapCenter web client. Go to the Global Settings tab and then click Disaster Recovery. Make sure that the Enable Disaster Recovery checkbox is enabled.





## Restore Oracle application data

The following process provides instructions on how to recover Oracle application data in VMware Cloud Services in AWS in the event of a disaster that renders the on-premises site inoperable.

Complete the following prerequisites to continue with the recovery steps:

1. The Oracle Linux server VM has been restored to the VMware Cloud SDDC using Veeam Full Restore.
2. A secondary SnapCenter server has been established and the SnapCenter database and configuration files have been restored using the steps outlined in this section ["SnapCenter backup and restore process summary."](#)

## Configure FSx for Oracle restore – Break the SnapMirror relationship

To make the secondary storage volumes hosted on the FSxN instance accessible to the Oracle servers, you must first break the existing SnapMirror relationship.

1. After logging into the FSx CLI, run the following command to view the volumes filtered by the correct name.

```
FSx-Dest::> volume show -volume VolumeName*
```

```
FSxId0ae40e08acc0dea67::> volume show -volume oraclesrv_03*
Vserver    Volume                Aggregate    State    Type    Size    Available    Used%
-----
ora_svm_dest
            oraclesrv_03_u01_dest
                        aggr1        online    DP        100GB    93.12GB     6%
ora_svm_dest
            oraclesrv_03_u02_dest
                        aggr1        online    DP        200GB    34.98GB    82%
ora_svm_dest
            oraclesrv_03_u03_dest
                        aggr1        online    DP        150GB    33.37GB    77%
3 entries were displayed.
FSxId0ae40e08acc0dea67::> █
```

2. Run the following command to break the existing SnapMirror relationships.

```
FSx-Dest::> snapmirror break -destination-path DestSVM:DestVolName
```

```
FSxId0ae40e08acc0dea67::> snapmirror break -destination-path ora_svm_dest:oraclesrv_03_u02_dest
Operation succeeded: snapmirror break for destination "ora_svm_dest:oraclesrv_03_u02_dest".

FSxId0ae40e08acc0dea67::> snapmirror break -destination-path ora_svm_dest:oraclesrv_03_u03_dest
Operation succeeded: snapmirror break for destination "ora_svm_dest:oraclesrv_03_u03_dest".
```

3. Update the junction-path in the Amazon FSx web client:

## oraclesrv\_03\_u01\_dest (fsvol-01167370e9b7aefa0)

Attach

Actions ▲

Update volume

Create backup

Delete volume

## Summary

Volume ID

fsvol-01167370e9b7aefa0 


Creation time

2022-03-08T14:52:09-05:00

SVM ID

[svm-02b2ad25c6b2e5bc2](#)

Volume name

oraclesrv\_03\_u01\_dest 

Lifecycle state

 Created

Junction path

- 

UUID

3d7338ce-9f19-11ec-  
b007-4956fb75f45c

Volume type

ONTAP

Tiering policy name

SNAPSHOT\_ONLY

File system ID

[fs-0ae40e08acc0dea67](#) 


Size

100.00 GB 

Tiering policy cooling period (days)

2

Resource ARN

arn:aws:fsx:us-  
east-1:541696183547:volume/fs-  
0ae40e08acc0dea67/fsvol-  
01167370e9b7aefa0 

Storage efficiency enabled

Disabled

4. Add the junction path name and click Update. Specify this junction path when mounting the NFS volume from the Oracle server.

## Update volume



### Junction path

/oraclesrv\_03\_u01\_dest

The location within your file system where your volume will be mounted.

### Volume size

102400



Minimum 20 MiB; Maximum 104857600 MiB

### Storage efficiency

Select whether you would like to enable ONTAP storage efficiencies on your volume: deduplication, compression, and compaction.

- ☐ Enabled (recommended)
- ☒ Disabled

### Capacity pool tiering policy

You can optionally enable automatic tiering of your data to lower-cost capacity pool storage.

Snapshot Only




Cancel

Update

## Mount NFS volumes on Oracle Server


In Cloud Manager, you can obtain the mount command with the correct NFS LIF IP address for mounting the NFS volumes that contain the Oracle database files and logs.

1. In Cloud Manager, access the list of volumes for your FSx cluster.



Volume Name	State	Storage VM	Disk Type
oraclesrv_02_u02_dest	Online	ora_svm_dest	SSD
oraclesrv_02_u03_dest	Online	ora_svm_dest	SSD
oraclesrv_03_u01_dest	Online	ora_svm_dest	SSD

2. From the action menu, select Mount Command to view and copy the mount command to be used on our Oracle Linux server.



### Mount Volume NFS

oraclesrv\_03\_u01\_dest

Go to your linux machine and enter this mount command

Mount Command

```
mount 198.19.254.180:/oraclesrv_03_u01_dest <dest_d...
```

Copy

3. Mount the NFS file system to the Oracle Linux Server. The directories for mounting the NFS share already exist on the Oracle Linux host.
4. From the Oracle Linux server, use the mount command to mount the NFS volumes.

```
FSx-Dest::> mount -t oracle_server_ip:/junction-path
```

Repeat this step for each volume associated with the Oracle databases.



To make the NFS mount persistent upon rebooting, edit the `/etc/fstab` file to include the mount commands.

5. Reboot the Oracle server. The Oracle databases should start up normally and be available for use.

## Failback

Upon successful completion of the failover process outlined in this solution, SnapCenter and Veeam resume their backup functions running in AWS, and FSx for ONTAP is now designated as primary storage with no existing SnapMirror relationships with the original on-premises datacenter. After normal function has resumed on premises, you can use a process identical to the one outlined in this documentation to mirror data back to the on-premises ONTAP storage system.

As is also outlined in this documentation, you can configure SnapCenter to mirror the application data volumes from FSx for ONTAP to an ONTAP storage system residing on premises. Similarly, you can configure Veeam to replicate backup copies to Amazon S3 using a scale-out backup repository so that those backups are accessible to a Veeam backup server residing at the on-premises datacenter.

Failback is outside the scope of this documentation, but failback differs little from the detailed process outlined here.

## Conclusion

The use case presented in this documentation focuses on proven disaster recovery technologies that highlight the integration between NetApp and VMware. NetApp ONTAP storage systems provide proven data-mirroring technologies that allow organizations to design disaster recovery solutions that span on-premises and ONTAP technologies residing with the leading cloud providers.

FSx for ONTAP on AWS is one such solution that allows for seamless integration with SnapCenter and SyncMirror for replicating application data to the cloud. Veeam Backup & Replication is another well-known technology that integrates well with NetApp ONTAP storage systems and can provide failover to vSphere-native storage.

This solution presented a disaster recovery solution using guest connect storage from an ONTAP system hosting SQL Server and Oracle application data. SnapCenter with SnapMirror provides an easy-to-manage solution for protecting application volumes on ONTAP systems and replicating them to FSx or CVO residing in the cloud. SnapCenter is a DR-enabled solution for failing over all application data to VMware Cloud on AWS.

## Where to find additional information

To learn more about the information that is described in this document, review the following documents and/or websites:

- [Links to solution documentation](#)

[NetApp Hybrid Multicloud with VMware Solutions](#)

# TR-4931: Disaster Recovery with VMware Cloud on Amazon Web Services and Guest Connect


Authors: Chris Reno, Josh Powell, and Suresh Thoppay - NetApp Solutions Engineering

## Overview

A proven disaster recovery (DR) environment and plan is critical for organizations to ensure that business-critical applications can be rapidly restored in the event of a major outage. This solution focuses on demonstrating DR use cases with a focus on VMware and NetApp technologies, both on-premises and with VMware Cloud on AWS.

NetApp has a long history of integration with VMware as evidenced by the tens of thousands of customers that have chosen NetApp as their storage partner for their virtualized environment. This integration continues with guest-connected options in the cloud and recent integrations with NFS datastores as well. This solution focuses on the use case commonly referred to as guest-connected storage.

In guest-connected storage, the guest VMDK is deployed on a VMware-provisioned datastore, and application data is housed on iSCSI or NFS and mapped directly to the VM. Oracle and MS SQL applications are used to demonstrate a DR scenario, as shown in the following figure.



## Assumptions, pre-requisites and component overview

Before deploying this solution, review the overview of the components, the required pre-requisites to deploy the solution and assumptions made in documenting this solution.

### DR Solution Requirements, Pre-requisites and Planning

## Performing DR with SnapCenter

In this solution, SnapCenter provides application-consistent snapshots for SQL Server and Oracle application data. This configuration, together with SnapMirror technology, provides high-speed data replication between our on-premises AFF and FSx ONTAP cluster. Additionally, Veeam Backup & Replication provides backup and restore capabilities for our virtual machines.



In this section, we cover the configuration of SnapCenter, SnapMirror, and Veeam for both backup and restore.

The following sections cover configuration and the steps needed to complete a failover at the secondary site:

## Configure SnapMirror relationships and retention schedules

SnapCenter can update SnapMirror relationships within the primary storage system (primary > mirror) and to secondary storage systems (primary > vault) for the purpose of long-term archiving and retention. To do so, you must establish and initialize a data replication relationship between a destination volume and a source volume using SnapMirror.

The source and destination ONTAP systems must be in networks that are peered using Amazon VPC peering, a transit gateway, AWS Direct Connect, or an AWS VPN.

The following steps are required for setting up SnapMirror relationships between an on-premises ONTAP system and FSx ONTAP:



Refer to the [FSx for ONTAP – ONTAP User Guide](#) for more information on creating SnapMirror relationships with FSx.

## Record the source and destination Intercluster logical interfaces

For the source ONTAP system residing on-premises, you can retrieve the inter-cluster LIF information from System Manager or from the CLI.

1. In ONTAP System Manager, navigate to the Network Overview page and retrieve the IP addresses of Type: Intercluster that are configured to communicate with the AWS VPC where FSx is installed.

Name	Status	Storage VM	IPspace	Address	Current Node	Current Port	Portset	Protocols	Type	Thr
veeam_repo	✓	Backup	Default	10.61.181.179	E13A300_1	a0a-181		SMB/CIFS, NFS, S3	Data	0
CM01	✓		Default	10.61.181.180	E13A300_1	a0a-181			Cluster/Node Mgmt	0
HC_N1	✓		Default	10.61.181.183	E13A300_1	a0a-181			Intercluster, Cluster/Node Mgmt	0
HC_N2	✓		Default	10.61.181.184	E13A300_2	a0a-181			Intercluster, Cluster/Node Mgmt	0
lif_ora_vvm_614	✓	ora_vvm	Default	10.61.181.185	E13A300_1	a0a-181		SMB/CIFS, NFS, FL...	Data	0

2. To retrieve the Intercluster IP addresses for FSx, log into the CLI and run the following command:

```
FSx-Dest::> network interface show -role intercluster
```

```
FSxId0ae40e08acc0dea67::> network interface show -role intercluster
Vserver      Logical   Status   Network   Current   Current   Is
-----
Interface    Admin/Oper Address/Mask Node       Port      Home
-----
FSxId0ae40e08acc0dea67
inter_1      up/up    172.30.15.42/25 FSxId0ae40e08acc0dea67-01
                                     e0e      true
inter_2      up/up    172.30.14.28/26 FSxId0ae40e08acc0dea67-02
                                     e0e      true
2 entries were displayed.
```

## Establish cluster peering between ONTAP and FSx

To establish cluster peering between ONTAP clusters, a unique passphrase entered at the initiating ONTAP cluster must be confirmed in the other peer cluster.

1. Set up peering on the destination FSx cluster using the `cluster peer create` command. When prompted, enter a unique passphrase that is used later on the source cluster to finalize the creation process.

```
FSx-Dest::> cluster peer create -address-family ipv4 -peer-addr  
source_intercluster_1, source_intercluster_2  
Enter the passphrase:  
Confirm the passphrase:
```

2. At the source cluster, you can establish the cluster peer relationship using either ONTAP System Manager or the CLI. From ONTAP System Manager, navigate to Protection > Overview and select Peer Cluster.

**ONTAP System Manager**

**DASHBOARD**

**STORAGE** ^

- Overview
- Volumes
- LUNs
- Consistency Groups
- NVMe Namespaces
- Shares
- Buckets
- Qtrees
- Quotas
- Storage VMs
- Tiers

**NETWORK** ^

- Overview
- Ethernet Ports
- FC Ports

**EVENTS & JOBS** v

**PROTECTION** ^

- Overview 1
- Relationships

**HOSTS** v

## Overview

### < Intercluster Settings

#### Network Interfaces

IP ADDRESS

- ✓ 10.61.181.184
- ✓ 172.21.146.217
- ✓ 10.61.181.183
- ✓ 172.21.146.216

#### Cluster Peers

PEERED CLUSTER NAME

- ✓ FsxId0ae40e08acc0dea67
- ✓ OTS02

**Peer Cluster** 3

Generate Passphrase 2

Manage Cluster Peers

#### Mediator ?

Not configured.

**Configure**

#### Storage VM Peers

PEERED STORAGE VMS

- ✓ 3

3. In the Peer Cluster dialog box, fill out the required information:
  - a. Enter the passphrase that was used to establish the peer cluster relationship on the destination FSx cluster.
  - b. Select **Yes** to establish an encrypted relationship.
  - c. Enter the intercluster LIF IP address(es) of the destination FSx cluster.

d. Click Initiate Cluster Peering to finalize the process.

### Peer Cluster

Local

Remote

STORAGE VM PERMISSIONS

All storage VMs (incl... X

Storage VMs created in the future also will be given permissions.

1

PASSPHRASE ?

.....

It cannot be determined from the passphrase whether this relationship was encrypted. Is the relationship encrypted?

2

Yes

No

To generate passphrase, [Launch Remote Cluster](#)

3

Intercluster Network Interfaces IP Addresses

172.30.15.42

172.30.14.28

Cancel

+ Add

4

Initiate Cluster Peering

Cancel

4. Verify the status of the cluster peer relationship from the FSx cluster with the following command:

```
FSx-Dest::> cluster peer show
```

```
FSxId0ae40e08acc0dea67::> cluster peer show
Peer Cluster Name      Cluster Serial Number Availability  Authentication
-----
E13A300                1-80-000011      Available   ok
```


## Establish SVM peering relationship

The next step is to set up an SVM relationship between the destination and source storage virtual machines that contain the volumes that will be in SnapMirror relationships.


1. From the source FSx cluster, use the following command from the CLI to create the SVM peer relationship:

```
FSx-Dest::> vserver peer create -vserver DestSVM -peer-vserver Backup -peer-cluster OnPremSourceSVM -applications snapmirror
```

2. From the source ONTAP cluster, accept the peering relationship with either ONTAP System Manager or the CLI.
3. From ONTAP System Manager, go to Protection > Overview and select Peer Storage VMs under Storage VM Peers.



4. In the Peer Storage VM's dialog box, fill out the required fields:
  - The source storage VM
  - The destination cluster
  - The destination storage VM



5. Click Peer Storage VMs to complete the SVM peering process.

## Create a snapshot retention policy

SnapCenter manages retention schedules for backups that exist as snapshot copies on the primary storage system. This is established when creating a policy in SnapCenter. SnapCenter does not manage retention policies for backups that are retained on secondary storage systems. These policies are managed separately through a SnapMirror policy created on the secondary FSx cluster and associated with the destination volumes that are in a SnapMirror relationship with the source volume.

When creating a SnapCenter policy, you have the option to specify a secondary policy label that is added to the SnapMirror label of each snapshot generated when a SnapCenter backup is taken.



On the secondary storage, these labels are matched to policy rules associated with the destination volume for the purpose of enforcing retention of snapshots.

The following example shows a SnapMirror label that is present on all snapshots generated as part of a policy used for daily backups of our SQL Server database and log volumes.

### Select secondary replication options ⓘ

☐ Update SnapMirror after creating a local Snapshot copy.

☒ Update SnapVault after creating a local Snapshot copy.

Secondary policy label

Custom Label ⓘ

sql-daily

Error retry count

3 ⓘ

For more information on creating SnapCenter policies for a SQL Server database, see the [SnapCenter documentation](#).

You must first create a SnapMirror policy with rules that dictate the number of snapshot copies to retain.

1. Create the SnapMirror Policy on the FSx cluster.

```
FSx-Dest::> snapmirror policy create -vserver DestSVM -policy  
PolicyName -type mirror-vault -restart always
```

2. Add rules to the policy with SnapMirror labels that match the secondary policy labels specified in the SnapCenter policies.

```
FSx-Dest::> snapmirror policy add-rule -vserver DestSVM -policy  
PolicyName -snapmirror-label SnapMirrorLabelName -keep  
#ofSnapshotsToRetain
```

The following script provides an example of a rule that could be added to a policy:

```
FSx-Dest::> snapmirror policy add-rule -vserver sql_svm_dest -policy Async_SnapCenter_SQL -snapmirror-label sql-ondemand -keep 15
```



Create additional rules for each SnapMirror label and the number of snapshots to be retained (retention period).

### Create destination volumes

To create a destination volume on FSx that will be the recipient of snapshot copies from our source volumes, run the following command on FSx ONTAP:

```
FSx-Dest::> volume create -vserver DestSVM -volume DestVolName  
-aggregate DestAggrName -size VolSize -type DP
```

### Create the SnapMirror relationships between source and destination volumes

To create a SnapMirror relationship between a source and destination volume, run the following command on FSx ONTAP:

```
FSx-Dest::> snapmirror create -source-path  
OnPremSourceSVM:OnPremSourceVol -destination-path DestSVM:DestVol -type  
XDP -policy PolicyName
```

### Initialize the SnapMirror relationships

Initialize the SnapMirror relationship. This process initiates a new snapshot generated from the source volume and copies it to the destination volume.

To create a volume, run the following command on FSx ONTAP:

```
FSx-Dest::> volume create -vserver DestSVM -volume DestVolName  
-aggregate DestAggrName -size VolSize -type DP
```

### Deploy and configure Windows SnapCenter server on-premises.



## Deploy Windows SnapCenter Server on premises

This solution uses NetApp SnapCenter to take application-consistent backups of SQL Server and Oracle databases. In conjunction with Veeam Backup & Replication for backing up virtual machine VMDKs, this provides a comprehensive disaster recovery solution for on-premises and cloud-based datacenters.

SnapCenter software is available from the NetApp support site and can be installed on Microsoft Windows systems that reside either in a domain or workgroup. A detailed planning guide and installation instructions can be found at the [NetApp Documentation Center](#).

The SnapCenter software can be obtained at [this link](#).


After it is installed, you can access the SnapCenter console from a web browser using *https://Virtual\_Cluster\_IP\_or\_FQDN:8146*.

After you log into the console, you must configure SnapCenter for backup SQL Server and Oracle databases.

Add storage controllers to SnapCenter

To add storage controllers to SnapCenter, complete the following steps:

- 1. From the left menu, select Storage Systems and then click New to begin the process of adding your storage controllers to SnapCenter.




- 2. In the Add Storage System dialog box, add the management IP address for the local on-premises ONTAP cluster and the username and password. Then click Submit to begin discovery of the storage system.

## Add Storage System

### Add Storage System

Storage System	<input type="text" value="10.61.181.180"/>
Username	<input type="text" value="admin"/>
Password	<input type="password" value="••••••••"/>

### Event Management System (EMS) & AutoSupport Settings

- ☒ Send AutoSupport notification to storage system
- ☒ Log SnapCenter Server events to syslog
-  **More Options** : Platform, Protocol, Preferred IP etc..

- Repeat this process to add the FSx ONTAP system to SnapCenter. In this case, select More Options at the bottom of the Add Storage System window and click the check box for Secondary to designate the FSx system as the secondary storage system updated with SnapMirror copies or our primary backup snapshots.

## More Options



Platform

☒ Secondary 

Protocol

Port

Timeout



☐ Preferred IP



Save

Cancel

For more information related to adding storage systems to SnapCenter, see the documentation at [this link](#).

## Add hosts to SnapCenter

The next step is adding host application servers to SnapCenter. The process is similar for both SQL Server and Oracle.

1. From the left menu, select Hosts and then click Add to begin the process of adding storage controllers to SnapCenter.
2. In the Add Hosts window, add the Host Type, Hostname, and the host system Credentials. Select the plug-in type. For SQL Server, select the Microsoft Windows and Microsoft SQL Server plug-in.

**NetApp SnapCenter®**

**Managed Hosts**

Search by Name

<input type="checkbox"/>	Name
<input type="checkbox"/>	<a href="#">oraclesrv_01.sddc.netapp.com</a>
<input type="checkbox"/>	<a href="#">oraclesrv_02.sddc.netapp.com</a>
<input type="checkbox"/>	<a href="#">oraclesrv_03.sddc.netapp.com</a>
<input type="checkbox"/>	<a href="#">oraclesrv_04.sddc.netapp.com</a>
<input type="checkbox"/>	<a href="#">oraclesrv_05.sddc.netapp.com</a>
<input type="checkbox"/>	<a href="#">oraclesrv_06.sddc.netapp.com</a>
<input type="checkbox"/>	<a href="#">oraclesrv_07.sddc.netapp.com</a>
<input type="checkbox"/>	<a href="#">oraclesrv_08.sddc.netapp.com</a>
<input type="checkbox"/>	<a href="#">oraclesrv_09.sddc.netapp.com</a>
<input type="checkbox"/>	<a href="#">oraclesrv_10.sddc.netapp.com</a>

**Add Host**

Host Type: Windows

Host Name: sqlsrv-01.sddc.netapp.com

Credentials: sddc-jpowell

**Select Plug-ins to Install** SnapCenter Plug-ins Package 4.6 for Windows

- ☒ Microsoft Windows
- ☒ Microsoft SQL Server
- ☐ Microsoft Exchange Server
- ☐ SAP HANA

[More Options](#) : Port, gMSA, Install Path, Custom Plug-Ins...

**Submit** **Cancel**

3. For Oracle, fill out the required fields in the Add Host dialog box and select the check box for the Oracle Database plug-in. Then click Submit to begin the discovery process and to add the host to SnapCenter.

### Add Host

Host Type Linux ▾

Host Name oraclesrv\_11.sddc.netapp.com

Credentials root ▾



### Select Plug-ins to Install SnapCenter Plug-ins Package 4.6 for Linux

☒ Oracle Database

☐ SAP HANA

 [More Options](#) : Port, Install Path, Custom Plug-Ins...


Submit

Cancel

## Create SnapCenter policies

Policies establish the specific rules to be followed for a backup job. They include, but are not limited to, the backup schedule, replication type, and how SnapCenter handles backing up and truncating transaction logs.

You can access policies in the Settings section of the SnapCenter web client.



For complete information on creating policies for SQL Server backups, see the [SnapCenter documentation](#).

For complete information on creating policies for Oracle backups, see the [SnapCenter documentation](#).

### Notes:

- As you progress through the policy creation wizard, take special note of the Replication section. In this section you stipulate the types of secondary SnapMirror copies that you want taken during the backups process.
- The “Update SnapMirror after creating a local Snapshot copy” setting refers to updating a SnapMirror relationship when that relationship exists between two storage virtual machines residing on the same cluster.
- The “Update SnapVault after creating a local SnapShot copy” setting is used to update a SnapMirror relationship that exists between two separate cluster and between an on-premises ONTAP system and Cloud Volumes ONTAP or FSxN.

The following image shows the preceding options and how they look in the backup policy wizard.

## New SQL Server Backup Policy

1 Name

2 Backup Type

3 Retention

4 Replication

5 Script

### Select secondary replication options i

☐ Update SnapMirror after creating a local Snapshot copy.

☐ Update SnapVault after creating a local Snapshot copy.

Secondary policy label 

Choose i

Error retry count 

3 i

### Create SnapCenter Resource Groups

Resource Groups allow you to select the database resources you want to include in your backups and the policies followed for those resources.

1. Go to the Resources section in the left-hand menu.
2. At the top of the window, select the resource type to work with (In this case Microsoft SQL Server) and then click New Resource Group.

Name	Resource Count	Tags	Policies	Last Backup	Overall Status
SQLSRV-01	1		SQL-Daily SQL-Hourly SQL-OnDemand SQL-Weekly	05/11/2022 ...	Completed
SQLSRV-02	1		SQL-Daily SQL-Hourly SQL-OnDemand SQL-Weekly	03/28/2022 ...	Failed
SQLSRV-03	1		SQL-Daily SQL-Hourly	05/11/2022 ...	Completed

The SnapCenter documentation covers step-by-step details for creating Resource Groups for both SQL Server and Oracle databases.

For backing up SQL resources, follow [this link](#).

For Backing up Oracle resources, follow [this link](#).



## **Deploy and configure Veeam Backup Server**

Veeam Backup & Replication software is used in the solution to back up our application virtual machines and archive a copy of the backups to an Amazon S3 bucket using a Veeam scale-out backup repository (SOBR). Veeam is deployed on a Windows server in this solution. For specific guidance on deploying Veeam, see the [Veeam help Center Technical documentation](#).

## Configure Veeam scale-out backup repository

After you deploy and license the software, you can create a scale-out backup repository (SOBR) as target storage for backup jobs. You should also include an S3 bucket as a backup of VM data offsite for disaster recovery.


See the following prerequisites before getting started.

1. Create an SMB file share on your on-premises ONTAP system as the target storage for backups.
2. Create an Amazon S3 bucket to include in the SOBR. This is a repository for the offsite backups.

## Add ONTAP Storage to Veeam

First, add the ONTAP storage cluster and associated SMB/NFS filesystem as storage infrastructure in Veeam.

1. Open the Veeam console and log in. Navigate to Storage Infrastructure and then select Add Storage.



2. In the Add Storage wizard, select NetApp as the storage vendor and then select Data ONTAP.
3. Enter the management IP address and check the NAS Filer box. Click Next.

## New NetApp Data ONTAP Storage



### Name

Register NetApp Data ONTAP storage by specifying DNS name or IP address.

<b>Name</b>	Management server DNS name or IP address: <input type="text" value="10.61.181.180"/>
Credentials	Description: <input type="text" value="Created by SDDC\jpowell at 5/17/2022 10:34 AM."/>
NAS Filer	Role: <input type="checkbox"/> Block or file storage for VMware vSphere <input type="checkbox"/> Block storage for Microsoft Windows servers <input checked="" type="checkbox"/> NAS filer
Apply	
Summary	

4. Add your credentials to access the ONTAP cluster.

## New NetApp Data ONTAP Storage



### Credentials

Specify account with storage administrator privileges.

<b>Name</b>	Credentials: <input type="text" value="HCIEUC\Admin (HCIEUC\Admin, last edited: 98 days ago)"/> <input type="button" value="Add..."/>
Credentials	<a href="#">Manage accounts</a>
NAS Filer	Protocol: <input type="text" value="HTTPS"/>
Apply	Port: <input type="text" value="443"/>
Summary	

5. On the NAS Filer page choose the desired protocols to scan and select Next.

New NetApp Data ONTAP Storage ✕


**NAS Filer**

Specify how this storage can be accessed by file backup jobs.


Name	Protocol to use:
Credentials	<input checked="" type="checkbox"/> SMB
<b>NAS Filer</b>	<input type="checkbox"/> NFS
Apply	<input checked="" type="checkbox"/> Create required export rules automatically
Summary	Volumes to scan:
	<input style="width: 100%;" type="text" value="All volumes"/> <span style="float: right; border: 1px solid #ccc; padding: 2px 5px;">Choose...</span>
	Backup proxies to use:
	<input style="width: 100%;" type="text" value="Automatic selection"/> <span style="float: right; border: 1px solid #ccc; padding: 2px 5px;">Choose...</span>

< Previous
Apply
Finish
Cancel

- Complete the Apply and Summary pages of the wizard and click Finish to begin the storage discovery process. After the scan completes, the ONTAP cluster is added along with the NAS filers as available resources.



- Create a backup repository using the newly discovered NAS shares. From Backup Infrastructure, select Backup Repositories and click the Add Repository menu item.



8. Follow all steps in the New Backup Repository Wizard to create the repository. For detailed information on creating Veeam Backup Repositories, see the [Veeam documentation](#).

## New Backup Repository

**Share**

Type in UNC path to share (mapped drives are not supported), specify share access credentials and how backup jobs should write data to this share.

Name

Shared folder:

Browse...

Share

Use \\server\folder format

Repository

☒ This share requires access credentials:

sddc\administrator (sddc\administrator, last edited: 85 days ago)



Add...

Mount Server

[Manage accounts](#)

Review

Gateway server:

☒ Automatic selection☐ The following server:

Apply

Use this option to improve performance and reliability of backup to a NAS located in a remote site.

Summary

&lt; Previous

Next &gt;


Finish

Cancel

## Add the Amazon S3 bucket as a backup repository

The next step is to add the Amazon S3 storage as a backup repository.

1. Navigate to Backup Infrastructure > Backup Repositories. Click Add Repository.



2. In the Add Backup Repository wizard, select Object Storage and then Amazon S3. This starts the New Object Storage Repository wizard.



## Add Backup Repository

Select the type of backup repository you want to add.



### Direct attached storage

Microsoft Windows or Linux server with internal or direct attached storage. This configuration enables data movers to run directly on the server, allowing for fastest performance.



### Network attached storage

Network share on a file server or a NAS device. When backing up to a remote share, we recommend that you select a gateway server located in the same site with the share.



### Deduplicating storage appliance

Dell EMC Data Domain, ExaGrid, HPE StoreOnce or Quantum DXi. If you are unable to meet the requirements of advanced integration via native appliance API, use the network attached storage option instead.



### Object storage

On-prem object storage system or a cloud object storage provider. Object storage can only be used as a Capacity Tier of scale-out backup repositories, backing up directly to object storage is not currently supported.

3. Provide a name for your object storage repository and click Next.
4. In the next section, provide your credentials. You need an AWS Access Key and Secret Key.

### New Object Storage Repository



#### Account

Specify AWS account to use for connecting to Amazon S3 storage bucket.


Name	Credentials:
Account	<input type="text" value="AKIAH4H43ZT557HXQT2W (last edited: 107 days ago)"/> <a href="#">Add...</a>
	<a href="#">Manage cloud accounts</a>
Bucket	AWS region:
Summary	<input type="text" value="Global"/>
<input type="checkbox"/> Use the following gateway server:	
<input type="text" value="veeam.sddc.netapp.com (Backup server)"/>	
<small>Select a gateway server to proxy access to Amazon S3. If no gateway server is specified, all scale-out backup repository extents must have direct Internet access.</small>	
<div><span>&lt; Previous</span> <span>Next &gt;</span> <span>Finish</span> <span>Cancel</span></div>	

5. After the Amazon configuration loads, choose your datacenter, bucket, and folder and click Apply. Finally, click Finish to close out the wizard.

## Create scale-out backup repository

Now that we have added our storage repositories to Veeam, we can create the SOBR to automatically tier backup copies to our offsite Amazon S3 object storage for disaster recovery.

1. From Backup Infrastructure, select Scale-out Repositories and then click the Add Scale-out Repository menu item.



2. In the New Scale-out Backup Repository provide a name for the SOBR and click Next.
3. For the Performance Tier, choose the backup repository that contains the SMB share residing on your local ONTAP cluster.

## New Scale-out Backup Repository



### Performance Tier

Select backup repositories to use as the landing zone and for the short-term retention.

Name	Extents:				
Performance Tier	<table border="1"> <thead> <tr> <th>Name</th> <th></th> </tr> </thead> <tbody> <tr> <td>VBRRepo2</td> <td></td> </tr> </tbody> </table>	Name		VBRRepo2	
Name					
VBRRepo2					
Placement Policy	<div>Add...</div> <div>Remove</div>				

- For the Placement Policy, choose either Data Locality or Performance based your requirements. Select next.
- For Capacity Tier we extend the SOBR with Amazon S3 object storage. For the purposes of disaster recovery, select Copy Backups to Object Storage as Soon as They are Created to ensure timely delivery of our secondary backups.

## New Scale-out Backup Repository



### Capacity Tier

Specify object storage to copy backups to for redundancy and DR purposes. Older backups can be moved to object storage completely to reduce long-term retention costs while preserving the ability to restore directly from offloaded backups.

Name	
Performance Tier	
Placement Policy	
Capacity Tier	<div> <input checked="" type="checkbox"/> Extend scale-out backup repository capacity with object storage:           <div> <div>Amazon S3 Repo</div> <div>Add...</div> </div> </div>
Archive Tier	<div>Define time windows when uploading to capacity tier is allowed</div> <div>Window...</div>
Summary	<div> <input checked="" type="checkbox"/> Copy backups to object storage as soon as they are created            Create additional copy of your backups for added redundancy by having all backups copied to the capacity tier as soon as they are created on the performance tier.         </div> <div> <input checked="" type="checkbox"/> Move backups to object storage as they age out of the operational restore window            Reduce your long-term retention costs by moving older backups to object storage completely while preserving the ability to restore directly from offloaded backups.         </div> <div>           Move backup files older than <input type="text" value="14"/> days (your operational restore window)           <div>Override...</div> </div> <div> <input type="checkbox"/> Encrypt data uploaded to object storage            Password: <div></div> <div>Add...</div> <div>Manage passwords</div> </div>

< Previous

Next >

Finish

Cancel

- Finally, select Apply and Finish to finalize creation of the SOBR.

## Create the scale-out backup repository jobs

The final step to configuring Veeam is to create backup jobs using the newly created SOBR as the backup destination. Creating backup jobs is a normal part of any storage administrator's repertoire and we do not cover the detailed steps here. For more complete information on creating backup jobs in Veeam, see the [Veeam Help Center Technical Documentation](#).

## Cloud backup tools and configuration

To conduct a failover of application VMs and database volumes to VMware Cloud Volume services running in AWS, you must install and configure a running instance of both SnapCenter Server and Veeam Backup and Replication Server. After the failover is complete, you must also configure these tools to resume normal backup operations until a failback to the on-premises datacenter is planned and executed.

### Deploy secondary Windows SnapCenter Server

SnapCenter Server is deployed in the VMware Cloud SDDC or installed on an EC2 instance residing in a VPC with network connectivity to the VMware Cloud environment.

SnapCenter software is available from the NetApp support site and can be installed on Microsoft Windows systems that reside either in a domain or workgroup. A detailed planning guide and installation instructions can be found at the [NetApp documentation center](#).

You can find the SnapCenter software at [this link](#).

### Configure secondary Windows SnapCenter Server

To perform a restore of application data mirrored to FSx ONTAP, you must first perform a full restore of the on-premises SnapCenter database. After this process is complete, communication with the VMs is reestablished and application backups can now resume using FSx ONTAP as the primary storage.

To achieve this, you must complete the following items on the SnapCenter Server:

1. Configure the computer name to be identical to the original on-premises SnapCenter Server.
2. Configure networking to communicate with VMware Cloud and the FSx ONTAP instance.
3. Complete the procedure to restore the SnapCenter database.
4. Confirm that SnapCenter is in Disaster Recovery mode to make sure that FSx is now the primary storage for backups.
5. Confirm that communication is reestablished with the restored virtual machines.

For more information on completing these steps, see to section "[SnapCenter database Restore Process](#)".

### Deploy secondary Veeam Backup & Replication server

You can install the Veeam Backup & Replication server on a Windows server in the VMware Cloud on AWS or on an EC2 instance. For detailed implementation guidance, see the [Veeam Help Center Technical Documentation](#).

## Configure secondary Veeam Backup & Replication server

To perform a restore of virtual machines that have been backed up to Amazon S3 storage, you must install the Veeam Server on a Windows server and configure it to communicate with VMware Cloud, FSx ONTAP, and the S3 bucket that contains the original backup repository. It must also have a new backup repository configured on FSx ONTAP to conduct new backups of the VMs after they are restored.

To perform this process, the following items must be completed:

1. Configure networking to communicate with VMware Cloud, FSx ONTAP, and the S3 bucket containing the original backup repository.
2. Configure an SMB share on FSx ONTAP to be a new backup repository.
3. Mount the original S3 bucket that was used as part of the scale-out backup repository on premises.
4. After restoring the VM, establish new backup jobs to protect SQL and Oracle VMs.

For more information on restoring VMs using Veeam, see the section ["Restore Application VMs with Veeam Full Restore"](#).

## SnapCenter database backup for disaster recovery

SnapCenter allows for the backup and recovery of its underlying MySQL database and configuration data for the purpose of recovering the SnapCenter server in the case of a disaster. For our solution, we recovered the SnapCenter database and configuration on an AWS EC2 instance residing in our VPC. For more information on this step, see [this link](#).

### SnapCenter backup prerequisites

The following prerequisites are required for SnapCenter backup:

- A volume and SMB share created on the on-premises ONTAP system to locate the backed-up database and configuration files.
- A SnapMirror relationship between the on-premises ONTAP system and FSx or CVO in the AWS account. This relationship is used for transporting the snapshot containing the backed-up SnapCenter database and configuration files.
- Windows Server installed in the cloud account, either on an EC2 instance or on a VM in the VMware Cloud SDDC.
- SnapCenter installed on the Windows EC2 instance or VM in VMware Cloud.

## SnapCenter backup and restore process summary

- Create a volume on the on-premises ONTAP system for hosting the backup db and config files.
- Set up a SnapMirror relationship between on-premises and FSx/CVO.
- Mount the SMB share.
- Retrieve the Swagger authorization token for performing API tasks.
- Start the db restore process.
- Use the xcopy utility to copy the db and config file local directory to the SMB share.
- On FSx, create a clone of the ONTAP volume (copied via SnapMirror from on-premises).
- Mount the SMB share from FSx to EC2/VMware Cloud.
- Copy the restore directory from the SMB share to a local directory.
- Run the SQL Server restore process from Swagger.

## Back up the SnapCenter database and configuration

SnapCenter provides a web client interface for executing REST API commands. For information on accessing the REST APIs through Swagger, see the SnapCenter documentation at [this link](#).

## Log into Swagger and obtain authorization token

After you have navigated to the Swagger page, you must retrieve an authorization token to initiate the database restore process.

1. Access the SnapCenter Swagger API web page at *https://<SnapCenter Server IP>:8146/swagger/*.



### SnapCenter API

[ Base URL: /api ]

<https://snapcenter.sddc.netapp.com:8146/Content/swagger/SnapCenter.yaml>

Manage your SnapCenter Server using the SnapCenter API.

To access the swagger documentation of "SnapCenter Plug-in for VMware vSphere" API's, please use [https://{SCV\\_hostname}:{SCV\\_host\\_port}/api/swagger-ui.html](https://{SCV_hostname}:{SCV_host_port}/api/swagger-ui.html)

2. Expand the Auth section and click Try it Out.

#### Auth

**POST** **/4.6/auth/login** Service login

The login endpoint exposes the method required to log in to the SnapCenter service. The login method returns a token that is used to authenticate subsequent requests.

Parameters Try it out

3. In the UserOperationContext area, fill in the SnapCenter credentials and role and click Execute.



Name	Description
TokenNeverExpires	Token never expires
boolean (query)	<div>false</div>
<b>UserOperationContext</b> * required	User credentials
object (body)	<div>Edit Value   Model</div> <pre>{   "UserOperationContext": {     "User": {       "Name": "localhost\\scadmin",       "Passphrase": "NetApp321",       "Rolename": "SnapCenterAdmin"     }   } }</pre> <div>Cancel</div> <div>Parameter content type</div> <div>application/json</div> <div>Execute</div>

- In the Response body below, you can see the token. Copy the token text for authentication when executing the backup process.

200 Response body


```
{
  "PluginName": null,
  "HostId": 0,
  "RoleId": null,
  "JobIds": null
},
{
  "User": {
    "Token": "KlYxOg==tsV6EOdttdAmAYpe8q5SG6wcoGaSjwME6jrNy5CsY63HQ5LkoZLIESRNAhpGJJ00UQynENDgtVGDZnvx+I/ZJZIn5M1NZrj6CLfGTApplGmcagT08bqb5bMfx07EcdRAidzAXUDb3GyLOKtW0GdwKzSeUwKj3uVupnk1E3lslK6PRBv9RS8j0qHQvo4v4RL0hhThhwPhV9/23nFeJVP/p1Ev4vrV/zeZVTUHFHUM069XRe5cuW9nwYj4b0I5Y5FN3XDkjqQ=",
    "Name": "SCAdmin",
    "TokenHashed": null,
    "Type": "",
    "TokenTime": "2022-03-22T14:21:57.3665661-07:00",
    "Id": "1",
    "FullName": "SCAdmin",
    "Host": null,
    "Author": null,
    "UserName": "",
    "Domain": "",
    "Passphrase": ""
  }
}
```

Download

## Perform a SnapCenter database backup

Next go to the Disaster Recovery area on the Swagger page to begin the SnapCenter backup process.

1. Expand the Disaster Recovery area by clicking it.

**Disaster Recovery** 

GET

/4.6/disasterrecovery/server/backup

Fetch all the existing SnapCenter Server DR Backups.

POST

/4.6/disasterrecovery/server/backup

Starts the SnapCenter Server DR backup.

DELETE

/4.6/disasterrecovery/server/backup

Deletes the existing Snapcenter DR backup.

POST

/4.6/disasterrecovery/server/restore

Starts SnapCenter Server Restore.

POST

/4.6/disasterrecovery/storage

Enable or disable the storage disaster recovery.

2. Expand the /4.6/disasterrecovery/server/backup section and click Try it Out.

POST

/4.6/disasterrecovery/server/backup

Starts the SnapCenter Server DR backup.

Starts and creates a new SnapCenter Server DR backup.

Parameters 

Try it out

3. In the SmDRBackupRequest section, add the correct local target path and select Execute to start the backup of the SnapCenter database and configuration.



The backup process does not allow backing up directly to an NFS or CIFS file share.

Name	Description
<b>Token</b> * required string (header)	User authorization token <div>TUHFHUM069XRe5cuW9nwyj4b0l5Y5FN3XDkjQ==</div>
<b>SmDRBackupRequest</b> * required object (body)	Parameters to take Backup <div>Edit Value   Model <pre>{   "TargetPath": "C:\\\\SnapCenter_Backups\\\\" }</pre></div> <div>Cancel</div> <div>Parameter content type application/json</div>

Execute

## Monitor the backup job from SnapCenter

Log into SnapCenter to review log files when starting the database restore process. Under the Monitor section, you can view the details of the SnapCenter server disaster recovery backup.

### Job Details

#### SnapCenter Server disaster recovery backup

- ✓ ▾ SnapCenter Server disaster recovery backup
  - ✓ ▶ Precheck validation
  - ✓ ▶ Disaster recovery backup of 'oraclesrv\_04.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of SnapCenter Server 'SnapCenter.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'oraclesrv\_02.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'oraclesrv\_03.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'oraclesrv\_05.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'oraclesrv\_07.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'sqlsrv-02.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'sqlsrv-03.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'oraclesrv\_10.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'sqlsrv-04.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'sqlsrv-01.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'sqlsrv-05.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'oraclesrv\_09.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'sqlsrv-06.sddc.netapp.com'
  - ✓ ▶ Disaster recovery backup of 'sqlsrv-07.sddc.netapp.com'

**i** Task Name: SnapCenter Server disaster recovery backup Start Time: 03/23/2022 10:27:11 AM End Time: 03/23/2022 10:27:47 AM

[View Logs](#)[Cancel Job](#)[Close](#)

### Use XCOPY utility to copy the database backup file to the SMB share

Next you must move the backup from the local drive on the SnapCenter server to the CIFS share that is used to SnapMirror copy the data to the secondary location located on the FSx instance in AWS. Use xcopy with specific options that retain the permissions of the files.

Open a command prompt as Administrator. From the command prompt, enter the following commands:

```
xcopy <Source_Path> \\<Destination_Server_IP>\<Folder_Path> /O /X  
/E /H /K  
xcopy c:\SC_Backups\SnapCenter_DR \\10.61.181.185\snapcenter_dr /O  
/X /E /H /K
```

## Failover

### Disaster occurs at primary site

For a disaster that occurs at the primary on-premises datacenter, our scenario includes failover to a secondary site residing on Amazon Web Services infrastructure using VMware Cloud on AWS. We assume that the virtual machines and our on-premises ONTAP cluster are no longer accessible. In addition, both the SnapCenter and Veeam virtual machines are no longer accessible and must be rebuilt at our secondary site.

This section address failover of our infrastructure to the cloud, and we cover the following topics:

- SnapCenter database restore. After a new SnapCenter server has been established, restore the MySQL database and configuration files and toggle the database into disaster recovery mode in order to allow the secondary FSx storage to become the primary storage device.
- Restore the application virtual machines using Veeam Backup & Replication. Connect the S3 storage that contains the VM backups, import the backups, and restore them to VMware Cloud on AWS.
- Restore the SQL Server application data using SnapCenter.
- Restore the Oracle application data using SnapCenter.

## SnapCenter database restore process


SnapCenter supports disaster recovery scenarios by allowing the backup and restore of its MySQL database and configuration files. This allows an administrator to maintain regular backups of the SnapCenter database at the on-premises datacenter and later restore that database to a secondary SnapCenter database.

To access the SnapCenter backup files on the remote SnapCenter server, complete the following steps:

1. Break the SnapMirror relationship from the FSx cluster, which makes the volume read/write.
2. Create a CIFS server (if necessary) and create a CIFS share pointing to the junction path of the cloned volume.
3. Use xcopy to copy the backup files to a local directory on the secondary SnapCenter system.
4. Install SnapCenter v4.6.
5. Ensure that SnapCenter server has the same FQDN as the original server. This is required for the db restore to be successful.

To start the restore process, complete the following steps:

1. Navigate to the Swagger API web page for the secondary SnapCenter server and follow the previous instructions to obtain an authorization token.
2. Navigate to the Disaster Recovery section of the Swagger page, select `/4.6/disasterrecovery/server/restore`, and click Try it Out.




**POST** `/4.6/disasterrecovery/server/restore` Starts SnapCenter Server Restore.

Starts SnapCenter Server Restore.

Parameters Try it out

3. Paste in your authorization token and, in the SmDRResterRequest section, paste in the name of the backup and the local directory on the secondary SnapCenter server.



Name	Description
<b>Token</b> * required string (header)	User authorization token
<b>SmDRResterRequest</b> * required object (body)	Parameters to take for Restore

[Edit Value](#) [Model](#)

```
{
  "BackupName": "SnapCenter.sddc.netapp.com_03-23-2022_12.38.00.6713",
  "BackupPath": "C:\\SnapCenter\\"
}
```

4. Select the Execute button to start the restore process.

5. From SnapCenter, navigate to the Monitor section to view the progress of the restore job.

The screenshot shows the NetApp SnapCenter web interface. The top navigation bar includes 'Jobs', 'Schedules', 'Events', and 'Logs'. The left sidebar contains links to 'Dashboard', 'Resources', 'Monitor', 'Reports', 'Hosts', 'Storage Systems', 'Settings', and 'Alerts'. The 'Monitor' section is active, displaying a table of jobs. The table has columns for 'ID', 'Status', and 'Name'. The jobs listed are:

ID	Status	Name
20482	✓	SnapCenter Server Disaster Recovery
20481	✓	SnapCenter Server disaster recovery backup
20480	✗	SnapCenter Server disaster recovery backup
20475	✓	Backup of Resource Group 'SQLSRV-09' with policy 'SQL-Hourly'
20474	✓	Backup of Resource Group 'SQLSRV-05' with policy 'SQL-Hourly'
20473	⌚	Backup of Resource Group 'OracleSrv_06' with policy 'Oracle-Hourly'
20472	✗	SnapCenter Server disaster recovery backup

### Job Details

#### SnapCenter Server Disaster Recovery

- ✓ ▼ SnapCenter Server Disaster Recovery
- ✓ ▼ Prepare for restore job
- ✓ ▼ Precheck validation
- ✓ ▼ Saving original server state
- ✓ ▼ Schedule restore
- ✓ ▼ Repository restore
- ✓ ▼ Config restore
- ✓ ▼ Reset MySQL password

6. To enable SQL Server restores from secondary storage, you must toggle the SnapCenter database into Disaster Recovery mode. This is performed as a separate operation and initiated on the Swagger API web page.
- Navigate to the Disaster Recovery section and click `/4.6/disasterrecovery/storage`.
  - Paste in the user authorization token.
  - In the `SmSetDisasterRecoverySettingsRequest` section, change `EnableDisasterRecover` to `true`.
  - Click Execute to enable disaster recovery mode for SQL Server.

Name	Description
<b>Token</b> * required string (header)	User authorization token <div>KlYxOg==rMXzS7EPIGRzTXjfton6Q+JoNGpueQt</div>
<b>SmSetDisasterRecoverySettingsRequest</b> * required object (body)	Parameters to enable or disable the DR mode <div> Edit Value   Model <pre>{   "EnableDisasterRecovery": true }</pre> </div>



See comments regarding additional procedures.

## Restore application VMs with Veeam full restore




## Create a backup repository and import backups from S3

From the secondary Veeam server, import the backups from S3 storage and restore the SQL Server and Oracle VMs to your VMware Cloud cluster.

To import the backups from the S3 object that was part of the on-premises scale-out backup repository, complete the following steps:

1. Go to Backup Repositories and click Add Repository in the top menu to launch the Add Backup Repository wizard. On the first page of the wizard, select Object Storage as the backup repository type.



2. Select Amazon S3 as the Object Storage type.



## Object Storage



Select the type of object storage you want to use as a backup repository.



### S3 Compatible

Adds an on-premises object storage system or a cloud object storage provider.



### Amazon S3

Adds Amazon cloud object storage. Amazon S3, Amazon S3 Glacier (including Deep Archive) and Amazon Snowball Edge are supported.



### Google Cloud Storage

Adds Google Cloud storage. Both Standard and Nearline storage classes are supported.



### IBM Cloud Object Storage

Adds IBM Cloud object storage. S3 compatible versions of both on-premises and IBM Cloud storage offerings are supported.



### Microsoft Azure Storage

Adds Microsoft Azure cloud object storage. Microsoft Azure Blob Storage, Microsoft Azure Archive Storage and Microsoft Azure Data Box are supported.

3. From the list of Amazon Cloud Storage Services, select Amazon S3.



## Amazon Cloud Storage Services



Select the type of Amazon storage you want to use as a backup repository.



### Amazon S3

Adds Amazon S3 storage. Both Standard and Infrequent Access (IA) storage classes are supported.



### Amazon S3 Glacier

Adds Amazon S3 Glacier storage. Both Amazon S3 Glacier and Glacier Deep Archive are supported.









### AWS Snowball Edge





Adds AWS Snowball Edge appliance to enable seeding of backups into Amazon S3 object storage.

4. Select your pre-entered credentials from the drop-down list or add a new credential for accessing the cloud storage resource. Click Next to continue.

New Object Storage Repository


 **Account**  
Specify AWS account to use for connecting to Amazon S3 storage bucket.

Name	Credentials:
Account	 AKIAH4H43ZT53YJXPY2Y (last edited: 33 days ago)  
Bucket	<a href="#">Manage cloud accounts</a>
Summary	AWS region: Global 
	<input type="checkbox"/> Use the following gateway server: EC2AMAZ-3POTKQV (Backup server)  Select a gateway server to proxy access to Amazon S3. If no gateway server is specified, all scale-out backup repository extents must have direct Internet access.

5. On the Bucket page, enter the data center, bucket, folder, and any desired options. Click Apply.

New Object Storage Repository ✕

 **Bucket**  
Specify Amazon S3 bucket to use.

Name	Data center: US East (N. Virginia) <span>▼</span>
Account	Bucket: ehcveeamrepo <span>Browse...</span>
Bucket	Folder: RTP <span>Browse...</span>
Summary	<p><input type="checkbox"/> Limit object storage consumption to: 10 <span>▼</span> TB <span>▼</span> This is a soft limit to help control your object storage spend. If the specified limit is exceeded, already running backup offload tasks will be allowed to complete, but no new tasks will be started.</p> <p><input type="checkbox"/> Make recent backups immutable for: 30 <span>▼</span> days Protects backups from modification or deletion by ransomware, hackers or malicious insiders using native object storage capabilities.</p> <p><input type="checkbox"/> Use infrequent access storage class (may result in higher costs) With lower price per GB but higher retrieval and early deletion fees, this storage class is best suited for long-term storage of GFS full backups. Avoid using it for short-term storage of recent backups.</p> <p><input type="checkbox"/> Store backups in a single availability zone (even lower price per GB, reduced resilience)</p>


< Previous Apply Finish Cancel

6. Finally, select Finish to complete the process and add the repository.


## Import backups from S3 object storage

To import the backups from the S3 repository that was added in the previous section, complete the following steps.

1. From the S3 backup repository, select Import Backups to launch the Import Backups wizard.



2. After the database records for the import have been created, select Next and then Finish at the summary screen to start the import process.



3. After the import is complete, you can restore VMs into the VMware Cloud cluster.

## System



Name: **Configuration Database Resynchr...** Status: **Success**  
Action type: Configuration Resynchronize Start time: 4/6/2022 3:01:30 PM  
Initiated by: EC2AMAZ-3POTKQV\vdadmin End time: 4/6/2022 3:04:57 PM

## Log


Message	Duration
✓ Starting backup repositories synchronization	
✓ Enumerating repositories	
✓ Found 1 repository	
✓ Processing capacity tier extent of S3 Backup Repository 2	0:03:23
✓ S3 Backup Repository: added 2 unencrypted	0:03:20
✓ Importing backup 2 out of 2	0:03:15
✓ Backup repositories synchronization completed successfully	

Close

## Restore application VMs with Veeam full restore to VMware Cloud


To restore SQL and Oracle virtual machines to the VMware Cloud on AWS workload domain/cluster, complete the following steps.

1. From the Veeam Home page, select the object storage containing the imported backups, select the VMs to restore, and then right click and select Restore Entire VM.



2. On the first page of the Full VM Restore wizard, modify the VMs to backup if desired and select Next.






3. On the Restore Mode page, select Restore to a New Location, or with Different Settings.



Full VM Restore



Restore Mode

Specify whether selected VMs should be restored back to the original location, or to a new location or with different settings.

Virtual Machines

Restore Mode

Host

Resource Pool

Datastore

Folder

Network

Secure Restore

Summary

☐ Restore to the original location

Quickly initiate the restore of selected VM to its original location, with the original name and settings. This option minimizes the chance of user input error.

☒ Restore to a new location, or with different settings

Customize the restored VM location, and change its settings. The wizard will automatically populate all controls with the original VM settings as the defaults.

☐ Staged restore

Run the selected VM directly from backup files in the isolated DataLab to make changes to the guest OS or applications prior to placing the VM into production environment.

[Pick proxy to use](#)

☐ Quick rollback (restore changed blocks only)

Allows for quick VM recovery in case of guest OS software problem, or user error. Do not use this option when recovering from disaster caused by hardware or storage issue, or power loss.


< Previous

Next >

Finish

Cancel

4. On the host page, select the Target ESXi host or cluster to restore the VM to.



5. On the Datastores page, select the target datastore location for both the configuration files and hard disk.




×



- Virtual Machines
- Restore Mode
- Host
- Resource Pool
- Datastore
- Folder
- Network**
- Secure Restore
- Summary

[illegible]

Cancel



7. Select whether to scan the restored VM for malware, review the summary page, and click Finish to start the restore.

## Restore SQL Server application data

The following process provides instructions on how to recover a SQL Server in VMware Cloud Services in AWS in the event of a disaster that renders the on-premises site inoperable.

The following prerequisites are assumed to be complete in order to continue with the recovery steps:

1. The Windows Server VM has been restored to the VMware Cloud SDDC using Veeam Full Restore.
2. A secondary SnapCenter server has been established and SnapCenter database restore and configuration has been completed using the steps outlined in the section ["SnapCenter backup and restore process summary."](#)

## VM: Post restore configuration for SQL Server VM

After the restore of the VM is complete, you must configure networking and other items in preparation for rediscovering the host VM within SnapCenter.

1. Assign new IP addresses for Management and iSCSI or NFS.
2. Join the host to the Windows domain.
3. Add the hostnames to DNS or to the hosts file on the SnapCenter server.



If the SnapCenter plug-in was deployed using domain credentials different than the current domain, you must change the Log On account for the Plug-in for Windows Service on the SQL Server VM. After changing the Log On account, restart the SnapCenter SMCORE, Plug-in for Windows, and Plug-in for SQL Server services.



To automatically rediscover the restored VMs in SnapCenter, the FQDN must be identical to the VM that was originally added to the SnapCenter on premises.

## Configure FSx storage for SQL Server restore

To accomplish the disaster recovery restore process for a SQL Server VM, you must break the existing SnapMirror relationship from the FSx cluster and grant access to the volume. To do so, complete the following steps.

1. To break the existing SnapMirror relationship for the SQL Server database and log volumes, run the following command from the FSx CLI:

```
FSx-Dest::> snapmirror break -destination-path DestSVM:DestVolName
```

2. Grant access to the LUN by creating an initiator group containing the iSCSI IQN of the SQL Server Windows VM:

```
FSx-Dest::> igroup create -vserver DestSVM -igroup igroupName  
-protocol iSCSI -ostype windows -initiator IQN
```

3. Finally, map the LUNs to the initiator group that you just created:

```
FSx-Dest::> lun mapping create -vserver DestSVM -path LUNPath igroup  
igroupName
```

4. To find the path name, run the `lun show` command.

## Set up the Windows VM for iSCSI access and discover the file systems

1. From the SQL Server VM, set up your iSCSI network adapter to communicate on the VMware Port Group that has been established with connectivity to the iSCSI target interfaces on your FSx instance.
2. Open the iSCSI Initiator Properties utility and clear out the old connectivity settings on the Discovery, Favorite Targets, and Targets tabs.
3. Locate the IP address(es) for accessing the iSCSI logical interface on the FSx instance/cluster. This can be found in the AWS console under Amazon FSx > ONTAP > Storage Virtual Machines.

### Endpoints

Management DNS name

svm-045c077375d3d9799.fs-0ae40e08acc0dea67.fsx.us-east-1.amazonaws.com

NFS DNS name

svm-045c077375d3d9799.fs-0ae40e08acc0dea67.fsx.us-east-1.amazonaws.com

iSCSI DNS name

iscsi.svm-045c077375d3d9799.fs-0ae40e08acc0dea67.fsx.us-east-1.amazonaws.com

Management IP address

198.19.254.53


NFS IP address


198.19.254.53

iSCSI IP addresses

172.30.15.101, 172.30.14.49

4. From the Discovery tab, click Discover Portal and enter the IP addresses for your FSx iSCSI targets.





The image shows a 'Discover Target Portal' dialog box. It has a title bar with a close button (X). The main area contains two paragraphs of text: 'Enter the IP address or DNS name and port number of the portal you want to add.' and 'To change the default settings of the discovery of the target portal, click the Advanced button.' Below the text are two input fields. The first is labeled 'IP address or DNS name:' and contains the text '172.30.14.49'. The second is labeled 'Port: (Default is 3260.)' and contains the text '3260'. At the bottom of the dialog are three buttons: 'Advanced...', 'OK', and 'Cancel'. The 'OK' button is highlighted with a blue border.

Discover Target Portal

Enter the IP address or DNS name and port number of the portal you want to add.

To change the default settings of the discovery of the target portal, click the Advanced button.


IP address or DNS name: 172.30.14.49

Port: (Default is 3260.) 3260


Advanced... OK Cancel

5. On the Target tab, click Connect, select Enable Multi-Path if appropriate for your configuration and then click OK to connect to the target.






6. Open the Computer Management utility and bring the disks online. Verify that they retain the same drive letters that they previously held.




## Attach the SQL Server databases


1. From the SQL Server VM, open Microsoft SQL Server Management Studio and select Attach to start the process of connecting to the database.



2. Click Add and navigate to the folder containing the SQL Server primary database file, select it, and click OK.



3. If the transaction logs are on a separate drive, choose the folder that contains the transaction log.
4. When finished, click OK to attach the database.




## Confirm SnapCenter communication with SQL Server Plug-in

With the SnapCenter database restored to its previous state, it automatically rediscovers the SQL Server hosts. For this to work correctly, keep in mind the following prerequisites:

- SnapCenter must be placed in Disaster Recover mode. This can be accomplished through the Swagger API or in Global Settings under Disaster Recovery.
- The FQDN of the SQL Server must be identical to the instance that was running in the on-premises datacenter.
- The original SnapMirror relationship must be broken.
- The LUNs containing the database must be mounted to the SQL Server instance and the database attached.

To confirm that SnapCenter is in Disaster Recovery mode, navigate to Settings from within the SnapCenter web client. Go to the Global Settings tab and then click Disaster Recovery. Make sure that the Enable Disaster Recovery checkbox is enabled.



## Restore Oracle application data

The following process provides instructions on how to recover Oracle application data in VMware Cloud Services in AWS in the event of a disaster that renders the on-premises site inoperable.

Complete the following prerequisites to continue with the recovery steps:

1. The Oracle Linux server VM has been restored to the VMware Cloud SDDC using Veeam Full Restore.
2. A secondary SnapCenter server has been established and the SnapCenter database and configuration files have been restored using the steps outlined in this section ["SnapCenter backup and restore process summary."](#)

## Configure FSx for Oracle restore – Break the SnapMirror relationship

To make the secondary storage volumes hosted on the FSxN instance accessible to the Oracle servers, you must first break the existing SnapMirror relationship.

1. After logging into the FSx CLI, run the following command to view the volumes filtered by the correct name.

```
FSx-Dest::> volume show -volume VolumeName*
```

```
FSxId0ae40e08acc0dea67::> volume show -volume oraclesrv_03*
Vserver    Volume                Aggregate    State    Type    Size    Available    Used%
-----
ora_svm_dest
            oraclesrv_03_u01_dest
            aggr1        online    DP        100GB    93.12GB     6%
ora_svm_dest
            oraclesrv_03_u02_dest
            aggr1        online    DP        200GB    34.98GB    82%
ora_svm_dest
            oraclesrv_03_u03_dest
            aggr1        online    DP        150GB    33.37GB    77%
3 entries were displayed.
FSxId0ae40e08acc0dea67::> █
```

2. Run the following command to break the existing SnapMirror relationships.

```
FSx-Dest::> snapmirror break -destination-path DestSVM:DestVolName
```

```
FSxId0ae40e08acc0dea67::> snapmirror break -destination-path ora_svm_dest:oraclesrv_03_u02_dest
Operation succeeded: snapmirror break for destination "ora_svm_dest:oraclesrv_03_u02_dest".

FSxId0ae40e08acc0dea67::> snapmirror break -destination-path ora_svm_dest:oraclesrv_03_u03_dest
Operation succeeded: snapmirror break for destination "ora_svm_dest:oraclesrv_03_u03_dest".
```

3. Update the junction-path in the Amazon FSx web client:

## oraclesrv\_03\_u01\_dest (fsvol-01167370e9b7aefa0)

Attach

Actions ▲

Update volume

Create backup


Delete volume

## Summary

## Volume ID

fsvol-01167370e9b7aefa0 

## Volume name

oraclesrv\_03\_u01\_dest 


## UUID

3d7338ce-9f19-11ec-  
b007-4956fb75f45c

## File system ID

fs-0ae40e08acc0dea67 

## Resource ARN

arn:aws:fsx:us-  
east-1:541696183547:volume/fs-  
0ae40e08acc0dea67/fsvol-  
01167370e9b7aefa0 

## Creation time

2022-03-08T14:52:09-05:00

## Lifecycle state

 Created

## Volume type

ONTAP

## Size

100.00 GB 

## SVM ID

svm-02b2ad25c6b2e5bc2

## Junction path

- 

## Tiering policy name

SNAPSHOT\_ONLY

## Tiering policy cooling period (days)

2

## Storage efficiency enabled

Disabled

4. Add the junction path name and click Update. Specify this junction path when mounting the NFS volume from the Oracle server.



## Update volume



### Junction path

/oraclesrv\_03\_u01\_dest

The location within your file system where your volume will be mounted.

### Volume size

102400



Minimum 20 MiB; Maximum 104857600 MiB

### Storage efficiency

Select whether you would like to enable ONTAP storage efficiencies on your volume: deduplication, compression, and compaction.

- ☐ Enabled (recommended)
- ☒ Disabled

### Capacity pool tiering policy

You can optionally enable automatic tiering of your data to lower-cost capacity pool storage.

Snapshot Only




Cancel

Update

## Mount NFS volumes on Oracle Server

In Cloud Manager, you can obtain the mount command with the correct NFS LIF IP address for mounting the NFS volumes that contain the Oracle database files and logs.


1. In Cloud Manager, access the list of volumes for your FSx cluster.



The screenshot shows the HCAApps Cloud Manager interface. At the top, there is a navigation bar with 'Overview' and 'Volumes' tabs. The 'Volumes' tab is selected. Below the navigation bar, the text '50 Volumes' is displayed. A table with four columns is shown: 'Volume Name', 'State', 'Storage VM', and 'Disk Type'. The table contains three rows of data.

Volume Name	State	Storage VM	Disk Type
oraclesrv_02_u02_dest	Online	ora_svm_dest	SSD
oraclesrv_02_u03_dest	Online	ora_svm_dest	SSD
oraclesrv_03_u01_dest	Online	ora_svm_dest	SSD

2. From the action menu, select Mount Command to view and copy the mount command to be used on our Oracle Linux server.



### Mount Volume NFS

oraclesrv\_03\_u01\_dest

Go to your linux machine and enter this mount command

Mount Command

```
mount 198.19.254.180:/oraclesrv_03_u01_dest <dest_d...
```

Copy

3. Mount the NFS file system to the Oracle Linux Server. The directories for mounting the NFS share already exist on the Oracle Linux host.
4. From the Oracle Linux server, use the mount command to mount the NFS volumes.

```
FSx-Dest::> mount -t oracle_server_ip:/junction-path
```

Repeat this step for each volume associated with the Oracle databases.



To make the NFS mount persistent upon rebooting, edit the `/etc/fstab` file to include the mount commands.

5. Reboot the Oracle server. The Oracle databases should start up normally and be available for use.

## Failback

Upon successful completion of the failover process outlined in this solution, SnapCenter and Veeam resume their backup functions running in AWS, and FSx for ONTAP is now designated as primary storage with no existing SnapMirror relationships with the original on-premises datacenter. After normal function has resumed on premises, you can use a process identical to the one outlined in this documentation to mirror data back to the on-premises ONTAP storage system.

As is also outlined in this documentation, you can configure SnapCenter to mirror the application data volumes from FSx for ONTAP to an ONTAP storage system residing on premises. Similarly, you can configure Veeam to replicate backup copies to Amazon S3 using a scale-out backup repository so that those backups are accessible to a Veeam backup server residing at the on-premises datacenter.

Failback is outside the scope of this documentation, but failback differs little from the detailed process outlined here.

## Conclusion

The use case presented in this documentation focuses on proven disaster recovery technologies that highlight the integration between NetApp and VMware. NetApp ONTAP storage systems provide proven data-mirroring technologies that allow organizations to design disaster recovery solutions that span on-premises and ONTAP technologies residing with the leading cloud providers.

FSx for ONTAP on AWS is one such solution that allows for seamless integration with SnapCenter and SyncMirror for replicating application data to the cloud. Veeam Backup & Replication is another well-known technology that integrates well with NetApp ONTAP storage systems and can provide failover to vSphere-native storage.

This solution presented a disaster recovery solution using guest connect storage from an ONTAP system hosting SQL Server and Oracle application data. SnapCenter with SnapMirror provides an easy-to-manage solution for protecting application volumes on ONTAP systems and replicating them to FSx or CVO residing in the cloud. SnapCenter is a DR-enabled solution for failing over all application data to VMware Cloud on AWS.

## Where to find additional information

To learn more about the information that is described in this document, review the following documents and/or websites:

- Links to solution documentation

[NetApp Hybrid Multicloud with VMware Solutions](#)

# **AWS guest-connected storage disaster recovery**

## **Disaster recovery**

## Copyright information

Copyright © 2022 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

## Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.