```
                    MINGW64:/c/Users/Danielaa/Desktop/MIDPS                    ─

Danielaa@Daniela MINGW64 ~/Desktop/MIDPS (master)
$ ls
Lab1/  Lab2/  Lab3/  Lab4/  Lab5/  newFileToRevert.txt  ReadFile.txt  README.md

Danielaa@Daniela MINGW64 ~/Desktop/MIDPS (master)
$ git add *

Danielaa@Daniela MINGW64 ~/Desktop/MIDPS (master)
$ git add *
The following paths are ignored by one of your .gitignore files:
stupid_file.txt
Use -f if you really want to add them.

Danielaa@Daniela MINGW64 ~/Desktop/MIDPS (master)
$ git commit -m "First Version"
[master e82dbee] First Version
 2 files changed, 3 insertions(+), 1 deletion(-)
 create mode 100644 newFileToRevert.txt

Danielaa@Daniela MINGW64 ~/Desktop/MIDPS (master)
$ git push origin master
Counting objects: 4, done.
Delta compression using up to 4 threads.
Compressing objects: 100% (3/3), done.
Writing objects: 100% (4/4), 529 bytes | 0 bytes/s, done.
Total 4 (delta 1), reused 0 (delta 0)
remote: Resolving deltas: 100% (1/1), completed with 1 local objects.
To https://github.com/daniela-cazac/MIDPS
   000428d..e82dbee  master -> master

Danielaa@Daniela MINGW64 ~/Desktop/MIDPS (master)
$ ls
Lab1/  Lab3/  Lab5/                   ReadFile.txt  stupid_file.txt
Lab2/  Lab4/  newFileToRevert.txt  README.md

Danielaa@Daniela MINGW64 ~/Desktop/MIDPS (master)
$ git rm newFileToRevert.txt
rm 'newFileToRevert.txt'

Danielaa@Daniela MINGW64 ~/Desktop/MIDPS (master)
$ ls
Lab1/  Lab2/  Lab3/  Lab4/  Lab5/  ReadFile.txt  README.md  stupid_file.txt

Danielaa@Daniela MINGW64 ~/Desktop/MIDPS (master)
$ git add *
The following paths are ignored by one of your .gitignore files:
stupid_file.txt
Use -f if you really want to add them.

Danielaa@Daniela MINGW64 ~/Desktop/MIDPS (master)
$ git commit -m "Second Version"
[master aa14f87] Second Version
 1 file changed, 0 insertions(+), 0 deletions(-)
 delete mode 100644 newFileToRevert.txt
```