

Query Rewriting Algorithm for Data Integration Quality

Daniel A. S. Carvalho
Univ. Jean Moulin Lyon 3
Lyon, France
danielboni@gmail.com

Plácido A. Souza Neto
Instituto Federal do Rio
Grande do Norte - IFRN
Natal, Brazil
placido.neto@ifrn.edu.br

Chirine G. Guegan
Univ. Jean Moulin Lyon 3
Lyon, France
chirine.ghedira-
guegan@univ-lyon3.fr

Nadia Benani
CNRS-INS
Lyon, France
nadia.bennani@insa-
lyon.fr

Genoveva Vargas-Solar
CNRS-LIG-LAFMIA
Grenoble, France
genoveva.vargas@imag.fr

ABSTRACT

In this paper we describe *Rhone*, a query rewriting algorithm for data integration using quality measures. We present a running scenario to describe the *Rhone*'s implementation in order to validate the algorithm.

Keywords

Query rewriting, Data integration, Services composition

1. INTRODUCTION

Data integration is a well-know problem in the database domain (see [4]). Recently, with the emergency of cloud environments, this problem has also been threatened in the service-oriented domains [2, 3, 1]. Generally, these kind of applications deals with query rewriting problems. [2] proposed a query rewriting approach which processes queries on data provider services. [3] introduced a service composition framework to answer preference queries. In that approach, two algorithms based on [2] are presented to rank the best rewritings based on previously computed scores.

In this context, the aim of our work is to present the early stages of our ongoing work on developing the *Rhone* service-based query rewriting algorithm.

2. SERVICE-BASED QUERY REWRITING ALGORITHM

The algorithm described in this section is called *Rhone*. The *Rhone* service-based query rewriting algorithm addresses the problem of given a set of *abstract services*, a set of *concrete services*, a *user query* and a set of *user quality preferences*, derive a set of service compositions that answer the query and fulfill the quality preferences.

The basic input for the *Rhone* algorithm is: (1) a query; (2) a list of concrete services.

Definition 1 (Query): A query Q is defined as a set of *abstract services*, a set of *constraints*, and a set of *user preferences* in accordance with the grammar:

$$Q(\bar{I}, \bar{O}) := A_1(\bar{I}, \bar{O}), A_2(\bar{I}, \bar{O}), \dots, A_n(\bar{I}, \bar{O}), C_1, C_2, \dots, C_m[P_1, P_2, \dots, P_k]$$

The left side of the definition is called the *head* of the query; and the right side is called the *body*. \bar{I} and \bar{O} are a set of *input* and *output* parameters, respectively. Input parameters in both sides of the definition are called *head variables*. In contrast, input parameters only in the query body are called *local variables*.

The result if this step is a list of *candidate concrete services* which may be used in the rewriting process.

Definition 2 (Concrete service): A concrete service (S):

$$S(\bar{I}, \bar{O}) := A_1(\bar{I}, \bar{O}), A_2(\bar{I}, \bar{O}), \dots, A_n(\bar{I}, \bar{O})[P_1, P_2, \dots, P_k]$$

A concrete service (S) is defined as a set of abstract services (A), and by its quality constraints P . These quality constraints associated to the service represent the service level agreement exported by the concrete service.

The algorithm includes four steps: (i) select candidate concrete services; (ii) create mappings from concrete services to the query (called *concrete service description (CSD)*); (iii) combine the list of CSDs; and finally (iv) produce rewritings from the query Q .

Select candidate concrete services: This step consists of looking for concrete services that can be matched with the query (line 2). In this sense, there are three matching problems: (i) *abstract service matching*, (ii) *measure matching* and (iii) *concrete service matching*.

Considering *abstract service matching*, an abstract service A can be matched with a abstract service B only if (a) they have the same name. In the *measure matching*, all single measures in the query must exist in the concrete service, and all of them can not violate the measures in the query. For the *concrete service matching*, a concrete service can be matched with the query if all its abstract services can be matched with the abstract service in the query (satisfying the *abstract service matching* problem) and all the single measures in the

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. To copy otherwise, to republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee.

Copyright 20XX ACM X-XXXXX-XX-X/XX/XX ...\$15.00.

Algorithm 1 - RHONE

```

1: function rhone( $Q, S$ )
2:  $\mathcal{L}_S \leftarrow \text{SelectCandidateServices}(Q, S)$ 
3:  $\mathcal{L}_{CSD} \leftarrow \text{CreateCSDs}(Q, \mathcal{L}_S)$ 
4:  $I \leftarrow \text{CombineCSDs}(Q, \mathcal{L}_{CSD})$ 
5:  $R \leftarrow \emptyset$ 
6:  $p \leftarrow I.\text{next}()$ 
7: while  $p \neq \emptyset$  and  $\mathcal{T}_{\text{init}}[\text{Agg}(Q)]$  do
8:   if  $\text{isRewriting}(Q, p)$  then
9:      $R \leftarrow R \cup \text{Rewriting}(p)$ 
10:     $\mathcal{T}_{\text{inc}}[\text{Agg}(Q)]$ 
11:   end if
12:    $p \leftarrow I.\text{Next}()$ 
13: end while
14: return  $R$ 
15: end function

```

query can be matched with the concrete service measures (satisfying the *measures matching* problem).

The result if this step is a list of *candidate concrete services* which may be used in the rewriting process.

Creating concrete service descriptions: In this step of the algorithm tries to create *concrete services description* (CSD) to be used in the rewriting process (line 3). A CSD maps abstract services and variables of a concrete service to abstract services and variables of the query. A CSD is created according to the following variable mapping rules: (i) *head variables*, (ii) *local-head variables* and (iii) *local-local variables*.

Head variables in concrete services can be mapped to *head* or *local variables* in the query if they are from the same type. *Local-head variables* in concrete services can be mapped to *head variables* in the query if they are from the same type. *Local-local variables* in concrete services can be mapped to *local-local variables* in the query if: (a) they are from the same type; and (b) the concrete service cover all abstract service in the query that depends on this variable. Depends here means that this local variable is used as input in another abstract service. As result a list of CSDs is produced.

Combining CSDs. In this step, given all CSDs produced (line 4), all combinations of them is generated resulting in a list of lists of CSDs.

Producing rewritings. In the final step, given the list of lists of CSDs, the algorithm identifies which lists of CSDs are a valid rewriting of the user query (lines 5-13). A combination of CSDs is a valid rewriting if: (i) the number of *abstract services* in the query is equal to the result of adding the number of *abstract services* of each CSD; (ii) there is no abstract service in duplicity; (iii) there is mapping to all head variables in the query; and (iv) if the query contains a *composed measure*, this measure must be updated for each rewriting produced, and it can not be violated (represented as the called function $\text{isRewriting}(Q, p)$ - line 8). As result of this step we have a list of rewritings of the query (line 14).

3. IMPLEMENTATION AND RESULTS

Let us suppose the following medical scenario to illustrate our service-based query rewriting algorithm. Users can retrieve information about patients, diseases, dna information and others. To perform these function consider the *abstract*

services in table 3. *Abstract services* are a set of basic service capabilities.

Abstract Service	Description
$\text{DiseasePatients}(d?, p!)$	Given a disease d , a list of patients p infected by it is retrieved.
$\text{PatientDNA}(p?, \text{dna}!)$	Given a patient p , his DNA information dna is retrieved.
$\text{PatientInformation}(p?, \text{info}!)$	Given a patient p , his personal information info is retrieved.

Table 1: List of abstract services

In our scenario, a *query* expresses an abstract composition that describes the requirements of a user. *Queries* and *concrete services* are defined in terms of *abstract services*. They can be associated to a single *abstract service* or to a composition of them.

Let us consider the following query: *a user wants to retrieve patient's personal and DNA information of patients who were infected by a disease 'K' using services that have availability higher than 98%, price per call less than 0.2 dollars, and total cost less then 1 dollar.*

A query Q tagged with user preferences is defined in accordance with the grammar:

$$Q(\bar{I}, \bar{O}) := A_1(\bar{I}, \bar{O}), A_2(\bar{I}, \bar{O}), \dots, A_n(\bar{I}, \bar{O})[P_1, P_2, \dots, P_k]$$

where the left side is the *head* of the query; and the right side is the *body*. \bar{I} and \bar{O} are a set of *input* and *output* parameters, respectively. Input parameters present in both sides of the definition are called *head variables*. In contrast, input parameters only in the body are called *local variables*. A_1, A_2, \dots, A_n are *abstract services*. P_1, P_2, \dots, P_k are user preferences (over the services). Preferences are in the form $x \otimes \text{constant}$ such that $\otimes \in \{\geq, \leq, =, \neq, <, >\}$. The query which express the example following our grammar is below. The decorations ? and ! are used to specify input and output parameters, respectively.

$$Q(d?, \text{dna}!) := \text{DiseasePatients}(d?, p!), \text{PatientDNA}(p?, \text{dna}!), \\ [\text{availability} > 99\%, \text{price per call} < 0.2\$, \text{total cost} < 1\$]$$

We highlight that in the query there are two types of preferences (let's refer to them as *measures*): *single measures* (availability and price per call) and *composed measures* (total cost). The *single measures* are the simplest type. It is a static measure which is has a name associated with an operation and a value. The *composed measure* is dynamically computed measure. It is defined as aggregations of *single measures*.

Concrete services are defined following the same grammar as the *query*. The only difference is that concrete services do not have *composed measures*. We use 7 concrete services to run our approach.

In this example all the queries have 6 *abstract services* and 2 *single measures*. The number of local variables (dependencies) and CSDs is being modified to see how the algorithm works under these conditions.

By now, the analysis identified that the factor that influenciates the Rhone performance is the number of CSDs versus the number of abstract services in the query since they increase the number of possible combinations of CSDs.

4. CONCLUSIONS

The algorithm is implemented in Java. We are currently performing experiments in order to evaluate the performance of the Rhone.

5. REFERENCES

- [1] C. Ba, U. Costa, M. Halfeld Ferrari, R. Ferre, M. A. Musicante, V. Peralta, and S. Robert. Preference-Driven Refinement of Service Compositions. In *CLOSER (4th International Conference on Cloud Computing and Services Science)*, Proceedings of CLOSER 2014, page 8 pages, Barcelona, Spain, Apr. 2014. POSTER presentation.
- [2] M. Barhamgi, D. Benslimane, and B. Medjahed. A query rewriting approach for web service composition. *Services Computing, IEEE Transactions on*, 3(3):206–222, July 2010.
- [3] K. Benouaret, D. Benslimane, A. Hadjali, and M. Barhamgi. FuDoCS: A Web Service Composition System Based on Fuzzy Dominance for Preference Query Answering, Sept. 2011. VLDB - 37th International Conference on Very Large Data Bases - Demo Paper.
- [4] A. Y. Halevy. Answering queries using views: A survey. *The VLDB Journal*, 10(4):270–294, Dec. 2001.