Algorithms

Robert Sedgewick | Kevin Wayne

http://algs4.cs.princeton.edu

http://algs4.cs.princeton.edu

2.3 Quick-Select

Quick-select demo

Partition array so that:

- Entry a[j] is in place.
- No larger entry to the left of j.
- No smaller entry to the right of j.

Repeat in one subarray, depending on j; finished when j equals k.

select element of rank k = 5

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
50	21	28	65	39	59	56	22	95	12	90	53	32	77	33

k = 5

Quick-select demo

Partition array so that:

- Entry a[j] is in place.
- No larger entry to the left of j.
- No smaller entry to the right of j.

Repeat in one subarray, depending on j; finished when j equals k.

partition on leftmost entry

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
50	21	28	65	39	59	56	22	95	12	90	53	32	77	33

k = 5

Quick-select demo

Partition array so that:

- Entry a[j] is in place.
- No larger entry to the left of j.
- No smaller entry to the right of j.

Repeat in one subarray, depending on j; finished when j equals k.

partitioned array

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
22	21	28	33	39	32	12	50	95	56	90	53	59	77	65

k = 5

Quick-select demo

Partition array so that:

- Entry a[j] is in place.
- No larger entry to the left of j.
- No smaller entry to the right of j.

Repeat in one subarray, depending on j; finished when j equals k.

can safely ignore right subarray

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
22	21	28	33	39	32	12	50	95	56	90	53	59	77	65

k = 5

Quick-select demo

Partition array so that:

- Entry a[j] is in place.
- No larger entry to the left of j.
- No smaller entry to the right of j.

Repeat in one subarray, depending on j; finished when j equals k.

partition on leftmost entry

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
22	21	28	33	39	32	12	50	95	56	90	53	59	77	65

k = 5

Quick-select demo

Partition array so that:

- Entry a[j] is in place.
- No larger entry to the left of j.
- No smaller entry to the right of j.

Repeat in one subarray, depending on j; finished when j equals k.

partitioned array



0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
12	21	22	33	39	32	28	50	95	56	90	53	59	77	65

k = 5

Quick-select demo

Partition array so that:

- Entry a[j] is in place.
- No larger entry to the left of j.
- No smaller entry to the right of j.

Repeat in one subarray, depending on j; finished when j equals k.

can safely ignore left subarray

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
12	21	22	33	39	32	28	50	95	56	90	53	59	77	65

k = 5

Quick-select demo

Partition array so that:

- Entry a[j] is in place.
- No larger entry to the left of j.
- No smaller entry to the right of j.

Repeat in one subarray, depending on j; finished when j equals k.

partition on leftmost entry

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
12	21	22	33	39	32	28	50	95	56	90	53	59	77	65

k = 5

Quick-select demo

Partition array so that:

- Entry a[j] is in place.
- No larger entry to the left of j.
- No smaller entry to the right of j.

Repeat in one subarray, depending on j; finished when j equals k.

partitioned array



0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
12	21	22	32	28	33	39	50	95	56	90	53	59	77	65

k = 5

Quick-select demo

Partition array so that:

- Entry a[j] is in place.
- No larger entry to the left of j.
- No smaller entry to the right of j.

Repeat in one subarray, depending on j; finished when j equals k.

stop: partitioning item is at index k

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
12	21	22	32	28	33	39	50	95	56	90	53	59	77	65

k = 5