

Design Document for Better Graphics For A Robotics Grasping GUI

Shady Robots

Group 12

Justin Bibler

Matthew Huang

Daniel Goh

CS461: Senior Software Engineering Project

Fall 2016

December 1, 2016

Abstract: Our customer is using a simulation to create visuals that are used for online data collection. This simulation is using outdated libraries which result in outdated graphics. We, as the supplier, define the necessary designs that will be used to accomplish our customer's request. The request being to update the simulation's graphics with warm cool shaders, shadows and silhouettes.

Keywords: OpenInventor, OpenGL, OpenRave, shaders, warm cool shaders, silhouettes, shadows, robotic simulation, geometry, visualization, render, vertex lines, software requirements specification, system requirements specifications

1 INTRODUCTION

1.1 Purpose

1.2 Scope

1.3 Context

1.4 Summary

REFERENCES

- [1] Fraps, "Fraps." [Online]. Available: <http://www.fraps.com/>
- [2] J. Berkes, "ptime 1.0 - accurately measure program execution time." [Online]. Available: <http://www.pc-tools.net/win32/ptime/>
- [3] F. D. M. Pizka, "How to effectively define and measure maintainability." [Online]. Available: <http://www.itestra.de/fileadmin/Redaktion/Documents/07itestradeineandmeasuremaintainability.pdf>
- [4] Google, "Google forms." [Online]. Available: <https://www.google.com/forms/about/>
- [5] S. Monkey, "Writing good survey questions." [Online]. Available: <https://www.surveymonkey.com/mp/writing-survey-questions/>
- [6] Google, "Google sheets." [Online]. Available: <https://www.google.com/sheets/about/>
- [7] S. Monkey, "Making sense of the numbers: When to embrace relativity, and when to ignore it." [Online]. Available: <https://www.surveymonkey.com/blog/2012/06/28/making-sense-numbers-when-embrace-relativity-when-ignore-it/>

2 GLOSSARY

3 Body

4 REQUIREMENT: MEASURING THE SIMULATIONS RUNTIME, AND FPS

By Justin Bibler

4.1 Software Design Description

Our project requires us to measure and analyze the runtime and FPS of our altered simulation. This is done so that we can ensure that our additions fulfill our performance metrics: the simulation must maintain an average 30 FPS, and the initial launch of the simulation should take no more than 30 seconds. If we are unable to reach these metrics our implementations will be considered incorrect, and will require revisions.

4.2 Design Stakeholders

Justin Bibler, Matthew Huang, and Daniel Goh

4.3 Design Concerns

All stakeholders share similar design concerns.

Requirement design concerns:

- 1) Failing to meet our target FPS and runtime will result in revisions of our implementations.
- 2) Will our measurements be accurate for the majority of computers.
- 3) Software used for measuring may cost money.

4.4 Design Views

4.4.1 Information Viewpoint

The purpose of this viewpoint is describe how information will be gathered, and how it will be analyzed. Our team will be using two external tools to obtain data related to the simulation's runtime and FPS. Firstly, FRAPS will be used to examine the FPS and export the information into a file to be analyzed. Secondly, ptime will be used to measure the simulation's runtime.

4.4.1.1 Design Concern

Interface viewpoint concerns:

- 1) FRAPS is paid software.
- 2) Will our measurements be accurate for the majority of computers.

4.4.1.2 Design Elements

Name

Tools and Methodology for FPS and Runtime Data Collection, and Analysis.

Type

Tools, and Method.

Purpose

Data collected will be analyzed to ensure that our implementations into the simulation meet our requirements.

Data attribute

FRAPS will be used to capture data related to FPS, this will be done by using the benchmarking tools that come with the software. We will run this test for one minute ten times, on five different sample simulations with our updated graphics. This data will be exported into a file, from here we will analyze the data by finding the mean and median across all executions. If these values are within a certain standard deviation of 30 FPS, our implementation will be considered correct.

In regards to runtime, ptime will be run with the simulation to measure it's startup time. Just like how the FPS was measured, there will be ten tests on five different sample simulations. If the mean and median of the data is within a certain standard deviation of a 30 second runtime, then our implementation will be considered a success.

Author

FRAPS is owned by Beepa.[1] Ptime is created by Jem Berkes. [2]

4.5 Rational

Even though FRAPS is a paid software I've decided that it be best if we use it. It's ability to export data into a file allows our group to easily obtain and analyze data. Furthermore, our concern related to the validity of the data stems from the fact that our group members own above average computers. Thus, testing on our computers would most likely be inaccurate relative to the average computer. To circumvent this problem we plan to do most of our testing on the computers on the OSU campus.

5 REQUIREMENT: CODE MAINTAINABILITY

By Justin Bibler

5.1 Software Design Description

The goal behind code maintainability is to increase the cost effectiveness of changes being made to a system. [3] Our group has made this a requirement because our client wishes to be able to easily change, or add into our implementations. The primary logic behind this design is the use of good programming practices such as documentation, and commenting, but also the use of external resources which are described within the viewpoint below.

5.2 Design Stakeholders

Justin Bibler, Matthew Huang, and Daniel Goh

5.3 Design Concerns

All stakeholders share similar design concerns.

Requirement design concerns:

- 1) Cost of static code debugging tools.
- 2) Lack of documentation for preexisting code.
- 3) Lack of comments for preexisting code.

5.4 Design Views

5.4.1 Resource Viewpoint

External resources will be used to help us maintain and upkeep our code quality. The first resource we will be using, which within today's standard is almost a necessity, will be GitHub. GitHub is a repository that is used for code version control. Secondly, we will be using Cppcheck. Cppcheck is a static code analysis tool that examines code for bugs that a compiler may not catch.

5.4.1.1 Design Concern

Interface viewpoint concerns:

- 1) Using Cppcheck may bring about problems within preexisting code not written by us.

5.4.1.2 Design Elements

Entities

Both GitHub, and Cppcheck are free to use by the public

Name

Resources for Code Maintainability.

Type

External resource.

Function

GitHub will be used for version control of the code. Cppcheck will be used to assist in finding and fixing bugs within our code implementations.

Resource attribute

GitHub is important because it will allow us to have easy access to past versions of code. Using GitHub is like a safety net that will allow us to be free with how we edit the code, because in the case that we create a massive new problem; it is very easy for us to pull an earlier version of the code to work on. Along with this GitHub also has a built in wiki that will be used to record and document our new implementations and functions within the code. Allowing for easy reference for ourselves and our client.

Cppcheck will be used to examine our new implementations into the code. Using this tool will allow us to quickly find and eliminate bugs within the code. Few amount of bugs within code will allow us to make changing and creating new implementations safer and easier.

Author

GitHub is owned by GitHub, Inc. Cppcheck is open source.

5.5 Rational

The reason Cppcheck was decided upon was because it is open source and free, other static analysis tools cost a significant amount of money. Which makes the Cppcheck option the best for our group. Also, the design behind "Code Maintainability" can be improved by the use of the resources I talked about. However, a large part of it will rely more on how well our group documents the improvements we make through resources such as GitHub. It'll be important while we go forward to document both how we implemented our improvements, and how to use our improvements. This is because, as mentioned in the Requirement concerns, we are working off preexisting code. Thus, our client will need some sort of good reference of how to navigate the code, and how to make proper adjustments.

6 REQUIREMENT: ALLOWING PARTICIPANTS TO DETERMINE PROJECT IMPROVEMENT THROUGH ON-LINE SURVEY.

By Daniel Goh

6.1 Software Design Description

This requirement is established as a form of performance metric to determine if the visuals of the robotic simulation has improved from its initial state, and if the team's visual enhancement to the robotic simulation meets our client's needs. Google Forms is the selected platform to run the online survey, and Google Sheets will be used to analyze and visualize the collected data.

6.2 Design Stakeholders

Justin Bibler, Matthew Huang, and Daniel Goh

6.3 Design Concerns

All design stakeholders share similar design concerns to this requirement. The design concern that accompanies this requirement includes:

- 1) If participants will be able to understand the questions of the online survey and select their choice of better visuals.
- 2) If the data collected from the survey can be visualized to reflect the collective participants responses.

6.4 Design Views

6.4.1 Interface Viewpoint

6.4.1.1 Design Concern

Google Forms is the selected service that will be utilized to carry out the online survey. The design concern for the online survey will include if participants will be able to understand the questions of the online survey and select their choice of better visuals.

6.4.1.2 Design Elements

Name

Survey Interface Understandability

Type

System used to assess resulting visuals for the robot grasping simulation.

Purpose

This element exists to help guide the creation of an online survey that is easily understood and usable by the participants.

Function

Google Forms [4] is a matured survey platform that allows unlimited number of questions and the function to attach images to the created survey. Participants will be able to select a picture or answer based on the questions presented. The questions will cover the aesthetic aspects between pictures, the presence of shadows between pictures, and identification of object relativity or position within the picture.

Interface

Methods of interaction provided by Google Forms include:

- Allowing participants to view attached images for a question
- Allowing participants to select a single answer or image for a question
- Allowing participants to select multiple answers or images for a question (Check PLES)
- Participants responses will be stored as a data file within Google Forms and exportable to Google Sheets(.csv files, comma separated value files)

Users should not be overwhelmed by information in the interface while taking the survey. Survey questions should ask the user for a specific opinion (e.g. questions asking about presence of shadows should only focus on asking about shadows and nothing more) at a time and ideally have no more than one sentence [5]. Survey questions should be designed to be balanced and not biased. For example, stating the left visual is the improved visual in the question while asking the user to select the better visual is a form of bias.

6.4.2 Information Viewpoint

6.4.2.1 Design Concerns

Google Sheets [6] is the selected platform to parse and visualize the data collected from the online survey. The design concern includes if the data collected can be analyzed and visualized meaningfully to reflect the collective participants responses.

6.4.2.2 Design Elements

Name

Data Visualization

Type

System for data parsing and visualization that supports Google Forms

Purpose

The element exists to help guide the use of Google Sheets to create data visualizations.

Data Attribute

As Google Forms and Google Sheets are under one ecosystem, Google Sheets have access to parse the data collected directly into Google Forms. The resulting data content will contain individual responses on a single spreadsheet. Questions asked will be represented on the first horizontal row. Participant's responses are time stamped and is represented as a row for each individual. The participant's responses (answer to each questions) are recorded below the questions.

TABLE 1
Spreadsheet example with data

Respondent	Time stamp	Question 1	Question 2	...	Question N
1	11/12/2016 20:28:39	Choice 1	Choice 2	...	Choice 2
2	11/13/2016 1:55:37	Choice 1	Choice 2	...	Choice 1
3	11/13/2016 11:56:02	Choice 2	Choice 2	...	Choice 2
4	11/15/2016 23:52:12	Choice 1	Choice 2	...	Choice 1
5	11/18/2016 15:51:32	Choice 1	Choice 1	...	Choice 2

The selected data analysis method that will be used to determine the project's success will be based on frequency among all respondents [7]. An example model that represents the frequency method is as follow:

$$\frac{\text{NumberOfChoice1OccurrenceForQuestion1}}{\text{TotalRespondents}} = x\% \quad (1)$$

In this example, Choice 1 for Question 1 is the visuals with enhanced shadows implementation. x will need to be more than 79 in order for shadow implementations to be considered a success.

The data collected will be converted into visualizations using the charting functions provided in Google Sheets. For ease of understandability and quick visualization, the pie chart charting option will be used to display the collective responses.