TABLE VI[a]

t_g Sec.	t_F Sec.	$\frac{1}{t_F}$	$\frac{1}{t'_F}-\frac{1}{t_F}$	n'	$\frac{1}{n'}(\frac{1}{t'_F}-\frac{1}{t_F})$	$\frac{1}{t_g}+\frac{1}{t_F}$	n	$\frac{1}{n}(\frac{1}{t_g}+\frac{1}{t_F})$
11.848	80.708	.01236				.09655	18	.005366
11.890	22.366		.03234	6	.005390			
11.908	22.390	.04470				.12887	24	.005371
11.904	22.368		.03751	7	.005358			
11.882	140.565	.007192				.09138	17	.005375
			.005348	1	.005348			
11.906	79.600	.01254				.09673	18	.005374
11.838	34.748		.01616	3	.005387			
11.816	34.762	.02870				.11289	21	.005376
11.776	34.846							
11.840	29.286							
		.03414				.11833	22	.005379
11.904	29.236		.026872	5	.005375			
11.870	137.308	.007268				.09146	17	.005380
			.021572	4	.005393			
11.952	34.638	.02884				.11303	21	.005382
11.860			.01623	3	.005410			
11.846	22.104							
		.04507				.12926	24	.005386
11.912	22.268		.04307	8	.005384			
11.910	500.1	.002000				.08619	16	.005387
11.918	19.704		.04879	9	.005421			
		.05079				.13498	25	.005399
11.870	19.668							
			.03[79]4	7	.0054[20]			
11.888	77.630							
		.01285				.09704	18	.005390
11.894	77.806		.01079	2	.005395			
11.878	42.302	.02364				.10783	20	.005392
11.880			Means		.005386			.005384

Duration of exp.	= 45 min.	Pressure	= 75.62 cm.
Plate distance	= 16 mm.	Oil density	= .9199
Fall distance	= 10.21 mm.	Air viscosity	$= 1,824 \times 10^{-7}$ [poise]
Initial volts	= 5,088.8	Radius (a)	= .[0]000276 cm.
Final volts	= 5,081.2	$\frac{l}{a}$ [mean free path $\div$ a]	= .034
Temperature	= 22.82°C.	Speed of fall	= .08584 cm./sec.

$$e_i = 4.991 \times 10^{-10} \text{ [statcoulomb]}^b$$

[a] [The bracketed numbers are our corrections of errors in the original paper.]

[b] [The value presently accepted is 4.802×10^{-10} statcoulombs.]