

Control Valve Specification
Prepared By :

Customer : BASF
PO # :
Quote # :
Rev/By : 0.0 / ventas
Application : BUTADIENO

Project : PROYED-26-095
Proj Num :
Q. ID : ventas_WSBN9102PNXT17_77
Alternate :

Valve Tag # : PVK-2621
Page # : 1
P&ID :
Line :
Date / Ver : 31-Aug-2026 / 17,8080

Process Data For Control Valve Selection	1	Pipe Size, Up/Down	1.000 / 1.000				
	2	Pipe Sch, Up/Down	80 / 80				
	3	Allow Noise/Add Attn/Type	90 / 0 /				
	4	Process Fluid	BUTADIENO				
	5	Design Press./Temp.	/ bar (a) / / °C				
	6	Driving Cond.	Cond1	Cond2	Cond3	Cond4	
	7	Temperature (°C)	10.000				
	8	Inlet Press (bar (a))	15.000				
	9	Outlet Press (bar (a))	9.000				
	10	Liq Flow Rate (m³/h)	7.000				
	11	Gas Flow Rate (1000 SCFH)	0				
	12	Viscosity (cP)	0.160				
	13	Vapor Press (kPa (a))	245.000				
	14	SG-MW	0.621				
Calculated Data	15	Max Shutoff / Shutoff Class	87.023 psi / Class IV				
	16	Available Air Supply / Max. Allow. Supply	3.000 / 7.010 bar (a)				
	17	Valve Function / Amb Temp Min/Max	Throttling / -18/50 °C				
	18	Driving Cond.	Cond1	Cond2	Cond3	Cond4	
	19	Flow Coeff. (Cv)	2.604				
	20	Est Stroke (% Lift)	80.000				
	21	Pressure Drop (bar)	6.000				
	22	Choke Drop (bar)	12.088				
	23	Noise [IEC] (dBA)	<70				
	24	Valve Vel (ft/s)	12.598				
	25	Pipe Vel (ft/s)	13.755				
Valve Body Assembly	26	Model / Type / Design / Valve#	FlowTop / Globe / Three-Flange / V752				
	27	Size/Pressure Rating	1.00 / CL 150				
	28	Trim # - Cv / Characteristic	12A Cv:4,6 / Mod =%				
	29	Flow Direction / Stages	Flow Under /				
	30	Body Matl / Bonnet Matl	A216-WCC (CS) / Carbon Steel				
	31	End Connection / Sch	Integral Flange /				
	32	Flange Facing/Face to Face	ANSI B16.5 Form RF / ISA S75.08.01				
	33	Flange Finish	125 - 250 Ra				
	34	Bonnet Type	Standard				
	35	Balance Type / Guiding	Unbalanced / Post Guided				
	36	Plug Matl / Facing	316 SS /				
	37	Stem Material/Stem Protector	316 SS (Strain hardened level 2) /				
	38	Seat Ring Matl / Facing	316 SS /				
	39	Seat Design/Soft Seat Matl.	Clamped Seat /				
	40	Rangeability	50:1				
	41	Trim Type / Seat Ret. Matl.	Contoured Plug / A351-CF8M (SS)				
	42	Packing Matl / Style / Vac / Cert	Braided PTFE / Single / /				
	43	Packing Design/Live Loaded	External /				
	44	Bonnet Port Type					
	45	Bellows Type / Material	/				
	46	Jacket / Connections	/				
	47	Body Bolting Material	B7-2H Zinc Plated				
	48	Gaskets	Graphite				
	49	Packing Follower Material					
	50	P/B Seal Matl.					
		T1					
		T2					
		T3					
		T4					
	Customer Spec	01	Certification/Approval Type	/			
		02	Class or Gas Group	No Cert Req			
		03	Division or Zone	No Cert Req			
		04	Group	No Cert Req			
		05	Ingress / Temperature	NEMA 3 /			
06		NACE / Nuclear / Copper Restriction	NA / NA / None				
07		SIL Viv-Act / Pos					
08		Oxygen	NA				
Actuator	51	Actuator Type	FlowAct / Multifunction yoke				
	52	Size/Stroke Code	503 A				
	53	Strk/Strk Limitation	20 mm /				
	54	Spr Set/Range	503 A 0.2-1.0 bar				
	55	Fail/Air-To	Close / Open				
	56	Min./Max. Air Sup.	2,41 / 7,01 bar (a)				
	57	Tubing/Fittings	/ / /				
	58	Pos. Ornt./HW	HVR /				
	59	Actuator/HW Matl.	Carbon Steel /				
	60	Spud/Thread/Yoke					
	61	Act. Color	White /				
	62	Model	Logix 500 + Series				
	63	Model #	522MD+14-W1D100-GM1-0000				
	64	Comm/Sig/Diag	HART / 4 - 20 mA / / Pro				
	65	Housing/Shaft	Aluminum, White / Linear-D Shaft				
	66	Connections	M:5/16;P:1/4N;C:1/2N;V:1/4N				
	67	Action/Hart Version	3-way SA poppet relay / HART 6				
	68	Ind/Dispay/Mnt	None / None / Direct Mounted				
	69	Aux Slot 1/2	No Card / No Card				
	70	Internal switches	None				
	71	Manifold/Pos Tag	Gauge Manifold Aluminum /				
	72	Gauges	Nickel:Brass (psi,bar/kPa)				
	73	Model					
	74						
	75						
	76						
	Pos Ind Sw	77					
		78					
79							
80							
81							
82		Model/Qty	/				
83		Cv-Kv/Function	/				
84		Volt/Watt/Config	/ /				
Solenoid	85	Body/Housing Mtl	/				
	86	Body/Elect Conn	/				
	87	Port Size/Mtg	/				
	88	Tag/Reset-Override	/ / /				
	89	Air Filter/Mnting	/				
	90	Filter-Reg/Mnting	/				
	91	Flow Booster	/				
	92	Thr Chk Valve					
Others	93	Quick Exhaust					
	94	Supply Tubing					
	95	Lockup/Mnting	/				
	96	Plate ID					
	97	Plate Type					
	98	Packaging	Standard				
	99	Positioner Interface					
	100	Wiring Conn. Type					
	01	Rad. Exm/Mat Regu	/				
	02	Drawings					
	03	Seat Leak Test	FCI 70-2 Class IV (Air)				
	04	Final test certificates					
Special Req	05	PMI/Weld Req	/ ASME BPVC Section IX				
	06	Doc. / Cleaning	/				
	07	HydroTest/App.	/				
	08	CMTR/Mat Cert.	Body & Bonnet / EN 10204 3.1				
	09	Paint	Standard /				
	10	Diagnostic Test					
	11	Cust. Insp/Witn.	No / No				
	12						
	13						
	14	Flow Testing					
	S1						
	S2						

Sourcing Restrictions :
Quoted Delivery (Weeks) :
Factory Quote :

Line # : Remarks :

PRELIMINARY PARTS LIST REPORT

Customer : BASF
Project : PROYED-26-095
Proj Num :
PO # :
Quantity : 1
Tag # : PVK-2621

Rev/By : 0.0 / ventas
Contract : ventas_WSBN9102PNXT17_77
Alternate :
Application : BUTADIENO
Serial# :

Page # : 1
P&ID :
Line :
Date / Ver : 31-Aug-2026 / 17,8080