

Linear Regression

```
In [54]: % matplotlib inline

from IPython.core.display import display, HTML
display(HTML("<style>.container { width:90% !important; }</style>"))
import numpy as np
import pandas as pd
pd.set_option('display.max_columns', 100)

df = pd.read_csv('User_Knowledge.csv')

df.loc[df.UNS == 'very_low', 'grade'] = 0
df.loc[df.UNS == 'Low', 'grade'] = 1
df.loc[df.UNS == 'Middle', 'grade'] = 2
df.loc[df.UNS == 'High', 'grade'] = 3

df.sample(5)
```

Out[54]:

	STG	SCG	STR	LPR	PEG	UNS	grade
134	0.400	0.12	0.41	0.10	0.65	Middle	2.0
89	0.290	0.30	0.52	0.09	0.67	Middle	2.0
141	0.420	0.15	0.66	0.78	0.40	Middle	2.0
20	0.120	0.28	0.20	0.78	0.20	Low	1.0
78	0.245	0.10	0.71	0.26	0.20	very_low	0.0

Attribute Information

- STG (The degree of study time for goal object materails), (input value)
- SCG (The degree of repetition number of user for goal object materails) (input value)
- STR (The degree of study time of user for related objects with goal object) (input value)
- LPR (The exam performance of user for related objects with goal object) (input value)
- PEG (The exam performance of user for goal objects) (input value)
- UNS (The knowledge level of user) (target value)
 - Very Low: 50
 - Low:129
 - Middle: 122
 - High 130

```
In [55]: #y = List(df['UNS'])
y = df.grade

# feature selection, dropping SCG
#X = df.drop(columns=['SCG']).iloc[:,0:4]
# keeping all features
X = df.iloc[:,0:5]

X.sample()
```

Out[55]:

	STG	SCG	STR	LPR	PEG
197	0.73	0.2	0.07	0.72	0.26

```
In [56]: from sklearn.model_selection import train_test_split
from sklearn.preprocessing import StandardScaler

X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.33, random_state=0)

# separating transformed
sc = StandardScaler()
X_train_sc=sc.fit_transform(X_train)
X_test_sc=sc.transform(X_test)
```

Linear regression

```
In [57]: from sklearn.linear_model import LinearRegression

reg = LinearRegression()
reg_pca = LinearRegression()

reg.fit(X_train, y_train)
reg_y_pred=reg.predict(X_test)
print("Linear Regression accuracy: ", reg.score(X_test, y_test))
```

Linear Regression accuracy: 0.935041373654

```
In [58]: from sklearn import metrics
print("MAE: ", metrics.mean_absolute_error(y_test, reg_y_pred))
print("MSE: ", metrics.mean_squared_error(y_test, reg_y_pred))
print("RMSE: ", np.sqrt(metrics.mean_squared_error(y_test, reg_y_pred)))
```

MAE: 0.170240265657
MSE: 0.0532685328268
RMSE: 0.230799767822

Linear regression + SVC approach

```
In [59]: from sklearn.decomposition import PCA
pca = PCA(n_components=2)
X_train_pca = pca.fit_transform(X_train_sc)
X_test_pca = pca.transform(X_test_sc)

reg_pca.fit(X_train_pca, y_train)
reg_y_pred_pca = reg_pca.predict(X_test_pca)
print("Linear Regression (with PCA) accuracy: ", reg_pca.score(X_test_pca, y_test))
```

Linear Regression (with PCA) accuracy: 0.485295947626

```
In [60]: from sklearn import metrics
print("MAE: ", metrics.mean_absolute_error(y_test, reg_y_pred_pca))
print("MSE: ", metrics.mean_squared_error(y_test, reg_y_pred_pca))
print("RMSE: ", np.sqrt(metrics.mean_squared_error(y_test, reg_y_pred_pca)))
```

```
MAE: 0.541667047803
MSE: 0.422076808768
RMSE: 0.649674386726
```

Feature select. Dropping SCG to see whether RMSE improves

```

In [61]: # feature selection, dropping SCG to see whether RMSE improves
X = df.drop(columns=['SCG']).iloc[:,0:4]

X.sample()

from sklearn.model_selection import train_test_split
from sklearn.preprocessing import StandardScaler

X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.33, random_state=0)

# separating transformed
sc = StandardScaler()
X_train_sc=sc.fit_transform(X_train)
X_test_sc=sc.transform(X_test)

# Linear regression
from sklearn.linear_model import LinearRegression

reg = LinearRegression()
reg_pca = LinearRegression()

reg.fit(X_train, y_train)
reg_y_pred=reg.predict(X_test)
print("Linear Regression accuracy: ", reg.score(X_test, y_test))

from sklearn import metrics
print("MAE: ", metrics.mean_absolute_error(y_test, reg_y_pred))
print("MSE: ", metrics.mean_squared_error(y_test, reg_y_pred))
print("RMSE: ", np.sqrt(metrics.mean_squared_error(y_test, reg_y_pred)))

# Linear regression + SVC approach
from sklearn.decomposition import PCA
pca = PCA(n_components=2)
X_train_pca = pca.fit_transform(X_train_sc)
X_test_pca = pca.transform(X_test_sc)

reg_pca.fit(X_train_pca, y_train)
reg_y_pred_pca = reg_pca.predict(X_test_pca)
print("Linear Regression (with PCA) accuracy: ", reg_pca.score(X_test_pca, y_test))

from sklearn import metrics
print("MAE: ", metrics.mean_absolute_error(y_test, reg_y_pred_pca))
print("MSE: ", metrics.mean_squared_error(y_test, reg_y_pred_pca))
print("RMSE: ", np.sqrt(metrics.mean_squared_error(y_test, reg_y_pred_pca)))

Linear Regression accuracy:  0.932686320712
MAE:  0.169140096604
MSE:  0.0551997653979
RMSE:  0.234946303223
Linear Regression (with PCA) accuracy:  0.477349803784
MAE:  0.546350442153
MSE:  0.428592947546
RMSE:  0.65467010589

```

Linear Regression has a slight decrease, while Linear Regression with PCA shows a slight increase.