

NAME

mbgetesf – Extract swath bathymetry data flags into an edit save file.

VERSION

Version 5.0

SYNOPSIS

mbgetesf [-Fformat -Iinfile -Mmode -Oesffile -V -H]

DESCRIPTION

Swath bathymetry data is typically edited either with interactive tools such as **mbedit** or automatic filters such as **mbclean**. The beams which are deemed "bad" are flagged, and the flags are output to an "edit save file", which can be applied to data later by **mbprocess**. Occasionally, the need arises to translate data flagging information from one file to another which represents a different version of the same dataset. In particular, it may happen that editing has been done on a data format which does not support all of the original data stream (e.g. the edmb Hydrosweep format 22, which does not contain travel times or amplitudes), but the user now wishes to work with the complete data stream without having to redo the editing process.

The utility **mbgetesf** allows the user to extract the flagging information in the form of an "edit save file" like those generated by **mbedit** and **mbclean**. These edits can be applied to data later using **mbprocess**. If the edit save file is named properly (an ".esf" suffix added to the input swath file name), the edits can automatically be loaded into **mbedit** or **mbclean**.

The user can extract edit events from only the flagged beams (**-M1**), or can extract edit events specifying null and flagged beams (**-M2**), or all (good, flagged, and null) beams (**-M3**). The **-M2** and **-M3** cases are useful if previous editing has involved nulling beams that were originally classified as good or unflagging beams that were originally flagged.

The default input is from stdin, and the default output is to standard out.

MB-SYSTEM AUTHORSHIP

David W. Caress
Monterey Bay Aquarium Research Institute
Dale N. Chayes
Center for Coastal and Ocean Mapping
University of New Hampshire
Christian do Santos Ferreira
MARUM - Center for Marine Environmental Sciences
University of Bremen

OPTIONS

-B yr/mo/da/hr/mn/sc

This option sets the starting time for data allowed in the input data. The **-E** option sets the ending time for data. If the starting time is before the ending time, then any data with a time stamp before the starting time or after the ending time is ignored. If instead the starting time is after the ending time, then any data between the ending and starting time will be ignored. This scheme allows time windowing both inside and outside a specified interval. Default: yr/mo/da/hr/mn/sc = 1962/2/21/10/30/0.

- E** *yr/mo/da/hr/mn/sc*
This option sets the ending time for data allowed in the input data. See the **-B** option above. Default: *yr/mo/da/hr/mn/sc* = 2062/2/21/10/30/0.
- F** *format*
Sets the format for the input and output swath data using **MBIO** integer format identifiers. These utilities uses the **MBIO** library and will read any swath data format supported by **MBIO**. A list of the swath data formats currently supported by **MBIO** and their identifier values is given in the **MBIO** manual page.
- H**
This "help" flag causes the program to print out a description of its operation and then exit immediately.
- I** *infile*
Data file from which the input data will be read. If no input file is specified, the input will be read from stdin. Default: *infile* = stdin.
- K** *kluge*
Applies a kluge fix for a problem with EM300/EM3000 data stored in HDCS format (**MBIO** format id 151). If *kluge* = 1, then the beam flag values read in each ping are shifted down by one beam (with the last beam flagged null), correcting for a beam indexing offset found in some HDCS EM300/EM3000 datasets. This kluge is applied only when the input data format is 151 and has no effect otherwise. Default: *kluge* = 0 (no kluge applied).
- M** *mode*
Specifies which beam flag values are output as edit events. If *mode* = 1, then only flagged beams are output. If *mode* = 2, then flagged and null beams are output. If *mode* = 3, then an edit event will be output for every beam, including those that are "good" (neither flagged nor null). The *mode* values of 4 to 6 cause the output "edit save file" to have an embedded special mode that implicitly sets all beam flags not specified with an edit event to a default value. If *mode*=5 then the default value is null, if *mode*=6 then the default value is good, and if *mode*=4 then the default value is good for most formats and null for the few formats that have more null than valid beams. The default modes are used by programs **mbpreprocess** and **mbeditviz** when generating and using "global edit files" ("*.gef" suffix) that are used to completely specify the beam flag state of a raw swath bathymetry file. Default: *mode* = 1.
- O** *esffile*
Specifies output edit save file to which the edit events will be written. If no edit save file is specified, the output will be written to stdout. Default: *esffile* = stdout.
- V**
Normally, **mbgetesf** works "silently" without outputting anything to the stderr stream. If the **-V** flag is given, then **mbgetesf** works in a "verbose" mode and outputs the program version being used and all error status messages.

EXAMPLES

Suppose one has an edmb format (**MBIO** format id 22) Hydrosweep file called *hs_ew9103_143.mb22* which has been edited using older versions of **mbedit** so that no edit save file was generated. Further suppose that one's thesis advisor suggests that the bathymetry would be better if it were recalculated from travel times using a new water velocity model, requiring that the raw Hydrosweep data (originally collected in format 21 but recently translated to format 24) in the file *hs_ew9103_143.mb24* be used. First extract the edit events in the form of a edit save file from the edited edmb file:

```
mbgetesf -F22 -Ihs_ew9103_143.mb22 -Ohs_ew9103_143.mb24.esf -V
```

Note that the edit save file has been given the name of the second swath file with ".esf" appended. This naming convention is the same as if **mbedit** or **mbclean** had been run on *hs_ew9103_143.mb24*. Now, running either **mbedit** or **mbclean** will automatically load the edit events as a starting point for editing or filtering. To simply apply the extracted edit events to the swath bathymetry, first use **mbset** to enable applying the edits in the **mbprocess** parameter file, and then run **mbprocess** to actually apply the edits and generate a processed output

swath file:

```
mbset -lhs_ew9103_143.mb24 -PEDITSAVEMODE:1 -PEDITSAVE-  
FILE:hs_ew9103_143.mb24.esf -V  
mbprocess -lhs_ew9103_143.mb24 -V
```

The output swath file will be named hs_ew9103_143p.mb24.

SEE ALSO

mbsystem(1), mbedit(1), mbclean(1), mbset(1), mbprocess(1).

BUGS

Let us know.