

001

002

003

Supplementary Materials- A Meaningful
Perturbation Metric for Evaluating Explainability
Methods

001

002

003

004

Anonymous ECCV 2024 Submission

004

005

Paper ID #7602

005

006

1 Implementation Details

006

007

In this section, we provide additional implementation details of our method, as

007

008

described in Sec. 3 of the main paper. Kindly note that in addition to the pro-

008

009

vided details, we attach a ZIP file with our full code to reproduce the experiments

009

010

presented in the paper.

010

011

1.1 Data Construction

011

012

First, we provide additional details on the curation of our dataset I . As men-

012

013

tioned in the main paper, we begin by performing full inpainting (*i.e.*, from a

013

014

completely blacked out image) on all ImageNet [7] classes for a set of 20 random

014

015

seeds with the prompt “ $\{class-name\}$ ”. A class is deemed valid if and only if,

015

016

in over 50% of the instances, the classifier’s prediction of the image accurately

016

017

aligned with the specified class.

017

018

1.2 Inpainting details

018

019

We utilized the public version stable-diffusion-inpainting [6] from Hugging Face,

019

020

initialized with the weights of the Stable-Diffusion-v-1-2. As recommended the

020

021

guidance scale parameter was set to 7.5. The inpainting was run on NVIDIA

021

022

GeForce RTX 2080 Ti GPU with 11GB of memory. The images and their re-

022

023

spective masks were resized to 512×512 images to match the training resolu-

023

024

tion. Before reapplying the classifiers, the inpainted image was resized back to

024

025

224×224 .

025

026

2 Variance in Attribution Methods

026

027

As mentioned in the main paper, different attribution methods often yield very

027

028

different relevance maps. Therefore, it is necessary to develop evaluation metrics

028

029

that can clearly distinguish between them. Otherwise, it remains unclear which

029

030

method should be used in each use-case. To empirically substantiate this point,

030

031

Fig. 1 showcases representative examples of the relevance maps produced by

031

032

different attribution methods given the *same input* using both ResNet (top of

032




Fig. 1: Examples of relevance maps produced by different attribution methods for the same input using ResNet (top), and ViT (bottom). Different attribution methods often result in entirely different attribution maps, necessitating a metric to distinguish between them.

Fig. 1), and ViT (bottom of Fig. 1). Observe that, for example, given an input image of a dog (ViT top row) each attribution method classifies different image pixels as the most relevant ones. In the absence of a metric that can clearly distinguish between the different maps, we would not be able to determine which attribution method is most faithful. As demonstrated in Fig. 2 of the main paper, the baseline metrics often produce results that are very similar across all examined attribution methods. This can be explained by the OOD effect described in the paper; the perturbations applied by the baselines drive the image out of distribution, causing a change in the prediction which does not necessarily reflect the actual relevance of the modified pixels (see Figs. 1,3,4 on the main paper). In contrast, when applying our metric, the perturbed images remain plausible and in-distribution, thus clear and statistically significant results are obtained across various models.

3 Additional baselines

Alongside the primary baselines presented in the main paper, we enclose a comparison against two additional baselines. The first is faithfulness violation [5]




Fig. 2: Perturbation comparison against additional baselines with ResNet-50, VGG, AlexNet-based binary classifier, and ViT-B (please zoom in to view better). For each model, we consider the most common explainability algorithms, in addition to a *random* selection of pixels. As can be observed, the other perturbation methods often struggle with separating random maps from actual relevance maps (Violations [5]) and appear to produce very similar results for all methods (Saliency [1]). Conversely, our method produces consistent ranking and meaningful distinction from the random baseline.

which checks that the deletion of the relevant pixels decreases the confidence of the predicted class. The second baseline is a saliency-based evaluation [1] where for each percentage of perturbation pixels (10%, ..., 50%), one first extracts the smallest rectangle patch that contains the top pixels, and then applies the classifier to that patch to test whether or not the prediction remains the same.

Similar to the main paper, we compare the baselines against our method in two main aspects, (i) the separation of the random attribution baseline from the real attribution methods (to assess robustness to OOD inputs), and (ii) the separation between the attribution methods themselves (following the variance in the resulting relevance maps, as detailed in Sec. 2).

Fig. 2 shows that the violation method fails to clearly separate the random baseline from the real attribution methods, and over all examined models, the random baseline is ranked in between the valid attribution methods, indicating that, similar to other methods that apply unnatural perturbation, the violation tests are susceptible to OOD modifications to the input.

Additionally, the saliency-based metric often produces near indistinguishable outputs for various attribution methods (for all classifiers with the exception of

ViT). As explained in the section above, the ability to make these distinctions is crucial for the evaluation of different methods. Moreover, the random baseline cannot be clearly separated from the valid attribution methods for all models except for ViT.

References

1. Dabkowski, P., Gal, Y.: Real time image saliency for black box classifiers. In: Neural Information Processing Systems (2017), <https://api.semanticscholar.org/CorpusID:41766449> 3
2. Dosovitskiy, A., Beyer, L., Kolesnikov, A., Weissenborn, D., Zhai, X., Unterthiner, T., Dehghani, M., Minderer, M., Heigold, G., Gelly, S., et al.: An image is worth 16x16 words: Transformers for image recognition at scale. arXiv preprint arXiv:2010.11929 (2020) 3
3. He, K., Zhang, X., Ren, S., Sun, J.: Deep residual learning for image recognition. In: Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition. pp. 770–778 (2016) 3
4. Krizhevsky, A., Sutskever, I., Hinton, G.E.: Imagenet classification with deep convolutional neural networks. In: Proceedings of the Advances in Neural Information Processing Systems. pp. 1097–1105 (2012) 3
5. Liu, Y., Li, H., Guo, Y., Kong, C., Li, J., Wang, S.: Rethinking attention-model explainability through faithfulness violation test. ArXiv **abs/2201.12114** (2022), <https://api.semanticscholar.org/CorpusID:246411233> 2, 3
6. Rombach, R., Blattmann, A., Lorenz, D., Esser, P., Ommer, B.: High-resolution image synthesis with latent diffusion models. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR). pp. 10684–10695 (June 2022) 1
7. Russakovsky, O., Deng, J., Su, H., Krause, J., Satheesh, S., Ma, S., Huang, Z., Karpathy, A., Khosla, A., Bernstein, M., et al.: Imagenet large scale visual recognition challenge. International journal of computer vision **115**(3), 211–252 (2015) 1
8. Simonyan, K., Vedaldi, A., Zisserman, A.: Deep inside convolutional networks: Visualising image classification models and saliency maps. arXiv preprint arXiv:1312.6034 (2013) 3