National University of Singapore School of Computing CS1010S: Programming Methodology Semester I, 2018/2019

Solutions for Recitation 3 Higher Order Functions

Python

1. *lambda* - lambda *params*: expression Creates an anonymous function equivalent to:

```
def function(params):
    return expression
```

Definitions

The following are two higher-order functions discussed in lecture:

```
def sum(term, a, next, b):
    if a > b:
        return 0
    else:
        return term(a) + sum(term, next(a), next, b)

def fold(op, f, n):
    if n == 0:
        return f(0)
    else:
        return op(f(n), fold(op, f, n-1))
```

Note: it is <u>not</u> necessary to memorize these defintions, or even the names of these functions. Definitions of such functions (if they are used) will be given in an Appendix for examinations. What you need to be able to do is to read the definition for such functions and understand what they do and be able to use them.

Problems

1. Evaluate the return values of the following expressions:

```
(a) x = 2
   def f():
      x = 5
      y = x + 5
      return x + y
   f() + x
   Answer: 17
(b) x = 2
   y = 3
   def g(x):
      y = x + 5
      x = 7
      return x + y
   g(y)+y
   Answer: 18
(c) x = 4
   def foo(x):
      return x(3)
   foo(lambda x: x+1)
   Answer: 4
(d) x = 5
   def bar(x, y):
      return y(x)
   bar(4, lambda x: x**2)
   Answer: 16
```

2. Write a function my_sum that computes the following sum, for $n \ge 1$:

```
1 \times 2 + 2 \times 3 + \cdots + n \times (n+1)
```

Answer:

```
def my_sum(n):
    if n == 1:
        return 2
    else:
        return n * (n + 1) + my_sum(n - 1)
```

3. Is the function my_sum as defined above a recursive process or an iterative process? What is the order of growth in time and in space?

Answer: Recursive. Time: O(n), space: O(n).

4. If your answer in Question 2 is a recursive process, re-write my_sum as an iterative process. If your answer in Question 2 is an iterative process, re-write my_sum as a recursive process. What is the new order of growth in time and space?

Answer:

```
def my_sum(n):
    sum = 0
    for i in range(1,n+1):
        sum = sum + i * (i + 1)
    return sum

Alternative:

def my_sum(n):
    sum = 0
    while n != 0:
        sum = sum + n * (n + 1)
        n = n - 1
```

Time: O(n), space: O(1).

return sum

5. We can also define my_sum in terms of the higher-order function sum. Complete the definition of my_sum below. You cannot change the definition of sum; you may only call it with appropriate arguments.

```
T1: lambda x: x * (x + 1)

T2: 1

T3: lambda x: x + 1

T4: n
```

6. Suppose instead we define my_sum in terms of the higher-order function fold. Complete the definition of my_sum below.

```
def my_sum(n):
    return fold(<T1>, <T2>, <T3>)
T1: lambda x, y: x + y
T2: lambda x: (x + 1) * (x + 2)
T3: n - 1
```

In this solution, we are matching f(0) to 1×2 , f(1) to 2×3 , and so forth, until f(n-1) to $n \times (n+1)$.

Alternative:

```
def my_sum(n):
    return fold(<T1>, <T2>, <T3>)
T1: lambda x, y: x + y
T2: lambda x: x * (x + 1)
T3: n
```

In this solution, because f(0) = 0, we are matching f(1) to 1×2 , f(1) to 2×3 , and so forth, until f(n) to $n \times (n+1)$.

7. Write an iterative version of sum.

Answer:

```
def sum(term, a, next, b):
    total = 0
    while a <= b:
        total = total + term(a)
        a = next(a)
    return total</pre>
```

8. **Homework:** Write an iterative version of fold.

Answer:

```
def fold(op, f, n):
    res = f(0)
    curr = 1
    while curr <= n:
        res = op(f(curr), res)
        curr = curr + 1
    return res

# if your answer is significantly different, you may want to check
# boundary cases: fold(op, f, 0)
# order of operations: op(f(n), ... op(f(3), op(f(2), op(f(1), f(0))))...)</pre>
```