

National University of Singapore
School of Computing
CS1010S: Programming Methodology
Semester I, 2018/2019

Recitation 1

Introduction to CS1010S, Python & Functional Abstraction

Overview

1. Fun with IDLE
2. Assignment & Operators
3. Boolean operations
4. Conditional Statements
5. Functions

Python

1. *if-elif-else*:

```
if expression:
    statement(s)
elif expression:
    statement(s)
else:
    statement(s)
```

Consider each pre-condition *in sequence*, if the value of the any expression is not False, evaluate the corresponding statement(s). Otherwise evaluate the statement(s) under else.

2. Ternary Operator Form [To read only. Not expected to write code like that.]

[on_true] if [expression] else [on_false]

is equivalent to

```
if [expression]:
    [on_true]
else:
    [on_false]
```

Problems

1. Python supports a large number of different binary operators. Experiment with each of these, using arguments that are both integer, both floating point, and both

string. Not all operators work with each argument type. In the following table, put a cross in the appropriate boxes corresponding to the argument and operator combinations that result in error.

Operator	Integer	Floating point	String
+			
-			X
*			X
/			X
**			X
//			X
%			X
<			
>			
<=			
>=			
==			
!=			

Correct

Some of these operators were not discussed in lecture. Find out what they do. You might be asked to explain them to the rest of the class in recitation.

2. Evaluate the following expressions assuming x is bound to 3, y is bound to 5 and z is bound to -2 :

$x + y / z$ 0.5

$x ** y \% x$ -1

$y <= z$ False

$x > z * y$ True

$y // x$ 1

$x + z != z + x$ True

```

if True:
    1 + 1
else:
    17                2

if False:
    False
else:
    42                42

if (x > 0):
    x
else:
    (-x)              -3      3 because x > 0 tsk

if 0:
    1
else:
    2                2

if x:
    7
else:
    what-happened-here    7

if True:
    1
elif (y>1):
    False
else:
    wake-up            1

```

3. Suppose we're designing an point-of-sale and order-tracking system for a new burger joint. It is a small joint and it only sells 4 options for combos: Classic Single Combo (hamburger with one patty), Classic Double With Cheese Combo (2 patties), and Classic Triple with Cheese Combo (3 patties), Avant-Garde Quadruple with Guacamole Combo (4 patties). We shall encode these combos as 1, 2, 3, and 4 respectively. Each meal can be *biggie_sized* to acquire a larger box of fries and drink. A *biggie_sized* combo is represented by 5, 6, 7, and 8 respectively, for combos 1, 2, 3, and 4 respectively.

- (a) Write a function called `biggie_size` which when given a regular combo returns a *biggie_sized* version.

```

def biggie_size(combo):
    return combo + 4

```

- (b) Write a function called `unbiggie_size` which when given a *biggie_sized* combo returns a non-*biggie_sized* version.

```
def unbiggie_size(bigcombo):
    return bigcombo - 4
```

- (c) Write a function called `is_biggie_size` which when given a combo, returns True if the combo has been *biggie_sized* and False otherwise.

```
def is_biggie_size(combo):
    return combo >= 5
```

- (d) Write a function called `combo_price` which takes a combo and returns the price of the combo. Each patty costs \$1.17, and a *biggie_sized* version costs \$.50 extra overall.

```
def combo_price(combo):
    price = 0
    if combo % 4 == 0:
        price += 1.17 * 4
    else:
        price += 1.17 * (combo % 4)
    if combo >= 5:
        price += 0.5
    return price

    if is_biggie_size(combo):
        return 1.17*(combo-4)+0.5
    else:
        return combo*1.17
```

- (e) An order is a collection of combos. We'll encode an order as each digit representing a combo. For example, the order 237 represents a Double, Triple, and *biggie_sized* Triple. Write a function called `empty_order` which takes no arguments and returns an empty order which is represented by 0.

```
def empty_order():
    return 0
```

- (f) Write a function called `add_to_order` which takes an order and a combo and returns a new order which contains the contents of the old order and the new combo. For example, `add_to_order(1,2) -> 12`.

```
def add_to_order(old, add):
    return old + add

    return old*10 + add OR
    return int(str(old) + str(add))
```