

Machine Learning

Daniel Mao

Contents

1	Logistic Regression	1
1.1	Hypothesis Representation	1
1.2	Decision Boundary	2
1.3	Cost Function	2
1.4	Optimization	3
1.5	Multiclass Classification	4
2	Dimensionality Reduction	5
2.1	Motivations	5
2.2	Principal Component Analysis	5

Chapter 1

Logistic Regression

1.1 Hypothesis Representation

Logistic Regression Model

Want $0 \leq h_{\theta}(x) \leq 1$.

$$h_{\theta}(x) = g(\theta^{\top} x)$$

where

$$g(z) = \frac{1}{1 + e^{-z}}.$$

So

$$h_{\theta}(x) = \frac{1}{1 + e^{-\theta^{\top} x}}.$$

Sigmoid function (logistic function)

$$g(z) = \frac{1}{1 + e^{-z}}.$$

Properties:

- $g(0) = 0.5$.
- $\lim_{z \rightarrow +\infty} g(z) = 1$.
- $\lim_{z \rightarrow -\infty} g(z) = 0$.

Interpretation of the Hypothesis Output

$h_\theta(x)$ is the probability that $y = 1$ on input x . i.e. $h_\theta(x) = P(y = 1 \mid x; \theta)$, the probability that $y = 1$, given x , parameterized by θ .

Since y is either 0 or 1,

$$P(y = 0 \mid x; \theta) + P(y = 1 \mid x; \theta) = 1, \text{ or}$$

$$P(y = 0 \mid x; \theta) = 1 - P(y = 1 \mid x; \theta).$$

1.2 Decision Boundary

Predict $y = 1$ if $h_\theta(x) \geq 0.5$ and predict $y = 0$ if $h_\theta(x) < 0.5$.

$$h_\theta(x) \geq 0.5 \iff \theta^\top x \geq 0.$$

Consider $\theta = \begin{bmatrix} -3 \\ 1 \\ 1 \end{bmatrix}$. Predict “ $y = 1$ ” if $\theta^\top x = -3 + x_1 + x_2 \geq 0$. That is,

$x_2 \geq 3 - x_1$. This gives a “half space” in \mathbb{R}^2 . The line $x_1 + x_2 = 3$ separates \mathbb{R}^2 into a region where the model predicts “ $y = 0$ ” and a region where the model predicts “ $y = 1$ ”.

Non-linear Decision Boundary

Consider

$$h_\theta(x) = g(\theta_0 + \theta_1 x_1 + \theta_2 x_2 + \theta_3 x_1^2 + \theta_4 x_2^2)$$

and $\theta = \begin{bmatrix} -1 \\ 0 \\ 0 \\ 1 \\ 1 \end{bmatrix}$. Then the model predicts “ $y = 1$ ” if $-1 + x_1^2 + x_2^2 \geq 0$. That is, if $x_1^2 + x_2^2 \geq 1$.

1.3 Cost Function

Training set: $\{(x^{(1)}, y^{(1)}), \dots, (x^{(m)}, y^{(m)})\}$. $x_0 = 1$. $x = \begin{bmatrix} x_0 \\ x_1 \\ \vdots \\ x_n \end{bmatrix} \in \mathbb{R}^{n+1}$. $y \in \{0, 1\}$.

If

$$\text{cost}(h_\theta(x^{(i)}, y^{(i)})) = \frac{1}{2}(h_\theta(x^{(i)}) - y^{(i)})^2$$

as in linear regression, then the cost function is non-convex.

Logistic Regression Cost Function

$$\text{cost}(h_\theta(x), y) := \begin{cases} -\log(h_\theta(x)), & \text{if } y = 1 \\ -\log(1 - h_\theta(x)), & \text{if } y = 0. \end{cases}$$

Property:

- If $y = 1$ and $h_\theta(x) \uparrow 1$, then $\text{cost}(h_\theta(x), y) \approx 0$.
- If $y = 1$ and $h_\theta(x) \downarrow 0$, then $\text{cost}(h_\theta(x), y) \rightarrow +\infty$.
- Similar for $y = 0$.

Captures intuition that if $h_\theta(x) = 0$ (the model predicts $P(y = 1 \mid x; \theta) = 0$), but $y = 1$, we'll penalize the learning algorithm by a very large cost.

Cost Function for the Training Set

$$J(\theta) := \frac{1}{m} \sum_{i=1}^m \text{cost}(h_\theta(x^{(i)}, y^{(i)}))$$

where cost is the function given above.

Rewrite the cost function:

$$\text{cost}(h_\theta(x), y) = -y \log(h_\theta(x)) - (1 - y) \log(1 - h_\theta(x)).$$

So

$$J(\theta) = -\frac{1}{m} \sum_{i=1}^m \left[y^{(i)} \log(h_\theta(x^{(i)})) + (1 - y^{(i)}) \log(1 - h_\theta(x^{(i)})) \right].$$

To fit parameter θ : $\min_\theta J(\theta)$.

1.4 Optimization

Gradient Descent

$$\frac{\partial}{\partial \theta_j} J(\theta) = \sum_{i=1}^m (h_\theta(x^{(i)}) - y^{(i)}) x_j^{(i)}.$$

This looks identical to linear regression.

Other Optimization Algorithms

- Conjugate Gradient
- BFGS
- L-BFGS

Advantages:

- No need to pick learning rate α .
- Often faster than gradient descent.

1.5 Multiclass Classification

One-vs-rest

$$h_{\theta}^{(i)}(x) = P(y = i \mid x; \theta) \quad i = 1, 2, 3.$$

Train a logistic regression classifier for each i to predict the probability that $y = i$. On a new input x , pick class $i = \operatorname{argmax}_i h_{\theta}^{(i)}(x)$.

Chapter 2

Dimensionality Reduction

2.1 Motivations

- Data compression.
- Data visualization.

2.2 Principal Component Analysis

PCA is trying to find a lower dimensional surface onto which to project the data so as to minimize squared projection error.

Principal component analysis vs. linear regression:

- Linear regression tries to minimize residuals. PCA tries to minimize projection error.
- In linear regression, we try to predict one feature with other features. In PCA, all features are equivalent.

Algorithm: (from n dimensions to k dimensions)

- Preprocessing: mean normalization and feature scaling (standardization).
- Compute covariance matrix

$$\Sigma = \frac{1}{m} \sum_{i=1}^m (x^{(i)})(x^{(i)})^T.$$

- Compute the eigenvalues of Σ .

$$\Sigma = USV.$$

Let U_{reduce} denote the first k columns of U . Then $z = U_{reduce}^T x$.

Choosing k :

- Average squared projection error:

$$\frac{1}{m} \sum_{i=1}^m \|x^{(i)} - x_{approx}^{(i)}\|^2.$$

- Total variation in the data:

$$\frac{1}{m} \sum_{i=1}^m \|x^{(i)}\|^2.$$

- Typically, we choose k to be the smallest value so that

$$\frac{\text{average squared projection error}}{\text{total variation}} < 0.01,$$

i.e. 99% of variance is retained.

- The above ratio can be computed in an easier way. Say

$$S = \begin{bmatrix} s_{11} & & O \\ & \ddots & \\ O & & s_{nn} \end{bmatrix}.$$

Then

$$\frac{\text{average squared projection error}}{\text{total variation}} = 1 - \frac{\sum_{i=1}^k s_{ii}}{\sum_{i=1}^n s_{ii}}.$$

So we can start with $k = 1$ and increase k and check whether

$$\frac{\sum_{i=1}^k s_{ii}}{\sum_{i=1}^n s_{ii}} > 0.99.$$