# Introduction to Ruby on Rails

### **Ruby on Rails**

- **Ruby on Rails** (RoR or Rails) is a web framework written in Ruby.
- RoR was developed by the Danish developer David Heinemeier Hansson, and its current version is 7.0.
- It's a **server-side** framework, which implements the Model-View-Controller (**MVC**) pattern.
- RoR provides a default directory structure to manage the database, web pages and other assets.
- It relies on known **patterns**, such as, Convention over Configuration, Don't repeat yourself (DRY) and Active Record.
- RoR influenced many web frameworks, like Grails, Laravel, CakePHP AND Django.
- It is used in **sites** like GitHub, Twitch, Shopify and Airbnb.

### **Setting up the environment**

- **Ruby** should be installed (check using ruby -v in a CLI).
- A DBMS. SQLite3 is recommended for learning and testing purposes.
  - 1. Download your OS's version from here: <a href="https://www.sqlite.org/download.html">https://www.sqlite.org/download.html</a>
  - 2. Follow the instructions for your OS found here: <a href="https://www.tutorialspoint.com/sqlite/sqlite\_installation.htm">https://www.tutorialspoint.com/sqlite/sqlite\_installation.htm</a>
  - 3. In Windows, it will consist in:
    - Downloading SQLite DLL and command line tools.
    - Unzipping all of it in a newly created folder.
    - Adding this folder to the PATH environment variable, as you'll find out here: <a href="https://www.architectryan.com/2018/03/17/add-to-the-path-on-windows-10/">https://www.architectryan.com/2018/03/17/add-to-the-path-on-windows-10/</a>
  - 4. You can check using SQLite3 --version in a CLI.
- Install RoR using gem install rails in a CLI. Then, you can check using rails --version

### **Creating an app**

- You can perform many tasks using the rails command and its several instructions.
- You can create a new app using:

```
rails new [app name]
```

- The command above will create a directory structure detailed here: <a href="https://guides.rubyonrails.org/getting\_started.html">https://guides.rubyonrails.org/getting\_started.html</a>
- Once you are situated in the directory created, you can tun the app using the command:
  - ruby bin/rails server in Windows.
  - bin/rails server otherwise.
- You can stop the server using *Control+C*.

# **Basic Components in Ruby on Rails**

- Basic components in Ruby on Rails are routes, controllers, actions and views.
- A **route** maps a request to a controller action. It's a rule written in a Ruby DSL.
- A controller action performs the necessary work to handle the request, it includes preparing data for a view. The controller is a Ruby class whose public methods are actions.
- A view prepares the resulting data in a desired format. Views are templates, written using HTML and embedded Ruby.

# Creating a "Hello, World"

1. Add a route to the config/routes.rb file:

```
get "/products", to: "products#index"
```

This means that GET products requests map to the index action within ProductsController.

2. Create the appropriate controller and view (but not the route) using the following command:

```
ruby bin/rails generate controller Products index --skip-routes
```

- 3. It will create, among other files, the controller (product\_controllers.rb) and the view (index.html.erb).
- 4. You can invoke the view from the controller. If not, the framework will invoke a matching one. You can now edit both files.

### **Creating a Model**

- As we have seen, RoR is based on the MVC pattern, where the Model manages the data of the application.
- Just as with controllers, we can create a model using:

```
ruby bin/rails generate model Product name:string description:text
```

- You can see on screen what files were created. However, we'll focus on the model (product.rb) and the migration (\_create\_products.rb) files. The table created will have its explicit fields, an id field and its timestamps.
- We should, also, run the migration using: ruby bin/rails db:migrate
- In Ruby, as in many similar frameworks, we use **migrations** to alter the structure of the application's database.

### Interacting with the Model Using the Console

- We can run the console using: ruby bin/rails console
- Using the console, we can create a product, using: a \_product = Product.new(name: "Xbox", description: "A good gaming console!")
- Then, we can save it to the database, using: a product.save
- We can get all the products in the database, using: Product.all
- Also, we can get a product given its id, using: Product.find(1)
- This can be useful to automate database population.

### **Listing from a Model**

- In RoR, we can **list**, easily, the items from a model. In this case, we'll list all the items from the products model.
- Firstly, we get all the items from the **model**, in the corresponding **action** of the desired **controller**. In our case, we add the following line in the **index** action of the **products** controller: <code>@products = Product.all</code>
- Then, we can iterate over the **instance variable** products in the **index** view, resulting in the products list:

• Now, we can review the whole MVC pattern as implemented by Ruby on Rails.

# **Using a Route Parameter (1/2)**

- For a controller, it is common to receive requests with **parameters**. They usually include some info that is important within the request.
- For instance, we'll enable to show the information of just one product receiving its id as a parameter.
- Firstly, we'll add the following route in the corresponding file: get "/products/:id", to: "products#show"
- Then, we'll add the corresponding action to the products controller (below the index one).

```
def show
  @product = Product.find(params[:id])
end
```

### Using a Route Parameter (2/2)

• Now, let's create a view (show.html.erb) with the content that you want, but including the following lines:

```
<h1><%= @product.name %></h1>
<%= @product.description %>
```

• Finally, we'll modify the index view to include the link to the other view:

### **Towards a CRUD Using Ruby on Rails**

- Many use cases while developing a web application comprise CRUDs. RoR offers some tolos to
  ease their development.
- Since creating a CRUD implies creating several routes, RoR implements resourceful routing. It's
  about defining a resource, which will automatically create the routes needed.
- To check this, firstly run this command in the CLI rails routes, and among others, we'll see just our two routes.
- Now, replace the two existing routes for these lines of code, the index and a resource:

```
root "products#index"
resources :products
```

Then, let's inspect the routes again.

#### Some Helpers Enabled by Resources

- Resources define some helpers to get the right paths easily given a model.
- One of those helpers is path, which will give us the proper path for a given product:

• The other one is link to, which will generate a link to the path of the model in its second parameter, with the text in its first one:

#### **Useful Resources**

- MVC Pattern (English): <a href="https://www.freecodecamp.org/news/the-model-view-controller-pattern-mvc-architecture-and-frameworks-explained/">https://www.freecodecamp.org/news/the-model-view-controller-pattern-mvc-architecture-and-frameworks-explained/</a>
- MVC Pattern (Spanish): <a href="https://codigofacilito.com/articulos/mvc-model-view-controller-explicado">https://codigofacilito.com/articulos/mvc-model-view-controller-explicado</a>
- Convention over Configuration: <a href="https://senthilnayagan.medium.com/convention-over-configuration-d17930f712de">https://senthilnayagan.medium.com/convention-over-configuration-d17930f712de</a>
- Active Record Basics (Ruby on Rails): <a href="https://guides.rubyonrails.org/active\_record\_basics.html">https://guides.rubyonrails.org/active\_record\_basics.html</a>
- Getting Started with Rails: <a href="https://guides.rubyonrails.org/getting\_started.html">https://guides.rubyonrails.org/getting\_started.html</a>
- Ruby on Rails Controllers Overview: <a href="https://guides.rubyonrails.org/action\_controller\_overview.html">https://guides.rubyonrails.org/action\_controller\_overview.html</a>
- Rails Routing from the Outside In: <a href="https://guides.rubyonrails.org/routing.html">https://guides.rubyonrails.org/routing.html</a>
- Action View Overview: <a href="https://guides.rubyonrails.org/action-view-overview.html">https://guides.rubyonrails.org/action-view-overview.html</a>
- Learn Ruby on Rails Full Course: <a href="https://www.youtube.com/watch?v=fmyvWz5TUWg&ab\_channel=freeCodeCamp.org">https://www.youtube.com/watch?v=fmyvWz5TUWg&ab\_channel=freeCodeCamp.org</a>
- Curso Ruby on Rails en Español: <u>https://www.youtube.com/watch?v=0Qj3LUxx3Zg&list=PLP06kydD\_xaUS6plnsdonHa5ySbPx1PrP&ab\_channel=aprendev</u>

