MyAccounting System — Database Data Model & Data Dictionary

Database: `myaccounting`
Server: `localhost`
Engine: Microsoft SQL Server
Authentication: Windows Trusted Connection (SSPI)
Driver: ODBC Driver 17 for SQL Server

Table of Contents

1. Entity-Relationship Overview
2. Table Inventory
3. Data Dictionary
    - 3.1 glmaster
    - 3.2 gldetails
    - 3.3 glsummary
    - 3.4 journalmaster
    - 3.5 journaldetails
    - 3.6 invoicemaster
    - 3.7 invoicedetails
    - 3.8 invoice_attachments
    - 3.9 cashreceipts
    - 3.10 customers
    - 3.11 inventory
    - 3.12 projects
    - 3.13 salesmen
    - 3.14 taxcodes
    - 3.15 taxcodedetail
    - 3.16 payment_terms
    - 3.17 country
    - 3.18 provinces
    - 3.19 timesheetmaster
    - 3.20 timesheetdetail
    - 3.21 timesheetworkitem
    - 3.22 users
    - 3.23 useraccess
    - 3.24 settings
    - 3.25 passwords
    - 3.26 todolist
4. Foreign Key Relationships
5. Settings Key Reference
6. Enumerated Value Reference

---

1. Entity-Relationship Overview

```
country ──< provinces

glmaster ──< gldetails

journalmaster ──< journaldetails

invoicemaster ──< invoicedetails
invoicemaster ──< invoice_attachments

customers ──< invoicemaster
customers ──< cashreceipts
customers ──< timesheetmaster

salesmen ──< invoicemaster
salesmen ──< timesheetmaster

inventory ──< invoicedetails (via item_code)

projects ──< invoicemaster

taxcodes ──< taxcodedetail
taxcodes ──< customers (tax_code)

payment_terms ──< customers (payment_terms_id)

users ──< useraccess
users ──< passwords

timesheetmaster ──< timesheetdetail
timesheetdetail ──< timesheetworkitem
```

2. Table Inventory

#	Table	Category	Description
1	`glmaster`	General Ledger	Chart of accounts
2	`gldetails`	General Ledger	Posted transaction lines
3	`glsummary`	General Ledger	Aggregate balances per account
4	`journalmaster`	Journal	Journal entry headers
5	`journaldetails`	Journal	Journal entry debit/credit lines
6	`invoicemaster`	Accounts Receivable	Invoice headers
7	`invoicedetails`	Accounts Receivable	Invoice line items
8	`invoice_attachments`	Accounts Receivable	File attachments per invoice
9	`cashreceipts`	Accounts Receivable	Cash receipt records
10	`customers`	Master Data	Customer / client records
11	`inventory`	Master Data	Products and services catalog
12	`projects`	Master Data	Project codes
13	`salesmen`	Master Data	Consultants / salespeople
14	`taxcodes`	Reference	Tax code definitions
15	`taxcodedetail`	Reference	Tax component breakdown per code
16	`payment_terms`	Reference	Named payment terms
17	`country`	Reference	Country codes and currencies
18	`provinces`	Reference	Provinces and states per country
19	`timesheetmaster`	Timesheets	Timesheet headers (per consultant/month)
20	`timesheetdetail`	Timesheets	Daily time entries
21	`timesheetworkitem`	Timesheets	Work items per daily entry
22	`users`	Security	Application user accounts
23	`useraccess`	Security	Per-module access levels
24	`settings`	System	Application configuration key-value pairs
25	`passwords`	Security	Encrypted credential vault
26	`todolist`	System	To-do task list

3. Data Dictionary

3.1 `glmaster` — General Ledger Chart of Accounts

Stores the chart of accounts. Each row represents one GL account.

Column	Data Type	Nullable	Key	Default	Description
`account_number`	NVARCHAR(20)	NOT NULL	PK	—	Unique account identifier (e.g., `1000`, `4100`)
`account_name`	NVARCHAR(200)	NULL	—	—	Descriptive name of the account
`opening_balance`	DECIMAL(18,2)	NOT NULL	—	`0`	Opening balance at fiscal year start
`balance`	DECIMAL(18,2)	NULL	—	—	Cached running balance (informational)
`balance_type`	NVARCHAR(5)	NULL	—	—	Normal balance side: `Dr` (debit) or `Cr` (credit)

Notes:

- Account number ranges used by reports: `1000–3999` = Balance Sheet accounts; `4000–9999` = Income Statement accounts.
- The `balance` column is a cached value; the authoritative balance is computed from `opening_balance` + `gldetails` (debit/credit sums).

3.2 `gldetails` — General Ledger Transaction Lines

Records every posted transaction line in the general ledger. Each GL posting (from journal entries, invoices, cash receipts) inserts one or more rows here.

Column	Data Type	Nullable	Key	Default	Description
`detail_id`	INT	NOT NULL	PK (Identity)	—	Surrogate primary key
`account_number`	NVARCHAR(20)	NULL	FK → glmaster	—	GL account this line affects
`trans_date`	DATE	NULL	—	—	Transaction date
`description`	NVARCHAR(200)	NULL	—	—	Line description / narrative
`source_number`	NVARCHAR(50)	NULL	—	—	Source document number (invoice, receipt, journal)
`trans_no`	NVARCHAR(20)	NULL	—	—	Transaction / batch number
`debits`	DECIMAL(18,2)	NULL	—	—	Debit amount for this line
`credits`	DECIMAL(18,2)	NULL	—	—	Credit amount for this line
`balance_type`	NVARCHAR(5)	NULL	—	—	Normal balance side inherited from `glmaster`: `Dr` or `Cr`

Notes:

- Exactly one of `debits` or `credits` will be non-zero per line in a balanced entry.
- The `source_number` links back to the originating document (invoice_number, receipt_number, entry_number).

3.3 `glsummary` — General Ledger Summary

Holds pre-aggregated balances per account. Populated by import utilities; not updated in real time by the application.

Column	Data Type	Nullable	Key	Default	Description
`account_number`	NVARCHAR(20)	NOT NULL	PK	—	GL account number
`opening_balance`	DECIMAL(18,2)	NULL	—	—	Opening balance at import
`total_debits`	DECIMAL(18,2)	NULL	—	—	Total debits posted
`total_credits`	DECIMAL(18,2)	NULL	—	—	Total credits posted
`balance`	DECIMAL(18,2)	NULL	—	—	Net balance
`balance_type`	NVARCHAR(5)	NULL	—	—	Normal balance side: `Dr` or `Cr`

3.4 `journalmaster` — Journal Entry Header

Represents the header of a manual journal entry.

Column	Data Type	Nullable	Key	Default	Description
`entry_id`	INT	NOT NULL	PK (Identity)	—	Surrogate primary key
`entry_number`	NVARCHAR(20)	NOT NULL	—	—	User-facing journal entry number (e.g., `JE-1001`)
`entry_date`	DATE	NOT NULL	—	—	Date of the journal entry
`description`	NVARCHAR(200)	NULL	—	—	Entry-level description / memo
`reference`	NVARCHAR(50)	NULL	—	—	External reference (cheque number, contract, etc.)
`status`	NVARCHAR(20)	NOT NULL	—	`'Draft'`	Workflow status: `Draft` or `Posted`
`created_date`	DATETIME	NULL	—	`GETDATE()`	Timestamp when the entry was created
`posted_date`	DATETIME	NULL	—	NULL	Timestamp when the entry was posted to the GL

3.5 `journaldetails` — Journal Entry Lines

Holds the individual debit and credit lines for each journal entry.

Column	Data Type	Nullable	Key	Default	Description
`line_id`	INT	NOT NULL	PK (Identity)	—	Surrogate primary key
`entry_id`	INT	NOT NULL	FK → journalmaster	—	Parent journal entry
`account_number`	NVARCHAR(20)	NULL	—	—	GL account to debit or credit
`description`	NVARCHAR(200)	NULL	—	—	Line-level description
`debit`	DECIMAL(18,2)	NOT NULL	—	`0`	Debit amount (0 if credit line)
`credit`	DECIMAL(18,2)	NOT NULL	—	`0`	Credit amount (0 if debit line)

Constraint: Sum of `debit` must equal sum of `credit` across all lines with the same `entry_id` before the entry can be posted.

3.6 `invoicemaster` — Invoice Header

Stores the header information for each customer invoice.

Column	Data Type	Nullable	Key	Default	Description
`invoice_id`	INT	NOT NULL	PK (Identity)	—	Surrogate primary key
`invoice_number`	NVARCHAR(50)	NULL	—	—	User-facing invoice number (e.g., `INV-1001`)
`invoice_date`	DATE	NULL	—	—	Invoice issuance date
`customer_id`	INT	NULL	FK → customers	—	Billed customer
`project_id`	INT	NULL	FK → projects	—	Associated project (optional)
`salesman_id`	INT	NULL	FK → salesmen	—	Issuing consultant (applied via migration)
`total_amount`	DECIMAL(18,2)	NULL	—	—	Invoice subtotal before tax
`tax_amount`	DECIMAL(18,2)	NULL	—	—	Total tax amount
`status`	NVARCHAR(50)	NULL	—	—	Workflow status: `Draft`, `Posted`, `Paid`, `Void`
`comments`	NVARCHAR(1000)	NULL	—	NULL	Free-text comments printed on the invoice

---

3.7 `invoicedetails` — Invoice Line Items

Holds individual line items for each invoice.

Column	Data Type	Nullable	Key	Default	Description
`detail_id`	INT	NOT NULL	PK (Identity)	—	Surrogate primary key
`invoice_id`	INT	NULL	FK → invoicemaster	—	Parent invoice
`item_code`	NVARCHAR(100)	NULL	—	—	Inventory item code
`description`	NVARCHAR(200)	NULL	—	—	Line description
`quantity`	DECIMAL(18,4)	NULL	—	—	Quantity billed
`unit_price`	DECIMAL(18,2)	NULL	—	—	Unit price
`amount`	DECIMAL(18,2)	NULL	—	—	Extended amount (`quantity × unit_price`)
`line_type`	NVARCHAR(20)	NOT NULL	—	`'item'`	Line type: `item`, `header`, or `comment`

Notes:

- `line_type = 'header'`: printed as a bold section heading; quantity/price ignored.
- `line_type = 'comment'`: printed as a plain text note; quantity/price ignored.
- `line_type = 'item'`: standard billable line.

3.8 `invoice_attachments` — Invoice File Attachments

Links external file attachments to invoices (stored as file-system paths).

Column	Data Type	Nullable	Key	Default	Description
`attachment_id`	INT	NOT NULL	PK (Identity)	—	Surrogate primary key
`invoice_id`	INT	NOT NULL	FK → invoicemaster (CASCADE DELETE)	—	Parent invoice
`filename`	NVARCHAR(260)	NOT NULL	—	—	File name (derived from `filepath`)
`filepath`	NVARCHAR(1000)	NOT NULL	—	—	Absolute file-system path
`added_date`	DATE	NOT NULL	—	`CAST(GETDATE() AS DATE)`	Date the attachment was linked

3.9 `cashreceipts` — Cash Receipts

Records customer cash/cheque payments received.

Column	Data Type	Nullable	Key	Default	Description
`receipt_id`	INT	NOT NULL	PK (Identity)	—	Surrogate primary key
`receipt_number`	NVARCHAR(50)	NOT NULL	—	—	User-facing receipt number (e.g., `CR-1001`)
`receipt_date`	DATE	NOT NULL	—	—	Date payment was received
`customer_id`	INT	NULL	FK → customers	—	Paying customer
`invoice_id`	INT	NULL	FK → invoicemaster	—	Invoice being paid (optional)
`amount`	DECIMAL(18,2)	NOT NULL	—	`0`	Amount received
`bank_account`	NVARCHAR(20)	NULL	—	—	GL account number for the bank/cash account (DR)
`ar_account`	NVARCHAR(20)	NULL	—	—	GL account number for Accounts Receivable (CR)
`memo`	NVARCHAR(200)	NULL	—	—	Payment note or cheque number
`status`	NVARCHAR(20)	NOT NULL	—	`'Draft'`	Workflow status: `Draft` or `Posted`

3.10 `customers` — Customer Master

Stores all customer and client records. Columns have been extended by migrations over time.

Column	Data Type	Nullable	Key	Default	Description
`customer_id`	INT	NOT NULL	PK (Identity)	—	Surrogate primary key
`company`	NVARCHAR(100)	NULL	—	—	Company / organization name
`contact`	NVARCHAR(100)	NULL	—	—	Primary contact name
`address1`	NVARCHAR(200)	NULL	—	—	Billing street address line 1
`address2`	NVARCHAR(200)	NULL	—	—	Billing street address line 2
`city`	NVARCHAR(100)	NULL	—	—	Billing city
`province`	NVARCHAR(100)	NULL	—	—	Billing province/state
`country`	NVARCHAR(100)	NULL	—	—	Billing country
`postal`	NVARCHAR(20)	NULL	—	—	Billing postal/zip code
`phone`	NVARCHAR(30)	NULL	—	—	Main phone number
`cell`	NVARCHAR(30)	NULL	—	—	Mobile phone number
`fax`	NVARCHAR(30)	NULL	—	—	Fax number
`email`	NVARCHAR(200)	NULL	—	—	Primary email address
`website`	NVARCHAR(200)	NULL	—	—	Website URL
`currency`	NVARCHAR(10)	NULL	—	—	Default billing currency (e.g., `CAD`)
`customer_type`	NVARCHAR(50)	NULL	—	—	Customer classification
`salesman_id`	INT	NULL	FK → salesmen	—	Assigned consultant/salesman
`ship_address1`	NVARCHAR(200)	NULL	—	—	Shipping address line 1
`ship_address2`	NVARCHAR(200)	NULL	—	—	Shipping address line 2
`ship_city`	NVARCHAR(100)	NULL	—	—	Shipping city

Column	Data Type	Nullable	Key	Default	Description
`ship_prov`	NVARCHAR(100)	NULL	—	—	Shipping province/state
`ship_pcodezip`	NVARCHAR(20)	NULL	—	—	Shipping postal/zip code
`ship_country`	NVARCHAR(100)	NULL	—	—	Shipping country
`revenue_account`	NVARCHAR(20)	NULL	—	—	Default GL revenue account for this customer
`tax_code`	NVARCHAR(10)	NULL	FK → taxcodes	—	Default tax code for invoicing
`credit_limit`	DECIMAL(18,2)	NULL	—	—	Credit limit (informational)
`payment_terms_id`	INT	NULL	FK → payment_terms	—	Default payment terms
`notes`	NVARCHAR(MAX)	NULL	—	—	Free-form customer notes
`language`	VARCHAR(2)	NOT NULL	—	`'en'`	Preferred invoice language: `en` or `fr`
`preferred_delivery`	NVARCHAR(50)	NULL	—	—	Preferred invoice delivery method (e.g., `email`)
`manager_name`	NVARCHAR(100)	NULL	—	—	Client manager name (for timesheet email)
`manager_phone`	NVARCHAR(30)	NULL	—	—	Client manager phone
`manager_email`	NVARCHAR(200)	NULL	—	—	Client manager email address

3.11 `inventory` — Products & Services

Catalog of billable items used when creating invoice line items.

Column	Data Type	Nullable	Key	Default	Description
`inventory_id`	INT	NOT NULL	PK (Identity)	—	Surrogate primary key
`item_code`	NVARCHAR(100)	NULL	—	—	Short item code / SKU
`description`	NVARCHAR(200)	NULL	—	—	Item description
`item_type`	NVARCHAR(50)	NULL	—	—	Type: `Service`, `Product`, etc.
`unit`	NVARCHAR(50)	NULL	—	—	Unit of measure (e.g., `hr`, `each`)
`price`	DECIMAL(18,2)	NULL	—	—	Default selling price
`cost`	DECIMAL(18,2)	NULL	—	—	Cost price (informational)
`account`	NVARCHAR(20)	NULL	—	—	Default GL revenue account for this item

---

3.12 `projects` — Project Codes

Simple project reference table used to associate invoices with projects.

Column	Data Type	Nullable	Key	Default	Description
`project_id`	INT	NOT NULL	PK (Identity)	—	Surrogate primary key
`project_code`	NVARCHAR(100)	NULL	—	—	Project identifier / name
`start_date`	DATE	NULL	—	—	Project start date

3.13 `salesmen` — Consultants

Stores consultant profiles. Also stores Google OAuth tokens for email integration.

Column	Data Type	Nullable	Key	Default	Description
`salesman_id`	INT	NOT NULL	PK (Identity)	—	Surrogate primary key
`salesman_name`	NVARCHAR(50)	NOT NULL	—	—	Consultant's full name
`signature_image`	NVARCHAR(500)	NULL	—	NULL	File path to signature image for PDF documents
`google_email`	NVARCHAR(200)	NULL	—	NULL	Google account email address
`google_client_id`	NVARCHAR(500)	NULL	—	NULL	Google OAuth 2.0 client ID
`google_client_secret`	NVARCHAR(500)	NULL	—	NULL	Google OAuth 2.0 client secret
`google_refresh_token`	NVARCHAR(2000)	NULL	—	NULL	OAuth 2.0 long-lived refresh token
`google_access_token`	NVARCHAR(2000)	NULL	—	NULL	OAuth 2.0 short-lived access token (cached)
`google_token_expiry`	DATETIME	NULL	—	NULL	Expiry timestamp of the cached access token

Security note: Google tokens are stored in SQL Server and protected by the database's Windows access controls. Do not grant database access to unauthorized users.

3.14 `taxcodes` — Tax Code Master

Defines named tax codes used on invoices.

Column	Data Type	Nullable	Key	Default	Description
`tax_code`	NVARCHAR(10)	NOT NULL	PK	—	Short tax code identifier (e.g., `HST`, `GST+QST`)
`tax_name`	NVARCHAR(100)	NULL	—	—	Descriptive name
`tax_rate`	DECIMAL(10,4)	NOT NULL	—	`0`	Aggregate tax rate (sum of components, informational)
`tax_account`	NVARCHAR(20)	NULL	—	NULL	Default GL tax payable account

---

3.15 `taxcodedetail` — Tax Code Components

Breaks a tax code into individual component rates (e.g., GST 5% + QST 9.975%).

Column	Data Type	Nullable	Key	Default	Description
`tax_code`	NVARCHAR(10)	NOT NULL	PK (composite), FK → taxcodes	—	Parent tax code
`seq`	INT	NOT NULL	PK (composite)	—	Component sequence / order
`detail_name`	NVARCHAR(100)	NOT NULL	—	—	Component name (e.g., `GST`, `QST`)
`tax_rate`	DECIMAL(10,4)	NOT NULL	—	`0`	Individual component rate
`tax_account`	NVARCHAR(20)	NULL	—	NULL	GL account for this tax component

---

3.16 `payment_terms` — Payment Terms

Lookup table for named payment terms.

Column	Data Type	Nullable	Key	Default	Description
`payment_terms_id`	INT	NOT NULL	PK (Identity)	—	Surrogate primary key
`payment_terms_name`	NVARCHAR(50)	NOT NULL	—	—	Description (e.g., `Net 30`, `Due on Receipt`)

3.17 `country` — Country Reference

Reference table seeded with 20 countries.

Column	Data Type	Nullable	Key	Default	Description
`code`	NVARCHAR(3)	NOT NULL	PK	—	ISO 2-letter country code (e.g., `CA`, `US`)
`name`	NVARCHAR(100)	NOT NULL	—	—	Country name
`currency`	NVARCHAR(10)	NOT NULL	—	—	Default currency code (e.g., `CAD`, `USD`)

Seeded countries: CA, US, GB, AU, FR, DE, MX, JP, CN, IN, BR, IT, ES, NL, BE, CH, SE, NO, DK, NZ.

3.18 `provinces` — Province / State Reference

Provinces and states keyed by country. Seeded with all Canadian provinces/territories, US states/DC, Australian states, and UK nations.

Column	Data Type	Nullable	Key	Default	Description
`country_code`	NVARCHAR(3)	NOT NULL	PK (composite)	—	FK → country.code
`prov_code`	NVARCHAR(10)	NOT NULL	PK (composite)	—	Province/state abbreviation
`prov_name`	NVARCHAR(100)	NOT NULL	—	—	Full province/state name

3.19 `timesheetmaster` — Timesheet Header

One row per consultant per calendar month.

Column	Data Type	Nullable	Key	Default	Description
`ts_id`	INT	NOT NULL	PK (Identity)	—	Surrogate primary key
`salesman_id`	INT	NOT NULL	FK → salesmen	—	Owning consultant
`ts_year`	INT	NOT NULL	—	—	Calendar year (e.g., `2026`)
`ts_month`	INT	NOT NULL	—	—	Calendar month (1–12)
`client`	NVARCHAR(200)	NULL	—	NULL	Client name (free text, copied to PDF)
`project`	NVARCHAR(200)	NULL	—	NULL	Project name (free text, copied to PDF)
`customer_id`	INT	NULL	FK → customers	—	Linked customer (used for manager email)
`status`	NVARCHAR(20)	NOT NULL	—	`'Draft'`	Workflow status: `Draft`, `Submitted`, `Approved`
`notes`	NVARCHAR(MAX)	NULL	—	NULL	Free-form timesheet notes
`created_date`	DATE	NOT NULL	—	`CAST(GETDATE() AS DATE)`	Date record was created

Unique constraint: `(salesman_id, ts_year, ts_month)` — one timesheet per consultant per month.

3.20 `timesheetdetail` — Timesheet Daily Lines

One row per working day within a timesheet.

Column	Data Type	Nullable	Key	Default	Description
`line_id`	INT	NOT NULL	PK (Identity)	—	Surrogate primary key
`ts_id`	INT	NOT NULL	FK → timesheetmaster (CASCADE DELETE)	—	Parent timesheet
`work_date`	DATE	NOT NULL	—	—	Calendar date of this row
`am_start`	NVARCHAR(5)	NULL	—	NULL	AM session start time (HH:MM, 24-h)
`am_end`	NVARCHAR(5)	NULL	—	NULL	AM session end time
`pm_start`	NVARCHAR(5)	NULL	—	NULL	PM session start time
`pm_end`	NVARCHAR(5)	NULL	—	NULL	PM session end time
`other_start`	NVARCHAR(5)	NULL	—	NULL	Other/evening session start time
`other_end`	NVARCHAR(5)	NULL	—	NULL	Other/evening session end time
`total_hours`	DECIMAL(5,2)	NOT NULL	—	`0`	Total hours for this day (sum of work items)

3.21 `timesheetworkitem` — Work Items Per Day

Holds the individual work-item/task lines for each daily timesheet entry. Multiple work items can exist per day.

Column	Data Type	Nullable	Key	Default	Description
`item_id`	INT	NOT NULL	PK (Identity)	—	Surrogate primary key
`line_id`	INT	NOT NULL	FK → timesheetdetail (CASCADE DELETE)	—	Parent daily line
`sort_order`	INT	NOT NULL	—	`0`	Display order within the day
`description`	NVARCHAR(500)	NULL	—	NULL	Work item description / task narrative
`devops_work_item`	NVARCHAR(200)	NULL	—	NULL	Azure DevOps work item reference (e.g., `#12345`)
`hours`	DECIMAL(5,2)	NOT NULL	—	`0`	Hours for this specific work item

---

3.22 `users` — Application Users

Stores the application's user accounts for authentication.

Column	Data Type	Nullable	Key	Default	Description
`user_id`	INT	NOT NULL	PK (Identity)	—	Surrogate primary key
`username`	NVARCHAR(50)	NOT NULL	UNIQUE	—	Login username
`userfullname`	NVARCHAR(100)	NOT NULL	—	`''`	Display name
`password`	NVARCHAR(255)	NOT NULL	—	—	Hashed password: `<salt_hex>:<hash_hex>` (PBKDF2-SHA256, 260k iterations)
`email`	NVARCHAR(100)	NULL	—	NULL	User's email address
`role`	NVARCHAR(20)	NOT NULL	—	`'accountant'`	Role: `admin` or `accountant`
`is_active`	BIT	NOT NULL	—	`1`	`1` = active account; `0` = disabled

Default seeded user: username `admin`, password `admin`, role `admin` (created on first startup when no users exist).

3.23 `useraccess` — Module Access Control

Defines per-module access levels for non-admin users.

Column	Data Type	Nullable	Key	Default	Description
`access_id`	INT	NOT NULL	PK (Identity)	—	Surrogate primary key
`user_id`	INT	NOT NULL	FK → users (CASCADE DELETE)	—	Owning user
`modulename`	NVARCHAR(50)	NOT NULL	—	—	Module name (see enumerated values)
`access_level`	NVARCHAR(20)	NOT NULL	—	`'view only'`	Access level: `full` or `view only`

Unique constraint: `(user_id, modulename)`.

Module names: `GL Chart of accounts`, `journal entry`, `reports`, `configuration`, `invoicing`, `cash receipts`, `timesheets`.

3.24 `settings` — Application Settings

Key-value store for all application configuration. One row per setting.

Column	Data Type	Nullable	Key	Default	Description
`setting_key`	NVARCHAR(100)	NOT NULL	PK	—	Setting identifier
`setting_value`	NVARCHAR(500)	NULL	—	NULL	Setting value (stored as text)

See Section 5 for a full list of recognized setting keys.

3.25 `passwords` — Encrypted Password Vault

Stores application credentials encrypted with Fernet symmetric encryption.

Column	Data Type	Nullable	Key	Default	Description
`password_id`	INT	NOT NULL	PK (Identity)	—	Surrogate primary key
`user_id`	INT	NOT NULL	FK → users (CASCADE DELETE)	`1`	Owning user
`password_name`	NVARCHAR(100)	NOT NULL	—	—	Entry label / name
`purpose`	NVARCHAR(MAX)	NULL	—	NULL	Description of the credential's use
`password_enc`	NVARCHAR(MAX)	NOT NULL	—	—	Fernet-encrypted password token
`created_date`	DATETIME	NOT NULL	—	`GETDATE()`	Creation timestamp
`modified_date`	DATETIME	NOT NULL	—	`GETDATE()`	Last modification timestamp

Encryption: Fernet (AES-128-CBC + HMAC-SHA256). Key stored in `pm.key` file in the application directory.

3.26 `todolist` — To-Do Items

Stores user to-do tasks displayed on the dashboard.

Column	Data Type	Nullable	Key	Default	Description
`todo_id`	INT	NOT NULL	PK (Identity)	—	Surrogate primary key
`title`	NVARCHAR(200)	NOT NULL	—	—	Task title / summary
`notes`	NVARCHAR(MAX)	NULL	—	NULL	Detailed notes
`due_date`	DATE	NULL	—	NULL	Optional due date
`priority`	NVARCHAR(10)	NOT NULL	—	`'Normal'`	Priority level: `Low`, `Normal`, `High`
`status`	NVARCHAR(20)	NOT NULL	—	`'Open'`	Status: `Open` or `Done`
`created_date`	DATE	NOT NULL	—	`CAST(GETDATE() AS DATE)`	Creation date

---

4. Foreign Key Relationships

Child Table	Child Column	Parent Table	Parent Column	On Delete
`journaldetails`	`entry_id`	`journalmaster`	`entry_id`	RESTRICT
`invoicedetails`	`invoice_id`	`invoicemaster`	`invoice_id`	RESTRICT
`invoice_attachments`	`invoice_id`	`invoicemaster`	`invoice_id`	CASCADE
`timesheetmaster`	`salesman_id`	`salesmen`	`salesman_id`	RESTRICT
`timesheetdetail`	`ts_id`	`timesheetmaster`	`ts_id`	CASCADE
`timesheetworkitem`	`line_id`	`timesheetdetail`	`line_id`	CASCADE
`taxcodedetail`	`tax_code`	`taxcodes`	`tax_code`	RESTRICT
`useraccess`	`user_id`	`users`	`user_id`	CASCADE
`passwords`	`user_id`	`users`	`user_id`	CASCADE

---

5. Settings Key Reference

All keys are stored in the `settings` table with `setting_value` as NVARCHAR(500).

Company Information

Key	Default	Description
`company_name`	`My Company`	Company legal name
`address1`	*(empty)*	Street address line 1
`address2`	*(empty)*	Street address line 2
`city`	*(empty)*	City
`province`	*(empty)*	Province/state
`postal`	*(empty)*	Postal/zip code
`country`	`Canada`	Country
`phone`	*(empty)*	Phone number
`fax`	*(empty)*	Fax number
`email`	*(empty)*	Company email
`website`	*(empty)*	Company website
`logo_path`	*(empty)*	File path to company logo image

Fiscal Year & Accounting

Key	Default	Description
`fiscal_year_start`	`2024-01-01`	Fiscal year start date (YYYY-MM-DD)
`fiscal_year_end`	`2024-12-31`	Fiscal year end date (YYYY-MM-DD)
`currency`	`CAD`	Default currency code
`tax_rate`	`13.00`	Default tax rate percentage
`ar_account`	*(empty)*	Default Accounts Receivable GL account
`revenue_account`	*(empty)*	Default Revenue GL account
`tax_account`	*(empty)*	Default Tax Payable GL account
`cash_account`	*(empty)*	Default Cash/Bank GL account

Invoice Numbering

Key	Default	Description
`invoice_prefix`	`INV-`	Prefix for generated invoice numbers
`next_invoice_number`	`1001`	Next auto-incremented invoice sequence

Journal Numbering

Key	Default	Description
`next_journal_number`	`1001`	Next auto-incremented journal entry sequence

Cash Receipt Numbering

Key	Default	Description
`receipt_prefix`	`CR-`	Prefix for generated receipt numbers
`next_receipt_number`	`1001`	Next auto-incremented receipt sequence

Timesheet Settings

Key	Default	Description
`timesheet_shift`	`8to4`	Default shift template
`timesheet_require_approval`	`0`	`1` = approval workflow enabled; `0` = disabled
`checkin_reminder_time`	`16:00`	Daily check-in reminder time (HH:MM)

Email / SMTP

Key	Default	Description
`smtp_host`	`smtp.videotron.ca`	SMTP server hostname
`smtp_port`	`587`	SMTP port
`smtp_user`	*(configured)*	SMTP authentication username
`smtp_password`	*(configured)*	SMTP authentication password
`smtp_tls`	`1`	`1` = use STARTTLS; `0` = plain
`support_email`	*(configured)*	Support / from email address
`invoice_email_subject`	`Invoice {invoice_number} from {company}`	Email subject template
`invoice_email_body`	*(multi-line template)*	Email body template with placeholders

Invoice email body placeholders: `{customer}`, `{invoice_number}`, `{total}`, `{consultant}`, `{company}`, `{email}`, `{phone}`.

User Interface

Key	Default	Description
`ui_language`	`en`	UI language: `en` (English) or `fr` (French)

---

6. Enumerated Value Reference

`journalmaster.status`

Value	Description
`Draft`	Entry created but not yet posted to the GL
`Posted`	Entry has been posted; lines exist in `gldetails`

`invoicemaster.status`

Value	Description
`Draft`	Invoice in progress, not posted
`Posted`	Invoice posted to GL
`Paid`	Invoice fully paid
`Void`	Invoice voided

`invoicedetails.line_type`

Value	Description
`item`	Standard billable line item
`header`	Section heading (printed bold, no amounts)
`comment`	Free-text comment line (no amounts)

`cashreceipts.status`

Value	Description
`Draft`	Receipt entered but not posted
`Posted`	Posted to GL (DR Cash / CR AR)

`timesheetmaster.status`

Value	Description
`Draft`	Timesheet in progress
`Submitted`	Submitted for approval
`Approved`	Approved by manager

`todolist.priority`

Value	Description
`Low`	Low priority
`Normal`	Normal priority (default)
`High`	High priority

`todolist.status`

Value	Description
`Open`	Task not yet completed
`Done`	Task completed

`users.role`

Value	Description
`admin`	Full access to all modules; bypasses `useraccess` table
`accountant`	Access per `useraccess` table

`useraccess.access_level`

Value	Description
`full`	Read and write access
`view only`	Read-only; editing controls are disabled

`glmaster.balance_type` / `gldetails.balance_type`

Value	Description
`Dr`	Account has a normal debit balance (assets, expenses)
`Cr`	Account has a normal credit balance (liabilities, equity, revenue)

`customers.language`

Value	Description
`en`	English — invoices and PDF documents generated in English
`fr`	French — invoices and PDF documents generated in French