



Preparing cluster ports on an existing controller module

ONTAP MetroCluster

Ivana Devine, Martin Houser, Thom Illingworth
August 27, 2021

This PDF was generated from https://docs.netapp.com/us-en/ontap-metrocluster/upgrade/task_prepare_cluster_ports_on_the_exist_controller.html on September 24, 2021. Always check docs.netapp.com for the latest.

Table of Contents

Preparing cluster ports on an existing controller module 1

Preparing cluster ports on an existing controller module

Before installing a new controller module, you must configure cluster ports on the existing controller module so that the cluster ports can provide cluster communication with the new controller module.

About this task

If you are creating a two-node switchless cluster (with no cluster network switches), you must enable the switchless cluster networking mode.

For detailed information about port, LIF, and network configuration in ONTAP, see the [Network Management Guide](#).

Steps

1. Determine which ports should be used as the node's cluster ports.

For a list of the default port roles for your platform, see the [Hardware Universe](#)

The *Installation and Setup Instructions* for your platform on the NetApp Support Site contains information about the ports for cluster network connections.

2. For each cluster port, identify the port roles:

```
network port show
```

In the following example, ports "e0a", "e0b", "e0c", and "e0d" must be changed to cluster ports:

```
cluster_A::> network port show
```

```
Node: controller_A_1
```

```
Speed(Mbps) Health
```

Port	IPspace	Broadcast Domain	Link	MTU	Admin/Oper	Status
e0M	Default	mgmt_bd_1500	up	1500	auto/1000	healthy
e0a	Default	Default	up	1500	auto/10000	healthy
e0b	Default	Default	up	1500	auto/10000	healthy
e0c	Default	Default	up	1500	auto/10000	healthy
e0d	Default	Default	up	1500	auto/10000	healthy
e0i	Default	Default	down	1500	auto/10	-
e0j	Default	Default	down	1500	auto/10	-
e0k	Default	Default	down	1500	auto/10	-
e0l	Default	Default	down	1500	auto/10	-
e2a	Default	Default	up	1500	auto/10000	healthy
e2b	Default	Default	up	1500	auto/10000	healthy
e4a	Default	Default	up	1500	auto/10000	healthy
e4b	Default	Default	up	1500	auto/10000	healthy

```
13 entries were displayed.
```

3. For any data LIF that is using a cluster port as the home-port or current-port, modify the LIF to use a data port as its home-port:

```
network interface modify
```

The following example changes the home port of a data LIF to a data port:

```
cluster1::> network interface modify -lif datalif1 -vserver vs1 -home  
-port e1b
```

4. For each LIF that you modified, revert the LIF to its new home port:

```
network interface revert
```

The following example reverts the LIF "datalif1" to its new home port "e1b":

```
cluster1::> network interface revert -lif datalif1 -vserver vs1
```

5. Remove any VLAN ports using cluster ports as member ports and ifgrps using cluster ports as member ports.

- a. Delete VLAN ports:

```
network port vlan delete -node node-name -vlan-name portid-vlandid
```

For example:

```
network port vlan delete -node node1 -vlan-name elc-80
```

b. Remove physical ports from the interface groups:

```
network port ifgrp remove-port -node node-name -ifgrp interface-group-name
-port portid
```

For example:

```
network port ifgrp remove-port -node node1 -ifgrp ala -port e0d
```

c. Remove VLAN and interface group ports from broadcast domain::

```
network port broadcast-domain remove-ports -ipspace ipspace -broadcast
-domain broadcast-domain-name -ports nodename:portname,nodename:portname,..
```

d. Modify interface group ports to use other physical ports as member as needed.:

```
ifgrp add-port -node node-name -ifgrp interface-group-name -port port-id
```

6. Verify that the port roles have changed:

```
network port show
```

The following example shows that ports "e0a", "e0b", "e0c", and "e0d" are now cluster ports:

```
Node: controller_A_1
Speed(Mbps) Health
Port      IPspace      Broadcast Domain Link  MTU    Admin/Oper  Status
-----
e0M       Default      mgmt_bd_1500  up    1500    auto/1000  healthy
e0a       Cluster      Cluster       up    9000    auto/10000 healthy
e0b       Cluster      Cluster       up    9000    auto/10000 healthy
e0c       Cluster      Cluster       up    9000    auto/10000 healthy
e0d       Cluster      Cluster       up    9000    auto/10000 healthy
e0i       Default      Default       down  1500    auto/10    -
e0j       Default      Default       down  1500    auto/10    -
e0k       Default      Default       down  1500    auto/10    -
e0l       Default      Default       down  1500    auto/10    -
e2a       Default      Default       up    1500    auto/10000 healthy
e2b       Default      Default       up    1500    auto/10000 healthy
e4a       Default      Default       up    1500    auto/10000 healthy
e4b       Default      Default       up    1500    auto/10000 healthy
13 entries were displayed.
```

7. Add the ports to the cluster broadcast domain:

```
broadcast-domain add-ports -ipSpace Cluster -broadcast-domain Cluster -ports  
port-id, port-id, port-id...
```

For example:

```
broadcast-domain add-ports -ipSpace Cluster -broadcast-domain Cluster  
-ports cluster1-01:e0a
```

8. If your system is part of a switched cluster, create cluster LIFs on the cluster ports: `network interface create`

The following example creates a cluster LIF on one of the node's cluster ports. The `-auto` parameter configures the LIF to use a link-local IP address.

```
cluster1::> network interface create -vserver Cluster -lif clus1 -role  
cluster -home-node node0 -home-port e1a -auto true
```

9. If you are creating a two-node switchless cluster, enable the switchless cluster networking mode:

a. Change to the advanced privilege level from either node:

```
set -privilege advanced
```

You can respond `y` when prompted whether you want to continue into advanced mode. The advanced mode prompt appears (`*>`).

b. Enable the switchless cluster networking mode:

```
network options switchless-cluster modify -enabled true
```

c. Return to the admin privilege level:

```
set -privilege admin
```



Cluster interface creation for the existing node in a two-node switchless cluster system is completed after cluster setup is completed through a netboot on the new controller module.

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.