

Exercise: Units of the wave equation

mass \times acceleration = forces

$$[\text{kg}] \quad \left[\frac{\text{m}}{\text{s}^2} \right] \quad [N] = \left[\frac{\text{kg} \cdot \text{m}}{\text{s}^2} \right] \text{ Newton}$$

We mostly use the wave equation written as

$$\rho \frac{\partial^2 u}{\partial t^2} - \nabla \cdot \underline{T} = \underline{f}$$

What are the corresponding units?

The material properties are given by

- density ρ

- bulk & shear modulus, Young modulus,
Lamé parameters

→ what follows for the elastic
tensor $\underline{\underline{C}}$?

Consider Hooke's law

$$\underline{\underline{T}} = \underline{\underline{C}} : \underline{\underline{\epsilon}} \quad \text{with strain } \underline{\underline{\epsilon}} \\ \text{and stress } \underline{\underline{T}}$$

What are the units of $\underline{\underline{T}}$ and $\underline{\underline{\epsilon}}$?

Response: $\rho \partial_t^2 \underline{u} - \nabla \cdot \underline{T} = \underline{f}$

$$\left[\frac{\text{kg}}{\text{m}^3} \right] \left[\frac{\text{m}}{\text{s}^2} \right] \left[\frac{1}{\text{m}} \right] \left[\frac{\text{N}}{\text{m}^2} \right] \left[\frac{\text{N}}{\text{m}^3} \right]$$

with f : force per unit volume

- bulk & shear modulus, Young modulus,
Lamé parameter

$$[\text{GPa}] = [10^9 \text{ Pa}] \quad \text{with } [\text{Pa}] = \left[\frac{\text{N}}{\text{m}^2} \right]$$

Pascal
unit of pressure

typical values for rocks:

$$\lambda, \mu \sim 20 - 120 \text{ GPa}$$

For isotropic media

$$c_{ijkl} = \lambda \delta_{ij} \delta_{kl} + \mu (\delta_{ik} \delta_{jl} + \delta_{il} \delta_{jk})$$

has units $[\text{Pa}]$


Considering Hooke's law

$$\underline{T} = \underline{c} : \underline{\varepsilon} \quad \text{with strain } \underline{\varepsilon} = \frac{1}{2} [\underline{\nabla} \underline{u} + (\underline{\nabla} \underline{u})^T]$$

$$[\text{Pa}] = \left[\frac{\text{N}}{\text{m}^2} \right] \quad [\text{Pa}] \quad [\cdot]$$


$[\cdot] \quad \left[\frac{1}{\text{m}} \right] [\text{m}]$
is dimensionless

Example on strain: Strain is the change in length compared to original length



$$\epsilon \sim \frac{\text{change of length}}{\text{original length}}$$

as estimate $\epsilon \sim \frac{4A}{\lambda}$ — max. amplitude
— wavelength



Let's assume a harmonic wave

$$u(x, t) = A \sin(\omega t - kx)$$

ω : angular frequency

k : wavenumber

with wavelength $\lambda = vT$,

period $T = \frac{2\pi}{\omega}$ and thus

$$\lambda = \frac{2\pi}{k}$$

Given (λ, v) : period $T = \frac{\lambda}{v}$
 $= \frac{8 \text{ km}}{5 \text{ km/s}} = 1.6 \text{ s}$

frequency $\omega = \frac{2\pi}{T} \sim 3.9 \text{ (rad)}$

wavenumber $k = \frac{2\pi}{\lambda}$
 $\sim 0.8 \text{ (km}^{-1}\text{)}$

Harmonic wave

$$u(x, t) = A \sin(\omega t - kx) \\ = A \sin\left(\frac{2\pi}{\lambda}(\omega t - x)\right)$$

Consider strain $\epsilon = \frac{1}{2}(\nabla u + (\nabla u)^T)$

with

$$\frac{\partial}{\partial x} u = -\frac{2\pi}{\lambda} A \cos\left(\frac{2\pi t}{T} - \frac{2\pi x}{\lambda}\right)$$

$$\text{leads to } \epsilon_{\max} \sim \frac{2\pi A}{\lambda} = \frac{2\pi \cdot 0.04 \text{ m}}{8 \text{ km}} \\ \sim 3 \cdot 10^{-5}$$