AI Assistant Triage

Evaluation matrix: criteria, basis, weights and data format

Criteria as of 2026-10-31 · 43 scored criteria in 8 groups · generated from `criteria.json`

How to read this

Each criterion below shows **what it evaluates**, **what the score is based on** (the evidence an evaluator must record), its **suggested weight**, the allowed **score values** with suggested points, and how a score is **recorded** programmatically. Criteria are listed alphabetically by name within each group. IDs (`C01`–`C43`) are stable and do not imply order.

Status: SUGGESTED, not yet adopted by Daniel (proposed by Agent (Claude Opus 5.5), 2026-10-31). Scorecards do not use them yet.

Suggested scoring

Weights	`top` = 3, `high` = 2, `normal` = 1. Derived from the priority tags in criteria.md: priority: top = 3, priority: high = 2, untagged = 1.
Points	0 to 1 per value, best value = 1. `?` and `N/A` are excluded, not scored 0.
Tool score	tool_score = sum(weight_i * points_i) / sum(weight_i), over criteria whose value is not in excluded_values. Report the coverage (scored criteria / total) next to the score, since '?' cells are left out rather than scored 0.
Group score	Same formula restricted to one group, so groups can be compared without one dominating.
Qualifiers	Some criteria carry a qualifier as well as a score (e.g. C22 storage, C34 format, C13-C15 type). Qualifiers are recorded but not scored.

Every score also records

- **Value**: one of the allowed values for the criterion.
- **Note**: a one-line implementation note (the *how* often matters more than the yes/no).
- **Source**: a link, or “observed by Daniel, YYYY-MM-DD”. Required for every non-`?` value.
- **Evidence**: `confirmed` (tested, or current vendor docs read) or `assumed`.
- **By**: `Daniel` or `Agent (<model>)`. Daniel’s observation wins; contradictions are flagged in the note.
- At scorecard level: evaluation date (`YYYY-MM-DD`) and plan/tier evaluated.

Groups at a glance

Group	Criteria (alphabetical)	Count	Weight sum
A Connector ecosystem	C02 Connector access by subscription tier · C01 Connector catalogue size · C34 Custom marketplaces · C23 Custom MCP connections · C41 Native private connectors · C40 Official connector directory: URLs · C42 Plugin authorship and listing · C33 Plugin packaging format · C32 Progressive tool discovery and tool limits · C25 Purpose-built for integrations · C39 Subscription pricing and restrictions	11	14
B Google Workspace	C05 Gmail access level · C06 Gmail attachments · C12 Google Calendar access level · C07 Google Contacts access level · C04 Google Drive access level · C03 Google Workspace integration	6	12

Group	Criteria (alphabetical)	Count	Weight sum
C Multiple accounts per connector	C08 Multiple accounts per connector · C10 Profile limit per connector · C09 Profile naming / aliases · C11 Profile selection handling	4	12
D Connector usage and control	C36 Autonomy modes and permission structure · C19 Connector invocation mode · C20 Human-in-the-loop controls · C43 Team federation of plugin access	4	4
E Own infrastructure and local tools	C31 Distributed deployments / satellites · C30 Locally hosted tool integration (e.g. Home Assistant) · C24 Tunnels to own infrastructure / AI gateway	3	7
F Data ownership	C27 Backup / export API · C28 Bring your own memory · C26 Output routing to own storage	3	3
G Agents, projects and coding	C35 Agent-to-agent (A2A) support · C29 Background agents, scheduled tasks and reminders · C37 CLI working-directory binding · C38 Native GitHub integration · C21 Parallel CLI coding product · C22 Project boundaries and where project data lives	6	8
H Clients and platforms	C15 Android app · C16 Cross-device conversation history sync · C14 Linux CLI · C13 Linux desktop app · C18 Native speech-to-text, Android · C17 Native speech-to-text, desktop	6	6

A. Connector ecosystem

What connectors exist, who gets them, and whether integration is the product's core.

C02 Connector access by subscription tier

NORMAL ×1 general

Evaluates Is connector access restricted by tier, available to every paying subscriber, or free?

Based on Which tiers get what; cheapest tier with connector access and its monthly price (currency and region; no US egress); whether custom connectors are gated differently from catalogue ones.

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
`Free`	1	
`All paid`	0.7	
`Tiered`	0.4	
`Enterprise only`	0.1	
`?`	excluded	

Record as

```
"C02": {
  "value": "Free" | "All paid" | "Tiered" | "Enterprise only" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C01 Connector catalogue size

NORMAL ×1 general

Evaluates How many ready-to-integrate connectors can a user switch on without writing or hosting anything?

Based on Approximate count with date and place counted (directory page, docs, in-app); who builds them (vendor, partner, community); whether bring-your-own connectors are also allowed (note only).

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
`Large`	1	100+
`Medium`	0.66	20-99
`Small`	0.33	1-19
`None`	0	0
`?`	excluded	

Record as

```
"C01": {
  "value": "Large" | "Medium" | "Small" | "None" | "?",
  "raw": <integer count>,
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C34 Custom marketplaces NORMAL ×1 daniel

Evaluates Can you add your own plugin marketplaces beyond the vendor's? How many, and in what format?

Based on How a marketplace is declared (Git repo with manifest, JSON URL, MCP registry API); limit on marketplaces; whether private (authenticated) marketplaces work; sync across clients.

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
Yes	1	record the number allowed or Unlimited
Partial	0.5	admin-only, or one private catalogue on business plans
No	0	
?	excluded	

Record as

```
"C34": {
  "value": "Yes" | "Partial" | "No" | "?",
  "format": "Standard" | "Proprietary",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C23 Custom MCP connections HIGH ×2 daniel

Evaluates Can the user add their own MCP server, not just pick from the catalogue?

Based on Remote (URL) and/or local (stdio); transports (streamable HTTP, SSE); auth (OAuth, bearer/API-key header, none); tiers; clients (web, desktop, mobile); admin approval on business plans; tool limits per server.

Suggested weight 2 (priority: high)

Score values

Value	Points	Meaning
Yes	1	
Partial	0.5	mode-gated, admin-only, read-only tools or desktop-only
No	0	
?	excluded	

Record as

```
"C23": {
  "value": "Yes" | "Partial" | "No" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C41 Native private connectors NORMAL ×1 daniel

Evaluates Is there native support for private connectors you or your org build and use without publishing them publicly?

Based on Mechanism (custom MCP URL, unlisted/draft app, org-private catalogue, developer mode); who can create and see it; tiers; auth options; whether vendor review is needed.

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
Yes	1	first-class private connectors shared with chosen people
Partial	0.5	only a per-user custom MCP URL, or business plans only
No	0	
?	excluded	

Record as

```
"C41": {
  "value": "Yes" | "Partial" | "No" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C40 Official connector directory: URLs NORMAL ×1 general

Evaluates Is the connector library published at an official URL a human can browse, and as a programmatic list (JSON or API/registry endpoint) an agent can read?

Based on Both URLs; whether the JSON needs auth; fields carried (name, description, auth type, MCP URL); official vs community mirror (mirrors do not count).

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
`Both`	1	
`JSON only`	0.6	
`Human only`	0.5	
`In-app only`	0.2	
`None`	0	
`?`	excluded	

Record as

```
"C40": {
  "value": "Both" | "JSON only" | "Human only" | "In-app only" | "None" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C42 Plugin authorship and listing NORMAL ×1 general

Evaluates How does a third party get a connector listed in the official directory?

Based on Submission URL; requirements (MCP server, manifest, privacy policy, security review, verified domain); review time; fees or revenue share; whether individuals can publish.

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
`Open submission`	1	
`Partner only`	0.4	
`Closed`	0	
`?`	excluded	

Record as

```
"C42": {
  "value": "Open submission" | "Partner only" | "Closed" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C33 Plugin packaging format NORMAL ×1 daniel

Evaluates How is a plugin (bundle of connectors, instructions, skills, commands) packaged and declared? Open standard or proprietary?

Based on Manifest file and schema with spec link; what a plugin can contain; install from local path or Git URL; whether the package works in another vendor's tool.

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
`Standard`	1	
`Documented proprietary`	0.6	
`Closed`	0.2	
`No plugins`	0	
`?`	excluded	

Record as

```
"C33": {
  "value": "Standard" | "Documented proprietary" | "Closed" | "No plugins" |
"?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C32 Progressive tool discovery and tool limits NORMAL ×1 daniel

Evaluates Are tool definitions loaded up front, or discovered progressively (tool search, deferred loading)? What limits apply to the number of tools?

Based on Documented and observed limits (per server, per chat, total servers); behaviour at the limit (error, truncation, dropped tools); whether progressive loading covers custom MCP servers.

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
`Progressive`	1	
`Eager, high limit`	0.5	
`Eager, low limit`	0.1	
`?`	excluded	

Record as

```
"C32": {
  "value": "Progressive" | "Eager, high limit" | "Eager, low limit" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C25 Purpose-built for integrations TOP ×3 daniel

Evaluates Is connecting an AI to external tools the platform's main purpose, or is it a general conversational tool with an integration feature added on?

Based on Judgement call from positioning, where connectors sit in the UI and docs, whether the product is usable at all without them, and depth of connector management (profiles, permissions, logs, testing).

Suggested weight 3 (priority: top)

Score values

Value	Points	Meaning
`Integration-first`	1	
`General + integrations`	0.4	
`?`	excluded	

Record as

```
"C25": {
  "value": "Integration-first" | "General + integrations" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C39 Subscription pricing and restrictions NORMAL ×1 daniel

Evaluates What does each tier cost, and what restrictions affect agentic use (message/credit caps, connector or account caps, task limits, seat minimums, annual-only billing)?

Based on Every tier with price, currency and period as displayed (region noted); what each tier unlocks for connectors; documented restrictions; pricing page link and date read.

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
`<= 25/mo`	1	
`26-60/mo`	0.6	
`61-150/mo`	0.3	
`> 150/mo or sales-only`	0	
`?`	excluded	

Note Price bands are a suggestion; convert to one currency at the date read before banding.

Record as

```
"C39": {
  "value": "<= 25/mo" | "26-60/mo" | "61-150/mo" | "> 150/mo or sales-only" |
"?",
  "raw": <cheapest tier that gets C03-C12 at their best level for that tool,
e.g. 'Plus $20/mo'>,
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

B. Google Workspace

Native or catalogue Google access; custom-MCP-only scores Partial. Note personal vs Workspace accounts.

C05 Gmail access level

HIGH ×2 daniel

Evaluates Is Gmail access read-only or read-write?

Based on Whether write means sending directly, drafts only (scored Read-write, noted), or labelling/archiving; connector route as for C03.

Suggested weight 2 (priority: high)

Score values

Value	Points	Meaning
`Read-write`	1	
`Read-only`	0.4	
`None`	0	
`?`	excluded	

Record as

```
"C05": {
  "value": "Read-write" | "Read-only" | "None" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C06 Gmail attachments

HIGH ×2 daniel

Evaluates Does the Gmail integration support attachments?

Based on Whether incoming attachments can be read and whether mail can be sent or drafted with attachments.

Suggested weight 2 (priority: high)

Score values

Value	Points	Meaning
`Both`	1	
`Read only`	0.5	
`Send only`	0.5	
`None`	0	
`?`	excluded	

Record as

```
"C06": {
  "value": "Both" | "Read only" | "Send only" | "None" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C12 Google Calendar access level

HIGH ×2 daniel

Evaluates Is Google Calendar access read-only or read-write?

Based on Whether write means creating, editing/deleting events, or both; whether non-primary calendars are visible; connector route as for C03.

Suggested weight 2 (priority: high)

Score values

Value	Points	Meaning
`Read-write`	1	
`Read-only`	0.4	
`None`	0	
`?`	excluded	

Record as

```
"C12": {
  "value": "Read-write" | "Read-only" | "None" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C07 Google Contacts access level HIGH ×2 daniel

Evaluates Is Google Contacts access read-only or read-write?

Based on Whether contacts can be created and edited, or only searched and read; connector route as for C03.

Suggested weight 2 (priority: high)

Score values

Value	Points	Meaning
`Read-write`	1	
`Read-only`	0.4	
`None`	0	
`?`	excluded	

Record as

```
"C07": {
  "value": "Read-write" | "Read-only" | "None" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C04 Google Drive access level HIGH ×2 daniel

Evaluates Is Google Drive access read-only or read-write?

Based on File types searched/read (Docs, Sheets, arbitrary files); whether write means creating new files, editing existing ones, or both; connector route as for C03.

Suggested weight 2 (priority: high)

Score values

Value	Points	Meaning
`Read-write`	1	
`Read-only`	0.4	
`None`	0	
`?`	excluded	

Record as

```
"C04": {
  "value": "Read-write" | "Read-only" | "None" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C03 Google Workspace integration HIGH ×2 daniel

Evaluates Does the platform support Google Workspace integration at all?

Based on How access is provided: native vendor connector or third-party catalogue connector (count as Yes) vs custom MCP only (Partial); personal accounts, Workspace accounts, or both.

Suggested weight 2 (priority: high)

Score values

Value	Points	Meaning
`Yes`	1	
`Partial`	0.4	custom MCP only, or limited
`No`	0	
`?`	excluded	

Record as

```
"C03": {
  "value": "Yes" | "Partial" | "No" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C. Multiple accounts per connector

One connector type connected to several accounts (personal + work) in the same assistant.

C08 Multiple accounts per connector

TOP ×3 daniel

Evaluates Can the same connector be connected more than once, to different accounts (profiles)?

Based on Observed or documented ability to add a second instance of one connector (reference: ChatGPT, two Gmail connectors, observed by Daniel 2026-10-31).

Suggested weight 3 (priority: top)

Score values

Value	Points	Meaning
Yes	1	
Partial	0.4	only via a duplicate custom MCP server, or one active at a time
No	0	
?	excluded	

Record as

```
"C08": {
  "value": "Yes" | "Partial" | "No" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C10 Profile limit per connector

TOP ×3 daniel

Evaluates Is there a maximum number of profiles per connector, or per account?

Based on The limit and whether it is documented or observed.

Suggested weight 3 (priority: top)

Score values

Value	Points	Meaning
Unlimited	1	
5+	0.8	
2-4	0.5	
1	0	
?	excluded	

Note Bands are a suggestion; criteria.md records the raw number.

Record as

```
"C10": {
  "value": "Unlimited" | "5+" | "2-4" | "1" | "?",
  "raw": <integer limit or 'Unlimited'>,
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C09 Profile naming / aliases

TOP ×3 daniel

Evaluates Can each connected profile be given its own name or alias (e.g. 'Gmail personal', 'Gmail work')?

Based on Whether aliasing exists, and whether the alias is visible to the model or only in the settings UI.

Suggested weight 3 (priority: top)

Score values

Value	Points	Meaning
Yes	1	
No	0	
?	excluded	

Record as

```
"C09": {
  "value": "Yes" | "No" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C11 Profile selection handling TOP ×3 daniel

Evaluates When several profiles of one connector exist, how do you specify which one to use?

Based on Mechanisms available (naming in the prompt, per-chat toggle, per-project default, composer picker, automatic); behaviour when ambiguous (asks, guesses, uses all).

Suggested weight 3 (priority: top)

Score values

Value	Points	Meaning
`Explicit`	1	user can pin a profile
`Prompt only`	0.5	
`Auto only`	0.2	
`?`	excluded	

Record as

```
"C11": {
  "value": "Explicit" | "Prompt only" | "Auto only" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

D. Connector usage and control

How connectors are invoked and what stops them acting without you.

C36 Autonomy modes and permission structure

NORMAL ×1 daniel

Evaluates What levels of agent supervision exist, from fully supervised to fully autonomous, and how is the permission structure built?

Based on Mode names; how rules are expressed (per tool, command pattern, path, connector); where stored (user, project, admin policy) and which layer wins; mid-session switching; whether chat app and CLI share the model.

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
`Full range`	1	
`Partial`	0.5	
`Supervised only`	0.2	
`Autonomous only`	0.2	
`?`	excluded	

Record as

```
"C36": {
  "value": "Full range" | "Partial" | "Supervised only" | "Autonomous only" |
"?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C19 Connector invocation mode

NORMAL ×1 daniel

Evaluates Are connectors available in ordinary chat, or only in a specific mode, model or project setting?

Based on Exact mode/toggle names; whether custom and catalogue connectors behave differently; whether it differs between web, desktop and mobile; what a gating mode loses.

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
`Always on`	1	
`Per-chat toggle`	0.6	
`Mode-gated`	0.2	
`?`	excluded	

Record as

```
"C19": {
  "value": "Always on" | "Per-chat toggle" | "Mode-gated" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C20 Human-in-the-loop controls NORMAL ×1 daniel

Evaluates Is there deterministic, user-configurable control over when the assistant must ask before a connector action runs?

Based on Where settings live; 'remember for this chat' vs 'always'; whether policy covers custom connectors; how approval works for background tasks (prompt, push, task waits vs fails).

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
`Deterministic, granular`	1	
`Deterministic, coarse`	0.6	
`Model-driven`	0.25	
`Notifications only`	0.15	
`None`	0	
`?`	excluded	

Record as

```
"C20": {
  "value": "Deterministic, granular" | "Deterministic, coarse" | "Model-driven"
| "Notifications only" | "None" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C43 Team federation of plugin access NORMAL ×1 daniel

Evaluates On team plans, can an admin add connectors once for the org, allow/block them, scope them to groups, and choose per-user vs shared credentials?

Based on Admin location; SSO/SCIM group-driven access; per-user vs service credentials; pushing custom/private connectors to members; audit logging; tier needed.

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
`Granular`	1	
`Coarse`	0.5	
`None`	0	
`N/A`	excluded	no team plan
`?`	excluded	

Record as

```
"C43": {
  "value": "Granular" | "Coarse" | "None" | "N/A" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

E. Own infrastructure and local tools

Reaching things you host: gateways, home network tools, your own servers.

C31 Distributed deployments / satellites TOP ×3 daniel

Evaluates Is there built-in support for a network of deployments, e.g. the main app delegating to a CLI on a local server acting as a satellite?

Based on How instances are paired and authenticated; whether the satellite uses its local tools/files for the main app; whether it works from mobile.

Suggested weight 3 (priority: top)

Score values

Value	Points	Meaning
`Native`	1	
`Partial`	0.5	remote control of one CLI session, no delegation
`DIY`	0.2	only by wrapping the CLI as an MCP server
`No`	0	
`?`	excluded	

Record as

```
"C31": {
  "value": "Native" | "Partial" | "DIY" | "No" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C30 Locally hosted tool integration (e.g. Home Assistant) HIGH ×2 daniel

Evaluates How would the platform reach and control a locally hosted tool like Home Assistant natively?

Based on The concrete Home Assistant route (official connector, HA MCP server integration, desktop app on the LAN); which clients it works from; user reports.

Suggested weight 2 (priority: high)

Score values

Value	Points	Meaning
`Native`	1	
`Via tunnel`	0.7	
`DIY`	0.3	
`No`	0	
`?`	excluded	

Record as

```
"C30": {
  "value": "Native" | "Via tunnel" | "DIY" | "No" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C24 Tunnels to own infrastructure / AI gateway HIGH ×2 daniel

Evaluates Can the assistant reach your own infrastructure (home server, private network, own MCP/AI gateway)? How?

Based on Implementation; auth supported in front of the tunnel (e.g. Cloudflare Access service-token headers vs OAuth only); user feedback from forums, GitHub issues, Reddit with links and dates.

Suggested weight 2 (priority: high)

Score values

Value	Points	Meaning
`Official tunnel`	1	
`Local bridge`	0.6	
`DIY only`	0.3	
`No`	0	
`?`	excluded	

Record as

```
"C24": {
  "value": "Official tunnel" | "Local bridge" | "DIY only" | "No" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

F. Data ownership

Getting your data out and keeping memory under your control.

C27 Backup / export API NORMAL ×1 daniel

Evaluates Is there a native API or scheduled export for getting your data out (conversations, projects, memory, files)?

Based on What is included (memory and project files often missing); format; whether business plans get a compliance/export API consumer plans don't.

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
`API`	1	
`Scheduled export`	0.7	
`Manual export only`	0.3	
`No`	0	
`?`	excluded	

Record as

```
"C27": {
  "value": "API" | "Scheduled export" | "Manual export only" | "No" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C28 Bring your own memory NORMAL ×1 daniel

Evaluates Is there first-party support for using your own memory store, or are you forced onto the built-in memory?

Based on Whether built-in memory can be disabled, viewed, edited and exported; whether an external memory connector is an official backend or a workaround.

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
`First-party BYO`	1	
`Workaround`	0.5	
`Forced built-in`	0	
`?`	excluded	

Record as

```
"C28": {
  "value": "First-party BYO" | "Workaround" | "Forced built-in" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C26 Output routing to own storage NORMAL ×1 daniel

Evaluates Can conversations, outputs or files be routed as they happen to storage you own (Drive folder, S3/R2, Git repo, webhook, local folder)?

Based on Destinations supported; automatic vs manual; format (Markdown, JSON). Expected to be rare (not seen anywhere by Daniel, 2026-10-31).

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
`Yes`	1	
`Partial`	0.5	
`No`	0	
`?`	excluded	

Record as

```
"C26": {
  "value": "Yes" | "Partial" | "No" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

G. Agents, projects and coding

Work that outlives a single chat: background agents, project boundaries, the companion coding product.

C35 Agent-to-agent (A2A) support TOP ×3 daniel

Evaluates Can the assistant call, be called by, and delegate between agents? Via an open protocol (e.g. A2A) or a proprietary one?

Based on Direction (calls, is called, both); protocol and version; auth between agents; whether delegated agents keep their tools and connectors; how results return. Links to C31.

Suggested weight 3 (priority: top)

Score values

Value	Points	Meaning
`Standard A2A`	1	
`Proprietary`	0.6	
`Subagents only`	0.3	
`No`	0	
`?`	excluded	

Record as

```
"C35": {
  "value": "Standard A2A" | "Proprietary" | "Subagents only" | "No" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C29 Background agents, scheduled tasks and reminders NORMAL ×1 daniel

Evaluates Can you create background or persistent agents that run without an open chat, and schedule future tasks and reminders?

Based on Where they run (vendor cloud, your machine); connector and custom MCP access; delivery (push, email, in chat); limits on number/frequency; whether they run with all clients closed. Links to C20.

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
`Yes`	1	
`Partial`	0.5	reminders only, or tasks without connector access
`No`	0	
`?`	excluded	

Record as

```
"C29": {
  "value": "Yes" | "Partial" | "No" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C37 CLI working-directory binding NORMAL ×1 daniel

Evaluates How tightly is the CLI bound to the directory it was launched in?

Based on Enforcement by permission system or sandbox; how extra directories are added (flag, command, config); whether config and memory are keyed to the CWD; whether it can run from ~ as a general assistant.

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
`Arbitrary`	1	
`Expandable`	0.7	
`Strict`	0.2	
`N/A`	excluded	no vendor CLI
`?`	excluded	

Record as

```
"C37": {
  "value": "Arbitrary" | "Expandable" | "Strict" | "N/A" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C38 Native GitHub integration NORMAL ×1 daniel

Evaluates Is there a native, vendor-supported GitHub integration, rather than only a custom MCP server or the CLI calling gh?

Based on Connector vs GitHub App vs OAuth; private repo and org access; supported actions; chat, coding agent, or both; whether the cloud coding agent can open PRs.

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
`Read-write`	1	
`Read-only`	0.5	
`Custom only`	0.2	
`No`	0	
`?`	excluded	

Record as

```
"C38": {
  "value": "Read-write" | "Read-only" | "Custom only" | "No" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C21 Parallel CLI coding product NORMAL ×1 daniel

Evaluates Does the vendor ship a CLI coding agent alongside the chat assistant, and how does it relate to the chat app?

Based on Product name; same subscription or not; whether chat-app connectors/MCP carry over to the CLI; whether a cloud coding agent shows up in the chat app.

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
`Integrated`	1	
`Partly shared`	0.7	
`Separate workspace`	0.5	
`No`	0	
`?`	excluded	

Note criteria.md scores Yes/No plus a relationship; the relationship values above imply Yes.

Record as

```
"C21": {
  "value": "Integrated" | "Partly shared" | "Separate workspace" | "No" | "?",
  "product name": <string>,
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C22 Project boundaries and where project data lives NORMAL ×1 daniel

Evaluates Can you define projects that bound context, files, instructions and connectors? Is project data in the cloud or local?

Based on What a project scopes (instructions, files, memory, history, connectors); whether memory leaks across projects or can be isolated; cross-device sync.

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
`Yes`	1	
`Partial`	0.5	
`No`	0	
`?`	excluded	

Record as

```
"C22": {
  "value": "Yes" | "Partial" | "No" | "?",
  "storage": "Cloud" | "Local" | "Both",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

H. Clients and platforms

Official clients only; PWAs count only for C13 and must be labelled.

C15 Android app

NORMAL ×1 daniel

Evaluates Is there an official Android app?

Based on Distribution channel (Play Store, APK, F-Droid; PWA scores No unless it is the vendor's official Android app).

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
Yes	1	
No	0	
?	excluded	

Record as

```
"C15": {
  "value": "Yes" | "No" | "?",
  "type": "Play Store" | "APK" | "F-Droid" | "PWA",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C16 Cross-device conversation history sync

NORMAL ×1 daniel

Evaluates Is conversation history synced through the cloud across web, desktop, Android and CLI?

Based on Which clients are in the sync and which keep history local.

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
Yes	1	
Partial	0.5	
No	0	
?	excluded	

Record as

```
"C16": {
  "value": "Yes" | "Partial" | "No" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C14 Linux CLI

NORMAL ×1 daniel

Evaluates Is there an official CLI client that runs on Linux and uses the same account/subscription (not just a raw API key)?

Based on Install type (npm, pip/uv, binary, Homebrew, apt/repo, cargo, go install, Docker); whether it works only with API billing.

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
Yes	1	
No	0	
?	excluded	

Record as

```
"C14": {
  "value": "Yes" | "No" | "?",
  "type": "npm" | "pip/uv" | "binary" | "Homebrew" | "apt/repo" | "cargo" | "go
install" | "Docker",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C13 Linux desktop app NORMAL ×1 daniel

Evaluates Is there an official Linux desktop app?

Based on Distribution channels (deb, rpm, AppImage, Flatpak, Snap, AUR, tarball); for a PWA, how it installs and what it loses (global hotkey, local MCP, dictation). Community clients score No and are named.

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
`Yes (native)`	1	
`Yes (PWA)`	0.5	
`No`	0	
`?`	excluded	

Record as

```
"C13": {
  "value": "Yes (native)" | "Yes (PWA)" | "No" | "?",
  "type": "deb" | "rpm" | "AppImage" | "Flatpak" | "Snap" | "AUR" | "tarball" |
"PWA",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C18 Native speech-to-text, Android NORMAL ×1 daniel

Evaluates Does the Android app have built-in voice dictation beyond the system keyboard's?

Based on Dictation vs voice mode; language support (Hebrew if known).

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
`Yes`	1	
`No`	0	
`?`	excluded	

Record as

```
"C18": {
  "value": "Yes" | "No" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```

C17 Native speech-to-text, desktop NORMAL ×1 daniel

Evaluates Does the desktop client (or web app, if no desktop app) have built-in voice dictation into the chat input?

Based on Dictation vs full voice-conversation mode; whether it works on the Linux client specifically.

Suggested weight 1 (priority: normal)

Score values

Value	Points	Meaning
`Yes`	1	
`No`	0	
`?`	excluded	

Record as

```
"C17": {
  "value": "Yes" | "No" | "?",
  "note": <string>, "source": <url | "observed by Daniel, YYYY-MM-DD">,
  "evidence": "confirmed" | "assumed", "by": "Daniel" | "Agent (<model>)"
}
```