

OPERATING SYSTEMS EXERCISE 1

Assignment B – HTTP

Implement a client and a server for the Hypertext Transfer Protocol (HTTP).

HTTP is a text-based request-response application layer protocol, which is used to transfer files between a client and a server. Typically a client sends a request for a file located on the server. The server then responds and transmits the requested file.

HTTP requests start with a line which contains the request method (for instance `GET`), the location of the desired resource and the protocol version. This line is followed by an arbitrary number of header fields. Each header field is a line with a keyword and a value, separated by a colon (:). The request header ends with an empty line, which may be followed by a request body if the client wishes to transmit a resource to the server.

```
GET /index.html HTTP/1.1
Host: www.myhost.at
```

Example of a HTTP request: Request method `GET` is used to request the file `index.html` using HTTP version 1.1. The request header contains only one header field, the `Host` field, which specifies the hostname of the server. An empty line ends the header and since there is no body this is also the end of the request message.

The response starts with a line containing the protocol version, a status code and a textual description of the status code. As in the request, this line is followed by an arbitrary number of header fields and again the header ends with an empty line. The header is followed by the response body, which is typically the content of the requested file.

```
HTTP/1.1 200 OK
Date: Sun, 11 Nov 2018 22:55:00 GMT
Content-Type: text/html; charset=UTF-8
Content-Length: 146
Last-Modified: Mon, 01 Oct 2018 12:15:00 GMT
Connection: close

<!DOCTYPE html>
<html>
  <head>
    <title>My website</title>
  </head>
  <body>
    <h1>Hi!</h1>
    <p>This is my website.</p>
  </body>
</html>
```

Example of a HTTP response: The server responds to the above request with status code 200, which indicates that the request was successful. The header contains several fields with information about the content, such as the file format, the file length or the last time it was modified. The header ends with an empty line, which is followed by the file content.

The HTTP specification requires that each line ending in the header consists of two characters, a carriage return followed by a linefeed character, instead of the linefeed only which is standard on UNIX systems. In a C-string this sequence can be encoded as `"\r\n"`. Note that this does not apply to the content in the response body, which is transmitted as it is read from the file without modifications.

Instructions

Write a client program and a server program which partially implement version 1.1 of the HTTP.

Client

The client takes an URL as input, connects to the corresponding server and requests the file specified in the URL. The transmitted content of that file is written to `stdout` or to a file.

SYNOPSIS

```
client [-p PORT] [ -o FILE | -d DIR ] URL
```

EXAMPLE

```
client http://pan.vmars.tuwien.ac.at/osue/
```

The client may be called with a number of options:

- Option `-p` can be used to specify the port on which the client shall attempt to connect to the server. If this option is not used the port defaults to 80, which is the standard port for HTTP.
- Either option `-o` or `-d` can be used to write the requested content to a file. Option `-o` is used to specify a filename to which the transmitted content is written. Option `-d` is used to specify a directory in which a file of the same name as the requested file is created and filled with the transmitted content. If none of these options is given, the transmitted content is written to `stdout`.

The client creates a TCP/IP socket and connects to the hostname specified in the URL. For the purpose of this exercise we only consider URLs which start with the scheme identifier `http://`, immediately followed by a hostname. For simplicity you may therefore assume that the hostname is the part after the initial `http://` and before any of the following characters:

```
; / ? : @ = &
```

Once the connection is established, the client sends a request for the file specified in the URL (the filename is the part starting at and including the first `/` after the initial `http://`) using the HTTP method `GET`. The request header must start with the request line and must contain the `Host` field, which gives the hostname as specified in the URL. Also, the header field `Connection` with the value `close` should be added to the header (which tells the server that the connection should be closed after transmitting one file). For instance, the request header for the URL `http://pan.vmars.tuwien.ac.at/osue/` is:

```
GET /osue/ HTTP/1.1
Host: pan.vmars.tuwien.ac.at
Connection: close
```

After transmitting its request, the client waits for a response from the server. Your client must correctly parse the status code in the first line of the response.

If the response header is invalid, the client prints the message `"Protocol error!"` and terminates with exit code 2. You can consider the response header to be invalid if the first line does not start with `HTTP/1.1` or if this is not followed by a number which can be parsed with `strtol(3)`.

If the response status in the first line of the response header is not 200, the client prints a message with the response status (status code and the textual description after it) and terminates with exit code 3.

The client may ignore any header fields and directly skip ahead to the content in the response body by looking for the empty line which ends the header. The remainder of the response is the content of the requested file and is either written to `stdout` or to a file, according to the options listed above.

Server

The server waits for connections from clients and transmits the requested files.

SYNOPSIS

```
server [-p PORT] [-i INDEX] DOC_ROOT
```

EXAMPLE

```
server -p 1280 -i index.html ~/Documents/my_website/
```

The server may be called with following options:

- Option `-p` can be used to specify the port on which the server shall listen for incoming connections. If this option is not used the port defaults to 8080 (port 80 requires root privileges).
- Option `-i` is used to specify the index filename, i.e. the file which the server shall attempt to transmit if the request path is a directory. The default index filename is `index.html`.

The argument `DOC_ROOT` is the path of the document root directory, which contains the files that can be requested from the server.

The server listens for connections on the specified port and upon accepting a connection from a client, it reads the request message from the connection socket. Your server must be able to correctly identify the request method and the path of the requested resource.

If the request header is invalid, the server sends a response header with status code 400 (**Bad Request**) and closes the connection. You can consider the request header to be invalid if the first line does not consist of 3 values separated by whitespaces: first the request method, second the path of the requested file and third the protocol and version identifier `HTTP/1.1`.

The server must support the request method `GET`. If a different request method is sent by a client, the server sends a response header with status code 501 (**Not implemented**) and closes the connection.

If the first line of the request message is valid, the server may ignore all the rest of the request message and directly proceed to transmitting the requested file. The server prepends the document root path `DOC_ROOT` to the requested path¹. If the path of the requested resource ends with a `/`, the default index filename (see options above) is appended to it. If the server cannot open the resulting filename, it sends a response header with status code 404 (**Not Found**) and closes the connection.

If the file was successfully opened, the server first sends a response header with status code 200 (**OK**) and at minimum the fields **Date**, which contains the current date and time expressed in UTC (often also referred to as GMT) and encoded as specified in RFC 822², **Content-Length**, which gives the size of the requested file in bytes, and **Connection**, which should contain the value `close`. Your server may for instance transmit a response header as follows:

```
HTTP/1.1 200 OK
Date: Sun, 11 Nov 2018 22:55:00 GMT
Content-Length: 146
Connection: close
```

Once the header is transmitted, the server proceeds with the transmission of the requested file, by reading the content of the file and writing it to the connection as is without any modifications. When the server is done with the transmission it closes the connection and waits for the next connection.

¹ For the purpose of this exercise you may simply concatenate the root path and the request path, for instance by using `strncat(3)`. Your server is not required to check whether the resulting path effectively lies within the document directory.

²RFC 822, Section 5: Date and Time Specification, <https://tools.ietf.org/html/rfc822#section-5>

The response header transmitted in case of an invalid request, unsupported request method or missing file must contain the header field **Connection** with the value **close**, but all other header fields can be omitted and no content is transmitted.

The server must handle the signals **SIGINT** and **SIGTERM**. If any of these signals is received, the server completes an ongoing request and then terminates with exit code 0. If there are no open connections to clients when receiving the signal, the server terminates immediately with exit code 0.

Hints

- When parsing the URL in order to extract the hostname and the filepath, the functions **strchr(3)**, **strpbrk(3)** or **strsep(3)** will be helpful to locate the first occurrence of a character in a string.
- Since HTTP is a text-based protocol, you might want to use the functions of the stream API. This has the advantage that you can process the message headers line by line by using for instance **fgets(3)** or **getline(3)**. Be aware though that the transmission of binary content in the message body requires other functions.
- The first line of both the request and the response headers of the HTTP consists of 3 values separated by whitespaces. You might find it helpful to separate these using **strtok(3)**.
- You might want to use **strftime(3)** to format date and time as required for the response header. Take a close look at the 'Example' section of the man page for advice on date formatting in compliance with various standards.
- Be aware that the server must read the entire request from the connection socket before writing anything to that socket. This is also true if your server is responding with an error status.

Testing

In order to test the functionality and correct implementation of the protocol, you should test your programs in 3 different ways:

Your client requests files from your server

Create a directory and populate it with one or more example files. Verify that requested files are transmitted correctly using the utility `diff`.

```
$ ls ./my_website
test.html
$ ./server ./my_website &
$ ./client -o received.html -p 8080 localhost/test.html
$ diff ./my_website/test.html received.html
```

Your client requests files from servers on the internet

Using a web browser (e.g. Firefox), download a file which is publicly available on the internet, such as for instance <http://pan.vmars.tuwien.ac.at/osue/index.html> and save it locally (e.g. under `~/Downloads/test.html`). Request the same file using your client and verify that the content of both files is identical, again using `diff`.

```
$ ./client -o index.html http://pan.vmars.tuwien.ac.at/osue/
$ diff ~/Downloads/test.html index.html
```

Verify that your client correctly downloads various filetypes, including binary files, such as images.

```
$ ./client -d . http://pan.vmars.tuwien.ac.at/osue/countdown.js
$ diff ~/Downloads/countdown.js countdown.js
$ ./client -d . http://pan.vmars.tuwien.ac.at/osue/cat.png
$ diff ~/Downloads/cat.png received.png
```

Unfortunately most websites recently refuse to transmit files via HTTP and instead require HTTPS, the encrypted version of HTTP. However, websites which still accept HTTP are for instance <http://pan.vmars.tuwien.ac.at/osue/>, <http://wiki.happyfab.at/> or <http://cpsiot.at/>.

Your server processes requests from a web browser

Start your server and request files from it using a web browser (for instance using Firefox, which is the default browser in the TILAB).

```
$ ls ./my_website
test.html
$ ./server -i test.html ./my_website
```

Now your server should transmit the file `test.html` when you type `127.0.0.1:8080` in the address bar of the browser (`127.0.0.1` is the IP address for localhost and `:8080` is used to specify the port).

If you are working remotely via SSH you can also use the command-line utility `wget` instead of a browser with GUI.

Bonus Points

Bonus points are only awarded if your programs are **FULLY FUNCTIONAL** and **COMPLY WITH ALL INSTRUCTIONS!** When adding features for bonus tasks, check that the basic requirements are still fulfilled, otherwise you risk losing more points than you might gain!

Server

- **Header field Content-Type (2):** Add support for the header field **Content-Type** to your server. This field is used to inform the client about the MIME-type³ of the transmitted content. Your server should recognize following file types:

File extension	MIME type
.html, .htm	text/html
.css	text/css
.js	application/javascript
.png	image/png
.pdf	application/pdf

2 bonus point are awarded if your server's response header contains the field **Content-Type** with the corresponding MIME type value if the requested file has any of the above extensions. If the file extension is none of those listed in the table, the field **Content-Type** should not be used.

- **Compression (4):** Implement compression of the transferred content in the gzip format. Make use of the zlib compression library (see sect. "Using zlib") for compressing the data.

4 bonus points are awarded if your server recognizes clients which accept data encoded in gzip format (by searching for the field **Accept-Encoding** in the request header and checking whether it contains the value **gzip**), responds to requests from these clients with the line

Content-Encoding: gzip

in the response header and correctly compresses the content in the body into that format.

Test this feature by requesting files from your server using a web browser, for instance Firefox!

Client

- **Decompression (4):** Implement decompression of content in the gzip format. Make use of the zlib compression library (see sect. "Using zlib") for decompressing the data.

4 bonus points are awarded if your client advertises this capability with the line

Accept-Encoding: gzip

in the request header and is able to correctly decompress content sent with that encoding.

Test this feature by requesting files from a web server which supports gzip, such as <http://pan.vmars.tuwien.ac.at/osue/> (note that this server only compresses text files).

Using zlib

zlib⁴ is pre-installed on most UNIX systems. You can use it by including the **zlib.h** header:

```
#include <zlib.h>
```

Also, you will have to link the zlib library by adding **-lz** to your linker options. Make sure to test this in the TILAB in order to avoid linker warnings or errors.

³ Media type, a two-part identifier for file formats, see https://en.wikipedia.org/wiki/Media_type

⁴<http://zlib.net/>

Coding Rules and Guidelines

Your score depends upon the compliance of your submission to the presented guidelines and rules. Violations result in deductions of points. Hence, before submitting your solution, go through the following list and check if your program complies.

Rules

Compliance with these rules is essential to get any points for your submission. In other words, a violation of any of the following rules results in 0 points for your submission.

1. The program must compile via

```
$ gcc -std=c99 -pedantic -Wall -D.DEFAULT_SOURCE -D.BSD_SOURCE -D.SVID_SOURCE  
-D.POSIX_C_SOURCE=200809L -g -c filename.c
```

without *errors*. These flags must be used in the Makefile, of course. The feature test macros must not be bypassed (i.e., by undefining these macros or adding some in the C source code).

2. The functionality of the program must conform to the assignment. The program shall operate according to the specification/assignment given the test cases in the respective assignment.

General Guidelines

Violation of following guidelines leads to a deduction of points.

1. The program must compile with

```
$ gcc -std=c99 -pedantic -Wall -D.DEFAULT_SOURCE -D.BSD_SOURCE -D.SVID_SOURCE  
-D.POSIX_C_SOURCE=200809L -g -c filename.c
```

without *warnings and info messages*.

2. There must be a Makefile for the program implementing the targets: **all** to build the program from the sources (this must be the first target in the Makefile); **clean** to delete all files that can be built from your sources with the Makefile.
3. The program shall operate according to the specification/assignment without major issues (e.g., segmentation fault, memory corruption).
4. Arguments have to be parsed according to UNIX conventions (we strongly encourage the use of **getopt(3)**). The program has to conform to the given synopsis/usage in the assignment. If the synopsis is violated (e.g., unspecified options or too many arguments), the program has to terminate with the usage message containing the program name and the correct calling syntax. Argument handling should also be implemented for programs without arguments.
5. Correct (=normal) termination, including a cleanup of resources.
6. Upon success the program has to terminate with exit code 0, in case of errors with an exit code greater than 0. We recommend to use the macros **EXIT_SUCCESS** and **EXIT_FAILURE** (defined in **stdlib.h**) to enable portability of the program.
7. If a function indicates an error with its return value, it *should* be checked in general. If the subsequent code depends on the successful execution of a function (e.g. resource allocation), then the return value *must* be checked.

8. Functions that do not take any parameters have to be declared with **void** in the signature, e.g., `int get_random_int(void);`.
9. Procedures (i.e., functions that do not return a value) have to be declared as **void**.
10. Error messages shall be written to **stderr** and should contain the program name **argv[0]**.
11. It is forbidden to use the functions: **gets**, **scanf**, **fscanf**, **atoi** and **atol** to avoid crashes due to invalid inputs.

FORBIDDEN	USE INSTEAD
<code>gets</code>	<code>fgets</code>
<code>scanf</code>	<code>fgets</code> , <code>sscanf</code>
<code>fscanf</code>	<code>fgets</code> , <code>sscanf</code>
<code>atoi</code>	<code>strtol</code>
<code>atol</code>	<code>strtol</code>

12. Documentation is mandatory. Format the documentation in Doxygen style (see Wiki and Doxygen's intro).
13. Write meaningful comments. For example, meaningful comments describe the algorithm, or why a particular solution has been chosen, if there seems to be an easier solution at a first glance. Avoid comments that just repeat the code itself (e.g., `i = i + 1; /* i is incremented by one */`).
14. The documentation of a module must include: name of the module, name and student id of the author (**@author** tag), purpose of the module (**@brief**, **@details** tags) and creation date of the module (**@date** tag).
Also the Makefile has to include a header, with author and program name at least.
15. Each function shall be documented either before the declaration or the implementation. It should include purpose (**@brief**, **@details** tags), description of parameters and return value (**@param**, **@return** tags) and description of global variables the function uses (**@details** tag).
You should also document **static** functions (see **EXTRACT_STATIC** in the file **Doxyfile**). Document visible/exported functions in the header file and local (**static**) functions in the C file. Document variables, constants and types (especially **structs**) too.
16. Documentation, names of variables and constants shall be in English.
17. Internal functions shall be marked with the **static** qualifier and are not allowed to be exported (e.g., in a header file). Only functions that are used by other modules shall be declared in the header file.
18. All exercises shall be solved with functions of the C standard library. If a required function is not available in the standard library, you can use other (external) functions too. Avoid reinventing the wheel (e.g., re-implementation of **strcmp**).
19. Name of constants shall be written in upper case, names of variables in lower case (maybe with first letter capital).
20. Use meaningful variable and constant names (e.g., also semaphores and shared memories).
21. Avoid using global variables as far as possible.
22. All boundaries shall be defined as constants (macros). Avoid arbitrary boundaries. If boundaries are necessary, treat its crossing.
23. Avoid side effects with **&&** and **||**, e.g., write `if (b != 0) c = a/b;` instead of `if (b != 0 && c = a/b).`

24. Each `switch` block must contain a `default` case. If the case is not reachable, write `assert(0)` to this case (defensive programming).
25. Logical values shall be treated with logical operators, numerical values with arithmetic operators (e.g., test 2 strings for equality by `strcmp(...) == 0` instead of `!strcmp(...)`).
26. Indent your source code consistently (there are tools for that purpose, e.g., `indent`).
27. Avoid tricky arithmetic statements. Programs are written once, but read more times. Your program is not better if it is shorter!
28. For all I/O operations (read/write from/to `stdin`, `stdout`, files, sockets, pipes, etc.) use *either* standard I/O functions (`fdopen(3)`, `fopen(3)`, `fgets(3)`, etc.) *or* POSIX functions (`open(2)`, `read(2)`, `write(2)`, etc.). Remember, standard I/O functions are buffered. Mixing standard I/O functions and POSIX functions to access a common file descriptor can lead to undefined behaviour and is therefore forbidden.
29. If asked in the assignment, you must implement signal handling (`SIGINT`, `SIGTERM`). You must only use *async-signal-safe* functions in your signal handlers.
30. Close files, free dynamically allocated memory, and remove resources after usage.
31. Don't waste resources due to inconvenient programming. Header files shall not include implementation parts (exception: macros).

Exercise 1 Guidelines

No additional guidelines, but note that correct argument parsing and sockets (1B) will be the main focus.