

b.

The recursive procedure forms a tree with branching factor 4 (4 possible activity), with each branch created by either full service, regular service, minor service and no service. From the root, we start with 1 node, then on the next level, we will have 4 nodes, and then the next level, will be 16 nodes, and so on. With couple more levels, we can summarize there is a geometric series:

To calculate the total number of nodes in the tree after k depth (levels), we sum the geometric series.

$$\sum_{i=0}^k 4^i = 1 + 4 + 4^2 + 4^3 + \dots + 4^k = \frac{4^{k+1} - 1}{4 - 1} = \frac{4^{k+1} - 1}{3}$$

This give us an asymptotic lower bound $\Omega(4^k)$ on the worse case time complexity.

d.

From the procedure of implementation of building the bottom-up table below:

```
for (int i(current hour) = k - 1(last hour); i >= 0; i--) {
    for (int h(hours since service) = 0; h <= i + 1; h++) {
        // add to table
    }
}
```

We can write the two for loop into mathematic form which is equivalent to

$$\begin{aligned} \sum_{i=0}^{k-1} \sum_{h=0}^i 1 &= \sum_{i=1}^k \sum_{h=1}^{i+1} 1 = \sum_{i=1}^k (i+1) \\ \sum_{i=1}^k i + \sum_{i=1}^k 1 &= \left(\sum_{i=1}^k i \right) + k \\ \frac{k(k+1)}{2} + k &= \frac{k^2 + k}{2} + k = \frac{k^2 + 3k}{2} \end{aligned}$$

his give us an asymptotic upper-bound $O(k^2)$ on the worse case time complexity.