Real-Time Luxury Auction Engine

Core Engine, Bidding Lua, Server-Sent Events (SSE) & API Implementation

Metadata	Value
Prepared By :	System Architecture & Delivery Team
Date :	24 Oct 2026
Version :	2.0
Classification :	Strictly Confidential / Technical Specification

1. Governance

1.1 Contributors

Name	Position
Daniel H. S.	System Analyst / Solution Architect
Alini	Technical Lead
Geri Setyo Andrian	Project Manager

1.2 Approvals

Name	Position	Date	Signature
Geri Setyo Andrian	Project Manager Delivery Team	24 Oct 2026	`[ APPROVED & SIGNED ]`
Alini	Technical Architect / Tech Lead Delivery Team	24 Oct 2026	`[ APPROVED & SIGNED ]`
Daniel H. S.	System Analyst Delivery Team	24 Oct 2026	`[ APPROVED & SIGNED ]`

1.3 Revision History

Version	Date	Author	Summary of Changes
0.1	24 Oct 2026	Daniel H. S.	Initial Technical Draft (Components & Goroutines)
0.5	24 Oct 2026	Daniel H. S.	Added Lua Scripting Logic, Settlement Daemon, and 14 API Endpoints
1.0	24 Oct 2026	Daniel H. S.	Baseline Alignment with Enterprise Template Structure & Sign-Off
2.0	24 Oct 2026	Daniel H. S.	**Deep Technical Refinement:** Transisi WebSocket ke Server-Sent Events (SSE HTTP/2), full code Lua atomik, struktur Go struct murni, kontrak teknis 14 API dengan standar envelope BE (`success`/`error`), dan manajemen auto-logout JWT versi Redis.

2. Table of Contents

- [1. Governance](#1-governance)

- [1.1 Contributors](#11-contributors)

- [1.2 Approvals](#12-approvals)

- [1.3 Revision History](#13-revision-history)

- [2. Table of Contents](#2-table-of-contents)

- [3. Introduction & Technical Architecture Stack](#3-introduction--technical-architecture-stack)

- [3.1 Low-Level Design Overview](#31-low-level-design-overview)

- [3.2 Technology Stack Details](#32-technology-stack-details)

- [3.3 Glossaries](#33-glossaries)

- [3.4 Standard Response Envelope & Monetary Format](#34-standard-response-envelope--monetary-format)

- [3.5 References](#35-references)

- [4. System & Integration Landscape](#4-system--integration-landscape)

- [4.1 Component Interaction Diagram](#41-component-interaction-diagram)

- [4.2 Impacted Objects & Detailed Functionality](#42-impacted-objects--detailed-functionality)

- [4.3 Go Domain Models (Pure Structs)](#43-go-domain-models-pure-structs)

- [5. Detailed Sequence Diagrams & Algorithms](#5-detailed-sequence-diagrams--algorithms)

- [5.1 Incremental Bid Execution (bid_placement.lua)](#51-incremental-bid-execution-bid_placementlua)

- [5.2 Settlement Daemon Expiry Flow](#52-settlement-daemon-expiry-flow)

- [5.3 Role Promotion & Mandatory Auto-Logout Sequence](#53-role-promotion--mandatory-auto-logout-sequence)

- [6. Application Interfaces & API Contracts](#6-application-interfaces--api-contracts)

- [6.1 Complete Endpoint Specifications](#61-complete-endpoint-specifications)

- [6.2 Server-Sent Events (SSE) Protocol & Broadcast Hub](#62-server-sent-events-sse-protocol--broadcast-hub)

- [7. In-Memory, Caching & Data Structures](#7-in-memory-caching--data-structures)

- [7.1 Complete Lua Script: bid_placement.lua](#71-complete-lua-script-bid_placementlua)

- [7.2 Redis Key Schema & TTL Management](#72-redis-key-schema--ttl-management)

- [8. State Machine & Lifecycle Specifications](#8-state-machine--lifecycle-specifications)

- [9. Document Sign-Off Section](#9-document-sign-off-section)

3. Introduction & Technical Architecture Stack

3.1 Low-Level Design Overview

Dokumen Low-Level Design (LLD) ini menguraikan spesifikasi implementasi perangkat lunak pada tingkat kode, modul Go, skrip in-memory Redis Lua, antarmuka REST API, streaming **Server-Sent Events (SSE)**, serta state machine database relasional untuk **Real-Time Luxury Auction Engine**.

3.2 Technology Stack Details

Platform dibangun menggunakan arsitektur enterprise modern dengan standar performa dan konkurensi tinggi:

- **Backend Runtime:** Go (Golang) v1.22+ menggunakan router berperforma tinggi (`Chi` / `Gin`) dengan concurrency berbasis Goroutine dan Channels.
- **In-Memory Cache & Mutex:** Redis v7.2 Cluster (Replication Mode) dengan *Lua Engine* untuk eksekusi atomik hot-path penawaran lelang (< 5 ms execution time) dan Pub/Sub message broker.
- **Authoritative Database:** PostgreSQL v16 dengan konfigurasi ACID transaction level `SERIALIZABLE` untuk mutasi saldo e-wallet dan double-entry ledger.
- **Real-Time Streaming:** **Server-Sent Events (SSE)** berjalan di atas **HTTP/2** persisten (`text/event-stream`), ramah terhadap enterprise firewall, proxy WAF, dan hemat bandwidth dibandingkan WebSocket konvensional.
- **Identity & Authentication:** Dual-method Authentication: NIRO OAuth2 SSO untuk `BIDDER` & `ADMIN` (Auction Manager), serta Email & Password dengan PBKDF2/Argon2id dan Progressive Lockout untuk `SUPERADMIN`.
- **Image Storage Engine:** Kolom PostgreSQL `BYTEA` (Binary Large Object) yang disimpan langsung di database tanpa ketergantungan storage S3 pihak ketiga, di-serve ke frontend sebagai string terkompresi Base64.
- **Frontend Web Application:** Next.js v14+ (React 18, TypeScript, Tailwind CSS) dengan modul HTML5 `EventSource` untuk konsumsi stream SSE lelang.

3.3 Glossaries

No	Terms	Expansion	Definition
1	**SSE**	Server-Sent Events	Protokol streaming data satu arah (Server-to-Client) berbasis HTTP/2 persisten (`text/event-stream`) dengan auto-reconnect bawaan peramban.
2	**EVALSHA**	Evaluate SHA1 Digest	Perintah Redis untuk mengeksekusi skrip Lua yang telah di-cache server secara atomic tanpa overhead transfer skrip berulang.
3	**BYTEA**	Byte Array	Tipe data kolom PostgreSQL untuk menyimpan representasi biner gambar produk secara langsung di database.
4	**ZSET**	Sorted Set	Struktur data Redis berurutan berdasarkan score waktu untuk tracking expiry lelang secara real-time.
5	**float64**	64-bit IEEE 754 Floating-Point	Tipe data standar pada Go/JSON untuk merepresentasikan seluruh nilai moneter rupiah dan saldo akun secara presisi.
6	**Token Revocation**	Pembatalan Sesi Instan	Mekanisme pembatalan JWT seketika menggunakan versioning key di Redis (`token_version:{user_id}`) saat role user dinaikkan.

3.4 Standard Response Envelope & Monetary Format

Sesuai standar Backend Coding Guidelines:

1. **Respon Sukses (HTTP 200 / 201):**

```json
{
"status": "success",
"data": {}
}
```

2. **Respon Gagal (HTTP 4xx / 5xx):**

```json
{
"status": "error",
"error": {
"code": "ERROR_CODE_STRING",
"message": "Pesan deskriptif dalam Bahasa Indonesia"
}
}
```

3. **Format Moneter:** Seluruh field moneter (`available_balance`, `locked_balance`, `current_price`, `bid_amount`, `min_price`, `max_price`) wajib menggunakan representasi numerik desimal `float64` tanpa pembulatan integer parsial.

3.5 References

- **High-Level Design Document:** [`high-level-design.md`](file:///d:/Projects/Salt-Hackaton-2026/02_Projects/real-time-auction-engine/04_Design/high-level-design.md)
- **Database Schema & Redis Lua Design:** [`database-schema.md`](file:///d:/Projects/Salt-Hackaton-2026/02_Projects/real-time-auction-engine/06_Data_Design/database-schema.md)
- **API Contracts Specification:** [`api-contracts.md`](file:///d:/Projects/Salt-Hackaton-2026/02_Projects/real-time-auction-engine/05_Integration/api-contracts.md)

---

4. System & Integration Landscape

4.1 Component Interaction Diagram

Arsitektur internal modul Go dan transport Server-Sent Events (SSE):

```
flowchart TD
    subgraph Client ["Client Presentation"]
        NextJS["Next.js Web App (EventSource SSE)"]
    end

    subgraph Transport ["Transport Layer (Go Chi / Gin)"]
        HTTPHandler["REST API Handler (JSON Envelope)"]
        SSEHub["SSE Event Hub Broadcaster (text/event-stream)"]
    end

    subgraph Usecase ["Application Usecase Layer"]
        AuthUC["Auth & Session Usecase"]
        BidUC["Bid Engine & Proxy Usecase"]
        LotUC["Auction Lot Management Usecase"]
        WalletUC["Wallet & Collateral Usecase"]
        SettleDaemon["Settlement Daemon (Ticker 1s)"]
    end

    subgraph Memory ["In-Memory Data Tier (Redis 7)"]
        LuaEngine["Lua Atomic Script (bid_placement.lua)"]
        PubSub["Redis Pub/Sub (auction:{id}:events)"]
        ExpiryZSet["Expiry Index (auctions:expiry_zset)"]
        SessionStore["Token Version & Progressive Lockout"]
    end

    subgraph Storage ["Persistent Storage Tier (PostgreSQL 16)"]
        PGUsers["users (NIRO & Superadmin)"]
        PGWallets["wallets & ledger_entries (ACID Ledger)"]
        PGAuctions["auctions (image_data BYTEA)"]
        PGBids["bids & asset_ownership"]
    end

    NextJS ⟶|HTTP POST/GET| HTTPHandler
    NextJS ⟶|GET text/event-stream| SSEHub

    HTTPHandler ⟶ AuthUC
    HTTPHandler ⟶ BidUC
    HTTPHandler ⟶ LotUC
    HTTPHandler ⟶ WalletUC

    AuthUC ⟶ SessionStore
    AuthUC ⟶ PGUsers

    BidUC ⟶ LuaEngine
    LuaEngine ⟶ PubSub
    LuaEngine ⟶ ExpiryZSet

    PubSub ⟶|Subscription Stream| SSEHub

    SettleDaemon ⟶ ExpiryZSet
    SettleDaemon ⟶ PGWallets
    SettleDaemon ⟶ PGAuctions
    SettleDaemon ⟶ PGBids
```

4.2 Impacted Objects & Detailed Functionality

No	Impact	Object Name	Functions & Technical Details
1	**New**	`internal/domain`	Definisi Go struct murni: `User`, `Wallet`, `Auction`, `Bid`, `LedgerEntry` dengan strict tipe moneter `float64`.
2	**New**	`internal/usecase/bid`	Validasi kelipatan tombol bertingkat diskrit, kalkulasi instant buy-out ceiling, dan orkestrasi skrip Redis Lua atomik.
3	**New**	`internal/usecase/auth`	Login NIRO SSO, progressive lockout Superadmin (1m $\rightarrow$ 2m $\rightarrow$ 1h), serta **Token Revocation (Auto-Logout)** via versioning key Redis.
4	**New**	`internal/repository/redis`	Eksekusi EVALSHA `bid_placement.lua`, pool koneksi Redigo/go-redis, Sorted Set expiry (`ZRANGEBYSCORE`), dan pub/sub channel.
5	**New**	`internal/transport/sse`	Multiplexing koneksi client persistent HTTP `text/event-stream`, event dispatcher fan-out, dan heartbeat pulse ping setiap 15 detik.
6	**New**	`internal/daemon/settlement`	Daemon berjadwal per 1 detik yang membaca lelang kedaluwarsa, mengunci lelang via distributed lock, dan menyelesaikan mutasi ACID.

4.3 Go Domain Models (Pure Structs)

```
package domain

import (
	"time"
	"github.com/google/uuid"
)

type Role string

const (
	RoleBidder     Role = "BIDDER"
	RoleAdmin      Role = "ADMIN"      // Auction Manager
	RoleSuperAdmin Role = "SUPERADMIN"
)

type User struct {
	ID           uuid.UUID `json:"id"`
	NiroUserID   *string   `json:"niro_user_id,omitempty"`
	Username     string    `json:"username"`
	Email        string    `json:"email"`
	PasswordHash *string   `json:"-"`
	AuthProvider string    `json:"auth_provider"` // "NIRO" | "LOCAL"
	Role         Role      `json:"role"`
	TokenVersion int64     `json:"token_version"`
	CreatedAt    time.Time `json:"created_at"`
	UpdatedAt    time.Time `json:"updated_at"`
}

type Wallet struct {
	ID               uuid.UUID `json:"id"`
	UserID           uuid.UUID `json:"user_id"`
	AvailableBalance float64   `json:"available_balance"` // float64 mandatory
	LockedBalance    float64   `json:"locked_balance"`    // float64 mandatory
	Version          int64     `json:"version"`
	UpdatedAt        time.Time `json:"updated_at"`
}

type AuctionModel string
type AuctionStatus string
type AssetCategory string

const (
	ModelUncapped AuctionModel = "UNCAPPED"
	ModelCapped   AuctionModel = "CAPPED"

	StatusDraft         AuctionStatus = "DRAFT"
	StatusActive        AuctionStatus = "ACTIVE"
	StatusClosedAwarded AuctionStatus = "CLOSED_AWARDED"
	StatusSettled       AuctionStatus = "SETTLED"
	StatusExpiredUnsold AuctionStatus = "EXPIRED_UNSOLD"

	CatWatches     AssetCategory = "LUXURY_WATCHES"
	CatBags        AssetCategory = "DESIGNER_BAGS"
	CatJewelry     AssetCategory = "FINE_JEWELRY"
	CatVehicles    AssetCategory = "COLLECTIBLE_VEHICLES"
	CatMemorabilia AssetCategory = "RARE_MEMORABILIA"
)

type Auction struct {
	ID                          uuid.UUID     `json:"id"`
```

```
        Title                       string         `json:"title"`
        Category                    AssetCategory  `json:"category"`
        ConditionGrade              string         `json:"condition_grade"`
        AuthenticityGuarantee       string         `json:"authenticity_guarantee"`
        Description                 string         `json:"description"`
        ImageData                   []byte         `json:"-"`                    // Stored as BYTEA in DB
        ImageMimeType               string         `json:"image_mime_type"`
        MinPrice                    float64        `json:"min_price"`            // float64
        AllowedIncrementSteps       []float64      `json:"allowed_increment_steps"` // float64 array
        MaxPrice                    *float64       `json:"max_price,omitempty"`  // Buyout Ceiling
        CurrentPrice                float64        `json:"current_price"`        // float64
        StartTime                   time.Time      `json:"start_time"`
        EndTime                     time.Time      `json:"end_time"`
        AntiSnipingExtensionMinutes int            `json:"anti_sniping_extension_minutes"`
        HighestBidderID             *uuid.UUID     `json:"highest_bidder_id,omitempty"`
        ModelType                   AuctionModel   `json:"model_type"`
        Status                      AuctionStatus  `json:"status"`
        CreatedBy                   uuid.UUID      `json:"created_by"`
        CreatedAt                   time.Time      `json:"created_at"`
        UpdatedAt                   time.Time      `json:"updated_at"`
}
```

5. Detailed Sequence Diagrams & Algorithms

5.1 Incremental Bid Execution (bid_placement.lua)

```
sequenceDiagram
    autonumber
    participant UI as Next.js Client
    participant API as Bid Usecase
    participant Lua as Redis (bid_placement.lua)
    participant PS as Redis Pub/Sub
    participant SSE as SSE Broadcast Hub
    participant PG as PostgreSQL (bids log)

    UI->>API: POST /api/v1/auctions/{id}/bids {step_increment: 5000000.00}
    API->>API: Validasi role == 'BIDDER' & step_increment terdaftar di allowed_increment_steps
    API->>API: Hitung new_price = current_price + step_increment
    API->>Lua: EVALSHA bid_placement.lua (user_id, lot_id, new_price, now_ms)

    critical Atomic Lua Execution (< 5 ms)
        Lua->>Lua: Cek lot status == 'ACTIVE' & now_ms < end_time
        Lua->>Lua: Cek new_price ≥ (current_price + min_increment)
        Lua->>Lua: Cek wallet available_balance ≥ new_price
        Lua->>Lua: HINCRBYFLOAT available_balance -new_price
        Lua->>Lua: HINCRBYFLOAT locked_balance +new_price
        Lua->>Lua: Catatan: Dana penawar sebelumnya TIDAK di-release (Hold During Auction)
        Lua->>Lua: Evaluasi Anti-Sniping (Sisa waktu ≤ 120s & Velocity ≥ 10 bid/s)
        Lua->>Lua: Jika triggered: end_time = end_time + extend_ms & update ZSET
        Lua->>Lua: Evaluasi Capped Ceiling (jika new_price ≥ ceiling → status = CLOSED_AWARDED)
        Lua->>Lua: Simpan current_price & highest_bidder_id
    end

    Lua-->>API: Return {new_price, new_end_time, is_extended, is_buyout}
    API->>PS: PUBLISH auction:{id}:events {payload JSON}
    PS->>SSE: Relay event frame
    SSE-->>UI: event: PRICE_UPDATED (Push to connected browsers via SSE < 300 ms)
    API-)PG: Async insert log into bids table
    API-->>UI: 200 OK {"status": "success", "data": {"bid_status": "ACCEPTED"}}
```

5.2 Settlement Daemon Expiry Flow

```
sequenceDiagram
    autonumber
    participant Daemon as Settlement Daemon (Ticker 1s)
    participant Redis as Redis ZSET & Keys
    participant Lock as Redis Distributed Lock
    participant DB as PostgreSQL (ACID Ledger)
    participant SSE as SSE Broadcast Hub

    Daemon->>Redis: ZRANGEBYSCORE auctions:expiry_zset -inf (now_timestamp)
    Redis-->>Daemon: Daftar lot_id yang kedaluwarsa
    loop Setiap Lot Kedaluwarsa
        Daemon->>Lock: SET lock:settle:{lot_id} "active" NX EX 10
        alt Berhasil Dapatkan Lock
            Daemon->>Redis: HGETALL auction:{lot_id}
            Redis-->>Daemon: Data pemenang akhir & harga lelang
            Daemon->>DB: BEGIN TRANSACTION (ISOLATION LEVEL SERIALIZABLE)
            Daemon->>DB: Potong permanen locked_balance pemenang (insert AUCTION_WIN_PAYMENT)
            Daemon->>DB: Ubah status auction menjadi 'SETTLED'
            Daemon->>DB: Terbitkan kepemilikan di asset_ownership
            Daemon->>DB: Release 100% held locked_balance seluruh penawar yang kalah ke available_balance
            Daemon->>DB: COMMIT TRANSACTION
            Daemon->>Redis: DEL auction:{lot_id} & ZREM auctions:expiry_zset {lot_id}
            Daemon->>Lock: DEL lock:settle:{lot_id}
            Daemon->>SSE: Broadcast AUCTION_CONCLUDED event via SSE
        else Gagal Mendapatkan Lock
            Note over Daemon: Lot sedang diproses oleh instance daemon lain
        end
    end
```

5.3 Role Promotion & Mandatory Auto-Logout Sequence

Ketika Superadmin mempromosikan user dari `BIDDER` menjadi `ADMIN` (Auction Manager), sesi lama user wajib dibatalkan seketika agar hak akses lama tidak disalahgunakan.

```
sequenceDiagram
    autonumber
    actor Super as Superadmin Platform
    participant UI as Admin Console
    participant UC as AdminUserUsecase
    participant Redis as Redis Session Cache
    participant DB as PostgreSQL
    actor User as Pengguna (Mantan Bidder)

    Super->>UI: Klik Promosikan ke Auction Manager (ADMIN)
    UI->>UC: PATCH /api/v1/admin/users/{id}/role {role: "ADMIN"}
    UC->>DB: UPDATE users SET role = 'ADMIN', updated_at = NOW() WHERE id = $1
    UC->>Redis: INCR token_version:{user_id}
    Note over Redis: Token JWT lama otomatis INVALID karena token_version di JWT < token_version di Redis
    UC-->>UI: 200 OK {"status": "success", "data": {"user_id": "...", "new_role": "ADMIN"}}

    par Klien Pengguna Mencoba Akses
        User->>UC: Request API dengan Token JWT Lama
        UC->>Redis: GET token_version:{user_id}
        Redis-->>UC: Version Mismatch (Revoked)
        UC-->>User: 401 Unauthorized {"status": "error", "error": {"code": "AUTH_TOKEN_REVOKED", "message":
        User->>User: Auto-Logout & Redirect ke Halaman Login NIRO
    end
```

6. Application Interfaces & API Contracts

6.1 Complete Endpoint Specifications

Seluruh 14 endpoint implementasi transport API pada sistem dirancang dengan standar HTTP status, role authorization, dan response envelope baku:

Method	Endpoint	Role	Deskripsi Teknis & Kontrak
`GET`	`/api/v1/auth/niro/authorize-url`	Publik	Mendapatkan redirect URL resmi NIRO SSO beserta CSRF state token.
`POST`	`/api/v1/auth/login/niro`	Publik	Menerima `niro_token`. Jika baru, auto-register role `BIDDER`; jika terdaftar, buat sesi JWT dan load saldo dompet (`float64`).
`POST`	`/api/v1/auth/login/email`	Publik	Login email & password khusus `SUPERADMIN` (min. 12 karakter) dengan progressive lockout berbasis Redis TTL.
`GET`	`/api/v1/admin/users`	`SUPERADMIN`	Mengambil daftar direktori pengguna NIRO (lengkap dengan pagination meta).
`PATCH`	`/api/v1/admin/users/:id/role`	`SUPERADMIN`	Mempromosikan role user menjadi `ADMIN` (Auction Manager) & memicu auto-logout via `token_version` Redis.
`GET`	`/api/v1/wallet/me`	`BIDDER`	Mengambil saldo likuid (`available_balance`) dan tertahan (`locked_balance`) tipe `float64`.
`POST`	`/api/v1/wallet/topup`	`BIDDER`	Menambah saldo dompet khusus penawar (minimal deposit Rp 100.000,00, kelipatan rupiah utuh).
`GET`	`/api/v1/auctions/active`	Publik	Daftar lot barang mewah aktif, pagination meta, dan thumbnail Base64 terkompresi.
`GET`	`/api/v1/auctions/:id`	Publik	Detail lengkap lot, foto Base64 utuh, step increment tombol diskrit, jaminan keaslian, dan aturan lelang.
`POST`	`/api/v1/auctions/:id/bids`	`BIDDER`	Mengirim penawaran tombol bertingkat diskrit; mengeksekusi skrip Lua atomik, validasi buy-out & anti-sniping.
`POST`	`/api/v1/auctions/:id/proxy-bid`	`BIDDER`	Mengonfigurasi bot penawaran proxy otomatis dengan batas limit maksimal (`max_limit`).
`DELETE`	`/api/v1/auctions/:id/proxy-bid`	`BIDDER`	Membatalkan / mematikan bot penawaran proxy otomatis pada lot tertentu.
`POST`	`/api/v1/admin/auctions`	`ADMIN`	Membuat listing lot baru via `multipart/form-data`, file gambar biner langsung disimpan ke kolom PostgreSQL `BYTEA`.
`GET`	`/api/v1/sse/auctions/:id`	Universal	**Server-Sent Events (SSE):** Streaming mutasi harga, countdown timer, dan event lelang per lot lelang.
`GET`	`/api/v1/sse/catalog`	Universal	**Server-Sent Events (SSE):** Streaming ticker pembaruan katalog global di beranda / marketplace.

6.2 Server-Sent Events (SSE) Protocol & Broadcast Hub

Sistem secara ketat menggunakan **Server-Sent Events (SSE)** sebagai pengganti WebSocket untuk penyiaran data real-time:

- **Header HTTP Server:**

```http
```

HTTP/1.1 200 OK

Content-Type: text/event-stream

Cache-Control: no-cache

Connection: keep-alive

X-Accel-Buffering: no

Access-Control-Allow-Origin: *

```

- **Koneksi Room Lot:** `GET /api/v1/sse/auctions/:id`
- **Koneksi Global Catalog:** `GET /api/v1/sse/catalog`
- **Heartbeat Ping:** Setiap 15 detik, server mengirim komentar `: ping\n\n` untuk mencegah pemutusan koneksi oleh NAT/Load Balancer.
- **Auto-Reconnect:** Peramban Next.js menggunakan antarmuka native `EventSource`. Jika koneksi terputus, peramban otomatis menyambung ulang dengan menyertakan header `Last-Event-ID`.

### Payload Event Streaming Resmi:

#### 1. Event `PRICE_UPDATED` (Penawaran Baru Sah)

```
event: PRICE_UPDATED
id: 1729782400123
data: {"lot_id":"e0b9b3e1-872b-42e7-91a6-f7615cb38421","current_price":360000000.00,"highest_bidder_id":"3f
```

#### 2. Event `TIME_EXTENDED` (Anti-Sniping Triggered)

```
event: TIME_EXTENDED
id: 1729782415456
data: {"lot_id":"e0b9b3e1-872b-42e7-91a6-f7615cb38421","extension_minutes":2,"new_end_time":"2026-10-25T14:
```

3. Event `AUCTION_BUYOUT_CLOSED` (Instant Buyout Tercapai)

```
event: AUCTION_BUYOUT_CLOSED
id: 1729782420789
data: {"lot_id":"e0b9b3e1-872b-42e7-91a6-f7615cb38421","winner_id":"3fa85f64-5717-4562-b3fc-2c963f66afa6","
```

4. Event `AUCTION_CONCLUDED` (Lelang Selesai & Settle Selesai)

```
event: AUCTION_CONCLUDED
id: 1729782490000
data: {"lot_id":"e0b9b3e1-872b-42e7-91a6-f7615cb38421","final_price":360000000.00,"winner_id":"3fa85f64-571
```

```

7. In-Memory, Caching & Data Structures

7.1 Complete Lua Script: bid_placement.lua

Skrip berikut dieksekusi secara atomik di dalam engine memori Redis melalui perintah `EVALSHA`:

```
-- KEYS: [1] auction_key, [2] bidder_wallet_key, [3] expiry_zset, [4] velocity_key
-- ARGV: [1] bidder_id, [2] bid_amount, [3] now_ms, [4] extension_minutes

local auction = redis.call('HMGET', KEYS[1], 'status', 'current_price', 'min_increment', 'end_time', 'model
local status = auction[1]
local current_price = tonumber(auction[2] or '0')
local min_increment = tonumber(auction[3] or '0')
local end_time = tonumber(auction[4] or '0')
local model_type = auction[5]
local valuation_ceiling = tonumber(auction[6] or '0')

local bidder_id = ARGV[1]
local bid_amount = tonumber(ARGV[2])
local now_ms = tonumber(ARGV[3])
local extension_minutes = tonumber(ARGV[4] or '2')

-- 1. Validasi Status Lelang dan Waktu Aktif
if status ~= 'ACTIVE' or now_ms ≥ end_time then
    return redis.error_reply("ERR_AUCTION_NOT_ACTIVE")
end

-- 2. Validasi Kenaikan Harga (Harus ≥ current_price + min_increment)
if bid_amount < (current_price + min_increment) then
    return redis.error_reply("ERR_BID_TOO_LOW")
end

-- 3. Validasi Saldo Likuid Penawar Baru
local available_bal = tonumber(redis.call('HGET', KEYS[2], 'available_balance') or '0')
if available_bal < bid_amount then
    return redis.error_reply("ERR_INSUFFICIENT_COLLATERAL")
end

-- 4. Kunci Agunan Penawar Baru Secara Atomik
redis.call('HINCRBYFLOAT', KEYS[2], 'available_balance', -bid_amount)
redis.call('HINCRBYFLOAT', KEYS[2], 'locked_balance', bid_amount)

-- CATATAN ATURAN BISNIS HACKATHON 2026:
-- Saldo penawar sebelumnya TIDAK dilepaskan (Hold During Bidding).
-- Seluruh dana peserta tetap tertahan di locked_balance sampai lelang berakhir (Settled).

-- 5. Evaluasi Anti-Sniping (Critical Zone 2 Menit Terakhir = 120.000 ms)
local is_extended = 0
local new_end_time = end_time
local remaining_time_ms = end_time - now_ms

if remaining_time_ms ≤ 120000 then
    -- Hitung velositas bid dalam sliding window 1 detik via Redis sliding window counter
    local current_sec = math.floor(now_ms / 1000)
    local hits = redis.call('INCR', KEYS[4] .. ':' .. current_sec)
    redis.call('EXPIRE', KEYS[4] .. ':' .. current_sec, 5)

    if hits ≥ 10 then
        -- Lonjakan frekuensi penawaran ≥ 10 hit/detik → Perpanjang waktu lelang
        local extension_ms = extension_minutes * 60 * 1000
        new_end_time = end_time + extension_ms
        is_extended = 1
        redis.call('HSET', KEYS[1], 'end_time', tostring(new_end_time))
        redis.call('ZADD', KEYS[3], new_end_time, KEYS[1]) -- Update expiry score di ZSET
    end
end

-- 6. Evaluasi Capped Valuation Ceiling (Buyout)
```

```
local is_buyout = 0
if model_type == 'CAPPED' and valuation_ceiling > 0 and bid_amount ≥ valuation_ceiling then
    is_buyout = 1
    redis.call('HSET', KEYS[1], 'status', 'CLOSED_AWARDED')
    redis.call('ZREM', KEYS[3], KEYS[1]) -- Hapus dari active expiry ZSET
end

-- 7. Perbarui Penawar Tertinggi dan Harga Terkini
redis.call('HMSET', KEYS[1], 'current_price', tostring(bid_amount), 'highest_bidder_id', bidder_id)

-- Return hasil eksekusi: {bid_amount, new_end_time, is_extended, is_buyout}
return {tostring(bid_amount), tostring(new_end_time), is_extended, is_buyout}
```

7.2 Redis Key Schema & TTL Management

Key Name Pattern	Redis Type	TTL	Penjelasan & Struktur Data
`auction:{lot_id}`	`HASH`	No TTL (Persistent selama aktif)	Fields: `status`, `current_price`, `min_increment`, `end_time`, `highest_bidder_id`, `model_type`, `valuation_ceiling`.
`wallet:{user_id}`	`HASH`	No TTL	Fields: `available_balance`, `locked_balance` (selalu dihitung via `HINCRBYFLOAT`).
`auctions:expiry_zset`	`ZSET`	Persistent Index	Score: `end_time` (epoch milliseconds), Member: `{lot_id}`. Digunakan oleh Settlement Daemon.
`auction:velocity:{lot_id}:{sec}`	`STRING`	5 detik	Counter sliding window integer penawaran per detik untuk evaluasi anti-sniping.
`token_version:{user_id}`	`STRING`	30 hari	Integer version counter. Di-increment saat role diubah menjadi `ADMIN` untuk memicu auto-logout.
`lockout:superadmin:{email}`	`STRING`	60s / 120s / 3600s	Progressive counter percobaan login gagal Superadmin sebelum akun dibekukan sementara.
`lock:settle:{lot_id}`	`STRING`	10 detik	Distributed Mutex lock (`SET NX EX 10`) untuk menjamin settlement lelang dieksekusi tepat satu kali.

8. State Machine & Lifecycle Specifications

```
stateDiagram-v2
    [*] ⟶ DRAFT : Auction Manager Buat Lot Baru
    DRAFT ⟶ ACTIVE : Waktu Start Time Tercapai (Katalog Terbuka)
    ACTIVE ⟶ CLOSED_AWARDED : Instant Buyout (Harga Mencapai Ceiling)
    ACTIVE ⟶ CLOSED_AWARDED : Countdown Berakhir & Ada Penawar Tertinggi
    ACTIVE ⟶ EXPIRED_UNSOLD : Countdown Berakhir Tanpa Penawaran Masuk
    CLOSED_AWARDED ⟶ SETTLED : Settlement Daemon Eksekusi Debet Pemenang & Kepemilikan Sah
    EXPIRED_UNSOLD ⟶ SETTLED : Settlement Daemon Rilis Seluruh Dana Agunan
    SETTLED ⟶ [*]
```

9. Document Sign-Off Section

Dokumen perancangan tingkat rendah (*Low-Level Design*) v2.0 ini telah ditinjau secara mendalam dari segi kelayakan teknis, struktur data, algoritma usecase, antarmuka streaming Server-Sent Events (SSE), dan kesiapan pengujian TDD, serta

secara resmi disahkan untuk tahap koding.

PROJECT MANAGER **Geri Setyo Andrian**	TECH LEAD / TECHNICAL ARCHITECT **Alini**	SYSTEM ANALYST / SOLUTION ARCHITECT **Daniel H. S.**
		
Tanggal: 24 / 10 / 2026 **Status:** [✓] Disetujui [ ] Revisi	**Tanggal:** 24 / 10 / 2026 **Status:** [✓] Disetujui [ ] Revisi	**Tanggal:** 24 / 10 / 2026 **Status:** [✓] Disetujui [ ] Revisi