



**University of
Zurich^{UZH}**

Dynamic Distributed Constraint Optimization in Signal/Collect

Thesis

January 14, 2015

Daniel Hegglin

of Oerlikon ZH, Switzerland

Student-ID: 08-721-102

dani.hegglin@gmail.com

Advisor: **Mihaela Verman**

Prof. Abraham Bernstein, PhD

Institut für Informatik

Universität Zürich

<http://www.ifi.uzh.ch/ddis>

Acknowledgements

First and foremost, I'd like to thank my advisor Mihaela Verman, Research Assistant and PhD Candidate at the DDIS group for her excellent support during the course of this thesis. She was always reachable and helped me with many technical and formal questions. Without her continuous efforts and valuable inputs, this work would not have been possible.

Special thanks go to Dr. Thomas Scharrenbach for arranging the thesis proposal and his guidance at the beginning of this work. I'd also like to thank Philip Stutz for his work on the Signal/Collect framework that made my research possible and his support in technical questions regarding the usage of the framework.

Finally, I'd like to thank the Dynamic and Distributed Systems Group (DDIS) at the University of Zurich and Prof. Abraham Bernstein for the opportunity to write my master thesis in their department.

Zusammenfassung

Distributed constraint optimization ermöglicht Problemlösungen in beispielweise Terminplanung, Verkehrsflusskontrolle oder dem Management von Sensor Netzwerken. Es ist ein gut erforschtes Feld und es wurden viele verschiedenen Algorithmen zur Berechnung vorgestellt. Allerdings wird häufig von einer statischen Problemdefinition ausgegangen und der Aspekt von in der Realität häufig auftretenden Änderungen an der Problemstellung findet wenig Beachtung. Ausserdem fehlt es an einem theoretischen Fundament und standardisierten Verfahren um die Performanz von DCOP Algorithmen hinsichtlich sich ändernder Probleme zu erfassen. Diese Arbeit hatte das Ziel das Verhalten und die Leistung von verschiedenen Arten von DCOP Algorithmen in dynamischen Umgebungen mit einem Fokus auf lokale, iterative Algorithmen und Hauptaugenmerk auf den Max-Sum Algorithmus zu untersuchen. Zum Vergleich wurde eine komplette und eine lokal, iterative "message-passing" sowie eine "best-response" Variante implementiert. Zum Test eines realen Problems wurde Terminplanung ausgewählt und als DCOP formuliert. Es wurde ausserdem ein Framework entwickelt, welches die dynamische Änderungen von Constraints, Variablen und der Problemdomäne ermöglicht. Die Algorithmen wurden mit Fokus auf Qualität über Zeit, sowohl in einer statischen wie auch in einer dynamischen Umgebung getestet. Diese Arbeit schlägt ausserdem eine Lösung zur Speicherung, Weiterverarbeitung und Überwachung der Resultate der Berechnungen in Echtzeit vor, welche die Performanz der Algorithm nicht beeinflusst.

Abstract

Distributed constraint optimization allows to solve problems in domains like scheduling, traffic flow management or sensor network management. It is a well-researched field and various algorithms have been proposed. However, the dynamic nature of many of these problems in the real world has often been overlooked from researchers and problems are assumed to be static during the course of the computation. The benchmarking of DCOP algorithms with changing problem definitions currently lacks a theoretical foundation and standardized protocols. This thesis aimed to measure the performance of different types of DCOP algorithms on dynamic problems with a focus on local-iterative algorithms and especially on the MaxSum algorithm. A complete, a local-iterative message-passing and a local-iterative approximate best-response algorithm for distributed constraint optimization have been implemented for comparison. The meeting scheduling problem has been mapped as distributed constraint optimization problem as a real-world use case for benchmarking. A framework has been designed that allows dynamic changes to constraints, variables and the problem domain during runtime. The algorithms have been benchmarked in a static as well as in a dynamic environment with various parameters and with a focus on solution quality over time. This thesis further proposes a solution to store, further process and monitor the results of the computation in real-time without affecting the performance of the algorithms.

Table of Contents

1	Introduction	1
1.1	Motivation & Goal	1
1.2	Structure	2
2	Background & Related Work	3
2.1	Dynamic Distributed Constraint Optimization	3
2.2	Meeting Scheduling Problem	4
2.3	Algorithm Design Approaches	4
2.3.1	Complete	5
2.3.2	Local-Iterative - Best Response	5
2.3.3	Local-Iterative - Message Passing	5
3	Design	7
3.1	Meeting Scheduling Problem	7
3.1.1	Formal Definition as DCOP	7
3.1.2	Problem Dataset Generation	8
3.2	Mapping of DPOP	8
3.2.1	Graph Structure	8
3.2.2	Vertices	8
3.3	Mapping of MGM	8
3.3.1	Graph Structure	9
3.3.2	Vertices	9
3.4	Mapping of MaxSum	9
3.4.1	Graph Structure	10
3.4.2	Vertices	10
3.5	Framework	10
3.5.1	Signal / Collect	10
3.5.2	Parameters & Modes	10
3.5.3	Functionality & Structure	10
3.5.4	Dynamics Controller	11
3.6	Monitoring Platform	11

4	Benchmark & Discussion	13
4.1	Results I: Algorithms Performance in Static Environments	13
4.1.1	Solution Quality over Time	13
4.1.2	Time to Convergence	13
4.1.3	Conflicts over Time	13
4.1.4	Number of Messages	13
4.2	Results II: Algorithms Performance in Dynamic Environments	14
4.2.1	Rebound Time	14
4.2.2	Stability	14
5	Limitations & Future Work	15
6	Conclusions	17
A	Appendix 15	21
A.1	Results I: Selected Data	21
A.2	Results II: Selected Data	21

Introduction

1.1 Motivation & Goal

Distributed Constraint optimization allows to solve a broad category of problems where multiple agents are involved and a global utility function needs to be optimized. Problems range from graph coloring [Modi et al., 2005] to task allocation and scheduling [Zhang et al., 2002], traffic congestion management [Leeuwen et al., 2002] or in disaster recovery [Hiroaki et al., 1999]. The distributed variant of constraint optimization has been extensively addressed by researchers and the formulation of numerous algorithms with diverse design approaches. However, most of those algorithms were designed and most studies are conducted on the premise that problems are static in their predefined state and do not change over the course of the problem solving process. This might work as a step by step procedure, but it does not work in a distributed manner with multiple agents [Petcu and Faltings, 2007]. As a matter of fact, many of these problems have dynamic properties and in an environment with ever increasing complexity and speed, those become ever more relevant for real-world applications. Constraints can change, but also the involved variables as well as the problem domain itself. Imagine for example a organizational software of a global logistics company where vehicles can get damaged and orders could be changed to other addresses or even canceled. Recalculation of the complete problem with a new static definition seems inefficient. Research in dynamic distributed constraint optimization is sparse. The benchmarking of DCOP algorithms with changing problem definitions currently lacks a theoretical foundation and standardized protocols [Mailler and Zheng, 2014].

This thesis tries to explore dynamic distributed constraint optimization by implementing a complete and two local-iterative variations of algorithm approaches and compare their performance in a dynamic environment. The complete algorithm acts as a baseline and the main focus is on the performance of the local-iterative types of algorithms. They do not guarantee complete solutions but are able to provide a good solution faster as they calculate on a local level with a lower communication overhead. They also have been proven to be more scalable because of this lack of organizational overhead [Chapman et al., 2011]. These attributes indicate their potential ability to adapt faster to problem changes and keep a better stability. The main focus is on the abilities of the

MaxSum algorithm, which is a local-iterative message-passing algorithm. It is further a goal to show ways of benchmarking these type of problems from various aspects. The real-world use case for the thesis will be meeting scheduling and a framework for dynamic changes will be implemented on top of Signal/Collect, a graph processing engine developed at the Dynamic and Distributed System Group at the Departement of Informatics of the University of Zurich.

The implemented software is made available online under the Apache license version 2.0.¹²

1.2 Structure

First, an overview will be given about various definitions and aspects of constraint optimization in general, as well as the aspects of the distributed and dynamic variations. Further, an examination will be provided about different approaches of algorithms to solve constraint optimization problems and their advantages and disadvantages in context of solution quality over time, scalability and adaptability to changes.

Secondly, the meeting scheduling problem definition and the mapping to a distributed constraint optimization problem, as well as the algorithm mapping to the Signal/Collect programming model will be detailed in the design chapter. Further, the design considerations for a framework for dynamic changes will be explained and the solution for data collection will also be briefly introduced.

Finally, the performed benchmarks will be evaluated and discussed. In a first series, the algorithms will be tested in static environments to evaluate the implementation. In a second series, various tests on changing constraints, variables and the domain with different rates and different problem densities will be run to determine the performance of the algorithms in dynamic environments. To wrap up, further work possibilities and limitations of the thesis will be pointed out and a conclusion about the achieved contributions and results will be given.

¹<https://github.com/danihegglin/DynDCO>

²<http://www.apache.org/licenses/LICENSE-2.0>

Background & Related Work

In this section, constraint optimization and the distributed, as well as dynamic variants are briefly explained and brought into context of the related work. Also, the meeting scheduling problem is described and different algorithm designs and their advantages and disadvantages are explained and related work is mentioned.

2.1 Dynamic Distributed Constraint Optimization

A constraint optimization problem contains of a set of variables $V = \{V_1, V_2, \dots, V_n\}$. These variables are assigned to a value or state $s_j \in S_j$, which is contained in a set of possible values defined by a finite problem domain $D = \{D_1, D_2, \dots, D_n\}$. A constraint $C = \langle V_c, R_c \rangle$ contains one (unary), two (binary) or multiple (k-ary) variables and their relationship. The constraint defines a rule for the variables that needs to be fulfilled. One of those rules could be that none of the variables should take the same value. This would for example be the case for a meeting scheduling problem where none of the meetings should take place at the same time.

A utility function $u_{c_k}(S_{c_k})$ needs to be formulated that defines a certain cost respectively reward for a given configuration of the involved states. The global utility function u_g would then be the summation of all utility functions of all constraints.

$$u_g(s) = u_{c_1}(s_{c_1}) \oplus \dots \oplus u_{c_k}(s_{c_k}) \oplus \dots \oplus u_{c_l}(s_{c_l})$$

Constraints can be attributed with varying levels of importance through weighting. One can, instead of so-called soft constraints, define hard constraints by multiplying their utility instead of using addition in the global utility function. By defining the utility of a violated hard constraint as 0, the global utility would also go to 0 if this hard constraint is not satisfied [Chapman et al., 2011, Petcu and Faltings, 2003]. A problem only containing hard constraints would represent a constraint satisfaction problem.

$$u_g(s) = \prod_{hc_k \in HC} u_{SC_g}(s) \left(\sum_{sc_k \in SC} u_{SC_g}(s) \right)$$

The definition of a distributed constraint problem extends the basic constraint optimization by distributing sets of variables to autonomous agents. These agents all

have the goal to maximize the utility of their variables in a private utility function and thereby also contribute to a global utility function. Agents whose variables are linked to a common constraint are called neighbours [Chapman et al., 2011, Farinelli et al., , Petcu and Faltings, 2003].

As a further extension to the optimization, the problem definition is moved from a static to a dynamic attribute. Constraints can change and therefore change neighbourhoods and the outcome of private and global utility functions. A change of constraints inherently changes the area of satisfying solutions if hard constraints have been included in a problem definition. Nguyen et al. state that changing the constraints might lead to the discovery of a better global optima.[Nguyen and Yao, 2012]. Mailler et al. define a dynamic DCSP as a sequence of DCSPs $\{P_0, P_1, \dots, P_n\}$ where every DCSP is a static problem definition. P_i is therefore a result of the previous DSCP in the sequence and the added and removed constraints: $P_i = P_{i-1} + c_{ia} - c_{ir}$ [Mailler and Zheng, 2014]. This definition should also hold for DCOPs. Utility functions could also be dynamically changed. Modifying this property could especially have an impact on real-world problems like meeting scheduling, where it could move the global optima from one disconnected solution space to another[Nguyen and Yao, 2012]. Furthermore, variables could be added or removed in a dynamic setting and the problem domain D also could be changed during the course of the problem solving process.

2.2 Meeting Scheduling Problem

Scheduling is the problem of allocating tasks to a given set of resources that is usually limited with a time component. The meeting scheduling problem is a exemplary type of this family of problems. Participants of a meeting have private schedules with preferences when a meeting should be held according to their calendar. [Farinelli et al.,].

One should further mention an inherent privacy aspect to the problem. Meeting participant's are often not willing to share their schedules with others except for finding a time for the specific meeting. It will later be shown that some of the algorithms can guarantee this privacy to a certain degree.

[Berger et al., 2008] [BenHassine and Ho, 2007] [Grubshtein et al.,]
 - hard constraints same, different

2.3 Algorithm Design Approaches

ANYTIME SYNCHRONOUS ASYNCHRONOUS

Distributed Constraint Optimization can be done with numerous approaches.

Other Approaches: Bee Hive optimization, Genetic Algorithms, .. DynDCOAA, SBDO, Bee Colony algorithm, Ant colony algorithm, adopt, dsa-a, dsa-b stochastic ... - brief related work - brief explanation of approaches and why they don't fit: too much information sent, centralized, too complicated, not localized




Figure 2.1: Categorization of DCO algorithms [Chapman et al., 2011]

The following subsections are going to explain the three chosen approaches for this thesis and which advantages, as well as disadvantages this approaches hold.

[?]

2.3.1 Complete

[Chapman et al., 2011]

- basic idea - advantages - disadvantages
- dpop description

2.3.2 Local-Iterative - Best Response

- neighbourhoods - only communicates his state - reacts to the states of others - privacy aspects

[Chapman et al., 2011] [Maheswaran et al., 2006]

- Local iterative approximate best-response algorithms, such as the distributed stochastic algorithm (Tel, 2000; Fitzpatrick Meertens, 2003), the maximum-gain messaging algorithm (Yokoo Hirayama, 1996; Maheswaran et al., 2005), fictitious play (Brown, 1951; Robinson, 1951), adaptive play (Young, 1993, 1998), and regret matching (Hart Mas-Colell, 2000). In this class, agents exchange messages containing only their state, or can observe the strategies of their neighbours. In game-theoretic parlance, this is known as standard monitoring², and, as the name suggests, is a typical informational assumption implicit in the literature on learning in games.

- advantages - disadvantages
- mgm description

2.3.3 Local-Iterative - Message Passing

[Chapman et al., 2011] -

- advantages -disadvantages - privacy aspects - maxsum description

3

Design

In this section, the benchmark problem will be defined and mapped as DCOP, the framework design will be explained and the mapping of the algorithms on to the Signal/Collect framework will be described. Additionally, the design and considerations regarding the implemented monitoring platform are detailed.

3.1 Meeting Scheduling Problem

3.1.1 Formal Definition as DCOP

The formulation of the meeting scheduling problem followed the basic definition of a distributed constraint optimization problem.

= i meeting - i variable

[Maheswaran and Tambe, 2004] TSAV (Time Slots As Variables): a variable $X_n(t)$ is the n -th resources t -th time slot. The complexity of TSAV grows if the time range increases or the time quantization interval decreases. EAV (Event As Variables): X_K represents the starting time of E_K , with domain t, \dots, t PEAV (Private Events As Variables): A modification of EAV to ensure privacy protection for agents information. As in EAV each participant controls a private variable corresponding to the starting time of a meeting. But the difference is that in this formulation agents don't share their internal valuation for the resources, thus maintaining privacy. The experimental results in shows that EAV outperforms PEAV by one order of magnitude when using passup in meeting scheduling. As in this project it is fundamental to preserve agents preferences as well as to have the best variable control scheme we will consider only PEAV formulation.

= i currently chosen meeting

- soft constraints - i timetable: blocked, free, preferred - i define a certain utility for the value

[Franzin et al.,]

- hard constraints - i no meeting of an agent on the same timeslot, every meeting participant on the timeslot - i otherwise no usable solution

- neighbourhood: the participants in the meeting

[Chapman et al., 2011] chun, andy 2003 grubshtein mes, martijn 2007

Multi-agent meeting scheduling with preferences: efficiency, privacy loss, and solution quality Franzin
 problem density, etc

3.1.2 Problem Dataset Generation

- Decision: Available datasets are not usable because it was not possible to scale to high numbers. It was chosen to create problems randomly. Frodo2
 - brauche ein paar papers die das untermauern
 - participations fixed -
- Distributed Meeting Scheduling: CHAPTER 10

3.2 Mapping of DPOP

based on: A Scalable Method for Multiagent Constraint Optimization
 - Why DPOP DPOP is a primary example for a complete algorithm

Algorithm 1 DPOP Pseudocode

```

1: procedure MYPROCEDURE
2:    $stringlen \leftarrow \text{length of } string$ 
3:    $i \leftarrow patlen$ 
4: top:
5:   if  $i > stringlen$  then return false
6:    $j \leftarrow patlen$ 
7: loop:
8:   if  $string(i) = path(j)$  then
9:      $j \leftarrow j - 1.$ 
10:     $i \leftarrow i - 1.$ 
11:    goto loop.
12:   close;
13:    $i \leftarrow i + \max(delta_1(string(i)), delta_2(j)).$ 
14:   goto top.
```

3.2.1 Graph Structure

3.2.2 Vertices

3.3 Mapping of MGM

- Why MGM Good example for Best-Response algorithm and DSA-B has already been implemented

Algorithm 2 MGM Pseudocode

```

procedure MYPROCEDURE
2:   stringlen  $\leftarrow$  length of string
      i  $\leftarrow$  patlen
4:   top:
      if i > stringlen then return false
6:   j  $\leftarrow$  patlen
      loop:
8:   if string(i) = path(j) then
      j  $\leftarrow$  j - 1.
10:  i  $\leftarrow$  i - 1.
      goto loop.
12:  close;
      i  $\leftarrow$  i + max(delta1(string(i)), delta2(j)).
14:  goto top.

```

3.3.1 Graph Structure

3.3.2 Vertices

3.4 Mapping of MaxSum

[Yedidsion and Zivan,] Farinelli2008 zivan2012 Aji, S. M. and McEliece, R. J. 2000. The generalized distributive law. IEEE Transactions on Information Theory 46,
 - Why MaxSum MaxSum is the new kid on the block.

Algorithm 3 Maxsum Pseudocode

```

procedure MYPROCEDURE
      stringlen  $\leftarrow$  length of string
3:   i  $\leftarrow$  patlen
      top:
      if i > stringlen then return false
6:   j  $\leftarrow$  patlen
      loop:
      if string(i) = path(j) then
9:   j  $\leftarrow$  j - 1.
      i  $\leftarrow$  i - 1.
      goto loop.
12:  close;
      i  $\leftarrow$  i + max(delta1(string(i)), delta2(j)).
      goto top.

```

3.4.1 Graph Structure

3.4.2 Vertices

3.5 Framework

3.5.1 Signal / Collect

It was decided to build a specific framework for benchmarking dynamic problems. The foundation of the framework is the Signal/Collect framework [Stutz et al., 2010]¹, which is built on top of Akka² and written in Scala³. It is a graph processing engine with a programming model that features vertices and edges. The vertices have a state and send signals along the edges to other vertices, which can contain any datatype. The signal usually is their state or in context of their state. The vertices collect the signals and perform a computation on the collected data, before adjusting their state according to the calculations and sending out the newly generated signal. This model allows to reduce complex algorithms to a few lines of code and is applicable for many problems. The reason for choosing this framework in this thesis is the structural fit to distributed constraint optimization problems and the possibility to add and remove vertices during runtime. This allows for dynamically changing problem computations. Further, the capability of running problems asynchronously or with synchronous signal steps and the possibility to distribute the system on multiple machines add to the advantages.

3.5.2 Parameters & Modes

This framework was designed with the benchmarks in mind. It should be possible to pass the general run parameters like which algorithm to use, which Signal/Collect run mode (synchronous/asynchronous) to use, normal run mode or dynamic variations (changeConstraints, changeVariable, changeDomain) with specific parameters. For testing, two test modes were implemented: SingleTest and MultiTest. Single Test is for single runs obviously and MultiTest allows to specify how many runs each specification should be doing to create a median of those runs, how much the agents respectively the meetings should increase after a specification has been processed and where to stop. By this, it is possible to explore an area of specifications. Finally, it should be possible to define different problems. For this thesis, the parameters for problem density (blocked timeslots percentage), timeslots, meetings and agents were defined.

3.5.3 Functionality & Structure

The considerations for the structure were that I needs to be hierarchical to allow different constraint optimization problems to be run on the framework. So, the hierachy goes

¹<http://uzh.github.io/signal-collect>

²<http://akka.io>

³<http://www.scala-lang.org>

from a Base to a Dynamic to a Problem level. It should include ProblemFactories and Problems, GraphFactories and Graphs, as well as Vertices.

- Problem Factory: Problem -> MeetingSchedulingProblem class diagram
- Graph Factory: Graph -> DPOP Graph, MGM Graph, MaxSum Graph explanation
- Graph
 - BasicVertex -> DynamicVertex -> MeetingSchedulingVertex -> DPOP, MGM, MaxSum Vertex class diagram!!!

3.5.4 Dynamics Controller

how does it work, what can it do

- Registration of vertices - change constraints - change variables - change domain
- Initial design consideration was to make it part of the graph as signal collect allows mixup of different types. Created weird problems because I need to pause the vertex for interval changes. not part of the graph but connected to vertices -> because it was a problem with convergence and there was a problem with thread sleep in akka

3.6 Monitoring Platform

It was decided to find a more sophisticated method to monitor the utility, quality, conflicts and stats of the calculations than to write to a logfile. Partially because File IO can possibly be limited in the number of open files and processing results to fit the log file format during calculations can affect the performance of the algorithm one tries to benchmark. Mainly because processing log files was too tedious and visibility was not given to the calculations.

Sending the results with non-blocking http requests to a restful server was considered to be an alternative and the Play Framework⁴ has been chosen because it is highly scalable, is able to handle thousands of simultaneous connections, lightweight, non-blocking and allows to process results on-the-fly with code in Java or Scala. It was also chosen because Akka is tightly integrated and the actors concept are an integral part of the framework. It further allows to preview the calculation of the graph in realtime with websockets, which can be helpful during the implementation of algorithms.

By using an actor based approach it is possible to contain run specific data in a closed entity and store when limits are reached. Through the chosen architecture one can run multiple tests in parallel without problems. The server is of course also limited by its resources.

⁴<https://www.playframework.com>



4

Benchmark & Discussion

In this chapter the three algorithms are benchmarked with different parameters and scenarios. The first series of tests is conducted in a static environment for a basic understanding of the algorithm performance and the second series is held in various dynamic settings to explore the dynamic capabilities of the algorithms. The testing environment was the minion cluster of the departement of informatics at the University of Zurich. The cluster consists of 16 machines and each machine has 128 GB RAM and two E5-2680 v2 at 2.80GHz processors. Every processor has 10 cores and the interlink between the machines is a 40Gbps Infiniband setup. The cluster has different partition speeds (slow, fast, superfast). All tests were conducted on superfast partitions.

4.1 Results I: Algorithms Performance in Static Environments

- Problem Density - Run Mode on Signal Collect
theoretical foundation: chapman benchmarking hybrid algorithms,

4.1.1 Solution Quality over Time

- Utility, Quality - Verlauf alle drei - Scalability: one, multiple machines - Quality Distribution

4.1.2 Time to Convergence

- More time to find a valid solution - could be local optima - Scalability: one, multiple machines - Convergence Distribution: how often does it converge - dpop should always converge

4.1.3 Conflicts over Time

- Verlauf alle drei - Scalability: one, multiple machines

4.1.4 Number of Messages

- Verlauf alle drei - Scalability: one, multiple machines - Message Distribution

4.2 Results II: Algorithms Performance in Dynamic Environments

petcu 2007

- Additional parameter - Different Scenarios: Constraints, Variables, Domain - Change one, multiple - Amount of Change: Percentage, Number
- Number of Agents: 10,100,1000 - Number of Meetings; 10,100, 1000 - Number of Timeslots: 1000
- constraints: mode, interval, percentage variables: mode, interval, new Neighbourhood, new Agent, add / remove, how many domain: mode, interval, percentage, increase / decrease

4.2.1 Rebound Time

- utility, quality - Single change - Distribution - Verlauf alle drei - given timeframe -j lowest to highest avg.

4.2.2 Stability

[?]

- Utility, Quality - Multiple change: Peak Average - Median Utility
- Rate / Avg. Conflicts - Density!! Mailler2014,
- messages

Limitations & Future Work

The main limiting factor in the work was the time to test more algorithms and more problems and more aspects of dynamic constraint optimization problems.

It would be interesting to see how the performance of other problems is.

The meeting scheduling problem could also be further explored by increasing the amount of maximum meeting participations of an agent. The amount of participations was limited during the course of this thesis to not further expand the number of possible cases for benchmarking.

The aspect of changing domains was also not much researched despite being in the framework as a possible test. This was mostly because of the lack of impact respectively damaging impact changed timeslots had on the scheduling problem. One could further investigate this property of dynamic constraint optimization problems.

The aspect of changing functions

Conclusions

A complete (DPOP), a local-iterative message-passing (MaxSum) and a local-iterative approximate best-response (MGM) algorithm have been implemented. The implementation on top of Signal/Collect was a good fit from a structural point of view.

The meeting scheduling problem has been mapped as a distributed constraint optimization problem, which also was a good fit.

The framework has proven to be a good starting point to dynamically change problems during runtime.

The monitoring platform has proven to be very helpful in the process of implementation as well as in the evaluation.

The results of test have shown that...

Benchmarks that made sense where...

References

- [BenHassine and Ho, 2007] BenHassine, A. and Ho, T. B. (2007). An agent-based approach to solve dynamic meeting scheduling problems with preferences. *Engineering Applications of Artificial Intelligence*, 20(6):857–873.
- [Berger et al., 2008] Berger, F., Klein, R., Nussbaum, D., Sack, J.-R., and Yi, J. (2008). A meeting scheduling problem respecting time and space. *GeoInformatica*, 13(4):453–481.
- [Chapman et al., 2011] Chapman, A. C., Rogers, A., Jennings, N. R., and Leslie, D. S. (2011). *A unifying framework for iterative approximate best-response algorithms for distributed constraint optimization problems*, volume 26.
- [Farinelli et al.,] Farinelli, A., Vinyals, M., Rogers, A., and Jennings, N. R. Chapter 12 Distributed Constraint Handling and Optimization. pages 1–43.
- [Franzin et al.,] Franzin, M. S., Freuder, E. C., Rossi, F., and Wallace, R. Multi-agent meeting scheduling with preferences : efficiency , privacy loss , and solution quality.
- [Grubshtein et al.,] Grubshtein, A., Gershman, A., and Meisels, A. Scheduling Meetings by Agents. *Citeseer*, (1):1–15.
- [Hiroaki et al., 1999] Hiroaki, K., Tadokoro, S., Noda, I., Matsubara, H., Takahashi, T., Shinjou, A., and Shimada, S. (1999). RoboCup Rescue : Search and Rescue in Large-scale Disasters as a Domain for Autonomous Agents Research and Robotics Can Make. pages 739–743.
- [Leeuwen et al., 2002] Leeuwen, P. V., Hesselink, H., and Rohling, J. (2002). Scheduling Aircraft Using Constraint Satisfaction. 76.
- [Maheswaran et al., 2006] Maheswaran, R., Pearce, J., and Tambe, M. (2006). A family of graphical-game-based algorithms for distributed constraint optimization problems. *Coordination of large-scale ...*, pages 1–19.
- [Maheswaran and Tambe, 2004] Maheswaran, R. and Tambe, M. (2004). Taking DCOP to the real world: Efficient complete solutions for distributed multi-event scheduling. *Proceedings of the ...*

- [Mailler and Zheng, 2014] Mailler, R. and Zheng, H. (2014). A new analysis method for dynamic distributed constraint satisfaction. *Proceedings of the 2014 international conference . . .*, pages 901–908.
- [Modi et al., 2005] Modi, P., Shen, W., Tambe, M., and Yokoo, M. (2005). Adopt: asynchronous distributed constraint optimization with quality guarantees. *Artificial Intelligence*, 161(1-2):149–180.
- [Nguyen and Yao, 2012] Nguyen, T. T. and Yao, X. (2012). Optimization - The Challenges. 16(6):769–786.
- [Petcu and Faltings, 2003] Petcu, A. and Faltings, B. (2003). A Scalable Method for Multiagent Constraint Optimization.
- [Petcu and Faltings, 2007] Petcu, A. and Faltings, B. (2007). Optimal solution stability in dynamic, distributed constraint optimization. *Proceedings of the 2007 IEEE/WIC/ACM . . .*
- [Stutz et al., 2010] Stutz, P., Bernstein, A., and Cohen, W. (2010). Signal/collect: graph algorithms for the (semantic) web. *The Semantic Web-ISWC 2010*.
- [Yedidsion and Zivan,] Yedidsion, H. and Zivan, R. Applying MaxSum to DCOP MST.
- [Zhang et al., 2002] Zhang, W., Xing, Z., and Louis, S. (2002). Distributed Breakout vs . Distributed Stochastic : A Comparative Evaluation on Scan Scheduling. *Proceedings of the AAMAS-02 workshop on Distributed Constraint Reasoning*, pages 192–201.

A

Appendix 15

A.1 Results I: Selected Data

A.2 Results II: Selected Data

List of Figures

2.1	Categorization of DCO algorithms [Chapman et al., 2011]	5
-----	---	---

List of Tables