




Oracle Database Architectural Components

Objectives

After completing this appendix, you should be able to do the following:

- List the major database architectural components
- Describe the background processes
- Explain the memory structures
- Correlate the logical and physical storage structures




Oracle Database Architecture: Overview

The Oracle Relational Database Management System (RDBMS) is a database management system that provides an open, comprehensive, integrated approach to information management.




Oracle Database Server Structures




ORACLE

Connecting to the Database

- Connection: Communication pathway between a user process and a database instance
- Session: A specific connection of a user to a database instance through a user process



Interacting with an Oracle Database




Oracle Memory Architecture

DB structures

→ Memory

- Process

- Storage




Process Architecture

DB structures

- Memory
- **Process**
- Storage

- User process:
 - Is started when a database user or a batch process connects to the Oracle Database
- Database processes:
 - Server process: Connects to the Oracle instance and is started when a user establishes a session
 - Background processes: Are started when an Oracle instance is started




ORACLE

Database Writer Process


Writes modified (dirty) buffers in the database buffer cache to disk:

- Asynchronously while performing other processing
- Periodically to advance the checkpoint



Log Writer Process


- Writes the redo log buffer to a redo log file on disk
- LGWR writes:
 - A process commits a transaction
 - When the redo log buffer is one-third full
 - Before a DBWn process writes modified buffers to disk



Checkpoint Process


Records checkpoint information in:

- The control file
- Each datafile header




System Monitor Process

- Performs recovery at instance startup
- Cleans up unused temporary segments



Process Monitor Process


- Performs process recovery when a user process fails:
 - Cleans up the database buffer cache
 - Frees resources used by the user process
- Monitors sessions for idle session timeout
- Dynamically registers database services with listeners





Oracle Database Storage Architecture

DB structures


- Memory
- Process
- **Storage**



Parameter file
Password file
Network files
Alert and trace files




Backup files



Archived log files

ORACLE

Logical and Physical Database Structures



Processing a SQL Statement


- Connect to an instance using:
 - The user process
 - The server process
- The Oracle server components that are used depend on the type of SQL statement:
 - Queries return rows.
 - Data manipulation language (DML) statements log changes.
 - Commit ensures transaction recovery.
- Some Oracle server components do not participate in SQL statement processing.

Processing a Query

- Parse:
 - Search for an identical statement.
 - Check the syntax, object names, and privileges.
 - Lock the objects used during parse.
 - Create and store the execution plan.
- Execute: Identify the rows selected.
- Fetch: Return the rows to the user process.

Shared Pool

- The library cache contains the SQL statement text, parsed code, and execution plan.
- The data dictionary cache contains table, column, and other object definitions and privileges.
- The shared pool is sized by `SHARED_POOL_SIZE`.




Database Buffer Cache

- The database buffer cache stores the most recently used blocks.
- The size of a buffer is based on `DB_BLOCK_SIZE`.
- The number of buffers is defined by `DB_BLOCK_BUFFERS`.




Program Global Area (PGA)

- Is not shared
- Is writable only by the server process
- Contains:
 - Sort area
 - Session information
 - Cursor state
 - Stack space




Processing a DML Statement




Redo Log Buffer


- Has its size defined by `LOG_BUFFER`
- Records changes made through the instance
- Is used sequentially
- Is a circular buffer



Rollback Segment



COMMIT Processing



Summary of the Oracle Database Architecture

