What Keeps a Generative Recommender Relevant? An Empirical Study of Reinforcement Fine-Tuning Against a Learned Reward Model

Daniil Antonov
ITMO University, Saint Petersburg, Russia
October 2026

Abstract. A recommender that generates its list item by item is a policy, so reinforcement learning (RL) can fine-tune it towards feedback that next-item training does not see. We study the setting with the fewest safeguards. PPO fine-tunes a GPT-2 recommender to raise the consumed share of its items as predicted by a second GPT-2, the reward model, and a KL penalty towards the pretrained recommender (the *anchor*) is the only term that asks for relevance. Because every reward gain is itself a prediction, we verify it with signals the policy cannot influence: a reward model trained on other users, the logged responses, and the same lists scored for another user. On KION (video) and Yambda-50M (music), with three seeds for every central comparison, RL raises the predicted share, by 24% on KION, where NDCG@10 falls by 1.8% at the anchor weight chosen on validation and by 11.5% at a weaker one. There the policy learns one re-weighting of the catalogue towards the titles finished most often, because the reward's own optimum is mostly that re-weighting. RL settings only move the policy along the resulting frontier between relevance and reward, which the closed-form optimum, computed at inference, reaches without training. The log and the list format move the frontier. Reward-weighted fine-tuning on the consumed share relative to what is typical for the item, with no reward model, raises a length-neutral logged response by 21% and personalisation by 19% over the same epoch of plain training. Predicting each list position from the real history is 6% more relevant than generating the list.

1 Introduction

Generative sequential recommenders [1], [2], [3], [4], [5] are trained to continue logged sequences, and the log records what users did, not what served them: 36% of music listens in Yambda stop before half of the track, and 52% of KION titles are abandoned before half of their length. A recommender that generates a list item by item is a policy, so RL can move it towards what will be received well [6], [7], [8], [9]. Where the reward comes from decides how safe this is. Petrov and Macdonald [8] keep relevance inside the reward. Matveev et al. [9] learn from logged feedback, and use a learned feedback model to evaluate and to select recommendations at inference time. Letting a learned model of user feedback *be* the training reward is the option with the fewest protections: a policy optimised against a learned model drifts to where the model is wrong [10], [11], in recommendation towards popularity and filter bubbles [12], [13].

We study this option in its barest form. A GPT-2 [14] recommender is fine-tuned to raise the consumed share that a second GPT-2 predicts, and a KL penalty towards the pretrained recommender, the *anchor*, is the only term that asks for relevance. Since every reward gain in this setting is reported by a model, the study rests on instruments the optimised model cannot influence, and on three seeds for every central comparison. Beyond measuring the trade-off, we test why it arises and what moves it, with methods from the post-training of language models: RL restricted to one score offset per item or to rank-1 updates, the policy's change split into its per-item part and the rest, the closed-form optimum computed at inference with and without a learned look-ahead, learning from logged responses alone, and lists predicted position by position from the real history. The study answers five questions about RL fine-tuning of a next-item recommender. Table 1 answers each briefly, Section 5 gives the evidence with one subsection per question, and Table 2 defines the terms that recur.

2 Related Work

Next-item models [1], [15], [16] run autoregressively as generative recommenders over items [2] or semantic identifiers [3], up to industrial scale [4], [5]. RL enters recommendation through off-policy policy gradients [6], slate values [7] and RL heads [17], and learned simulators replace the user [18], [19]. A policy optimised against a learned model exploits its errors [10], [11], [20], [21], and an ensemble of reward models does not stop this, because models trained alike share their errors [22]. Penalising divergence from a pretrained model is KL-control [23], [24], [25]; Gao et al. [10] compare best-of-n sampling with RL along this divergence. Consumption

Table 1: The five questions and their answers, on KION unless Yambda is named.

Question	Answer
Q1. How does the model's behaviour change after RL fine-tuning?	The predicted reward rises (+24% on KION, and a reward model trained on other users agrees), but what RL learns is one re-weighting of the catalogue towards titles that everybody finishes, which is the reward's own optimum.
Q2. Is relevance preserved? Does the model recommend the same items to everyone?	Relevance is traded along a frontier: NDCG@10 falls by 1.8% at the weight chosen on validation requests and by 11.5% at the main run, most for users with short histories, and without the anchor every user receives the same list. Yambda keeps both.
Q3. Can we get closer to long-term goals?	Return, likes and adoption can be predicted and rewarded, but their predictions rise by a few percent, and the largest gain lies beyond anything in the log; only an online test can show whether users return.
Q4. What happens when generating several steps ahead?	A generated list gains after a hit and loses after a miss, and simulated responses bias the reward of later steps; predicting each position from the real history removes the loss (+6.3% NDCG@10).
Q5. What is the trade-off between relevance and reward?	RL settings choose a point on the frontier, which inference reaches without training. The frontier moves when the reward comes from the log, as in reward-weighted fine-tuning on the logged relative share (+21% length-neutral logged response, +19% personalisation over the same epoch of plain training).

Table 2: Terms used throughout.

Term	Meaning
Base recommender π_0	The pretrained GPT-2 next-item model. Every method starts from it.
Generated, ranked list	Ten items chosen one at a time, each appended to the history as if consumed; or the ten items π_0 scores highest for the real history.
Consumed share ρ	The share of a title watched or a track played (`played_ratio` in the code).
Relative share q	ρ as a quantile among the item's training-period responses. 0.5 is usual for the item, so no item earns it by being easy to finish.
Reward model	A second GPT-2 that predicts the response to an item before it is consumed. The *training* copy gives the rewards; the *held-out* copy, trained on other users, only judges.
Anchor β, KL distance	The KL penalty towards π_0 and its weight; and how far a policy ended from π_0, in nats per generated item, which compares runs where β does not.
Frontier	The highest predicted share reached at each level of relevance. Moving along it trades one for the other; a method that moves it gains both.
Logged share, logged surplus	Per recommended item, the response the log recorded if the user went on to consume the item, else zero. The surplus counts $q - 1/2$ instead: positive only if users took to the items more than usual. Neither needs a model.
Personal part	The predicted share of a list for its own user minus that of the same list for another user.
Per-item share	The share of a change within one history that one effect per item explains: 1 if every user's items move alike.
Item offsets	RL restricted to one score offset per item, the same for every user.
Re-ranking, guided decoding	The closed-form optimum $\pi_0 \exp(r/\beta)$ computed at inference, over the candidates of π_0 at once or one position at a time.
Reward-weighted fine-tuning	Next-item training on logged items, each weighted by $\exp(r/\tau)$ of its logged response. It needs no reward model.
One head per position	A linear head per list position that predicts the item k events ahead from the real history.

time is confounded by item duration [26], [27], retention has been optimised directly [28], [29], and maximal marginal relevance [30] greedily optimises a list-dependent reward.

Our probes come from the post-training of language models: low-rank updates [31], which match full RL even at rank 1 [32]; the KL-anchored optimum computed at decoding time with a learned value of what follows [33], [34]; learning from logged rewards without a reward model [35], [36] and from preference pairs [37]; weight interpolation and extrapolation [38], [39], [40]; group-relative advantages [41]; and one head per future position [42].

Closest to this study, Chidambaram et al. [36] find that a learned reward model for a generative recommender predicts no better than item means, that PPO and DPO against it collapse ranking metrics, and that exponential reward-weighted fine-tuning on logged rewards does better; they derive the KL-anchored optimum in closed form and note that standardising rewards rescales its temperature. OneRec-V2 [43] found its reward model open to reward hacking and moved to user feedback, scoring watch time as a percentile within the user's own history of videos of similar duration. Our setting differs in what the reward model knows: it predicts responses far better than item means (AUC 0.755 against 0.656 on KION), yet RL extracts only its per-item part. We trace this before any collapse, at controlled KL distances, on two domains; we show whether the reward or the optimiser sets the per-item part and how much of RL's gain and loss it carries, and find what

moves the frontier it defines: their reward-weighted fine-tuning with a reward that compares a response with what is typical for the item, and lists predicted from the real history.

3 Method




Figure 1: The pipeline. The reward model of step 3 is the only source of reward; the instruments in the dashed box never influence the policy.

Models. A log is a set of events with a user, an item, a time and the *consumed share* $\rho \in [0, 1]$ of the track or title. The recommender π_0 is a GPT-2 decoder [14] over item tokens, trained with the full-softmax next-item cross-entropy. A list of $K = 10$ is obtained by *ranking* (the catalogue is scored once) or by *generation* (each chosen item is appended to the history as if consumed) [2]; fine-tuning changes the second mode. The *reward model* is a second GPT-2 whose token at position t carries the item i_t and the consumed share of the previous item, so it scores a candidate before its outcome exists. Its heads, trained with binary cross-entropy, predict the consumed share $\hat{\rho}$ (with ρ as a soft label); the *relative share* $\hat{q}$, the share as a mid-rank quantile among the item's training-period shares, which averages one half for every item and so cannot be earned by an item that is easy to finish; the probability that the session continues, $\hat{c}$, and that the user returns, $\hat{u}$; and on Yambda the probabilities of a like and a dislike, and of *adoption* $\hat{\alpha}$: a first play followed by another play in a later session within 14 days. Since the log holds only items that users chose, every head describes the response to an item *given* that the user starts it. Two copies are trained on disjoint halves of the users: the *training* model gives the rewards, the *held-out* model only judges. A third pair is trained with *hidden responses*: in half of the training windows the responses to the last 1 to 10 events are replaced by an "unknown" value, which is the situation of a generated list.

Fine-tuning. An episode generates one list for a training history; the reward model is the environment and is fed its own expectation for the responses to earlier generated items. The policy gradient uses a learned value model with generalised advantage estimates [44] and four steps of PPO's clipped surrogate per batch [45], a leave-one-out baseline over four lists per history [46], or group-relative advantages over the same four lists [41]; advantages are standardised in every case. The loss adds the exact divergence from π_0 at every position,

$$\mathcal{L}(\theta) = \mathcal{L}_{\mathrm{PG}}(\theta) + \beta \cdot \mathbb{E}_k[\mathrm{KL}(\pi_\theta(\cdot \mid s_k) \,\|\, \pi_0(\cdot \mid s_k))], \tag{1}$$

and a *KL budget* δ adapts β after every iteration so that the policy settles at δ nats per item. Two ablations remove credit along the list: $\gamma = 0$, and one-item episodes. For a reward $r(j \mid s)$ of item j in state s, the anchored objective at one position has the closed-form maximiser [23], [36]

$$\pi^*(j \mid s) = \frac{\pi_0(j \mid s) \exp(r(j \mid s)/\beta)}{Z(s)}. \tag{2}$$

Standardising the advantages makes the policy-gradient term scale-free but leaves the KL term as it is, so RL pursues this optimum with an effective weight $\beta\sigma_A$, where σ_A is the scale of the advantages before standardisation [36]. σ_A depends on the estimator and drifts during training: a weight cannot be compared between runs, the KL distance a run ends at can.

Rewards. All rewards are instances of

$$r_k = w_\rho \hat{\rho}_k + w_q \hat{q}_k + w_u \hat{u}_k + w_L\left(\hat{l}_k - \hat{d}_k\right) + w_A \hat{\alpha}_k + w_R \mathbb{1}[k = K]\hat{u}_K + w_F \frac{\mathbb{1}[a_k \in F]}{\log_2(k+1)}. \tag{3}$$

The default is $w_\rho = 1$ alone. The *return after the list* (w_R) is paid at the last item only, so it belongs to the list as a whole. The *logged-relevance* term of [8] (w_F) uses the user's real continuation F of a training history and sums to DCG@K. A *personal* reward subtracts what the model predicts for the same list shown to another user, and a *diversity* reward adds the mean distance between the items of the list.

Alternatives to on-policy RL. *Liked-only fine-tuning* continues next-item training on targets with $\rho \geq 0.5$. *Off-policy REINFORCE* [9] weights logged items by the logged reward that followed them, with importance weights capped at $\kappa = 0.5$. *Re-ranking* keeps the K of the 100 best candidates of π_0 with the highest $r(j \mid h) + w \log \pi_0(j \mid h)$, which orders items exactly as π^* of Equation 2 with $\beta = w$: it computes the top of the anchored optimum for the real history, without training. *Guided decoding* applies Equation 2 one position at a time: among the 50 most likely next items of π_0 it takes the one with the highest $\log \pi_0 + Q/\beta$ after the items already chosen, where Q is the item's predicted reward plus γ times a value U of what follows it, regressed on the discounted rewards of lists that π_0 samples (controlled decoding [33], the first step of Q♯ [34]); $\gamma = 0$ judges each item by its own reward. *Weight interpolation* takes $\theta_0 + a(\theta_{\mathrm{RL}} - \theta_0)$ for a from 0.25 to 2 [38], [39], [40].

What RL learns. *Item offsets* restrict RL to one score offset per item, the same for every user; *rank-1 LoRA* [31] updates only the transformer's projections. Both hold the KL budgets of full RL, with learning rates of $3 \cdot 10^{-3}$ and 10^{-4} against 10^{-5}. *Policy surgery* averages the main run's change of log-probabilities per item over validation histories and adds it to π_0 ("base + RL's item offsets") or subtracts it from the fine-tuned policy ("RL − its item offsets").

Learning from the log. *Reward-weighted fine-tuning* continues next-item training with each logged target weighted by $\exp(r/\tau)$, normalised over the batch, where r is the logged relative or consumed share: it fits Equation 2 to the log [35], [36]. *Within-user DPO* [37] learns from pairs of items one user consumed within 20 events after the same history, one with a relative share of at least 0.6 and one of at most 0.4, so neither is preferred for having been started or for being short. Both run one epoch at a learning rate of 10^{-4}. *One head per position* [42] predicts a list without reading its items: on the frozen π_0, a linear map per offset $k = 2, ..., K$, initialised as the identity, turns the state after the real history into one from which π_0's output layer scores the item k events ahead; position k takes head k's best allowed item.

Instruments. Let F be the next 20 items the user really consumed. A gain the *held-out reward model* does not confirm is exploitation of the training model. The *logged response* needs no model: the *logged share* $\frac{1}{K}\sum_k \mathbb{1}[a_k \in F]\rho(a_k)$ counts hits as much as responses, and the *logged surplus* $\frac{1}{K}\sum_k \mathbb{1}[a_k \in F]\big(q(a_k) - \frac{1}{2}\big)$ is positive only if users took to the recommended items more than is usual for those items. Scoring a user's lists for *another user* gives the share of a gain that depends on who receives the list, its *personal share*. *Relevance* is NDCG, Recall and MAP at $K = 1, 5, 10$ against F, and NDCG@10 or Recall@10 by outcome (liked, $\rho \geq 0.5$, or skipped; above or below the item's usual share), by the length of the history, and by position after a hit or a miss. *Concentration* is catalogue coverage, the Gini coefficient of impressions, the share of impressions of the 1% most shown items, and the overlap of two users' lists. The *per-item share* of a quantity, over the 100 best candidates of π_0 for every test user and weighted by π_0, is the share of its variation within a history that one effect per item explains: 1 if every history orders the items alike. For $\log \pi_\theta - \log \pi_0$ it measures how much of a policy's change is one preference per item applied to every user; for the reward model's predictions it measures the same for the optimum, since by Equation 2 the optimum changes $\log \pi_0$ by r/β plus a constant per history, at any β. *Simulation on real sequences* runs the reward model on the user's real next five items, with the earlier responses as logged or as a simulation has to assume them.

4 Experimental Setup

Data. Table 3 lists the data, the split and the models. On Yambda 0.77% of events are liked and 0.16% disliked, and 24% of first plays are adopted. The consumed share is bimodal, and on KION it depends on length: films are watched to 0.5 on average and the longest tenth of the catalogue, series, to 0.22, since the share is taken of the whole series.

Training and evaluation. Fine-tuning cuts its histories at a random moment of the training period of a random user with at least 8 training events. Lists of ten are generated greedily unless ranked lists are named, and every baseline reads the recommender's window of history. The KL distance of a run is the exact divergence over the catalogue on its own sampled training lists, averaged over the last 50 iterations. Operating points are selected on validation requests only: the highest held-out predicted share within 5% of the base recommender's NDCG@10. The main run's $\beta = 0.3$ was carried over from earlier iterations of the study and shows a clearly visible move along the frontier, not an optimum.

No leakage. Every trained model, from the recommender and the reward models to the baselines and every kind of fine-tuning, reads windows of the training period only, and RL samples its histories, and the logged continuation of each, inside the training period. The catalogue and every item statistic, the quantiles of the

Table 3: Data, split, models and fine-tuning.

	KION (main dataset)	**Yambda-50M (replication)**
Log	Online cinema [47]: one row per user and title, dated by its last view, with the share watched; an item table names every title and its type	Music service [48]: one row per listen, timed to the second, with the share played; likes and dislikes
Kept	Users with at least 5 and titles with at least 10 training events	Users with at least 50 training events; the 50k most played tracks
Size	256k users, 8k titles, 3.5M training events; a median of 10 per user	8.7k users, 50k tracks, 35M training events; a median of 2,638 per user
Split	The last 7 days are the test period, the 7 days before them the validation period	The same
Test requests	59,997, one per user at the start of the test week; the history is the last 38 events, the targets the next 20	7,593; the last 118 events and the next 20
Session, return	The next event on the same calendar day; a new day within a week	The next event within 30 minutes; a new session within a day
Models	GPT-2, 4 layers of width 256, windows of 48 events	The same, windows of 128 events
Fine-tuning	512 lists of 10 per iteration, $\gamma = 0.99$, learning rate 10^{-5}; the main run has $\beta = 0.3$ and 2,000 iterations, every other run 1,000	The same
History items	Never recommended again: one row per user and title	Allowed: repeats are normal
Chosen on validation	$\beta = 1$	$\beta = 0.05$

relative share included, come from the training period. Labels that look ahead, such as continuation, return, likes and adoption, are computed for training events from events before the validation period, and an outcome whose waiting time is not observed is left out. Early stopping and operating points use the validation period. The history of a test request includes the validation week, on which no model trained. On KION a title watched across the boundary appears only as a test target, and test events on items outside the training catalogue are dropped for every method alike. The repository's README lists each check next to the code that implements it.

Sessions and seeds. Each dataset ran a *final* session with the full grid (6.1 hours on KION, 12.3 on Yambda, on one 96 GB GPU), a *review* session with the long-term rewards, the reward models with hidden responses and the analyses by position, user and item, and a *frontier* session with the methods that probe what RL learns (4.8 and 6.0 hours). Seeds 1 and 2 repeat the core on both datasets (base models, main run, anchor sweep, a KL budget, credit and estimator comparisons, alternatives to RL, logged relevance) and the frontier comparisons on KION; Yambda's frontier session ran without likes and dislikes, which none of its rewards use. On KION a *control* session runs seeds 0 to 2 itself (20 minutes per seed) for learning from the log, and a *quick* session repeats the core of the study with seed 0 in 55 minutes, reproducing the final session's numbers. "±" is the standard deviation over three seeds, each quantity computed within its seed; other numbers are from seed 0. Every session retrains every model with the same seed, so a run present in two sessions differs in the third decimal; every table names its session. Every conclusion below holds in each seed.

5 Results

Base models. On KION the recommender is level with GRU4Rec, 13% above SASRec and 5% below BERT4Rec for ranked lists; on Yambda it is the best trained model, but below a replay of the user's own history, which reads the same 118 events (NDCG@10 0.117 against 0.187, mostly on repeated tracks), so relevance there is measured against this recommender (Table 16). The reward model predicts whether a held-out event is consumed at least half with AUC 0.755 on KION and 0.868 on Yambda, against 0.656 and 0.607 for the item's mean share; the like and dislike heads reach 0.74 and 0.73. The two copies are calibrated on their own users and differ in level on the same lists (0.417 and 0.455 for the base recommender on KION), so we compare their relative changes.

5.1 Q1. How does the model's behaviour change after RL fine-tuning?

Is the reward maximised? As far as the reward models can tell, yes: on KION the main run raises the consumed share predicted by the training reward model by 20.3% and by the held-out one by 21.5% (23.9% ± 2.1; Table 14). The two rise together from the first evaluation on validation requests, and 85% of the gain and 90% of the loss of NDCG@10 arrive within the first 250 iterations; the policy then moves on, from 0.06 to 0.09 nats per item from π_0, for little more reward (Figure 2). The log does not show users responding better. Against what is usual for each title, users took to the recommended titles less: the logged surplus




Figure 2: The main run over its iterations (final sessions): the predicted share of the generated lists for validation requests as each reward model predicts it; NDCG@10 of the generated and ranked lists for the same requests; and the KL from the base recommender, in nats per generated item, of the lists sampled in training, recorded from the first update of the policy.

falls by $61\% \pm 2$, from 0.0012 to 0.0005 per recommended title, and by 15% at the validation-selected $\beta = 1$. The logged share per recommended item, which mostly counts hits, rises by $1.1\% \pm 0.4$: users reached fewer recommended titles (hits $-8.8\% \pm 0.9$) and finished those more often ($+10.8\% \pm 1.6$), because they are titles everybody finishes.

How the recommendations differ. Films take 66% of the impressions of the base recommender's generated lists and 80% of the main run's (89% at $\beta = 0.1$, and all of them without an anchor). The titles that gained most are films of 1.4 to 2.2 hours usually watched to 0.54–0.69; four of the five that lost most are series of 9.5 to 22 hours whose usual share is 0.08 to 0.29 (Table 11). Popularity is not what the policy follows: one of the largest gains is a film that 953 users watched in the training period. Across the catalogue (Figure 3), the four tenths of titles with the lowest usual share fall from 34% to 13% of the impressions and the three highest rise from 29% to 46%; the longest tenth, mostly series, falls from 26% to 14%. Yambda's impressions move the same way, by a few points.

One re-weighting of the catalogue. Held to the same KL budget as full RL, RL that may change only one score offset per item reaches $93\% \pm 3$ of full RL's gain in predicted share at a budget of 0.1 nats and $89\% \pm 4$ at 0.5, at an NDCG@10 within 0.002 of full RL's (Table 4). The same lists scored for another user earn the same gain (personal share $0.2\% \pm 0.5\%$), and re-ranking by the item's mean share in the training log, with no reward model, reaches the main run's point (predicted share 0.549 at NDCG@10 0.109, against 0.553 at 0.105). The main run's average change per item, added to π_0, reproduces $88\% \pm 2$ of its gain and all of its loss of relevance (NDCG@10 $-11.0\% \pm 1.8$ against RL's own $-11.6\% \pm 1.5$ in the same sessions). Removed from the fine-tuned policy, it leaves $21\% \pm 2$ of the gain at the base relevance ($-0.1\% \pm 0.4$) and a personal part of the predicted share $20\% \pm 3$ above the base recommender's: the two parts pull personalisation in opposite directions and cancel in RL. An item's mean shift correlates 0.90 with its usual consumed share, 0.12 with its log popularity and -0.36 with its duration (review session): the policy learned a ranking of titles by how often they are finished and applies it to every user.

The reward or the optimiser? The per-item share of the reward model's predictions is that of the optimum, known before any RL. On KION it is 0.79 ± 0.01, and every run of the anchor sweep, the KL budgets and LoRA stays below it in every seed (main run 0.77 ± 0.01): the reward sets the re-weighting, and the optimiser follows it. The reason is what the reward measures: $\hat{\rho}$ is the share a user consumes given that they start the item, so it cannot penalise an item the user would never start, and on KION the share of a series is taken over all its episodes, so an item that everybody finishes earns a high reward whoever receives it. On Yambda the reward is mostly personal (0.42), and every RL run is more per-item than its reward (0.46 to 0.55): averaging a noisy signal over histories, a policy gradient accumulates first the direction that is the same for all of them. There, item offsets fall short: they stop at a KL of 0.25 with the anchor weight at zero and reach 34% of




Figure 3: Where the impressions went (final sessions): the share of all impressions in the test users' lists that each tenth of the catalogue received from the base recommender and from the main run. The catalogue is cut into tenths with as many items each, by the item's usual consumed share in the training period and by its length.

full RL's gain at a budget of 0.5, less than full RL reaches at a KL of 0.11. Rank-1 LoRA stays on full RL's frontier on both datasets (87% to 95% of its gain at a higher NDCG@10), as reported for language models [32]. On Yambda the reward model also knows more about the user than RL uses ($55\% \pm 9$ of re-ranking's gain is personal, $16\% \pm 16$ of RL's).

Answer to Q1. The reward is maximised as far as the reward models can tell, but RL learns one re-weighting of the catalogue, which carries its whole loss of relevance, and measured against what is usual for each title, users took to the recommendations less. On KION the reward sets this re-weighting, since 79% of its optimum is per item; on Yambda, where the reward is mostly personal, the optimiser amplifies the per-item part.

Table 4: What RL learns (frontier sessions). Restricted runs and full RL hold the same KL budget, except that item offsets end short of 0.5: at a KL of 0.41 on KION (full RL 0.53), and on Yambda at 0.25 with the anchor weight at zero. The parts of the main run are compared with the base recommender. The per-item share is measured on the base recommender's 100 best candidates for every test user; that of the reward model's predictions is the optimum's at any β (Equation 2).

	KION, 3 seeds	**Yambda, 1 seed**
Fine-tuning held to a KL budget: % of full RL's gain in predicted share		
One score offset per item, budget 0.1	93 ± 3	–
One score offset per item, budget 0.5	89 ± 4	34
Rank-1 LoRA, budget 0.1	87 ± 5	–
Rank-1 LoRA, budget 0.5	93 ± 6	95
The main run's change split into one offset per item and the rest		
Base + RL's item offsets: % of RL's gain	88 ± 2	52
Base + RL's item offsets: NDCG@10, change in %	-11.0 ± 1.8	+0.4
Base + RL's item offsets: personal part, change in %	-15.7 ± 3.1	+0.0
RL − its item offsets: % of RL's gain	21 ± 2	50
RL − its item offsets: NDCG@10, change in %	-0.1 ± 0.4	+0.3
RL − its item offsets: personal part, change in %	$+20.5 \pm 2.5$	+1.1
RL: NDCG@10, change in %	-11.6 ± 1.5	+0.6
RL: personal part, change in %	$+2.2 \pm 2.9$	+1.4
Share of within-history variation that one effect per item explains		
Reward model's predictions (the optimum's change)	0.79 ± 0.01	0.42
RL, main run	0.77 ± 0.01	0.50
RL, KL budget 0.5	0.73 ± 0.02	0.49
Rank-1 LoRA, budget 0.5	0.72 ± 0.01	0.52
Item offsets, budget 0.5 (their ceiling)	0.89 ± 0.00	0.85

Table 5: Ranking metrics of the main run against the base recommender (generated lists, final session). At $K = 1$ NDCG and MAP coincide.

	KION			Yambda		
	before	**after**	**change, %**	**before**	**after**	**change, %**
NDCG						
NDCG@1	0.0885	0.0814	−7.9	0.1667	0.1655	−0.7
NDCG@5	0.1044	0.0920	−11.9	0.1336	0.1342	+0.4
NDCG@10	0.1173	0.1047	−10.7	0.1172	0.1183	+0.9
Recall						
Recall@1	0.0439	0.0389	−11.4	0.0159	0.0157	−1.3
Recall@5	0.1220	0.1050	−14.0	0.0507	0.0508	+0.2
Recall@10	0.1620	0.1453	−10.3	0.0747	0.0756	+1.2
MAP						
MAP@1	0.0885	0.0814	−7.9	0.1667	0.1655	−0.7
MAP@5	0.0781	0.0682	−12.6	0.0997	0.0996	−0.1
MAP@10	0.0819	0.0719	−12.2	0.0753	0.0754	+0.1

5.2 Q2. Is relevance preserved? Does the model recommend the same items to everyone?

A frontier, not a verdict. How much relevance is kept is a choice of operating point (Figure 4). At the weight selected on validation requests, $\beta = 1$ on KION, NDCG@10 falls by 1.8% for an 8.3% higher predicted share and a 3.3% higher logged share (three seeds); at the main run, $\beta = 0.3$, it falls by $11.5\% \pm 1.3$ for 24%. On Yambda the validation rule selects $\beta = 0.05$ (NDCG@10 −4.9%, predicted share +5.0%), one grid step from the weight that collapses the policy in every seed; the main run moves little.

Relevance by Recall, NDCG and MAP. At the main run on KION every metric falls at every cut-off, by 8 to 14% (Table 5). The first item is chosen from the real history alone, so the loss at $K = 1$ (−7.9%) is the policy's own preference; from the second position on, the generated context adds to it (Section 5.4). By outcome, NDCG@10 on liked titles is kept (+1.3%), Recall@10 on skipped titles falls by 18.2% and NDCG@10 on titles watched above their usual share by 9.4%. On Yambda every metric stays within 1.3% of the base recommender. On KION the users with the least history lose most: −13.5% of NDCG@10 for 5 to 8 earlier events against −7.4% for 25 or more (Table 12); on Yambda no group loses.

The same items for everyone? Not at the main run, but closer to it (Table 13). On KION the base recommender's generated lists already give the 1% most shown titles 72% of the impressions (62% for ranked lists); the main run raises this to 76% and the Gini coefficient of impressions from 0.963 to 0.969. With a weaker anchor the lists converge: 92% at $\beta = 0.1$, and without an anchor nearly every user receives the same list (pair overlap 0.98 on KION, 1.00 on Yambda), which the held-out model still scores 51% above the base recommender. On Yambda the share moves from 18% to 20%. What makes the lists alike is the per-item part of the policy (Section 5.1).

What keeps relevance. Only the anchor asks for relevance, and its weight does not say how much it keeps. At $\beta = 0.3$ on KION the leave-one-out estimator ends 6.7 times further from π_0 than the value model (KL 0.543 ± 0.010 against 0.081 ± 0.004); under a KL budget of 0.1 the two end at the same relevance (NDCG@10 0.1037 ± 0.0021 and 0.1013 ± 0.0026) with weights 2.9 times apart. The effective weight $\beta\sigma_A$ explains most of this: before standardisation the value model's advantages are 2.2 times larger at that budget (σ_A 0.95 against 0.43) and 1.7 times at a budget of 0.5, where the weights differ 2.7 times, which accounts for 55% to 75% of the gap on a logarithmic scale. On Yambda $\beta = 0.1$ keeps relevance and $\beta = 0.03$ collapses the policy in every seed (NDCG@10 0.006 ± 0.004; Table 15).

> **Answer to Q2.** Relevance is traded along a frontier: at the validation-selected weight KION loses 1.8% of NDCG@10, at the main run 11.5%, at every cut-off and most for users with short histories, while impressions concentrate further; the per-item part of the policy carries both. Yambda keeps both. The anchor is what keeps relevance, the KL distance a run ends at says how much of it is kept far better than the anchor weight does, and without the anchor every user receives the same list.

5.3 Q3. Can we get closer to long-term goals?

Which signals. Four signals in the logs describe what follows an item: the session continues, the user returns, the user likes or dislikes the item, and the user adopts it (the last two on Yambda only). A reward helps a policy only if its signal differs between the items a user could be shown. The predicted return varies between




Figure 4: Every fine-tuning run of the default reward against the KL distance it ended at from the base recommender (logarithmic axis; the base recommender at the left edge; final session).

one user's candidates four times (KION) and nine times (Yambda) less than between users, and the probability of a like by only 0.003 between a user's candidates. Adoption is the exception: it varies between candidates half as much as between users (0.077 against 0.165), and it is the only signal that leans towards the items users really consumed next (AUC 0.56).

Rewards for return and continued interaction. We rewarded each signal per item, and the return also for the list as a whole, after its last item. Rewarding the return of each item raises it by 3 to 7% on KION for 8 to 23% of NDCG@10 and does not move it on Yambda (Table 19). The *return after the list* moves the KION policy further than any per-item reward (KL 0.51 at $\beta = 0.3$): the predicted return rises from 0.73 to 0.86 (+18%), as the held-out model also predicts, while NDCG@10 falls by 69% and the logged share by 64% (Table 6), and the mean duration of a recommended title falls from 5.7 to 2.2 hours. KION's format, one row per user and title dated by its last view, does not explain it: in every decile of the duration of an event's own or next title, the return rate is between 0.68 and 0.77. No group comes back at 0.86: both reward models extrapolate alike, so the held-out model cannot catch it. With discount 0 the policy hardly moves (KL 0.006): this is the one reward for which credit along the list matters. On Yambda it does not move.

Likes and adoption (Yambda). The like reward at $\beta = 0.3$ raises the predicted probability of a like from 1.08% to 1.17% for 2% of NDCG@10; at $\beta = 0.1$ likes rise by 49% and dislikes by 53%: the policy finds tracks that provoke reactions, not tracks that are liked more. Adoption is the one long-term reward that moved without a loss of relevance: at $\beta = 0.3$ its predicted probability rises from 0.233 to 0.277 (+19%), NDCG@10 by 1.5% and the logged share by 2.5%, while coverage falls from 0.52 to 0.41.

Steering at inference. The closed form steers the base recommender towards these rewards without fine-tuning it (Table 6). Guided by predicted adoption, the base recommender's lists on Yambda gain 6.5% of adoption and 3.7% of NDCG@10 at strength 0.3, and 20% of adoption for 0.8% of NDCG@10 at 0.1, where the RL run gained 19% and 1.5%; judging each track also by a learned value of what follows it adds 3 and 6 points of adoption. On KION the return after the list is paid only at the end, so guidance that judges each title by its own reward sees it only at the last position. Look-ahead doubles that gain (0.729 to 0.742 without it, to 0.753 with it, at strength 0.1) for 2.3% of NDCG@10, where RL paid 69% for 0.86, and the guided lists keep the length of their titles.

Offline or online. Offline we can check whether a signal is predictable, whether it varies between the items a policy chooses from, whether a held-out model agrees, and what it costs in relevance. Whether users return, continue or adopt more under a new policy is counterfactual: the log shows these outcomes only under the policy that produced it, adoption needs 14 days after a first play, which a test week does not have, and a prediction can leave the log's range, as the return after the list did. This needs the online experiment of Section 6.1.

Table 6: Long-term rewards (review session), and guided decoding by them, which leaves the recommender as it is (frontier session; "β": the strength of guidance). "Δ": change of NDCG@10 in percent; "Return": the held-out model's predicted return after the last item; P(like), P(adopt): its predicted probabilities (Yambda only); "Cover.": catalogue coverage; "Hours": mean duration of a recommended KION title.

	KL	NDCG@10	Δ, %	Return	P(like)	P(adopt)	Logged	Cover.	Hours
KION									
Base recommender	0.000	0.1173	+0.0	0.728	–	–	0.0173	0.495	5.7
Return after list, β = 0.3	0.507	0.0361	−69.2	0.858	–	–	0.0062	0.539	2.2
Return after list, β = 0.1	3.423	0.0012	−99.0	0.888	–	–	0.0002	0.059	1.7
same, discount 0, β = 0.3	0.006	0.1144	−2.5	0.733	–	–	0.0171	0.510	5.3
Yambda									
Base recommender	0.000	0.1172	+0.0	0.892	0.0108	0.233	0.0669	0.519	–
Like − dislike, β = 0.3	0.046	0.1148	−2.0	0.891	0.0117	0.234	0.0654	0.505	–
Like − dislike, β = 0.1	0.829	0.0841	−28.2	0.878	0.0161	0.207	0.0475	0.423	–
Adoption, β = 0.3	0.141	0.1189	+1.5	0.893	0.0121	0.277	0.0686	0.409	–
Adoption, β = 0.1	1.204	0.0737	−37.1	0.888	0.0164	0.342	0.0407	0.129	–
Return after list, β = 0.3	0.021	0.1170	−0.2	0.892	0.0107	0.233	0.0677	0.521	–
KION, guided decoding by the return after the list (frontier session)									
Base recommender	0.000	0.1173	+0.0	0.729	–	–	0.0173	0.495	5.7
Guided, own reward, β = 0.3	–	0.1173	+0.0	0.734	–	–	0.0173	0.494	5.6
Guided, own reward, β = 0.1	–	0.1172	−0.1	0.742	–	–	0.0173	0.496	5.6
Guided, look-ahead, β = 0.3	–	0.1162	−0.9	0.738	–	–	0.0172	0.506	5.6
Guided, look-ahead, β = 0.1	–	0.1146	−2.3	0.753	–	–	0.0171	0.518	5.4
Yambda, guided decoding by adoption (frontier session)									
Base recommender	0.000	0.1172	+0.0	0.890	–	0.237	0.0669	0.519	–
Guided, own reward, β = 0.3	–	0.1216	+3.7	0.889	–	0.252	0.0705	0.491	–
Guided, own reward, β = 0.1	–	0.1163	−0.8	0.889	–	0.283	0.0678	0.410	–
Guided, look-ahead, β = 0.3	–	0.1221	+4.2	0.890	–	0.260	0.0706	0.475	–
Guided, look-ahead, β = 0.1	–	0.1137	−3.0	0.886	–	0.297	0.0663	0.360	–

Answer to Q3. Rewards for return, likes and adoption can be learned and optimised, but at a moderate distance their predictions rise by a few percent, and the largest gain lies outside the log. Adoption is the most promising signal: steering the base recommender by it at inference, with a learned look-ahead, raises adoption and relevance together. Only an online test can show whether users return or adopt more.

5.4 Q4. What happens when generating several steps ahead?

A generated list appends each chosen item to the history as if the user had consumed it, so it plans several steps ahead under an assumption that is false for most items: at most 17% of the items at any position are hits.

Effect on the following recommendations. After a miss, a generated list continues from a context that did not happen and hits less often than a ranked list: 0.0273 against 0.0312 at position 5 on KION, 0.040 against 0.063 on Yambda (Figure 5). After a hit it hits more often: 0.112 against 0.093 at position 2 on KION,




Figure 5: Hit rate by position of the list, for all lists, after a miss and after a hit at the position before: the base recommender's ranked and generated lists, and the lists of one head per position (frontier sessions).

and on Yambda, where listening continues within albums and artists, 0.54 against 0.25 at position 5. Misses dominate on KION, where generation costs 4% of NDCG@10; on Yambda generation is ahead at positions 2 to 7. A list predicted position by position from the real history removes the loss: after a miss one head per position hits at least as often as a ranked list (0.033 at position 5 on KION, 0.073 on Yambda), after a hit as often as a ranked list. On KION it is $6.3\% \pm 0.4$ more relevant than generation and $2.5\% \pm 0.1$ more than ranking, with a logged surplus $25\% \pm 1$ above generation's; on Yambda, where hits after hits matter more, it is level with generation (+0.4%) and 3.4% above ranking, with less coverage. Steering shows the same: deciding each position after the items already chosen, guided decoding loses to re-ranking once on KION (predicted share at the main run's NDCG@10: 0.556 ± 0.024 against 0.564 ± 0.025, RL 0.548 ± 0.023) and beats it on Yambda, where generation beats ranking (Figure 6).

Effect on the reward estimate. On the users' real next five items, with logged responses fed back, the AUC of the predicted share rises along the list (0.757 to 0.782 on KION, 0.640 to 0.819 on Yambda), while under any simulated response it stays near its first-step level (Figure 7 in the appendix). Expected responses underestimate the next share on Yambda by 0.06 to 0.09, sampled ones overestimate slightly (at most +0.035), and assuming that earlier items were finished overestimates by 0.06 to 0.18. The reward model trained with hidden responses and fed "unknown" is nearly unbiased (+0.001 to +0.013) and reads observed responses as well as the standard model (AUC 0.755 against 0.758 on KION). Policies fine-tuned against it or with sampled responses land on the same frontier: the assumption sets the level of a multi-step predicted reward, not which policy wins.

Does planning help? At an equal KL budget, crediting each item with its own reward only is at least as relevant as crediting it with the rest of the list: NDCG@10 0.1070 ± 0.0027 against 0.1013 ± 0.0026 on KION (one-item episodes 0.1043 ± 0.0024), at predicted shares 1.4 to 1.6 points lower, and 0.1076 ± 0.0014 against 0.0960 ± 0.0008 on Yambda. The myopic policies lie on the same frontier of relevance against reward. Only the return after the list, paid at the end, needed full credit (Section 5.3). Look-ahead at inference agrees: a learned value of what follows lowers the predicted share that guided decoding reaches at the main run's NDCG@10 on KION (0.548 against 0.567, seed 0), and helps only the rewards that depend on what follows an item, the return after the list and adoption.

> **Answer to Q4.** Generation gains after a hit and loses after a miss, and simulated responses bias the reward of later steps unless the reward model was trained to read unknown ones. One head per position predicts the list from the real history and removes the loss after a miss: the most relevant list on KION, level with generation on Yambda. Credit along the list and look-ahead help only rewards that depend on what follows an item.

5.5 Q5. What is the trade-off between relevance and reward?

How RL settings and the reward shape it. Every RL setting we varied, the anchor weight, the KL budget, the estimator, the credit assignment, the simulated responses and the capacity, moves the policy along one curve (Figure 4, Section 5.4): **RL settings choose a point on the frontier; only the reward function moves the frontier.** Equation 2 says why for per-item rewards: the settings change how far the policy moves towards π^*, not where π^* lies, and only r does. Rank-1 LoRA lies on the frontier, and GRPO at most slightly above it: at equal KL it reaches 7% to 10% more predicted share than the value model at no lower NDCG@10 on KION, and on Yambda it trades along the frontier (76% of the value model's gain at a higher NDCG@10; seed 0).

Can the reward rise without a noticeable loss of accuracy? Table 10 in the appendix reads each method at equal relevance, within 1% or 5% of the base recommender's NDCG@10; between two runs of a method the curve is the straight line that a mixture of the two policies achieves. On KION, RL on the share gains 4.2% and 14.1% of predicted share and 1.8% and 3.7% of logged share. Ten times logged relevance in the reward moves the frontier: 16.9% and 23.1% of predicted share. Re-ranking by the same reward model reaches 14.9% and 20.7% with the largest logged gains (15.6%), of which its start from the ranked list contributes 11.7%. On Yambda the differences at 1% are within the noise between seeds, and the methods that learn from the log lead in logged share through repeats.

Does it take RL? Re-ranking with weight w computes the top of the anchored optimum for $\beta = w$. At the main run's predicted share it is more relevant (NDCG@10 0.1119 ± 0.0013 against 0.1041 ± 0.0020), has a higher logged share (0.0201 ± 0.0001 against 0.0176 ± 0.0002), and $8.9\% \pm 0.3$ of its gain is personal against 0.2% for RL (Table 17). Most of the relevance gap is a head start: ranked lists are 4% more relevant than




Figure 6: Methods against the predicted share (frontier sessions, seed 0). RL, its interpolated and extrapolated weights, re-ranking and guided decoding share one frontier; reward-weighted fine-tuning on the relative share and one head per position leave it towards relevance and a higher logged surplus. Re-ranking starts from the ranked lists, the other methods from the generated ones.

generated ones on KION, and from its own start each method pays about the same relevance for the same predicted share.

Does it take training? Not to reach the frontier (Figure 6). Weights between the base recommender and the main run lie on the anchor sweep or slightly above it at equal predicted share (NDCG@10 $+0.0001 \pm 0.0002$ to $+0.0009 \pm 0.0002$), and extrapolating to twice the change stays on it (-0.0009 ± 0.0014); on Yambda, whose main run barely moved, extrapolation falls 0.003 below the run at $\beta = 0.1$. Guided decoding beats RL at equal relevance on both datasets; on Yambda, at strength 0.3, it raises NDCG@10 by 2.1% and the logged surplus by 9% at about RL's predicted share.

Rewards that move the frontier. On KION the share plus ten times logged relevance at $\beta = 0.3$ improves on the base recommender's generated lists in relevance (NDCG@10 0.1202 ± 0.0007 against 0.1177 ± 0.0008), predicted share (+10%) and logged share (+7%) at once, though not on its ranked lists (0.1221 ± 0.0004). RL on the relative share removes the drift towards films and keeps relevance but gains almost nothing (Table 18); re-ranking by it, against the ranked lists it starts from, raises NDCG@10 from 0.1221 ± 0.0004 to 0.1234 ± 0.0006 and the logged surplus by 15% at $w = 0.3$, and the surplus by 38% for 0.5% of NDCG@10 at $w = 0.1$, in every seed (Table 9). On Yambda logged relevance alone raises NDCG@10 by 23% by replaying histories (relevance on new tracks falls from 0.0260 to 0.0198).

Learning from the log. Every method above reads the reward model; reading the log instead does better on the outcomes the reward model cannot inflate. Reward-weighted fine-tuning on the logged relative share ($\tau = 0.3$) raises NDCG@10 by $1.9\% \pm 0.5$, the logged surplus by $28\% \pm 3$, the personal part by $19\% \pm 1$ and coverage by $5\% \pm 2$ on KION, and the per-user intervals of NDCG@10 and of the surplus exclude zero in every seed (Table 7). It lowers the predicted share by 3.8%: it moves towards what a user takes to more than usual, not towards what the reward model rates. On the plain consumed share the same fine-tuning reproduces RL's drift without a reward model: predicted share $+20.8\% \pm 0.5$ against RL's $+24.0\% \pm 2.0$, NDCG@10 $-13.4\% \pm 0.3$, the logged surplus -75% and recommended titles half as long, so the drift lies in the definition of the share. Within-user DPO buys a larger surplus ($+42\% \pm 5$) and personal part ($+35\% \pm 6$) with relevance ($-3.7\% \pm 1.6$) and coverage ($-22\% \pm 2$). On Yambda reward-weighted fine-tuning raises the surplus by 13% at unchanged relevance, and liked-only fine-tuning, its hard-threshold form, does better (NDCG@10 +2.2%).

A control for the extra epoch. Reward-weighted fine-tuning trains π_0 for one more epoch at a tenth of its learning rate, and π_0 had stopped while its learning rate was still high; on KION its ranked lists are also 4%

Table 7: Learning from logged responses alone, without a reward model (frontier sessions): change against the base recommender's generated lists, in percent. "Logged surplus": the logged response to recommended items relative to what is typical for each item; "Personal part": the held-out reward model's prediction for the user minus that for another user.

	NDCG@10	Logged surplus	Personal part	Coverage	Pred. share
KION, 3 seeds					
RL, main run ($\beta = 0.3$)	-11.6 ± 1.5	-60.4 ± 3.7	$+2.2 \pm 2.9$	-13.0 ± 3.2	$+24.0 \pm 2.0$
Liked-only fine-tuning	-11.7 ± 0.3	-71.6 ± 3.5	$+2.2 \pm 1.5$	-4.8 ± 0.9	$+20.3 \pm 0.5$
Reward-weighted, relative share, $\tau = 0.3$	$+1.9 \pm 0.5$	$+27.7 \pm 2.8$	$+18.7 \pm 0.9$	$+5.3 \pm 1.7$	-3.8 ± 1.0
Reward-weighted, relative share, $\tau = 1$	$+1.3 \pm 0.1$	$+12.9 \pm 1.5$	$+6.9 \pm 0.9$	$+9.0 \pm 1.6$	-2.3 ± 0.8
Reward-weighted, consumed share, $\tau = 0.3$	-13.4 ± 0.3	-74.7 ± 0.9	$+0.5 \pm 2.2$	-3.4 ± 0.9	$+20.8 \pm 0.5$
Within-user DPO, $\beta = 0.5$	-3.7 ± 1.6	$+42.0 \pm 4.9$	$+35.1 \pm 5.5$	-22.3 ± 2.0	-8.0 ± 0.8
Within-user DPO, $\beta = 0.1$	-18.7 ± 2.9	$+1.1 \pm 6.3$	$+9.2 \pm 9.2$	-57.9 ± 2.4	-10.8 ± 3.7
Yambda, 1 seed					
RL, main run ($\beta = 0.3$)	$+0.6$	$+2.7$	$+1.4$	-2.7	$+1.6$
Liked-only fine-tuning	$+2.2$	$+7.9$	$+3.4$	-0.9	$+1.1$
Reward-weighted, relative share, $\tau = 0.3$	$+0.5$	$+12.9$	$+1.4$	-1.1	-0.1
Reward-weighted, relative share, $\tau = 1$	$+1.1$	$+7.9$	$+0.8$	-0.2	$+0.0$
Within-user DPO, $\beta = 0.1$	-24.2	$+32.3$	$+9.3$	-36.7	-0.6

more relevant than its generated ones. A control session with seeds 0 to 2 settles both, with the hypotheses written before the run (Table 8). The same epoch with every weight equal to one, *continued training*, lowers the next-item loss on the validation period in every seed and raises coverage by 10%, NDCG@10 of generated lists by 0.7% (significant in two seeds of three) and the logged surplus by 5% (one seed of three). Against it, the weights add $21\% \pm 4$ of logged surplus, $19\% \pm 2$ of personal part and $1.3\% \pm 0.5$ of NDCG@10 on generated lists, and 17%, 15% and 0.7% on ranked lists, each in every seed, while coverage falls by 3% to 4%. The fine-tuned recommender's ranked lists are also $0.9\% \pm 0.3$ more relevant than those of π_0, with 23% more logged surplus, in every seed. So the extra epoch gives a third of the relevance gain and all of the coverage gain; the weights give the other two thirds of the relevance gain and almost all of the length-neutral response and personalisation.

Answer to Q5. RL settings choose a point on the frontier, and re-ranking, guided decoding and weight interpolation reach it without RL training. The frontier moves when the reward contains the log: logged relevance in the reward, and above all reward-weighted fine-tuning on the logged relative share, which on KION raises a length-neutral logged response by 17–21% and personalisation by 15–19% over the same epoch of plain training, with relevance up, on generated and on ranked lists, without a reward model.

6 Discussion

A second reward model, the usual defence against reward hacking, catches the exploitation specific to one set of weights (0.84 against 0.69 without an anchor) and misses what any model of this kind invites, as Eisenstein et al. [22] found for ensembles: both of our models learned, correctly, that some titles are finished more often than others, and both extrapolate the return after the list past any rate in the log. Scoring the same lists for another user, splitting the policy's change into a part per item, and counting the logged response to recommended items expose this cheaply, and the per-item share of the reward's predictions says before any RL how much of a policy's change will be one re-weighting of the catalogue. For a reward that sums per-

Table 8: Learning from the log against the same epoch of training without its weights (KION, control session, seeds 0 to 2): change in percent, mean ± standard deviation over the seeds, each change computed within its seed and against lists of the same kind. "Continued training" weighs every logged item one; "Surplus": the logged surplus; "Personal": the personal part of the predicted share.

	Generated lists				Ranked lists			
	NDCG@10	Surplus	Personal	Coverage	NDCG@10	Surplus	Personal	Coverage
Against the base recommender's lists of the same kind								
Continued training	$+0.7 \pm 0.3$	$+5.3 \pm 2.3$	-0.4 ± 1.2	$+10.2 \pm 1.4$	$+0.2 \pm 0.3$	$+5.1 \pm 4.0$	-1.0 ± 2.1	$+8.8 \pm 1.2$
Reward-weighted, $\tau = 1$	$+1.3 \pm 0.1$	$+12.9 \pm 1.5$	$+6.9 \pm 0.9$	$+9.0 \pm 1.6$	$+0.6 \pm 0.4$	$+11.6 \pm 4.0$	$+4.5 \pm 1.3$	$+8.1 \pm 1.1$
Reward-weighted, $\tau = 0.3$	$+1.9 \pm 0.5$	$+27.7 \pm 2.8$	$+18.7 \pm 1.0$	$+5.3 \pm 1.7$	$+0.9 \pm 0.3$	$+22.7 \pm 4.6$	$+13.4 \pm 0.5$	$+5.4 \pm 1.1$
Within-user DPO, $\beta = 0.5$	-3.7 ± 1.6	$+42.0 \pm 4.9$	$+35.2 \pm 5.6$	-22.3 ± 2.0	-3.6 ± 0.4	$+40.6 \pm 1.1$	$+30.1 \pm 2.6$	-11.0 ± 1.0
Against continued training, lists of the same kind								
Reward-weighted, $\tau = 1$	$+0.6 \pm 0.3$	$+7.2 \pm 1.5$	$+7.3 \pm 0.8$	-1.1 ± 0.3	$+0.4 \pm 0.1$	$+6.2 \pm 0.7$	$+5.7 \pm 1.0$	-0.7 ± 0.1
Reward-weighted, $\tau = 0.3$	$+1.3 \pm 0.5$	$+21.3 \pm 3.7$	$+19.2 \pm 2.0$	-4.4 ± 0.5	$+0.7 \pm 0.1$	$+16.8 \pm 0.1$	$+14.6 \pm 2.2$	-3.2 ± 0.1
Within-user DPO, $\beta = 0.5$	-4.3 ± 1.6	$+35.0 \pm 6.9$	$+35.8 \pm 7.1$	-29.5 ± 1.7	-3.8 ± 0.1	$+33.9 \pm 4.1$	$+31.6 \pm 5.4$	-18.2 ± 1.3

item predictions, the anchored optimum is reached without a policy gradient (Equation 2). What moved the frontier was the log, through a reward that compares a response with what is typical for the item, and the list format, which should follow how strongly one consumption predicts the next. In practice: compute the reward's per-item share before fine-tuning; report the KL distance a run ended at, not its weight; re-rank or decode by the reward model before training against it; fit the anchored optimum of a length-neutral logged reward directly; and choose the list format on validation.

6.1 An online experiment

Offline evidence settles the collapse, the role of the anchor and the impersonality of the predicted gain. Whether users consume more of the fine-tuned lists, return more often or adopt more needs an experiment that serves them. Its arms are set by KL distance, since near Yambda's cliff a fixed weight does not fix a distance.

- *Arms:* (A) the base recommender; (B) RL held at the KL distance of the validation-selected run (0.015 nats per item on KION, 0.29 on Yambda); (C) re-ranking by the reward model at the predicted share of B; (D) reward-weighted fine-tuning on the relative share, $\tau = 0.3$; (E) one head per position; (F) on the music service, decoding guided by adoption with look-ahead at strength 0.3.
- *Primary metrics, per user, over four weeks of hashed assignment* (one week for exposure to settle, fourteen days of adoption window, one more for returns): the consumed share of served recommendations and its surplus over what is typical for each item, the return rate, and on Yambda the share of first plays of recommended tracks played again within 14 days.
- *Guardrails:* consumption per user, likes and dislikes, coverage and Gini of impressions, the share of new items, and every metric for the quartile of users with the shortest histories.
- *Analysis and size:* per-user differences with a CUPED adjustment on the four weeks before, bootstrap intervals, history quartiles as pre-registered segments; a 1% relative change in a binary outcome near 0.7 needs about $2(1.96 + 0.84)^2 \cdot 0.7 \cdot 0.3/0.007^2 \approx 67,000$ users per arm ($\alpha = 0.05$, power 0.8).

7 Limitations, Future Work and Conclusion

Limitations. All results are offline, and the logged check sees only recommended items that users reached on their own. Yambda's frontier session, the long-term rewards and the analyses by position, user and item have one seed, and adoption could not be verified on a test week. The models are small (4 layers of width 256), so a larger reward model may know more about users; Yambda's models read 118 events of a median 2,638, its grids are narrower than KION's, and the baselines are untuned. Guided decoding calls the reward model for 50 candidates at every position, the heads per position sit on a frozen recommender, and reward-weighted fine-tuning and DPO ran at one learning rate. Early stopping kept the base recommender while its learning rate was still high: one more epoch of plain training lowers its validation loss and raises NDCG@10 of its generated lists by 0.7%, a slack in every change measured against it that is small next to RL's loss and a third of the relevance gained by learning from the log. The equal-relevance curves interpolate between runs, the per-item share is measured on 100 candidates, and the personal part is the reward model's own belief.

Future work. The online experiment of Section 6.1 is the decisive next step. Offline: a base recommender trained until its learning rate has decayed, as the reference for every method; the per-user counterpart of the relative share from OneRec-V2 [43] as the logged reward of reward-weighted fine-tuning; heads per position trained together with the recommender and combined with reward-weighted fine-tuning; guided decoding with the value of the optimum rather than of π_0, as Q♯ iterates it [34]; a larger reward model, whose per-item share would say in advance whether RL can learn more than a re-weighting of the catalogue; a longer Yambda context; and a test period long enough to observe adoption.

Conclusion. We fine-tuned a generative recommender against a learned reward model, with only a KL anchor to keep it relevant. The predicted reward rose, and a reward model trained on other users confirmed the rise, but what RL had learned was largely one re-weighting of the catalogue towards the items finished most often. Measured against what is typical for each item, the logged response to the recommendations fell, and relevance was traded along a frontier that RL settings only move along and that inference reaches without training. What moved the frontier came from the log and from the list format. Reward-weighted fine-tuning on the consumed share relative to what is typical for the item improved a length-neutral logged response, personalisation and relevance beyond the same epoch of plain training, on generated and on ranked lists, and lists predicted position by position from the real history were more relevant than generated ones. A reward model is worth optimising with RL only if it knows something about the user that cannot be looked up per

item, and its per-item share shows whether it does before any training. Code, configurations and every table are in `github.com/daniilantonovv/RecSysMaxxing`.

References

[1] W.-C. Kang and J. McAuley, "Self-Attentive Sequential Recommendation," *arXiv preprint arXiv:1808.09781*, 2018.

[2] A. V. Petrov and C. Macdonald, "Generative Sequential Recommendation with GPTRec," *arXiv preprint arXiv:2306.11114*, 2023.

[3] S. Rajput *et al.*, "Recommender Systems with Generative Retrieval," *arXiv preprint arXiv:2305.05065*, 2023.

[4] J. Zhai *et al.*, "Actions Speak Louder than Words: Trillion-Parameter Sequential Transducers for Generative Recommendations," *arXiv preprint arXiv:2402.17152*, 2024.

[5] J. Deng *et al.*, "OneRec: Unifying Retrieve and Rank with Generative Recommender and Iterative Preference Alignment," *arXiv preprint arXiv:2502.18965*, 2025.

[6] M. Chen, A. Beutel, P. Covington, S. Jain, F. Belletti, and E. Chi, "Top-K Off-Policy Correction for a REINFORCE Recommender System," *arXiv preprint arXiv:1812.02353*, 2018.

[7] E. Ie *et al.*, "Reinforcement Learning for Slate-based Recommender Systems: A Tractable Decomposition and Practical Methodology," *arXiv preprint arXiv:1905.12767*, 2019.

[8] A. Petrov and C. Macdonald, "Aligning GPTRec with Beyond-Accuracy Goals with Reinforcement Learning," *arXiv preprint arXiv:2403.04875*, 2024.

[9] A. Matveev, S. Makeev, A. Krasilnikov, V. Baikalov, S. Liamaev, and K. Khrylchenko, "Session-Level Optimization for Large-Scale Retrieval using REINFORCE with Multi-Step Off-Policy Correction," *arXiv preprint arXiv:2607.02818*, 2026.

[10] L. Gao, J. Schulman, and J. Hilton, "Scaling Laws for Reward Model Overoptimization," *arXiv preprint arXiv:2210.10760*, 2022.

[11] J. Skalse, N. H. R. Howe, D. Krasheninnikov, and D. Krueger, "Defining and Characterizing Reward Hacking," *arXiv preprint arXiv:2209.13085*, 2022.

[12] C. Gao *et al.*, "Alleviating Matthew Effect of Offline Reinforcement Learning in Interactive Recommendation," *arXiv preprint arXiv:2307.04571*, 2023.

[13] R. Jiang, S. Chiappa, T. Lattimore, A. György, and P. Kohli, "Degenerate Feedback Loops in Recommender Systems," *arXiv preprint arXiv:1902.10730*, 2019.

[14] A. Radford, J. Wu, R. Child, D. Luan, D. Amodei, and I. Sutskever, "Language Models are Unsupervised Multitask Learners," technical report, 2019.

[15] B. Hidasi, A. Karatzoglou, L. Baltrunas, and D. Tikk, "Session-based Recommendations with Recurrent Neural Networks," *arXiv preprint arXiv:1511.06939*, 2015.

[16] F. Sun *et al.*, "BERT4Rec: Sequential Recommendation with Bidirectional Encoder Representations from Transformer," *arXiv preprint arXiv:1904.06690*, 2019.

[17] X. Xin, A. Karatzoglou, I. Arapakis, and J. M. Jose, "Self-Supervised Reinforcement Learning for Recommender Systems," *arXiv preprint arXiv:2006.05779*, 2020.

[18] E. Ie *et al.*, "RecSim: A Configurable Simulation Platform for Recommender Systems," *arXiv preprint arXiv:1909.04847*, 2019.

[19] K. Zhao *et al.*, "KuaiSim: A Comprehensive Simulator for Recommender Systems," *arXiv preprint arXiv:2309.12645*, 2023.

[20] T. Yu *et al.*, "MOPO: Model-based Offline Policy Optimization," *arXiv preprint arXiv:2005.13239*, 2020.

[21] R. Kidambi, A. Rajeswaran, P. Netrapalli, and T. Joachims, "MOReL: Model-Based Offline Reinforcement Learning," *arXiv preprint arXiv:2005.05951*, 2020.

[22] J. Eisenstein *et al.*, "Helping or Herding? Reward Model Ensembles Mitigate but do not Eliminate Reward Hacking," in *Conference on Language Modeling*, 2024.

[23] N. Jaques *et al.*, "Way Off-Policy Batch Deep Reinforcement Learning of Implicit Human Preferences in Dialog," *arXiv preprint arXiv:1907.00456*, 2019.

[24] D. M. Ziegler *et al.*, "Fine-Tuning Language Models from Human Preferences," *arXiv preprint arXiv:1909.08593*, 2019.

[25] L. Ouyang *et al.*, "Training language models to follow instructions with human feedback," *arXiv preprint arXiv:2203.02155*, 2022.

[26] R. Zhan *et al.*, "Deconfounding Duration Bias in Watch-time Prediction for Video Recommendation," *arXiv preprint arXiv:2206.06003*, 2022.

[27] H. Zhao, L. Zhang, J. Xu, G. Cai, Z. Dong, and J.-R. Wen, "Uncovering User Interest from Biased and Noised Watch Time in Video Recommendation," *arXiv preprint arXiv:2308.08120*, 2023.

[28] L. Zou, L. Xia, Z. Ding, J. Song, W. Liu, and D. Yin, "Reinforcement Learning to Optimize Long-term User Engagement in Recommender Systems," *arXiv preprint arXiv:1902.05570*, 2019.

[29] Q. Cai *et al.*, "Reinforcing User Retention in a Billion Scale Short Video Recommender System," *arXiv preprint arXiv:2302.01724*, 2023.

[30] J. Carbonell and J. Goldstein, "The Use of MMR, Diversity-Based Reranking for Reordering Documents and Producing Summaries," in *Proceedings of the 21st Annual International ACM SIGIR Conference on Research and Development in Information Retrieval*, 1998, pp. 335–336.

[31] E. J. Hu *et al.*, "LoRA: Low-Rank Adaptation of Large Language Models," in *International Conference on Learning Representations*, 2022.

[32] J. Schulman and Thinking Machines Lab, "LoRA Without Regret," *Thinking Machines Lab: Connectionism*, 2025, [Online]. Available: https://thinkingmachines.ai/blog/lora/

[33] S. Mudgal *et al.*, "Controlled Decoding from Language Models," in *Proceedings of the 41st International Conference on Machine Learning*, 2024.

[34] J. P. Zhou *et al.*, "Q♯: Provably Optimal Distributional RL for LLM Post-Training," in *Advances in Neural Information Processing Systems*, 2025.

[35] X. B. Peng, A. Kumar, G. Zhang, and S. Levine, "Advantage-Weighted Regression: Simple and Scalable Off-Policy Reinforcement Learning," *arXiv preprint arXiv:1910.00177*, 2019.

[36] K. Chidambaram, S. K. Krishnamurthy, Q. Xu, K.-J. Hsiao, and M. Bhattacharya, "Robust Post-Training for Generative Recommenders: Why Exponential Reward-Weighted SFT Outperforms RLHF," *arXiv preprint arXiv:2603.10279*, 2026.

[37] R. Rafailov, A. Sharma, E. Mitchell, S. Ermon, C. D. Manning, and C. Finn, "Direct Preference Optimization: Your Language Model is Secretly a Reward Model," in *Advances in Neural Information Processing Systems*, 2023.

[38] M. Wortsman *et al.*, "Robust Fine-Tuning of Zero-Shot Models," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2022.

[39] A. Ramé *et al.*, "WARP: On the Benefits of Weight Averaged Rewarded Policies," *arXiv preprint arXiv:2406.16768*, 2024.

[40] C. Zheng, Z. Wang, H. Ji, M. Huang, and N. Peng, "Model Extrapolation Expedites Alignment," in *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics*, 2025.

[41] Z. Shao *et al.*, "DeepSeekMath: Pushing the Limits of Mathematical Reasoning in Open Language Models," *arXiv preprint arXiv:2402.03300*, 2024.

[42] F. Gloeckle, B. Y. Idrissi, B. Rozière, D. Lopez-Paz, and G. Synnaeve, "Better & Faster Large Language Models via Multi-token Prediction," in *Proceedings of the 41st International Conference on Machine Learning*, 2024.

[43] G. Zhou *et al.*, "OneRec-V2 Technical Report," *arXiv preprint arXiv:2508.20900*, 2025.

[44] J. Schulman, P. Moritz, S. Levine, M. Jordan, and P. Abbeel, "High-Dimensional Continuous Control Using Generalized Advantage Estimation," *arXiv preprint arXiv:1506.02438*, 2015.

[45] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov, "Proximal Policy Optimization Algorithms," *arXiv preprint arXiv:1707.06347*, 2017.

[46] W. Kool, H. van Hoof, and M. Welling, "Buy 4 REINFORCE Samples, Get a Baseline for Free!," in *ICLR 2019 Workshop on Deep Reinforcement Learning Meets Structured Prediction*, 2019.

[47] A. Petrov, I. Safilo, D. Tikhonovich, and D. Ignatov, "MTS Kion Implicit Contextualised Sequential Dataset for Movie Recommendation," *arXiv preprint arXiv:2209.00325*, 2022.

[48] A. Ploshkin *et al.*, "Yambda-5B — A Large-Scale Multi-modal Dataset for Ranking And Retrieval," *arXiv preprint arXiv:2505.22238*, 2025.

A Supporting tables

Table 9: The central comparisons over three seeds (0, 1, 2): mean ± standard deviation. A seed fixes the initial weights of every model and the sampling of fine-tuning. "Budget" is a KL budget of 0.1 nats on KION and 0.5 on Yambda; "–": not run with three seeds on that dataset; "<0.0001": a spread below the four decimals at which seeds 1 and 2 were saved.

	KION	**Yambda**
Main run (β = 0.3) against the base recommender		
NDCG@10, change in %	−11.5 ± 1.3	+0.8 ± 0.7
Predicted share, held-out model, change in %	+23.91 ± 2.09	+1.67 ± 0.01
Logged share per recommended item, change in %	+1.1 ± 0.4	+1.7 ± 0.7
Logged surplus per recommended item, change in %	−60.6 ± 2.1	−3.8 ± 3.4
Personal share of the predicted gain, %	0.2 ± 0.5	15.9 ± 16.3
KL from the base recommender	0.091 ± 0.005	0.038 ± 0.001
What the anchor weight means		
KL at β = 0.3, value model	0.081 ± 0.004	–
KL at β = 0.3, leave-one-out baseline	0.543 ± 0.010	–
Weight holding the KL budget, value model	0.256 ± 0.004	0.076 ± 0.011
Weight holding the KL budget, leave-one-out	0.752 ± 0.017	–
NDCG@10 at the budget, whole rest of the list	0.1013 ± 0.0026	0.0960 ± 0.0008
NDCG@10 at the budget, own reward only	0.1070 ± 0.0027	0.1076 ± 0.0014
NDCG@10 at the budget, one item per episode	0.1043 ± 0.0024	0.1075 ± 0.0038
NDCG@10 at β = 0.03 (Yambda's cliff)	–	0.0061 ± 0.0043
Alternatives and rewards		
NDCG@10, RL main run	0.1041 ± 0.0020	0.1190 ± 0.0015
NDCG@10, re-ranking w = 0.3	0.1119 ± 0.0013	0.1155 ± 0.0008
Logged share per item, RL main run	0.0176 ± 0.0002	0.0689 ± 0.0008
Logged share per item, re-ranking w = 0.3	0.0201 ± 0.0001	0.0662 ± 0.0007
Personal share of the gain, re-ranking w = 0.3, %	8.9 ± 0.3	54.7 ± 8.8
NDCG@10, off-policy REINFORCE	0.1035 ± 0.0006	0.1256 ± 0.0009
NDCG@10, share + 10 × logged relevance, β = 0.3	0.1202 ± 0.0007	–
NDCG@10, logged relevance alone, β = 0	0.1179 ± 0.0004	0.1453 ± 0.0014
NDCG@10 on new items, logged relevance alone	–	0.0198 ± 0.0005
Validation-selected weight on KION (β = 1)		
NDCG@10 at β = 1	0.1156 ± 0.0011	–
Predicted share at β = 1	0.478 ± 0.020	–
Logged share per item at β = 1	0.0179 ± 0.0001	–
Logged surplus per item at β = 1	0.0010 ± 0.0001	–
KL at β = 1	0.015 ± 0.001	–
Re-ranking by the relative share on KION, against the ranked lists it starts from		
NDCG@10, ranked lists	0.1221 ± 0.0004	–
NDCG@10, re-ranking w = 0.3	0.1234 ± 0.0006	–
NDCG@10, re-ranking w = 0.1	0.1214 ± 0.0019	–
Logged surplus per item, ranked lists	0.00140 ± 0.00007	–
Logged surplus per item, re-ranking w = 0.3	0.00161 ± 0.00007	–
Logged surplus per item, re-ranking w = 0.1	0.00193 ± 0.00009	–
Reference		
NDCG@10, base recommender	0.1177 ± 0.0008	0.1181 ± 0.0010
Predicted share, base recommender	0.442 ± 0.019	0.596 ± 0.005
Logged share per item, base recommender	0.0174 ± 0.0002	0.0677 ± 0.0011
Logged surplus per item, base recommender	0.0012 ± <0.0001	–
NDCG@10 on new items, base recommender	–	0.0260 ± 0.0004
Reward model AUC, held-out copy	0.754 ± 0.001	0.867 ± 0.001

Table 10: Methods at equal relevance (final session): the largest change of the predicted share (held-out model) reached without losing more than 1% or 5% of the base recommender's NDCG@10, and the change of the logged share at that point, in percent. "–": the method does not reach that relevance.

	NDCG@10 at most 1% below the base		NDCG@10 at most 5% below the base	
	Predicted share, %	**Logged share, %**	**Predicted share, %**	**Logged share, %**
KION				
Ranked list of the base recommender	+2.4	+11.7	+2.4	+11.7
RL on the share, anchor sweep	+4.2	+1.8	+14.1	+3.7
RL on share + 10 × logged relevance	+16.9	+8.8	+23.1	+6.7
Re-ranking by the reward model	+14.9	+15.6	+20.7	+15.5
Off-policy REINFORCE	+1.4	+0.3	+6.9	+1.4
Liked-only fine-tuning	+1.7	+0.3	+8.4	+1.4
Yambda				
Ranked list of the base recommender	+0.6	−1.2	+1.9	−3.6
RL on the share, anchor sweep	+2.8	+0.1	+5.0	−2.5
RL on share + 10 × logged relevance	+1.4	+24.1	+1.4	+24.1
Re-ranking by the reward model	–	–	+5.3	−3.8
Off-policy REINFORCE	+1.9	+9.9	+1.9	+9.9
Liked-only fine-tuning	+1.2	+3.4	+1.2	+3.4




Figure 7: The reward model on the users' real next five items: bias and AUC of the predicted share at each step, with the earlier responses as logged, expected, sampled, finished, or unknown to the model trained with hidden responses (review session).

Table 11: KION: the titles whose number of lists among the 59,997 test requests grew and shrank most under the main run (review session). Titles as given in the English release of the KION item table, which translates the Russian titles; "usual share": the title's mean consumed share in the training period.

	Type	**Hours**	**Viewers in training**	**Usual share**	**Lists before**	**after**
Gained most						
White Snow (2021)	film	2.2	32,435	0.64	8,388	24,472
Palmyra (2020)	film	1.4	18,762	0.54	8,598	21,579
Devyataev (2021)	film	1.9	108,030	0.69	14,471	26,328
Dukhless (2011)	film	1.7	953	0.55	7,308	17,315
Masha (2020)	film	1.5	40,254	0.63	23,485	32,316
Lost most						
Themis sees (2019)	series	16.9	25,571	0.08	33,948	10,781
Listened to (2021)	series	9.5	62,651	0.18	16,278	3,343
The Scam (2021)	series	22.0	51,094	0.11	16,660	4,038
The Germans (2021)	series	10.9	33,452	0.29	14,654	5,371
Flash radio (2019)	film	1.7	8,811	0.33	11,925	5,088

Table 12: NDCG@10 and the change of the logged share per recommended item by the user's number of events before the request, in quartiles (review session, main run).

		NDCG@10				
	Users	**Base, ranked**	**Base, generated**	**RL**	**RL change, %**	**Logged change, %**
KION						
5–8 events	14552	0.1537	0.1515	0.1311	−13.5	−2.4
9–13 events	14121	0.1364	0.1311	0.1171	−10.7	+1.2
14–24 events	15849	0.1151	0.1097	0.0991	−9.7	−0.6
25–1143 events	15475	0.0861	0.0802	0.0743	−7.4	+3.3
Yambda						
50–1076 events	1897	0.1164	0.1147	0.1165	+1.6	+1.3
1077–2960 events	1899	0.1179	0.1236	0.1237	+0.1	+3.1
2961–6420 events	1898	0.1110	0.1158	0.1162	+0.3	+2.4
6421–25401 events	1899	0.1101	0.1150	0.1159	+0.8	+1.5

Table 13: Concentration of impressions: catalogue coverage, Gini coefficient of the impressions per item, and the share of impressions taken by the 1% most shown items (review session).

	Coverage	**Gini of impressions**	**Top 1% of items, % of impressions**
KION			
Base recommender, ranked	0.574	0.949	62
Base recommender, generated	0.495	0.963	72
RL, $\beta = 0.3$ (main run)	0.452	0.969	76
$\beta = 0.1$	0.278	0.990	92
$\beta = 0$	0.008	0.999	100
Yambda			
Base recommender, ranked	0.466	0.789	23
Base recommender, generated	0.519	0.737	18
RL, $\beta = 0.3$ (main run)	0.512	0.747	20
$\beta = 0.05$	0.446	0.808	29

Table 14: The main run ($\beta = 0.3$) against the base recommender, final session, seed 0. Changes are relative, in percent, with a 95% paired-bootstrap interval over users where the quantity is defined per user.

	KION			**Yambda**		
	before	**after**	**change, %**	**before**	**after**	**change, %**
Relevance against the user's logged future						
NDCG@10, all next items	0.1173	0.1047	−10.7 [−11.6, −9.8]	0.1172	0.1183	+0.9 [−0.7, +2.5]
NDCG@10, liked items	0.1214	0.1229	+1.3 [+0.1, +2.4]	0.1005	0.1029	+2.4 [+0.6, +4.3]
NDCG@10, items consumed above usual	0.1261	0.1142	−9.4 [−10.6, −8.2]	0.0998	0.1023	+2.5 [+0.7, +4.3]
Recall@10, skipped items	0.1382	0.1130	−18.2 [−19.6, −16.8]	0.0724	0.0735	+1.5 [−1.7, +4.6]
Predicted consumed share of the list						
Training reward model	0.417	0.502	+20.3 [+20.1, +20.4]	0.594	0.608	+2.2 [+2.1, +2.4]
Held-out reward model	0.455	0.553	+21.5 [+21.4, +21.7]	0.599	0.609	+1.7 [+1.5, +1.9]
Held-out, list shown to another user	0.442	0.539	+22.0 [+21.9, +22.2]	0.498	0.508	+2.0 [+1.7, +2.3]
Held-out, relative share	0.529	0.524	−1.0 [−1.1, −1.0]	0.469	0.468	−0.3 [−0.4, −0.1]
Logged response to the recommended items the user went on to consume						
Such items per list	0.359	0.329	−8.3	0.943	0.961	+1.9
Their logged share	0.481	0.528	+9.8	0.710	0.713	+0.5
Logged share per recommended item	0.0173	0.0174	+0.6 [−0.6, +1.7]	0.0669	0.0686	+2.5 [+0.3, +4.6]
Logged surplus per recommended item	0.0012	0.0005	−61.9 [−69.4, −54.4]	0.0033	0.0032	−3.0 [−15.2, +9.1]
Lists						
Catalogue coverage	0.495	0.449	−9.2	0.519	0.506	−2.6
Overlap between two users' lists	0.2092	0.2509	+20.0	0.0014	0.0020	+42.9
Mean duration of an item, minutes	339.1	205.7	−39.3	3.4	3.3	−3.0

Table 15: Anchor sweep with the value-model estimator, 1,000 iterations per run (final session). KL is in nats per generated item; "Training model" is the share predicted by the model that produced the rewards.

	KL	NDCG@10	on liked	Training model	Pred. share	Logged	Coverage	Overlap
KION								
Base recommender	0.000	0.1173	0.1214	0.417	0.455	0.0173	0.495	0.209
$\beta = 1$	0.015	0.1154	0.1245	0.445	0.487	0.0178	0.479	0.219
$\beta = 0.5$	0.040	0.1120	0.1256	0.470	0.517	0.0180	0.458	0.237
$\beta = 0.3$	0.080	0.1043	0.1233	0.500	0.553	0.0175	0.436	0.251
$\beta = 0.2$	0.140	0.0983	0.1193	0.521	0.576	0.0168	0.413	0.266
$\beta = 0.1$	0.590	0.0714	0.0910	0.616	0.655	0.0114	0.287	0.316
$\beta = 0$	6.215	0.0005	0.0008	0.841	0.687	0.0002	0.008	0.983
$\beta = 0.3$, 2,000 iterations	0.092	0.1047	0.1229	0.502	0.553	0.0174	0.449	0.251
Yambda								
Base recommender	0.000	0.1172	0.1005	0.594	0.599	0.0669	0.519	0.001
$\beta = 0.3$	0.029	0.1176	0.1018	0.604	0.608	0.0681	0.505	0.002
$\beta = 0.1$	0.102	0.1158	0.1008	0.615	0.617	0.0668	0.479	0.004
$\beta = 0.05$	0.286	0.1115	0.0980	0.629	0.629	0.0653	0.433	0.006
$\beta = 0.03$	4.391	0.0032	0.0033	0.871	0.774	0.0017	0.015	0.766
$\beta = 0$	6.926	0.0008	0.0009	0.861	0.810	0.0003	0.001	0.999
$\beta = 0.3$, 2,000 iterations	0.037	0.1183	0.1029	0.608	0.609	0.0686	0.506	0.002

Table 16: Baselines on generated or ranked lists of ten (final session); every baseline reads the recommender's window of history. On KION the history's items are blocked, so replay of the history reduces to popularity and the two rows coincide. The last two rows are the recommender that is fine-tuned.

	KION			Yambda			
	NDCG@10	Recall@10	Coverage	NDCG@10	on repeats	on new	Coverage
Most popular	0.0903	0.1303	0.004	0.0186	0.0193	0.0115	0.000
Replay of the history	0.0903	0.1303	0.004	0.1873	0.3722	0.0000	0.519
Markov chain	0.0959	0.1394	0.466	0.0550	0.0934	0.0139	0.457
GRU4Rec	0.1215	0.1721	0.544	0.1116	0.1706	0.0298	0.451
SASRec	0.1082	0.1580	0.335	0.0743	0.1070	0.0242	0.367
BERT4Rec	0.1290	0.1811	0.427	0.1036	0.1717	0.0232	0.461
GPT-2, ranked	0.1220	0.1726	0.574	0.1138	0.1765	0.0315	0.466
GPT-2, generated	0.1173	0.1620	0.495	0.1172	0.1865	0.0261	0.519

Table 17: Ways of raising the reward without on-policy RL (final session). Re-ranking starts from the ranked lists of the base recommender, every other method from its generated lists.

	NDCG@10	on liked	above usual	Pred. share	Logged	Surplus	Coverage
KION							
Base recommender	0.1173	0.1214	0.1261	0.455	0.0173	0.0012	0.495
Base recommender, ranked	0.1220	0.1293	0.1326	0.466	0.0193	0.0014	0.574
RL, $\beta = 0.3$ (main run)	0.1047	0.1229	0.1142	0.553	0.0174	0.0005	0.449
Liked-only fine-tuning	0.1036	0.1258	0.1134	0.545	0.0178	0.0003	0.473
Off-policy REINFORCE, $\varkappa = 0.5$	0.1032	0.1237	0.1127	0.531	0.0179	0.0005	0.504
Re-ranking, w = 1	0.1201	0.1334	0.1315	0.497	0.0199	0.0013	0.568
Re-ranking, w = 0.3	0.1127	0.1344	0.1249	0.545	0.0201	0.0009	0.531
Re-ranking, w = 0.1	0.0953	0.1234	0.1080	0.603	0.0186	0.0003	0.434
Best of 8 sampled lists	0.1049	0.1125	0.1128	0.502	0.0178	0.0010	0.499
Yambda							
Base recommender	0.1172	0.1005	0.0998	0.599	0.0669	0.0033	0.519
Base recommender, ranked	0.1138	0.0989	0.0986	0.611	0.0645	0.0029	0.466
RL, $\beta = 0.3$ (main run)	0.1183	0.1029	0.1023	0.609	0.0686	0.0032	0.506
Liked-only fine-tuning	0.1198	0.1035	0.1028	0.607	0.0692	0.0036	0.515
Off-policy REINFORCE, $\varkappa = 0.5$	0.1245	0.1090	0.1083	0.611	0.0735	0.0039	0.475
Re-ranking, w = 1	0.1144	0.0998	0.0995	0.613	0.0651	0.0030	0.463
Re-ranking, w = 0.3	0.1155	0.1012	0.1008	0.619	0.0659	0.0029	0.456
Re-ranking, w = 0.1	0.1134	0.0998	0.0993	0.630	0.0653	0.0028	0.440
Best of 8 sampled lists	0.1110	0.0967	0.0961	0.618	0.0655	0.0030	0.498

Table 18: Rewards that an item cannot earn on its own account, and logged relevance (final session). "Rel. share" is the held-out model's predicted share relative to what is typical for the item; 0.5 is "as usual".

	NDCG@10	on liked	Pred. share	Rel. share	Logged	Surplus	Coverage
KION							
Base recommender	0.1173	0.1214	0.455	0.529	0.0173	0.0012	0.495
Share (the main reward), $\beta = 0.3$	0.1043	0.1233	0.553	0.525	0.0175	0.0005	0.436
Base recommender, ranked	0.1220	0.1293	0.466	0.528	0.0193	0.0014	0.574
Relative share, $\beta = 0.3$	0.1168	0.1190	0.434	0.541	0.0168	0.0013	0.481
Relative share, $\beta = 0.1$	0.1114	0.1111	0.401	0.554	0.0154	0.0014	0.439
Re-ranking by relative share, $w = 0.1$	0.1206	0.1263	0.437	0.546	0.0185	0.0020	0.552
Share + 10 × logged relevance, $\beta = 0.3$	0.1194	0.1303	0.495	0.535	0.0185	0.0011	0.426
Share + 10 × logged relevance, $\beta = 0.1$	0.1158	0.1323	0.536	0.540	0.0188	0.0008	0.345
Logged relevance alone, $\beta = 0$	0.1180	0.1279	0.470	0.553	0.0172	0.0007	0.097
Yambda							
Base recommender	0.1172	0.1005	0.599	0.469	0.0669	0.0033	0.519
Share (the main reward), $\beta = 0.1$	0.1158	0.1008	0.617	0.465	0.0668	0.0029	0.479
Base recommender, ranked	0.1138	0.0989	0.611	0.473	0.0645	0.0029	0.466
Relative share, $\beta = 0.1$	0.1107	0.0960	0.595	0.487	0.0628	0.0040	0.476
Re-ranking by relative share, $w = 0.1$	0.1120	0.0977	0.610	0.486	0.0633	0.0034	0.444
Share + 10 × logged relevance, $\beta = 0.1$	0.1309	0.1139	0.606	0.468	0.0758	0.0035	0.516
Share + 10 × logged relevance, $\beta = 0$	0.1433	0.1245	0.608	0.467	0.0830	0.0037	0.501
Logged relevance alone, $\beta = 0$	0.1437	0.1259	0.604	0.468	0.0836	0.0039	0.486

Table 19: Rewards for continuing the session and for returning, per item (final session). "Continues" and "returns" are the held-out model's predictions; on KION a session is a calendar day.

	NDCG@10	Pred. share	Continues	Returns	Coverage	Overlap
KION						
Base recommender	0.1173	0.455	0.345	0.718	0.495	0.209
Session, $\beta = 0.3$	0.0951	0.438	0.404	0.754	0.567	0.078
Session, $\beta = 0.1$	0.0443	0.297	0.545	0.764	0.526	0.106
Return, $\beta = 0.3$	0.1077	0.459	0.368	0.739	0.521	0.141
Return, $\beta = 0.1$	0.0903	0.466	0.392	0.765	0.544	0.093
Share + return, $\beta = 0.3$	0.1091	0.502	0.355	0.733	0.491	0.183
Share + return, $\beta = 0.1$	0.0943	0.546	0.372	0.756	0.477	0.167
Yambda						
Base recommender	0.1172	0.599	0.947	0.913	0.519	0.001
Return, $\beta = 0.1$	0.1158	0.600	0.947	0.913	0.516	0.002