

## Product

Method	URI	Body(Request)	Database query	Body(Response)
POST	/product/	{ "name": "Smartphone Samsung", "description": "Samsung Galaxy S8", "purchasePrice": 2000, "salePrice": 3000, "sectionId": 1, "providerId": 1, "stock": 10 }	INSERT INTO products (name, description, purchasePrice, salePrice, sectionId, providerId, stock, enabled) VALUES('Smartphone Samsung', 'Samsung Galaxy S8', 2000, 3000, 1, 1, 10, true)	{ "code":200, "message": "Ok" }
PUT	/product/	{ "productId":1, "name": "Smartphone Samsung", "description": "Samsung Galaxy S8", "purchasePrice": 2000, "salePrice": 3000, "sectionId": 1, "providerId": 1, "stock": 10 }	UPDATE products SET name= 'Smartphone Samsung', description= 'Samsung Galaxy S8', purchasePrice= 2000, salePrice= 3000, sectionId= 1, providerId= 1, stock= 10 WHERE id_product=1	{ "code":200, "message": "Ok" }
PUT	/product/disable/	{ "productId":1 }	UPDATE products SET enabled=false WHERE id_product=1	{ "code":200, "message": "Ok" }
GET	/product/	-	SELECT name, description, purchasePrice, salePrice, sectionId, providerId, stock FROM products WHERE enabled= true	[ { "name": "Smartphone Samsung", "description": "Samsung Galaxy S8", "purchasePrice": 2000, "salePrice": 3000, "sectionId": 1, "providerId": 1, "stock": 10 } ]
GET	/product? productId=1	-	SELECT name, description, purchasePrice, salePrice, sectionId, providerId, stock FROM products WHERE enabled= true AND id_product=1	{ "name": "Smartphone Samsung", "description": "Samsung Galaxy S8", "purchasePrice":

			2000, "salePrice": 3000, "sectionId": 1, "providerId": 1, "stock": 10 }
--	--	--	--