

SDK update rules

▾ Android

Changelog

Important update for outdated versions of the AppMetrica SDK

List of modules

Excluding geo from the list of dependencies

Disabling automatic collection of Ad Revenue data

Getting advertising IDs

> Migration guides

▾ AppMetrica SDK

SDK integration

Library features

Tracking user activity

Logging

Usage examples

Analyzing crashes

AppMetrica Gradle Plugin

Deferred deeplinks support

Product flow and offer events

Error descriptions

SDK reference

> Push SDK

> iOS

> Unity

> Flutter

> React Native

> Push campaigns

> Setting up data collection

SDK Developer docs / [Android](#) / AppMetrica SDK / Library features

How the AppMetrica library works

The AppMetrica library consists of two parts: the client and the service. You should take their features into account during initialization:

- Client part: Pre-validates data and transmits it to the service part. An instance of the client part is created for each process of the application.
- Service part: It is responsible for storing data and sending it to the server. The service runs in the main application process. Therefore AppMetrica SDK saves the crash report to a file and sends them the next time it is run.

Recommendations for initialization

- If the application has multiple processes where you want to use AppMetrica, initialize the library with the same configuration in each process. Otherwise, the configuration may depend on which of the processes starts first.



You can use reporters for sending data. They can be initialized with different configurations. For more information see [Sending statistics to an additional API key](#).

- Initialize the AppMetrica library in the [Application.onCreate\(\)](#) method. As a result, the library will be initialized within the main process.
- Keep in mind that the [ContentProvider](#) instance is created before the [Application](#) instance. If you initialize the library in the [Application.onCreate\(\)](#) method, you can't send data from the [ContentProvider.onCreate\(\)](#) method.
- Don't add the code to the [Application.onCreate\(\)](#) method that should not be executed more than once. Run it when creating other components, or run it in a separate [Service](#).
- Avoid long-term operations in the [Application.onCreate\(\)](#) method and do not initialize other libraries in it. The time of this method directly affects the opening speed of the first [Activity](#), [Service](#), or [Receiver](#).

Learn more

- [How do I enable user location sending?](#)
- [How can I make sure that I have the latest versions of the Android libraries installed?](#)
- [Why aren't new installs shown in reports?](#)

If you didn't find the answer you were looking for, you can use the feedback form to submit your question. Please describe the problem in as much detail as possible. Attach a screenshot if possible.

[Contact support](#)[Suggest an improvement for documentation](#)

Was the article helpful?

 Yes No[Previous](#)[← SDK integration](#)[Tracking user activity](#)