

[SDK Developer docs](#) / [Android](#) / AppMetrica SDK / Product flow and offer events

Product flow and offer events



Product Flow module

To use this functionality, add the `io.appmetrica.analytics:analytics-product-flow` module. The module version must match the `io.appmetrica.analytics:analytics` library version.

Add the following dependency to your app's `build.gradle.kts` :

```
dependencies {  
    implementation("io.appmetrica.analytics:analytics-product-flow:8.5.1")  
}
```

About the approach

Product Flow is a new schema for standard AppMetrica events in apps with offers, purchases, applications, and multi-step and service checkout flows.

For more information about the module and complete user scenarios, see [Offer events in product scenarios](#).

This approach helps standardize analytics for the following entities and scenarios:

- product offerings;
- marketing offers;
- product and service purchases;
- user funnels;
- checkout steps;
- applications and approval results;
- asynchronous S2S results.

We recommend using the Product Flow approach for the following types of apps:

- banks;
- insurance services;
- telecom apps;
- booking and travel services;
- subscription services;
- delivery services;
- marketplaces;
- gaming apps;
- any apps with product scenarios, purchases, and funnel analytics.



Do not consume custom events and DSA limits

The new standard events are not counted toward:

- the `custom events` limit;
- the `Data Stream API` limit.

This lets you:

- gradually adopt the new event schema;
- send more product scenarios and steps;

[Register](#)[SDK](#) ▾[FAQ](#)[Changelog](#)[Pricing plans](#) ▾

- SDK update rules
- Android

Changelog

Important update for outdated versions of the AppMetrica SDK

List of modules

Excluding geo from the list of dependencies

Disabling automatic collection of Ad Revenue data

Getting advertising IDs
- Migration guides
- AppMetrica SDK

SDK integration

Library features

Tracking user activity

Logging

Usage examples

Analyzing crashes

AppMetrica Gradle Plugin

Deferred deeplinks support

Product flow and offer events

Error descriptions

SDK reference

Push SDK

iOS

Unity

Flutter

React Native

Push campaigns

Getting user data collection

Main events

The interaction schema is built around 4 main events:

Event	Meaning
<code>offerShown</code>	The user saw an offer or a proposal
<code>flowStart</code>	The user started the product checkout
<code>flowStep</code>	An intermediate checkout step
<code>flowResult</code>	The final result

Event examples

offerShown

The user saw a banner: "You are pre-approved for a loan of up to 500,000 ₺ at a rate starting from 12.5%."

```
AppMetrica.reportEvent(  
    ProductFlowEvent.offerShown("credit_q1", "financial_product")  
        .withProductId("personal_loan")  
        .withBenefitType("discount_percentage")  
        .withReferrer(  
            OfferReferrer.newBuilder()  
                .withType("banner")  
                .withIdentifier("main_screen_credit_banner")  
                .withScreen("main")  
                .build()  
        )  
        .withPayload(mapOf(  
            "campaign_id" to "credit_spring_2026",  
            "segment" to "preapproved_users",  
            "approved_limit" to "500000",  
            "currency" to "RUB",  
            "interest_rate" to "12.5"  
        ))  
        .build()  
)
```

flowStart

The user taps the banner and starts the application.

```
AppMetrica.reportEvent(  
    ProductFlowEvent.flowStart("personal_loan")  
        .withProductOfferId("credit_q1")  
        .build()  
)
```

flowStep

The user uploads documents.

```
AppMetrica.reportEvent(  
    ProductFlowEvent.flowStepForProduct("personal_loan", "documents")  
        .withProductOfferId("credit_q1")  
        .withStepOption("passport_upload")  
        .build()  
)
```

flowResult

Later the bank sends the final result via S2S.

```
AppMetrica.reportEvent(  
    ProductFlowEvent.flowResultForProduct(ProductFlowStatus.SUCCESS, "personal_loan")  
        .withProductOfferId("credit_q1")  
        .withPrice(OfferPrice(430000.0, "RUB"))  
        .withPayload(mapOf(  
            "application_id" to "loan_app_12345",  
            "decision_source" to "s2s"  
        ))  
        .build()  
)
```

If you didn't find the answer you were looking for, you can use the feedback form to submit your question. Please describe the problem in as much detail as possible. Attach a screenshot if possible.

[Contact support](#)[Suggest an improvement for documentation](#)

Was the article helpful?

 Yes

 No

[Previous](#)[← Deferred deeplinks support](#)[Error descr](#)