



H-FASADES PVC TREND 85 – TILT & TURN INWARD OPENING WINDOW

- advanced system for window profiles that are perfect for today's trends.

Inward-opening tilt & turn window that can also be supplied in TILT-FIRST version, when the window can be first open for air-ventilation position [tilt] and then open completely.

- + **Narrow profiles that provide better light entry**
- + **Triple sealing and good U-value**
- + **Can be supplied with solid colored profiles**
- + **Hidden hinges**
- + **Maintenance-friendly**
- + **Long service life**
- + **Recyclable - profiles consisting of 34% recycled PVC**

Dimensions

Fixed frame: Max width 2988 mm. Max height 2988 mm.
Total size max 6.0 m².
For opening window: Width: min 496, max 1766.
Height: min 577, max 2517.

Combinations

The window can be delivered in various combinations with fixed and opening windows in a frame.

Hardware/Handles

Hardware: Siegenia Titans with hidden hinges
Handle: Hoppe with Kisi child security. Can be also supplied with a lockable handle.

Decorative bars (sprossers)

Our windows can be supplied with decorative bars that can be glued on both sides of the glass, Georgians bars, removable Vindex bars or a combination.

PVC profile

Made of extruded, through-dyed, impact-resistant and climate-resistant PVC profiles with very good insulating properties, which give good u-values. Frame depth 85mm [85MD]. Steel reinforcements are added to the profiles for extra strength and stability.

Internal grooves

The products can be delivered with 10x10mm grooves from inside of the frame [utforingsnot].

Color

Standard white [RAL 9016]. A selection of other colors is available on request. See our websites for information: <https://www.hfasader.no/byggevarer/fargevalg/fargevalg-pvc/>. Can be supplied with solid colored profiles.

Maintenance

The PVC profiles do not require maintenance, only cleaning ordinary soapy water. Fittings require ordinary cleaning and lubrication.

