



## H-FASADES PVC TREND 85 – TILT & TURN INWARD OPENING WINDOW

- advanced system for window profiles that are perfect for today's trends.

Vinduet er innadslående og toveissvingende [vipp/drei], der vinduet først kan åpnes i luftestilling [vipp] for så å kunne åpnes helt, om ønskelig [drei]. En vrider for alle funksjoner.

- + **Narrow profiles that provide better light entry**
- + **Triple sealing and good U-value**
- + **Can be supplied with solid colored profiles**
- + **Hidden hinges**
- + **Maintenance-friendly**
- + **Long service life**
- + **Recyclable - profiles consisting of 34% recycled PVC**

### Dimensions

Fixed frame: Max width 2988 mm. Max height 2988 mm.  
Total size max 6.0 m<sup>2</sup>.  
For opening window: Width: min 496, max 1766.  
Height: min 577, max 2517.

### Combinations

The window can be delivered in various combinations with fixed and opening windows in a frame.

### Hardware/Handles

Hardware: Siegenia Titans with hidden hinges  
Handle: Hoppe with Kisi child security. Can be also supplied with a lockable handle.

### Decorative bars (sprossers)

Our windows can be supplied with decorative bars that can be glued on both sides of the glass, Georgians bars, removable Vindex bars or a combination.

### PVC profile

Made of extruded, through-dyed, impact-resistant and climate-resistant PVC profiles with very good insulating properties, which give good u-values. Frame depth 85mm [85MD]. Steel reinforcements are added to the profiles for extra strength and stability.

### Internal grooves

The products can be delivered with 10x10mm grooves from inside of the frame [utforingsnot].

### Color

Standard white [RAL 9016]. A selection of other colors is available on request. See our websites for information: <https://www.hfasader.no/byggevarer/fargevalg/fargevalg-pvc/>. Can be supplied with solid colored profiles.

### Maintenance

The PVC profiles do not require maintenance, only cleaning ordinary soapy water. Fittings require ordinary cleaning and lubrication.

