
NIPS 2018 Reply to Reviewers

Anonymous Author(s)

Affiliation

Address

email

1 Reviewer 1

2 Q: What is the motivation for being Bayesian about the LISTA algorithm. How does in the uncer-
3 tainty in the Bayesian LISTA procedure relate to the original linear model.

4 A: The LISTA algorithm introduces the weights in the model. Their point estimates are being
5 inferred during the training phase, this leads to the uncertainty of the estimation. In our Bayesian
6 model we infer the posterior distributions over these weights to estimate this uncertainty.

7
8
9 Q: how does the sparse promoting prior interact with the sparsity promoting non-linearity.

10 A: In the LISTA model the sequential estimates of β are obtained at each layer using the previous
11 estimate. At every layer the estimate becomes more sparse due to soft-thresholding non-linearity.
12 We do not specify sparsity priors over the β_{l-1} - we show that the distribution of these estimates
13 can be approximated with the spike-and-slab distribution, i.e. its sparsity naturally arises from the
14 Gaussian prior on NN weights and sparsity promoting soft thresholding nonlinearity.

15
16
17 Q: The approximations in section 4 are part of the approximate inference

18 A: Yes, they are part of the inference procedure, the model remains the same as in section 3. These
19 approximations are similar to mean-field approximations in variational inference.

20
21
22 Q: The assumption of mutual independence over the elements of S and β_{l-1}

23 A: Generally speaking, correlation is partially removed due to the soft-thresholding on the previous
24 layer. It requires further research to establish the influence of remaining correlation on the quality
25 of approximation.

26 27 28 Reviewer 3