

Week 1

July 21, 2020

*You are currently looking at **version 1.1** of this notebook. To download notebooks and datafiles, as well as get help on Jupyter notebooks in the Coursera platform, visit the [Jupyter Notebook FAQ](#) course resource.*

1 The Python Programming Language: Functions

`add_numbers` is a function that takes two numbers and adds them together.

```
In [1]: def add_numbers(x, y):  
        return x + y
```

```
add_numbers(1, 2)
```

```
Out[1]: 3
```

`add_numbers` updated to take an optional 3rd parameter. Using `print` allows printing of multiple expressions within a single cell.

```
In [2]: def add_numbers(x, y, z=None):  
        if (z==None):  
            return x+y  
        else:  
            return x+y+z  
  
        print(add_numbers(1, 2))  
        print(add_numbers(1, 2, 3))
```

```
3
```

```
6
```

`add_numbers` updated to take an optional flag parameter.

```
In [3]: def add_numbers(x, y, z=None, flag=False):
        if (flag):
            print('Flag is true!')
        if (z==None):
            return x + y
        else:
            return x + y + z

        print(add_numbers(1, 2, flag=True))
```

```
Flag is true!
3
```

Assign function add_numbers to variable a.

```
In [4]: def add_numbers(x,y):
        return x+y

        a = add_numbers
        a(1,2)
```

```
Out[4]: 3
```

The Python Programming Language: Types and Sequences
Use type to return the object's type.

```
In [5]: type('This is a string')
```

```
Out[5]: str
```

```
In [6]: type(None)
```

```
Out[6]: NoneType
```

```
In [7]: type(1)
```

```
Out[7]: int
```

```
In [8]: type(1.0)
```

```
Out[8]: float
```

```
In [9]: type(add_numbers)
```

```
Out[9]: function
```

Tuples are an immutable data structure (cannot be altered).

```
In [10]: x = (1, 'a', 2, 'b')
         type(x)
```

```
Out[10]: tuple
```

Lists are a mutable data structure.

```
In [11]: x = [1, 'a', 2, 'b']  
         type(x)
```

```
Out[11]: list
```

Use append to append an object to a list.

```
In [12]: x.append(3.3)  
         print(x)
```

```
[1, 'a', 2, 'b', 3.3]
```

This is an example of how to loop through each item in the list.

```
In [13]: for item in x:  
         print(item)
```

```
1  
a  
2  
b  
3.3
```

Or using the indexing operator:

```
In [14]: i=0  
         while( i != len(x) ):  
             print(x[i])  
             i = i + 1
```

```
1  
a  
2  
b  
3.3
```

Use + to concatenate lists.

```
In [15]: [1,2] + [3,4]
```

```
Out[15]: [1, 2, 3, 4]
```

Use * to repeat lists.

```
In [16]: [1]*3
```

```
Out[16]: [1, 1, 1]
```

Use the `in` operator to check if something is inside a list.

```
In [17]: 1 in [1, 2, 3]
```

```
Out[17]: True
```

Now let's look at strings. Use bracket notation to slice a string.

```
In [18]: x = 'This is a string'
         print(x[0]) #first character
         print(x[0:1]) #first character, but we have explicitly set the end character
         print(x[0:2]) #first two characters
```

```
T
T
Th
```

This will return the last element of the string.

```
In [19]: x[-1]
```

```
Out[19]: 'g'
```

This will return the slice starting from the 4th element from the end and stopping before the 2nd element from the end.

```
In [20]: x[-4:-2]
```

```
Out[20]: 'ri'
```

This is a slice from the beginning of the string and stopping before the 3rd element.

```
In [21]: x[:3]
```

```
Out[21]: 'Thi'
```

And this is a slice starting from the 4th element of the string and going all the way to the end.

```
In [22]: x[3:]
```

```
Out[22]: 's is a string'
```

```
In [23]: firstname = 'Christopher'
         lastname = 'Brooks'

         print(firstname + ' ' + lastname)
         print(firstname*3)
         print('Chris' in firstname)
```

```
Christopher Brooks
ChristopherChristopherChristopher
True
```

split returns a list of all the words in a string, or a list split on a specific character.

```
In [24]: firstname = 'Christopher Arthur Hansen Brooks'.split(' ')[0] # [0] selects the first element
        lastname = 'Christopher Arthur Hansen Brooks'.split(' ')[-1] # [-1] selects the last element
        print(firstname)
        print(lastname)
```

```
Christopher
Brooks
```

Make sure you convert objects to strings before concatenating.

```
In [25]: 'Chris' + 2
```

```
-----

TypeError                                 Traceback (most recent call last)

<ipython-input-25-1623ac76de6e> in <module>()
----> 1 'Chris' + 2

TypeError: must be str, not int
```

```
In [ ]: 'Chris' + str(2)
```

Dictionaries associate keys with values.

```
In [ ]: x = {'Christopher Brooks': 'brooks@umich.edu', 'Bill Gates': 'billg@microsoft.com'}
        x['Christopher Brooks'] # Retrieve a value by using the indexing operator

In [ ]: x['Kevyn Collins-Thompson'] = None
        x['Kevyn Collins-Thompson']
```

Iterate over all of the keys:

```
In [26]: for name in x:
        print(x[name])

-----
```

TypeError

Traceback (most recent call last)

```
<ipython-input-26-83966e427c06> in <module>()
    1 for name in x:
----> 2     print(x[name])
```

TypeError: string indices must be integers

Iterate over all of the values:

```
In [27]: for email in x.values():
         print(email)
```

AttributeError

Traceback (most recent call last)

```
<ipython-input-27-8a7ce0cd05ee> in <module>()
----> 1 for email in x.values():
      2     print(email)
```

AttributeError: 'str' object has no attribute 'values'

Iterate over all of the items in the list:

```
In [28]: for name, email in x.items():
         print(name)
         print(email)
```

AttributeError

Traceback (most recent call last)

```
<ipython-input-28-c502076bc9f2> in <module>()
----> 1 for name, email in x.items():
      2     print(name)
      3     print(email)
```

AttributeError: 'str' object has no attribute 'items'

You can unpack a sequence into different variables:

```
In [29]: x = ('Christopher', 'Brooks', 'brooks@umich.edu')
         fname, lname, email = x
```

```
In [30]: fname
```

```
Out[30]: 'Christopher'
```

```
In [31]: lname
```

```
Out[31]: 'Brooks'
```

Make sure the number of values you are unpacking matches the number of variables being assigned.

```
In [32]: x = ('Christopher', 'Brooks', 'brooks@umich.edu', 'Ann Arbor')
         fname, lname, email = x
```

```
-----
ValueError                                Traceback (most recent call last)

<ipython-input-32-9ce70064f53e> in <module>()
      1 x = ('Christopher', 'Brooks', 'brooks@umich.edu', 'Ann Arbor')
----> 2 fname, lname, email = x

ValueError: too many values to unpack (expected 3)
```

The Python Programming Language: More on Strings

```
In [33]: print('Chris' + 2)
```

```
-----
TypeError                                Traceback (most recent call last)

<ipython-input-33-82ccfdd3d5d3> in <module>()
----> 1 print('Chris' + 2)

TypeError: must be str, not int
```

```
In [34]: print('Chris' + str(2))
```

```
Chris2
```

Python has a built in method for convenient string formatting.

```
In [35]: sales_record = {
        'price': 3.24,
        'num_items': 4,
        'person': 'Chris'}

        sales_statement = '{} bought {} item(s) at a price of {} each for a total of {}'

        print(sales_statement.format(sales_record['person'],
                                     sales_record['num_items'],
                                     sales_record['price'],
                                     sales_record['num_items']*sales_record['price']))
```

Chris bought 4 item(s) at a price of 3.24 each for a total of 12.96

Reading and Writing CSV files

Let's import our datafile mpg.csv, which contains fuel economy data for 234 cars.

- mpg : miles per gallon
- class : car classification
- cty : city mpg
- cyl : # of cylinders
- displ : engine displacement in liters
- drv : f = front-wheel drive, r = rear wheel drive, 4 = 4wd
- fl : fuel (e = ethanol E85, d = diesel, r = regular, p = premium, c = CNG)
- hwy : highway mpg
- manufacturer : automobile manufacturer
- model : model of car
- trans : type of transmission
- year : model year

```
In [36]: import csv

        %precision 2

        with open('mpg.csv') as csvfile:
            mpg = list(csv.DictReader(csvfile))

        mpg[:3] # The first three dictionaries in our list.
```

```
Out[36]: [OrderedDict([('', '1'),
                       ('manufacturer', 'audi'),
                       ('model', 'a4'),
                       ('displ', '1.8'),
                       ('year', '1999'),
                       ('cyl', '4'),
                       ('trans', 'auto(15)')],
```



```

        ('drv', 'f'),
        ('cty', '18'),
        ('hwy', '29'),
        ('fl', 'p'),
        ('class', 'compact'))],
OrderedDict([(' ', '2'),
             ('manufacturer', 'audi'),
             ('model', 'a4'),
             ('displ', '1.8'),
             ('year', '1999'),
             ('cyl', '4'),
             ('trans', 'manual(m5)'),
             ('drv', 'f'),
             ('cty', '21'),
             ('hwy', '29'),
             ('fl', 'p'),
             ('class', 'compact'))],
OrderedDict([(' ', '3'),
             ('manufacturer', 'audi'),
             ('model', 'a4'),
             ('displ', '2'),
             ('year', '2008'),
             ('cyl', '4'),
             ('trans', 'manual(m6)'),
             ('drv', 'f'),
             ('cty', '20'),
             ('hwy', '31'),
             ('fl', 'p'),
             ('class', 'compact'))])

```

csv.Dictreader has read in each row of our csv file as a dictionary. len shows that our list is comprised of 234 dictionaries.

```
In [37]: len(mpg)
```

```
Out[37]: 234
```

keys gives us the column names of our csv.

```
In [38]: mpg[0].keys()
```

```
Out[38]: OrderedDict([(' ', 'manufacturer', 'model', 'displ', 'year', 'cyl', 'trans', 'drv', 'cty',
```

This is how to find the average cty fuel economy across all cars. All values in the dictionaries are strings, so we need to convert to float.

```
In [39]: sum(float(d['cty']) for d in mpg) / len(mpg)
```

```
Out[39]: 16.86
```

Similarly this is how to find the average hwy fuel economy across all cars.

```
In [40]: sum(float(d['hwy']) for d in mpg) / len(mpg)
```

```
Out[40]: 23.44
```

Use set to return the unique values for the number of cylinders the cars in our dataset have.

```
In [41]: cylinders = set(d['cyl'] for d in mpg)
cylinders
```

```
Out[41]: {'4', '5', '6', '8'}
```

Here's a more complex example where we are grouping the cars by number of cylinder, and finding the average cty mpg for each group.

```
In [42]: CtyMpgByCyl = []
```

```
for c in cylinders: # iterate over all the cylinder levels
    summpg = 0
    cyltypecount = 0
    for d in mpg: # iterate over all dictionaries
        if d['cyl'] == c: # if the cylinder level type matches,
            summpg += float(d['cty']) # add the cty mpg
            cyltypecount += 1 # increment the count
    CtyMpgByCyl.append((c, summpg / cyltypecount)) # append the tuple ('cylinder', 'avg
    CtyMpgByCyl.sort(key=lambda x: x[0])
    CtyMpgByCyl
```

```
Out[42]: [('4', 21.01), ('5', 20.50), ('6', 16.22), ('8', 12.57)]
```

Use set to return the unique values for the class types in our dataset.

```
In [43]: vehicleclass = set(d['class'] for d in mpg) # what are the class types
vehicleclass
```

```
Out[43]: {'2seater', 'compact', 'midsize', 'minivan', 'pickup', 'subcompact', 'suv'}
```

And here's an example of how to find the average hwy mpg for each class of vehicle in our dataset.

```
In [44]: HwyMpgByClass = []
```

```
for t in vehicleclass: # iterate over all the vehicle classes
    summpg = 0
    vclasscount = 0
    for d in mpg: # iterate over all dictionaries
        if d['class'] == t: # if the cylinder amount type matches,
            summpg += float(d['hwy']) # add the hwy mpg
```

```

        vclasscount += 1 # increment the count
        HwyMpgByClass.append((t, summpg / vclasscount)) # append the tuple ('class', 'avg m

HwyMpgByClass.sort(key=lambda x: x[1])
HwyMpgByClass

Out[44]: [('pickup', 16.88),
          ('suv', 18.13),
          ('minivan', 22.36),
          ('2seater', 24.80),
          ('midsize', 27.29),
          ('subcompact', 28.14),
          ('compact', 28.30)]

```

The Python Programming Language: Dates and Times

```

In [45]: import datetime as dt
         import time as tm

```

time returns the current time in seconds since the Epoch. (January 1st, 1970)

```

In [46]: tm.time()

```

```

Out[46]: 1595372247.02

```

Convert the timestamp to datetime.

```

In [47]: dtnow = dt.datetime.fromtimestamp(tm.time())
         dtnow

```

```

Out[47]: datetime.datetime(2020, 7, 21, 22, 57, 32, 556561)

```

Handy datetime attributes:

```

In [48]: dtnow.year, dtnow.month, dtnow.day, dtnow.hour, dtnow.minute, dtnow.second # get year,

```

```

Out[48]: (2020, 7, 21, 22, 57, 32)

```

timedelta is a duration expressing the difference between two dates.

```

In [49]: delta = dt.timedelta(days = 100) # create a timedelta of 100 days
         delta

```

```

Out[49]: datetime.timedelta(100)

```

date.today returns the current local date.

```

In [50]: today = dt.date.today()

```

```

In [51]: today - delta # the date 100 days ago

```

```
Out[51]: datetime.date(2020, 4, 12)
```

```
In [52]: today > today-delta # compare dates
```

```
Out[52]: True
```

The Python Programming Language: Objects and map()
An example of a class in python:

```
In [53]: class Person:
        department = 'School of Information' #a class variable

        def set_name(self, new_name): #a method
            self.name = new_name
        def set_location(self, new_location):
            self.location = new_location
```

```
In [54]: person = Person()
        person.set_name('Christopher Brooks')
        person.set_location('Ann Arbor, MI, USA')
        print('{} live in {} and works in the department {}'.format(person.name, person.location, person.department))
```

Christopher Brooks live in Ann Arbor, MI, USA and works in the department School of Information

Here's an example of mapping the min function between two lists.

```
In [55]: store1 = [10.00, 11.00, 12.34, 2.34]
        store2 = [9.00, 11.10, 12.34, 2.01]
        cheapest = map(min, store1, store2)
        cheapest
```

```
Out[55]: <map at 0x7f1e80c036d8>
```

Now let's iterate through the map object to see the values.

```
In [56]: for item in cheapest:
        print(item)
```

```
9.0
11.0
12.34
2.01
```

The Python Programming Language: Lambda and List Comprehensions
Here's an example of lambda that takes in three parameters and adds the first two.

```
In [57]: my_function = lambda a, b, c : a + b
```

```
In [58]: my_function(1, 2, 3)
```

```
Out[58]: 3
```

Let's iterate from 0 to 999 and return the even numbers.

```
In [59]: my_list = []  
         for number in range(0, 1000):  
             if number % 2 == 0:  
                 my_list.append(number)  
         my_list
```

```
Out[59]: [0,  
          2,  
          4,  
          6,  
          8,  
          10,  
          12,  
          14,  
          16,  
          18,  
          20,  
          22,  
          24,  
          26,  
          28,  
          30,  
          32,  
          34,  
          36,  
          38,  
          40,  
          42,  
          44,  
          46,  
          48,  
          50,  
          52,  
          54,  
          56,  
          58,  
          60,  
          62,  
          64,  
          66,  
          68,  
          70,  
          72,
```

74,
76,
78,
80,
82,
84,
86,
88,
90,
92,
94,
96,
98,
100,
102,
104,
106,
108,
110,
112,
114,
116,
118,
120,
122,
124,
126,
128,
130,
132,
134,
136,
138,
140,
142,
144,
146,
148,
150,
152,
154,
156,
158,
160,
162,
164,
166,
168,

170,
172,
174,
176,
178,
180,
182,
184,
186,
188,
190,
192,
194,
196,
198,
200,
202,
204,
206,
208,
210,
212,
214,
216,
218,
220,
222,
224,
226,
228,
230,
232,
234,
236,
238,
240,
242,
244,
246,
248,
250,
252,
254,
256,
258,
260,
262,
264,

266,
268,
270,
272,
274,
276,
278,
280,
282,
284,
286,
288,
290,
292,
294,
296,
298,
300,
302,
304,
306,
308,
310,
312,
314,
316,
318,
320,
322,
324,
326,
328,
330,
332,
334,
336,
338,
340,
342,
344,
346,
348,
350,
352,
354,
356,
358,
360,

362,
364,
366,
368,
370,
372,
374,
376,
378,
380,
382,
384,
386,
388,
390,
392,
394,
396,
398,
400,
402,
404,
406,
408,
410,
412,
414,
416,
418,
420,
422,
424,
426,
428,
430,
432,
434,
436,
438,
440,
442,
444,
446,
448,
450,
452,
454,
456,

458,
460,
462,
464,
466,
468,
470,
472,
474,
476,
478,
480,
482,
484,
486,
488,
490,
492,
494,
496,
498,
500,
502,
504,
506,
508,
510,
512,
514,
516,
518,
520,
522,
524,
526,
528,
530,
532,
534,
536,
538,
540,
542,
544,
546,
548,
550,
552,

554,
556,
558,
560,
562,
564,
566,
568,
570,
572,
574,
576,
578,
580,
582,
584,
586,
588,
590,
592,
594,
596,
598,
600,
602,
604,
606,
608,
610,
612,
614,
616,
618,
620,
622,
624,
626,
628,
630,
632,
634,
636,
638,
640,
642,
644,
646,
648,

650,
652,
654,
656,
658,
660,
662,
664,
666,
668,
670,
672,
674,
676,
678,
680,
682,
684,
686,
688,
690,
692,
694,
696,
698,
700,
702,
704,
706,
708,
710,
712,
714,
716,
718,
720,
722,
724,
726,
728,
730,
732,
734,
736,
738,
740,
742,
744,

746,
748,
750,
752,
754,
756,
758,
760,
762,
764,
766,
768,
770,
772,
774,
776,
778,
780,
782,
784,
786,
788,
790,
792,
794,
796,
798,
800,
802,
804,
806,
808,
810,
812,
814,
816,
818,
820,
822,
824,
826,
828,
830,
832,
834,
836,
838,
840,

842,
844,
846,
848,
850,
852,
854,
856,
858,
860,
862,
864,
866,
868,
870,
872,
874,
876,
878,
880,
882,
884,
886,
888,
890,
892,
894,
896,
898,
900,
902,
904,
906,
908,
910,
912,
914,
916,
918,
920,
922,
924,
926,
928,
930,
932,
934,
936,

```
938,  
940,  
942,  
944,  
946,  
948,  
950,  
952,  
954,  
956,  
958,  
960,  
962,  
964,  
966,  
968,  
970,  
972,  
974,  
976,  
978,  
980,  
982,  
984,  
986,  
988,  
990,  
992,  
994,  
996,  
998]
```

Now the same thing but with list comprehension.

```
In [60]: my_list = [number for number in range(0,1000) if number % 2 == 0]  
my_list
```

```
Out[60]: [0,  
2,  
4,  
6,  
8,  
10,  
12,  
14,  
16,  
18,  
20,
```

22,
24,
26,
28,
30,
32,
34,
36,
38,
40,
42,
44,
46,
48,
50,
52,
54,
56,
58,
60,
62,
64,
66,
68,
70,
72,
74,
76,
78,
80,
82,
84,
86,
88,
90,
92,
94,
96,
98,
100,
102,
104,
106,
108,
110,
112,
114,
116,

118,
120,
122,
124,
126,
128,
130,
132,
134,
136,
138,
140,
142,
144,
146,
148,
150,
152,
154,
156,
158,
160,
162,
164,
166,
168,
170,
172,
174,
176,
178,
180,
182,
184,
186,
188,
190,
192,
194,
196,
198,
200,
202,
204,
206,
208,
210,
212,

214,
216,
218,
220,
222,
224,
226,
228,
230,
232,
234,
236,
238,
240,
242,
244,
246,
248,
250,
252,
254,
256,
258,
260,
262,
264,
266,
268,
270,
272,
274,
276,
278,
280,
282,
284,
286,
288,
290,
292,
294,
296,
298,
300,
302,
304,
306,
308,

310,
312,
314,
316,
318,
320,
322,
324,
326,
328,
330,
332,
334,
336,
338,
340,
342,
344,
346,
348,
350,
352,
354,
356,
358,
360,
362,
364,
366,
368,
370,
372,
374,
376,
378,
380,
382,
384,
386,
388,
390,
392,
394,
396,
398,
400,
402,
404,

406,
408,
410,
412,
414,
416,
418,
420,
422,
424,
426,
428,
430,
432,
434,
436,
438,
440,
442,
444,
446,
448,
450,
452,
454,
456,
458,
460,
462,
464,
466,
468,
470,
472,
474,
476,
478,
480,
482,
484,
486,
488,
490,
492,
494,
496,
498,
500,

502,
504,
506,
508,
510,
512,
514,
516,
518,
520,
522,
524,
526,
528,
530,
532,
534,
536,
538,
540,
542,
544,
546,
548,
550,
552,
554,
556,
558,
560,
562,
564,
566,
568,
570,
572,
574,
576,
578,
580,
582,
584,
586,
588,
590,
592,
594,
596,

598,
600,
602,
604,
606,
608,
610,
612,
614,
616,
618,
620,
622,
624,
626,
628,
630,
632,
634,
636,
638,
640,
642,
644,
646,
648,
650,
652,
654,
656,
658,
660,
662,
664,
666,
668,
670,
672,
674,
676,
678,
680,
682,
684,
686,
688,
690,
692,

694,
696,
698,
700,
702,
704,
706,
708,
710,
712,
714,
716,
718,
720,
722,
724,
726,
728,
730,
732,
734,
736,
738,
740,
742,
744,
746,
748,
750,
752,
754,
756,
758,
760,
762,
764,
766,
768,
770,
772,
774,
776,
778,
780,
782,
784,
786,
788,

790,
792,
794,
796,
798,
800,
802,
804,
806,
808,
810,
812,
814,
816,
818,
820,
822,
824,
826,
828,
830,
832,
834,
836,
838,
840,
842,
844,
846,
848,
850,
852,
854,
856,
858,
860,
862,
864,
866,
868,
870,
872,
874,
876,
878,
880,
882,
884,

886,
888,
890,
892,
894,
896,
898,
900,
902,
904,
906,
908,
910,
912,
914,
916,
918,
920,
922,
924,
926,
928,
930,
932,
934,
936,
938,
940,
942,
944,
946,
948,
950,
952,
954,
956,
958,
960,
962,
964,
966,
968,
970,
972,
974,
976,
978,
980,

```
982,  
984,  
986,  
988,  
990,  
992,  
994,  
996,  
998]
```

The Python Programming Language: Numerical Python (NumPy)

```
In [61]: import numpy as np
```

Creating Arrays

Create a list and convert it to a numpy array

```
In [62]: mylist = [1, 2, 3]  
        x = np.array(mylist)  
        x
```

```
Out[62]: array([1, 2, 3])
```

Or just pass in a list directly

```
In [63]: y = np.array([4, 5, 6])  
        y
```

```
Out[63]: array([4, 5, 6])
```

Pass in a list of lists to create a multidimensional array.

```
In [64]: m = np.array([[7, 8, 9], [10, 11, 12]])  
        m
```

```
Out[64]: array([[ 7,  8,  9],  
                [10, 11, 12]])
```

Use the shape method to find the dimensions of the array. (rows, columns)

```
In [65]: m.shape
```

```
Out[65]: (2, 3)
```

arange returns evenly spaced values within a given interval.

```
In [66]: n = np.arange(0, 30, 2) # start at 0 count up by 2, stop before 30  
        n
```

```
Out[66]: array([ 0,  2,  4,  6,  8, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28])
```

reshape returns an array with the same data with a new shape.

```
In [67]: n = n.reshape(3, 5) # reshape array to be 3x5  
n
```

```
Out[67]: array([[ 0,  2,  4,  6,  8],  
               [10, 12, 14, 16, 18],  
               [20, 22, 24, 26, 28]])
```

linspace returns evenly spaced numbers over a specified interval.

```
In [68]: o = np.linspace(0, 4, 9) # return 9 evenly spaced values from 0 to 4  
o
```

```
Out[68]: array([ 0. ,  0.5,  1. ,  1.5,  2. ,  2.5,  3. ,  3.5,  4. ])
```

resize changes the shape and size of array in-place.

```
In [69]: o.resize(3, 3)  
o
```

```
Out[69]: array([[ 0. ,  0.5,  1. ],  
               [ 1.5,  2. ,  2.5],  
               [ 3. ,  3.5,  4. ]])
```

ones returns a new array of given shape and type, filled with ones.

```
In [70]: np.ones((3, 2))
```

```
Out[70]: array([[ 1.,  1.],  
               [ 1.,  1.],  
               [ 1.,  1.]])
```

zeros returns a new array of given shape and type, filled with zeros.

```
In [71]: np.zeros((2, 3))
```

```
Out[71]: array([[ 0.,  0.,  0.],  
               [ 0.,  0.,  0.]])
```

eye returns a 2-D array with ones on the diagonal and zeros elsewhere.

```
In [72]: np.eye(3)
```

```
Out[72]: array([[ 1.,  0.,  0.],  
               [ 0.,  1.,  0.],  
               [ 0.,  0.,  1.]])
```

diag extracts a diagonal or constructs a diagonal array.

```
In [73]: np.diag(y)
```

```
Out[73]: array([[4, 0, 0],
               [0, 5, 0],
               [0, 0, 6]])
```

Create an array using repeating list (or see `np.tile`)

```
In [74]: np.array([1, 2, 3] * 3)
```

```
Out[74]: array([1, 2, 3, 1, 2, 3, 1, 2, 3])
```

Repeat elements of an array using `repeat`.

```
In [75]: np.repeat([1, 2, 3], 3)
```

```
Out[75]: array([1, 1, 1, 2, 2, 2, 3, 3, 3])
```

Combining Arrays

```
In [76]: p = np.ones([2, 3], int)
         p
```

```
Out[76]: array([[1, 1, 1],
               [1, 1, 1]])
```

Use `vstack` to stack arrays in sequence vertically (row wise).

```
In [77]: np.vstack([p, 2*p])
```

```
Out[77]: array([[1, 1, 1],
               [1, 1, 1],
               [2, 2, 2],
               [2, 2, 2]])
```

Use `hstack` to stack arrays in sequence horizontally (column wise).

```
In [78]: np.hstack([p, 2*p])
```

```
Out[78]: array([[1, 1, 1, 2, 2, 2],
               [1, 1, 1, 2, 2, 2]])
```

Operations

Use `+`, `-`, `*`, `/` and `**` to perform element wise addition, subtraction, multiplication, division and power.

```
In [79]: print(x + y) # elementwise addition    [1 2 3] + [4 5 6] = [5 7 9]
         print(x - y) # elementwise subtraction [1 2 3] - [4 5 6] = [-3 -3 -3]
```

```
[5 7 9]
[-3 -3 -3]
```