v4.0.0 documentation

Release

Keystatic Demo Team

Table of Contents

1 Keystatic GitHub OAuth on Cloud Hub **1**
- 1.1 Changes . . . 1
- 1.2 Environment Variables Required . . . 2
- 1.3 Key Learnings . . . 2

1 Keystatic GitHub OAuth on Cloud Hub

This release enables Keystatic's GitHub authentication to work correctly when deployed on Cloud Hub.

1.1 Changes

1.1.1 Middleware for Proxy URL Rewriting

Added Astro middleware (`src/middleware.ts`) to handle reverse proxy URL rewriting. Cloud Hub's reverse proxy routes requests to containers, but the internal `Host` header shows `localhost:3000`. The middleware rewrites the request URL using:

- `x-forwarded-host` and `x-forwarded-proto` headers (if available)
- Falls back to `SITE_URL` environment variable

This ensures Keystatic generates the correct OAuth `redirect_uri` pointing to the Cloud Hub domain instead of localhost.

1.1.2 Cloud Hub Egress Configuration

Added egress labels to `docker-compose.yml` to allow outbound traffic to GitHub:

```yaml
labels:
  - 'com.calponia.egress.fqdns.0.exact=github.com'
  - 'com.calponia.egress.fqdns.1.exact=api.github.com'
```

Cloud Hub blocks all outbound internet traffic by default. Without these rules, the container cannot reach GitHub's API to exchange OAuth authorization codes for access tokens.

1.1.3 Debug Endpoints (Development)

Added temporary debug endpoints for troubleshooting:

- `/api/debug-env` - Verifies environment variables are correctly set
- `/api/test-github-token` - Tests GitHub API connectivity

1.2 Environment Variables Required

Variable	Description
`SITE_URL`	Full URL of the deployed site (e.g., `https://xxx.app.cloudhub.etas.com`)
`KEYSTATIC_GITHUB_CLIENT_ID`	GitHub OAuth App client ID
`KEYSTATIC_GITHUB_CLIENT_SECRET`	GitHub OAuth App client secret
`KEYSTATIC_SECRET`	Secret for session encryption (64 hex chars)
`PUBLIC_KEYSTATIC_GITHUB_APP_SLUG`	GitHub App slug name

1.3 Key Learnings

1. **Build-time vs Runtime**: Astro's `site` config is evaluated at build time. Pass `SITE_URL` as a build argument and set it in the Dockerfile.
2. **Cloud Hub Networking**: Containers have no internet access by default. Whitelist required domains via egress labels.
3. **Reverse Proxy Headers**: Don't assume `x-forwarded-*` headers are passed. Always have a fallback mechanism.