

ImagesToLARModel, a tool for creation of three-dimensional models from a stack of images

Danilo Salvati

December 10, 2015

Abstract

Here we will present a software for creating a three-dimensional model from a stack of images. This can be useful because of the simplicity of these type of representations. In particular a scope of use can be offered by medicine, where there is an enormous number of images but with very complex two-dimensional representations.

This work will use the LAR representation ([[CL13](#)]) with the Julia language, because of its simplicity, showing how it can be used for quickly process image data.

Contents

1	Introduction	4
1.1	Why Julia	5
2	Software structure	5
2.1	Julia packages	5
2.2	Architecture of ImagesToLARModel	6
3	ImagesToLARModel	7
3.1	Calling modules	7
3.2	Input loading	8
3.3	Starting conversion	10
4	PngStack2Array3dJulia	12
4.1	Module imports	12
4.2	Convert input to png	12
4.3	Getting data from a png	16
4.4	Centroids computation	18
4.5	Transform pixels into three-dimensional array	19
5	ImagesConversion	22
5.1	General algorithm	23
5.2	Module imports	24
5.3	Data preparation	25
5.4	Conversion pipeline	26
5.4.1	Images conversion step	30
5.4.2	Boundaries merge step	34
5.4.3	Block merge step	37
5.4.4	Smoothing step	39
5.4.5	Model creation step	43
6	GenerateBorderMatrix	43
6.1	Module imports	44
6.2	Get border matrix from file	44
6.3	Write border matrix on file	45
6.4	Compute border matrix	46
6.5	Transform border matrix	47

7	Lar2Julia	47
7.1	Module imports	48
7.2	Get boundary chain from a model	48
7.3	Get oriented cells from a chain	49
7.4	Transform relationships from arrays of arrays to a sparse matrix	50
8	LARUtils	51
8.1	Module imports	51
8.2	Transformation from matrix to array	52
8.3	Get bases of a LAR model	53
8.4	Double vertices and faces removal	56
8.5	Creation of a LAR model	60
8.6	Removing double faces and vertices from boundaries	67
9	Smoother	69
9.1	Get adjacent vertices	69
9.2	Laplacian smoothing	71
10	Model2Obj	72
10.1	Writing models to file	73
10.2	Merging block models	75
10.2.1	Parallel merging of obj files	77
10.3	Load models from files	83
11	Exporting the library	84
11.1	Installing the library	88
12	Conclusions	88
12.1	Results	88
12.2	Further improvements	88
A	Utility functions	88
B	Tests	88

1 Introduction

This work has the aim to transform a two-dimensional representation of a model (based on a stack of images) into a three-dimensional representation based on the LAR schema. In particular, it will produce a single obj model which can be viewed with standard graphics softwares.

In the past were developed other softwares using same principles (see [PDFJ15]). However, they were optimized for speed and cannot be able to accept huge amounts of data. With the rise of the big data era, we now have more and more data available for research purposes, so softwares must be able to deal with them. A typical hardware environment is based on a cluster of computers where computation can be distributed among a lot of different processes. However, as stated by *Amdahl's law*, the speedup of a program using multiple processors is limited by the time needed for the sequential fraction of the program. So use of parallel techniques for dealing with big data is not important for time performance gain but for memory space gain. In fact, our biggest problem is lack of memory, due to model sizes. As a consequence, every parts of this software is written with the clear objective of minimizing memory usage at the cost of losing something in terms of time performance. So, for example, images will be converted in blocks determined by a grid size (see section 5) among different processes and different machines of the cluster



Figure 1: Amdahl's law

1.1 Why Julia

Ricordare che precedenti versioni erano in python

Semplicità

Efficienza

Capacità di realizzare programmi paralleli con poco sforzo

2 Software structure

2.1 Julia packages

This software will be distributed as a Julia Package. For the actual release (Julia 0.4) a package is a simple git project with the structure showed in figure 2



Figure 2: Julia module structure

Source code must be in folder `src`, while in `test` folder there are module tests with a `runtests.jl` for executing them and with a `REQUIRE` file for specifying tests dependencies. For listing dependencies for the entire project, there is another `REQUIRE` file in main folder. As an example in figure 3 there is the `REQUIRE` file for `ImagesToLARMModel.jl`.

After creating this structure for a project it can be pushed on a git repository and installed on Julia systems. The usual installation procedure use this syntax:

```
Pkg.add("Package-name")
```

This will check for that package in METADATA.jl repository on github where there are all official Julia package. However it is also possible to install an unofficial package (on a public git repository) using this syntax:

```
julia 0.3
JSON
Logging
PyCall
Images
Colors
Clustering
```

Figure 3: REQUIRE contents for `ImagesToLARModel.jl`

```
Pkg.clone("git://repository-address.git")
```

This will install the package on your system with all the dependencies listed in REQUIRE file.

2.2 Architecture of ImagesToLARModel

In previous section we have seen how to create a Julia package for distribute our application. Now we focus on the structure of our application. In `src` folder we can find the following modules:

ImagesToLARModel.jl: main module for the software, it takes input parameters and start images conversion

ImagesConversion.jl: it is called by `ImagesToLARModel.jl` module and controls the entire conversion process calling all other modules

GenerateBorderMatrix.jl: it generates the boundary operator for grid specified in input, saving it in a JSON file

PngStack2Array3dJulia.jl: it is responsible of images loading and conversion into computable data

Lar2Julia.jl: it contains a small subset of LAR functions written in Julia language

LARUtils.jl: it contains utility functions for manipulation of LAR models

Smoother.jl: it contains function for smoothing of LAR models

Model2Obj.jl: it contains function that manipulates obj files

larcc.py: python larcc module for boundary computation. In next releases of the software it will be rewritten in Julia language




Figure 4: Schema of module dependencies of ImagesToLARModel

In figure 4 there is a simple schema of dependencies between modules.

Next sections of this document will explain in details all these modules showing also the code involved in conversion

3 ImagesToLARModel

This is the main module for the application; it takes the input data and start conversion calling `ImagesConversion.jl`.

3.1 Calling modules

As we have already said, this first module has the responsibility of starting the conversion calling all other modules in the package. In Julia calling modules requires that they are in a path specified by `LOAD_PATH` array. So at the beginning of this module we need to add this line:

`< update load path 6 > ≡`

```
push!(LOAD_PATH, Pkg.dir("ImagesToLARModel/src"))
◇
```

Fragment referenced in 83a.

`Pkg.dir()` function gives us the path of the Julia installation, so `Pkg.dir("ImagesToLARModel/src")` returns “*⟨Julia – path⟩/ImagesToLARModel/src*”

After this line we can now import all modules defined here and export public functions:

```
⟨modules import ImagesToLARModel 7⟩ ≡
    import JSON
    import ImagesConversion

    using Logging

    export convertImagesToLARModel

◇
```

Fragment referenced in 83a.

3.2 Input loading

Images conversion takes several parameters:

- `inputDirectory`: The path of the directory containing the stack of images
- `outputDirectory`: The path of the directory containing the output
- `bestImage`: Image chosen for centroid computation (see section 4)
- `nx, ny, nz`: Sizes of the grid chosen for image segmentation (see section 4)
- `DEBUG_LEVEL`: Debug level for Julia logger
- `parallelMerge` (experimental): Choose between sequential or parallel merge of files (see section 10)
- `noise_shape`: Intensity of the denoising filter for images (0 if you want to disable it)

Because of their number it has been realized a function for simply loading them from a JSON configuration file; this is the code:


```

⟨load JSON configuration 8⟩ ≡
function loadConfiguration(configurationFile)
  ""
  load parameters from JSON file

  configurationFile: Path of the configuration file
  ""

  configuration = JSON.parse(configurationFile)

  DEBUG_LEVELS = [DEBUG, INFO, WARNING, ERROR, CRITICAL]

  parallelMerge = false
  try
    if configuration["parallelMerge"] == "true"
      parallelMerge = true
    else
      parallelMerge = false
    end
  catch
  end

  noise_shape = 0
  try
    noise_shape = configuration["noise_shape"]
  catch
  end

  return configuration["inputDirectory"], configuration["outputDirectory"],
    configuration["bestImage"],
    configuration["nx"], configuration["ny"], configuration["nz"],
    DEBUG_LEVELS[configuration["DEBUG_LEVEL"]],
    parallelMerge, noise_shape

end
◇

```

Fragment referenced in 83a.

A valid JSON file has the following structure:

```

{
  "inputDirectory": "Path of the input directory",
  "outputDirectory": "Path of the output directory",

```

```

    "bestImage": "Name of the best image (with extension) ",
    "nx": x grid size,
    "ny": y grid size,
    "nz": border z,
    "DEBUG_LEVEL": julia Logging level (can be a number from 1 to 5)
    "parallelMerge": "true" or "false"
    "noise_shape": A number which indicates the intensity of the denoising
    filter (0 if you want to disable denoising)
}

```

For example, we can write:

```

{
  "inputDirectory": "/home/juser/IMAGES/"
  "outputDirectory": "/home/juser/OUTPUT/",
  "bestImage": "0009.tiff",
  "nx": 2,
  "ny": 2,
  "nz": 2,
  "DEBUG_LEVEL": 2
}

```

As we can see, in a valid JSON configuration file `DEBUG_LEVEL` can be a number from 1 to 5. Instead, when we explicitly define parameters, `DEBUG_LEVEL` can only be one of the following Julia constants:

- `DEBUG`
- `INFO`
- `WARNING`
- `ERROR`
- `CRITICAL`

parallelMerge and *noise_shape* are optional parameters

3.3 Starting conversion

As we have already said, this module has the only responsibility to collect data input and starts other modules. These are the functions that start the process and the only exposed to the application users:

⟨ Start conversion from JSON file 10a ⟩ ≡

```
function convertImagesToLARModel(configurationFile)
    """
    Start conversion of a stack of images into a 3D model
    loading parameters from a JSON configuration file

    configurationFile: Path of the configuration file
    """
    inputDirectory, outputDirectory, bestImage, nx, ny, nz,
        DEBUG_LEVEL, parallelMerge, noise_shape = loadConfiguration(open(configurationFile))
    convertImagesToLARModel(inputDirectory, outputDirectory, bestImage,
        nx, ny, nz, DEBUG_LEVEL, parallelMerge, noise_shape)
end
◇
```

Fragment referenced in 83a.

⟨ Start manual conversion 10b ⟩ ≡

```
function convertImagesToLARModel(inputDirectory, outputDirectory, bestImage,
    nx, ny, nz, DEBUG_LEVEL = INFO,
    parallelMerge = false, noise_shape = 0)
    """
    Start conversion of a stack of images into a 3D model

    inputDirectory: Directory containing the stack of images
    outputDirectory: Directory containing the output
    bestImage: Image chosen for centroids computation
    nx, ny, nz: Border dimensions (Possibly the biggest power of two of images dimensions)
    DEBUG_LEVEL: Debug level for Julia logger. It can be one of the following:
        - DEBUG
        - INFO
        - WARNING
        - ERROR
        - CRITICAL
    parallelMerge: Choose if you want to use the algorithm
    for parallel merging (experimental)
    noise_shape: The shape for image denoising
    """
    # Create output directory
    try
        mkpath(outputDirectory)
    catch
    end
end
```

```

    Logging.configure(level=DEBUG_LEVEL)
    ImagesConversion.images2LARModel(nx, ny, nz, bestImage,
                                     inputDirectory, outputDirectory, parallelMerge, noise_shape)
end
◇

```

Fragment referenced in 83a.

4 PngStack2Array3dJulia

This module has the responsibility of convert a png image into an array of values that will be passed to other modules

4.1 Module imports

These are modules needed for this part of the package and the public functions exported

```

⟨ modules import PngStack2Array3dJulia 11 ⟩ ≡
    using Images # For loading png images
    using Colors # For grayscale images
    using PyCall
    using Clustering
    using Logging
    @pyimport scipy.ndimage as ndimage

    export calculateClusterCentroids, pngstack2array3d, getImageData, convertImages
◇

```

Fragment referenced in 86.

We need `Images`, `Clustering` and `Colors` packages for manipulating png images and `PyCall` for using Python functions for noise removal from images. As a consequence, we need a python environment with `scipy` to be able to run the package

4.2 Convert input to png

First thing to do in our program is getting our input folder and convert the stack of images into png format. This process lets us to avoid managing an enormous variety of formats during computation, simplifying code used for transformation.

Conversion needs the following parameters:

- `inputPath`: path of the folder containing the original images
- `outputPath`: path where we will save png images
- `bestImage`: name of the image chosen for centroids computing (see section 4.4)

After conversion `outputPath` will contain our png images and the function will return the new name chosen for the best image.

Now we can examine single parts of conversion process. First of all we need to specify a new name for images, keeping the right order between them; so we need to define a prefix based on number of images:

```
⟨ Define string prefix 12a ⟩ ≡
    imageFiles = readdir(inputPath)
    numberOfImages = length(imageFiles)
    outputPrefix = ""
    for i in 1: length(string(numberOfImages)) - 1
        outputPrefix = string(outputPrefix,"0")
    end ◇
```

Fragment referenced in 14b.

Next we need to open the single image doing the following operations:

1. Open images using `Images` library (which relies on `ImageMagick`) and save them in greyscale png format
2. if one or both dimensions of the image are odd we need to remove one row (or column) of pixels to make it even. This will be more clear when we will introduce the grid for parallel computation (see section 5)

```
⟨ Greyscale conversion 12b ⟩ ≡
    rgb_img = convert(Image{ColorTypes.RGB}, img)
    gray_img = convert(Image{ColorTypes.Gray}, rgb_img) ◇
```

Fragment referenced in 14b.

As we can see, we first need to convert image to RGB and then reconvert to greyscale. Without the RGB conversion these rows will return a `stackoverflow` error due to the presence of alpha channel

```

< Image resizing 13a > ≡
    # resizing images if they do not have even dimensions
    dim = size(img)
    if(dim[1] % 2 != 0)
        debug("Image has odd x; resizing")
        xrange = 1: dim[1] - 1
    else
        xrange = 1: dim[1]
    end

    if(dim[2] % 2 != 0)
        debug("Image has odd y; resizing")
        yrange = 1: dim[2] - 1
    else
        yrange = 1: dim[2]
    end

    img = subim(gray_img, xrange, yrange) ◇

```

Fragment referenced in 14b.

Next we just have to search for the best image and add one image if they are odd (for same reasons we need even image dimensions)

```

< Search for best image 13b > ≡
    # Searching the best image
    if(imageFile == bestImage)
        newBestImage = string(outputPrefix[length(string(imageNumber)):end],
                                imageNumber, ".png")
    end
    imageNumber += 1 ◇

```

Fragment referenced in 14b.

```

< Add one image 13c > ≡
    # Adding another image if they are odd
    if(numberOfImages % 2 != 0)
        debug("Odd images, adding one")
        imageWidth, imageHeight = getImageData(string(outputPath, "/", newBestImage))

        if(imageWidth % 2 != 0)

```

```

        imageWidth -= 1
    end

    if(imageHeight % 2 != 0)
        imageHeight -= 1
    end

    imArray = zeros(UInt8, imageWidth, imageHeight)
    img = grayim(imArray)
    outputFilename = string(outputPath, "/",
                            outputPrefix[length(string(imageNumber)):end], imageNumber, ".png")
    imwrite(img, outputFilename)
end ◇

```

Fragment referenced in 14b.

Finally we have to reduce noise on the image. The better choice is using a *median filter* from package `scipy.ndimage` because it preserves better the edges of the image:

```

⟨ Reduce noise 14a ⟩ ≡
    # Denoising
    if noise_shape_detect != 0
        imArray = raw(img)
        imArray = ndimage.median_filter(imArray, noise_shape_detect)
        img = grayim(imArray)
    end ◇

```

Fragment referenced in 14b.

Where `imArray` is an array containing all raw data from images

Finally this is the code for the entire function:

```

⟨ Convert to png 14b ⟩ ≡

function convertImages(inputPath, outputPath, bestImage, noise_shape_detect = 0)
    """
    Get all images contained in inputPath directory
    saving them in outputPath directory in png format.
    If images have one of two odd dimensions, they will be resized
    and if folder contains an odd number of images another one will be
    added
    """
end

```

```

inputPath: Directory containing input images
outputPath: Temporary directory containing png images
bestImage: Image chosen for centroids computation
noise_shape_detect: Shape for the denoising filter

Returns the new name for the best image
"""

⟨ Define string prefix 12a ⟩

newBestImage = ""
imageNumber = 0
for imageFile in imageFiles
    img = imread(string(inputPath, imageFile))
    ⟨ Greyscale conversion 12b ⟩
    ⟨ Image resizing 13a ⟩
    outputFilename = string(outputPath, outputPrefix[length(string(imageNumber)):end],
                           imageNumber, ".png")
    imwrite(img, outputFilename)

    ⟨ Search for best image 13b ⟩
    ⟨ Reduce noise 14a ⟩

    imwrite(img, outputFilename)

end

⟨ Add one image 13c ⟩

return newBestImage
end
◇

```

Fragment referenced in 86.

4.3 Getting data from a png

Now we need to load information data from png images. In particular we are interested in getting width and height of an image. As stated in [W3C] document, a standard PNG file contains a *signature* followed by a sequence of *chunks* (each one with a specific type).

The signature always contain the following values:

137 80 78 71 13 10 26 10

This signature indicates that the remainder of the datastream contains a single PNG image, consisting of a series of chunks beginning with an IHDR chunk and ending with an IEND chunk. Every chunk is preceded by four bytes indicating its length.

As we are interested in width and height we need to parse the IHDR chunk. It is the first chunk in PNG datastream and its type field contains the decimal values:

73 72 68 82

The header also contains:

Width	4 bytes
Height	4 bytes
Bit depth	1 bytes
Color type	1 byte
Compression method	1 byte
Filter method	1 byte
Interlace method	1 byte

So for reading width and height we need first 24 bytes; the first eight contain the signature, then we have four bytes for length, four bytes for the type field and eight bytes for information we are interested in. This is the code:

```
< Get image data 16 > ≡
function getImageData(imageFile)
    """
    Get width and height from a png image
    """

    input = open(imageFile, "r")
    data = readbytes(input, 24)

    if (convert(Array{Int},data[1:8]) != reshape([137 80 78 71 13 10 26 10],8))
        error("This is not a valid png image")
    end

    w = data[17:20]
    h = data[21:24]

    width = reinterpret{Int32, reverse(w)}[1]
    height = reinterpret{Int32, reverse(h)}[1]

    close(input)
```

```

        return width, height
    end
    ◇

```

Fragment referenced in 86.

4.4 Centroids computation

As we have seen above, this package uses greyscale images for conversion into three-dimensional models and for next steps we need binary images so we can distinguish between the background and the model we want to represent. We can use clustering techniques for obtaining this result. First step is centroids calculation from a chosen image (this choice must be made from the user, because we cannot know in advance what is the best image for finding clusters). Moreover we compute these centroids only for an image and then reuse them when we want to cluster all other images, saving processing time. Actually we need only two centroids, because next steps should only recognize between background and foreground pixels. This is the code used for centroid computation:

⟨ Centroid computation 17 ⟩ \equiv

```

function calculateClusterCentroids(path, image, numberOfClusters = 2)
    """
    Loads an image and calculate cluster centroids for segmentation

    path: Path of the image folder
    image: name of the image
    numberOfClusters: number of desired clusters
    """
    imageFilename = string(path, image)

    img = imread(imageFilename) # Open png image with Julia Package

    imArray = raw(img)

    imageWidth = size(imArray)[1]
    imageHeight = size(imArray)[2]

    # Getting pixel values and saving them with another shape
    image3d = Array{Array{UInt8,2}, 0}

    # Inserting page on another list and reshaping
    push!(image3d, imArray)
    pixel = reshape(image3d[1], (imageWidth * imageHeight), 1)

```

```

centroids = kmeans(convert(Array{Float64},transpose(pixel)), 2).centers

return convert(Array{UInt8}, trunc(centroids))

end
◇

```

Fragment referenced in 86.

4.5 Transform pixels into three-dimensional array

Now we can study the most important part of this module, where images are converted into data usable by other modules for the creation of the three-dimensional model. The basic concept consists in transforming every single pixel in an integer value representing color, and then clustering them all using centroids computed earlier. So, we can obtain a matrix containing only two values (the two centroids) representing background and foreground of the image.

Now we will follow the code. This function uses four parameters

- path: Path of the images directory
- minSlice: First image to read
- maxSlice: Last image to read
- centroids: Array containing centroids for clustering

For every image we want to transform in the interval [minSlice, maxSlice) we have to read it from disk and save pixel informations into a multidimensional Array:

```

⟨ Read raw data 18a ⟩ ≡
    img = imread(imageFilename) # Open png image with Julia Package
    imArray = raw(img) # Putting pixel values into RAW 3d array ◇

```

Fragment referenced in 20.

The `Images.jl` `raw` function, get all pixel values saving them in an Array. In Figure 7 we can see how the array will be like for a sample greyscale image.

Finally we have to compute clusters obtaining images with only two values:

```

⟨ Clustering images 18b ⟩ ≡

```



Figure 5: Reading raw data from image. (a) Original greyscale image (b) A view of raw data array (c) The entire raw data array with main color highlighted

```
# Image Quantization
debug("page = ", page)
debug("image3d[page] dimensions: ", size(image3d[page])[1], "\t", size(image3d[page])[2])
pixel = reshape(image3d[page], size(image3d[page])[1] * size(image3d[page])[2] , 1)
kmeansResults = kmeans!(convert(Array{Float64},transpose(pixel)),
                        convert(Array{Float64},centroids))

qnt = kmeansResults.assigments
centers = kmeansResults.centers
if(centers[1] == centers[2])
    # The image has only a value
    index = findmin([abs(centroids[1]-centers[1]),abs(centroids[2]-centers[1])])[2]
    qnt = fill(index, size(qnt))
end

# Reshaping quantization result
```

```

centers_idx = reshape(qnt, size(image3d[page],1), size(image3d[page],2))

# Inserting quantized values into 3d image array
tmp = Array{UInt8, size(image3d[page],1), size(image3d[page],2))

for j in 1:size(image3d[1],2)
    for i in 1:size(image3d[1],1)
        tmp[i,j] = centroids[centers_idx[i,j]]
    end
end

image3d[page] = tmp ◊

```

Fragment referenced in 20.




Figure 6: Image transformation. (a) Original greyscale image (b) Denoised image (c) Two-colors image

We can see that sometimes the `Clustering.jl` library returns the same values for both centroid centers. This could happen when the images is completely empty or it has only colored pixels. So, we need to check this cases and fill the assignments array `qnt` with the right values based on the `centroids` parameter.

This is the complete code:

```

⟨ Pixel transformation 20 ⟩ ≡
function pngstack2array3d(path, minSlice, maxSlice, centroids)
    """
    Import a stack of PNG images into a 3d array

    path: path of images directory

```

```

minSlice and maxSlice: number of first and last slice
centroids: centroids for image segmentation
"""

# image3d contains all images values
image3d = Array(Array{UInt8,2}, 0)

debug("maxSlice = ", maxSlice, " minSlice = ", minSlice)
files = readdir(path)

for slice in minSlice : (maxSlice - 1)
    debug("slice = ", slice)
    imageFilename = string(path, files[slice + 1])
    debug("image name: ", imageFilename)
    ⟨ Read raw data 18a ⟩
    debug("imArray size: ", size(imArray))

    # Inserting page on another list and reshaping
    push!(image3d, imArray)

end

# Quantization
for page in 1:length(image3d)

    ⟨ Clustering images 18b ⟩

end

return image3d
end
◇

```

Fragment referenced in 86.

5 ImagesConversion

Now we will study the most important module for this package: `ImagesConversion`. It has the responsibility of doing the entire conversion process delegating tasks to the other modules.

5.1 General algorithm

Now we will examine, in a general way, the algorithm used for conversion from a two-dimensional to a three-dimensional representation of our biomedical models.

We have already seen in section 4 how to get information from a png image, obtaining arrays with only two values; one for the **background** color and one for **foreground** color. This is only the first step of the complete conversion process.

Now we focus only on a single image of the stack. Our two-dimensional representation, consists of pixels of two different colors (where only the one associated with foreground is significant); so we can obtain a three-dimensional representation simply replacing every foreground pixel with a small cube. Focusing on the entire stack of images, the full three-dimensional representation can be obtained simply overlapping all the image representations

This algorithm is very simple, however we does not considered problems concerning lack of memory. In fact, we could have images so big that we cannot build these models entirely in memory; moreover they would require a lot of CPU time for computation. A good solution to these problems consists in taking our representation based on images and divide according to a **grid**.




Figure 7: The grid used for parallel computation (a) 2D grid on a single image (b) 3D grid for the stack of images

So, instead of converting the entire model with a unique process, we can subdivide the input among a lot of processes, where every process will execute the conversion process on

a small number of **blocks** according to the grid subdivision.

Summing up we can define the following terms, which will be used in next parts of this documentation:

- **Grid:** It is the subdivision of the entire stack of images, with sizes defined by the user. They should be powers of two (for increasing performance during border matrix computation which we will see in section 6)
- **Block:** It is a single cell of the grid
- **xBlock:** It is the x-coordinate of a block
- **yBlock:** It is the y-coordinate of a block
- **zBlock:** It is the z-coordinate of a block

xBlock and *yBlock* are defined on a single image, while *zBlock* is defined on different images; in the code it will often be replaced by terms **StartImage** and **EndImage**, which indicate the first image and the last image of that block respectively.

In next subsections we will examine the conversion algorithm in detail, showing what happens for every block of the grid.

5.2 Module imports

These are modules needed for this part of the package and the public functions exported.

```
< modules import ImagesConversion 23 > ≡  
    import GenerateBorderMatrix  
    import PngStack2Array3dJulia  
    import Lar2Julia  
    import Model2Obj  
    import LARUtils  
    import Smoother  
  
    using Logging  
  
    export images2LARModel  
    ◇
```

Fragment referenced in 83b.

5.3 Data preparation

As a first thing, we will see how to prepare our data for conversion process. Firstly we need to convert input images to greyscale png; so we need to create a temporary directory for saving them.

Later, we need to compute the LAR boundary operator for finding boundaries of our cells (for the generation see section 6) getting width and height from our images.

Finally we can start conversion with all these parameters calling `startImageConversion` function, which will be explained in next subsection.

```
< main function for ImagesConversion 24 > ≡
function images2LARModel(nx, ny, nz, bestImage,
                        inputDirectory, outputDirectory,
                        parallelMerge, noise_shape_detect = 0)

    """
    Convert a stack of images into a 3d model
    """

    info("Starting model creation")

    numberOfClusters = 2 # Number of clusters for
                        # images segmentation

    info("Moving images into temp directory")
    try
        mkdir(string(outputDirectory, "TEMP"))
    catch
    end

    tempDirectory = string(outputDirectory, "TEMP/")

    newBestImage = PngStack2Array3dJulia.convertImages(inputDirectory, tempDirectory,
                                                         bestImage, noise_shape_detect)

    imageWidth, imageHeight = PngStack2Array3dJulia.getImageData(
                                string(tempDirectory, newBestImage))
    imageDepth = length(readdir(tempDirectory))

    # Computing border matrix
    info("Computing border matrix")
    try
        mkdir(string(outputDirectory, "BORDERS"))
    catch
    end
    borderFilename = GenerateBorderMatrix.getOriented3BorderPath(
                                string(outputDirectory, "BORDERS"), nx, ny, nz)
```

```

# Starting images conversion and border computation
info("Starting images conversion")
startImageConversion(tempDirectory, newBestImage, outputDirectory, borderFilename,
                    imageHeight, imageWidth, imageDepth,
                    nx, ny, nz,
                    numberOfClusters, parallelMerge)

end
◇

```

Fragment referenced in 83b.

5.4 Conversion pipeline

Now we can see how conversion of images works. In section 5.1 we have seen how to execute the single conversion of a pixel into a voxel using our grid for parallel computation. However, with that algorithm, we obtain models with internal boundaries between blocks and with squared edge. So we need to create a **conversion pipeline** which will progressively refine our models. In Figure 8 there are the steps used for our conversion




Figure 8: Images conversion pipeline

Every single step of the pipeline, is executed in parallel for every block of the grid; so we need a general purpose function for blocks iteration which will take as a parameter a function that will execute it. So we can define the `iterateOnBlocks` function which takes the following parameters:

- **inputDirectory**: Directory which contains input files for the process function
- **imageHeight, imageWidth, imageDepth**: Sizes of the stack of images
- **imageDx, imageDy, imageDz**: Sizes of the grid
- **processFunction**: Function that contains instructions for execution of a single step of the pipeline for a single block
- **outputDirectory**: Directory which will contains the output
- **centroids**: Centroids from the best image

- **boundaryMat**: Boundary operator for the chosen grid

This function will iterate on all blocks of the image grid executing the process function, which will be different for every pipeline step. This is the code used:

< parallel block iteration 26 > ≡

```
function iterateOnBlocks(inputDirectory,
                        imageHeight, imageWidth, imageDepth,
                        imageDx, imageDy, imageDz,
                        processFunction, outputDirectory,
                        centroidsCalc, boundaryMat)

    """
    Simple function that iterates on blocks for executing
    a task described by a processFunction

    inputDirectory: Directory which contains input files for the process function
    imageHeight, imageWidth, imageDepth: Images sizes
    imageDx, imageDy, imageDz: Sizes of cells grid
    processFunction: Function that will be executed on a separate task on
    the entire z-Block
    outputDirectory: Directory which will contains the output
    centroidsCalc: Centroids from the best image
    boundaryMat: Boundary operator for the chosen grid
    """

    beginImageStack = 0
    endImage = beginImageStack

    tasks = Array(RemoteRef, 0)
    for zBlock in 0:(imageDepth / imageDz - 1)
        startImage = endImage
        endImage = startImage + imageDz
        task = @spawn processFunction(inputDirectory,
                                    startImage, endImage,
                                    imageDx, imageDy,
                                    imageWidth, imageHeight,
                                    outputDirectory,
                                    centroidsCalc, boundaryMat)

        push!(tasks, task)
    end

    # Waiting for tasks
    for task in tasks
        wait(task)
    end
end ◇
```

Fragment referenced in 83b.

First of all we need to iterate on the grid finding the zBlock coordinate; we saw earlier that the *imageDz* parameter must be a divisor of the image depth, so we will have exactly *imageDepth/imageDz* blocks on the z coordinate. Moreover, at every zBlock correspond a startImage and an endImage where *endImage - startImage = imageDz*.

Now we can simply parallelize the conversion process spawning a new process for every zBlock, so we open at most *imageDz* images for process. Finally, we have to wait for tasks completion.

Now we can see the entire pipeline for images conversion.

First of all we need to compute the centroids from the best image using module `PngStack2Array3dJulia` and get the previously computed border matrix in csc sparse array format

```
< compute centroids and get border matrix 27a > ≡
# Create clusters for image segmentation
info("Computing image centroids")
debug("Best image = ", bestImage)
centroidsCalc = PngStack2Array3dJulia.calculateClusterCentroids(sliceDirectory,
                                                                bestImage, numberOfClusters)
debug(string("centroids = ", centroidsCalc))

try
    mkdir(string(outputDirectory, "BORDERS"))
catch
end
debug("Opening border file: border_", imageDx, "-", imageDy, "-", imageDz, ".json")
boundaryMat = GenerateBorderMatrix.getBorderMatrix(
                                                                string(outputDirectory,"BORDERS/", "border_",
                                                                imageDx, "-", imageDy, "-", imageDz, ".json"))

◇
```

Fragment referenced in 28.

Now we can start the pipeline:

```
< pipeline conversion 27b > ≡
```

```

# Starting pipeline conversion
info("Starting images conversion")
⟨ pixels to voxels conversion step 33 ⟩

info("Merging boundaries")
⟨ boundaries merge step 36a ⟩

info("Merging blocks")
⟨ block merge step 38a ⟩

info("Smoothing models")
⟨ smoothing step 42a ⟩

info("Merging obj models")
⟨ final file merge 42b ⟩
end ◇

```

Fragment referenced in 28.

As we can see, last pipeline step does not require iteration on all grid blocks. This is the code for the function that starts the pipeline, with the parts explained earlier:

⟨ start conversion of images 28 ⟩ ≡

```

function startImageConversion(sliceDirectory, bestImage, outputDirectory, borderFilename,
                             imageHeight, imageWidth, imageDepth,
                             imageDx, imageDy, imageDz,
                             numberOfClusters, parallelMerge)
    """
    Support function for converting a stack of images into a model

    sliceDirectory: directory containing the image stack
    imageForCentroids: image chosen for centroid computation
    """

    ⟨ compute centroids and get border matrix 27a ⟩
    ⟨ pipeline conversion 27b ⟩
end
◇

```

Fragment referenced in 83b.

5.4.1 Images conversion step

Now we will focus on the first step of our pipeline conversion: *images conversion*. First thing to do is read an image calling the `PngStack2Array3dJulia`, after that is necessary to sort the centroid array for choosing correct background and foreground pixels.

```
< image read and centroids sort 29a > ≡  
    info("Transforming png data into 3d array")  
    theImage = PngStack2Array3dJulia.pngstack2array3d(sliceDirectory,  
                                                    startImage, endImage, centroids)  
  
    centroidsSorted = sort(vec(reshape(centroids, 1, 2)))  
    background = centroidsSorted[1]  
    foreground = centroidsSorted[2]  
    debug(string("background = ", background, " foreground = ", foreground))  
    ◇
```

Fragment referenced in 32.

Now we can start iterating on other blocks of the grid:

```
< block iteration 29b > ≡  
    for xBlock in 0:(imageWidth / imageDx - 1)  
        for yBlock in 0:(imageHeight / imageDy - 1)  
  
            xStart = xBlock * imageDx  
            yStart = yBlock * imageDy  
            zStart = startImage  
  
            xEnd = xStart + imageDx  
            yEnd = yStart + imageDy  
  
            imageDz = length(theImage)  
  
            debug("*****")  
            debug(string("xStart = ", xStart, " xEnd = ", xEnd))  
            debug(string("yStart = ", yStart, " yEnd = ", yEnd))  
            debug("theImage dimensions: ", size(theImage)[1], " ",  
                  size(theImage[1])[1], " ", size(theImage[1])[2]) ◇
```

Fragment referenced in 32.

Here $xStart$ and $yStart$ are the absolute coordinates of the model and are calculated from the block coordinates. Now we can get the current slice for the entire image (with size $(imageDx, imageDy, imageDz)$), check values for every single pixel into it and, if it represents a foreground point, put it into an array called `chain3D`. This structure contains indexes of the linearized array created from the matrix. In Figure 9 there is a sample conversion from the matrix to the array

$$\begin{pmatrix} 0^0 & 0^2 \\ 0^1 & 0^3 \end{pmatrix} \begin{pmatrix} 46^4 & 0^6 \\ 46^5 & 46^7 \end{pmatrix} \rightarrow 0^0 \ 0^1 \ 0^2 \ 0^3 \ 46^4 \ 46^5 \ 0^6 \ 46^7$$

$$\begin{pmatrix} 0^0 & 0^2 \\ 0^1 & 0^3 \end{pmatrix} \begin{pmatrix} 0^4 & 46^6 \\ 46^5 & 46^7 \end{pmatrix} \rightarrow 0^0 \ 0^1 \ 0^2 \ 0^3 \ 0^4 \ 46^5 \ 46^6 \ 46^7$$

Figure 9: Transformation of a matrix resulting from a 2x2x2 grid into a linearized array (with cells indexes) (a) First example (b) Second example

As we can see from that figure, from a 2x2x2 grid we can obtain eight values for the single block (or **cell**), where the indexes for the foreground pixels represent indexes of non-empty cells in a 2x2x2 cuboidal geometry. This is the code for getting foreground pixels:

```

⟨ get image slice 30 ⟩ ≡
  chains3D = Array{Int, 0}
  for z in 1 : imageDz
    for y in 1 : imageDy
      for x in 1 : imageDx
        if(theImage[z][x + xStart, y + yStart] == foreground)
          index = x - 1 + (y - 1) * imageDx + (z - 1) * (imageDx * imageDy)
          push!(chains3D, index)
        end
      end
    end
  end
end ◇

```

Fragment referenced in 32.

Now that we have full cells for the geometry, we can convert them into a *LAR model*. In particular, we are interested in cell boundaries for every block (as we want to obtain only the boundaries for the final model) so we can call function `larBoundaryChain` from `Lar2Julia` module (which will be explained in section 7). In Figure 10 there are some examples of models extracted from a single $2 \times 2 \times 2$ block.

After model computation, next step is getting vertices and faces from model cells writing results to file. However, as we have already said, we are only interested in boundaries of




Figure 10: Sample models of 2x2x2 blocks

the final model while now we have only boundaries of a single block. Consequently, we have to separate boundaries from the inner faces of the block on different files (boundaries separation will be explained in section 8). As we can see later, we will merge boundaries together deleting common faces on both block borders, obtaining a model without internal faces. These are pieces of code for getting the inner block model with the boundaries and for file writing:

⟨ get inner model and boundaries 31a ⟩ ≡

```
models = LARUtils.computeModelAndBoundaries(imageDx, imageDy, imageDz,
                                             xStart, yStart, zStart, objectBoundaryChain)

V, FV = models[1][1] # inside model
V_left, FV_left = models[2][1]
V_right, FV_right = models[3][1] # right boundary
V_top, FV_top = models[4][1] # top boundary
V_bottom, FV_bottom = models[5][1] # bottom boundary
V_front, FV_front = models[6][1] # front boundary
V_back, FV_back = models[7][1] # back boundary
◇
```

Fragment referenced in 32.

⟨ write block models to file 31b ⟩ ≡

```
# Writing all models on disk
model_outputFilename = string(outputDirectory, "MODELS/model_output_", xBlock,
                              "-", yBlock, "_", startImage, "_", endImage)
Model2Obj.writeToObj(V, FV, model_outputFilename)
```



```

left_outputFilename = string(outputDirectory, "MODELS/left_output_", xBlock,
                             "-", yBlock, "_", startImage, "_", endImage)
Model2Obj.writeToObj(V_left, FV_left, left_outputFilename)

right_outputFilename = string(outputDirectory, "MODELS/right_output_", xBlock,
                              "-", yBlock, "_", startImage, "_", endImage)
Model2Obj.writeToObj(V_right, FV_right, right_outputFilename)

top_outputFilename = string(outputDirectory, "MODELS/top_output_", xBlock,
                             "-", yBlock, "_", startImage, "_", endImage)
Model2Obj.writeToObj(V_top, FV_top, top_outputFilename)

bottom_outputFilename = string(outputDirectory, "MODELS/bottom_output_", xBlock,
                                "-", yBlock, "_", startImage, "_", endImage)
Model2Obj.writeToObj(V_bottom, FV_bottom, bottom_outputFilename)

front_outputFilename = string(outputDirectory, "MODELS/front_output_", xBlock,
                               "-", yBlock, "_", startImage, "_", endImage)
Model2Obj.writeToObj(V_front, FV_front, front_outputFilename)

back_outputFilename = string(outputDirectory, "MODELS/back_output_", xBlock,
                              "-", yBlock, "_", startImage, "_", endImage)
Model2Obj.writeToObj(V_back, FV_back, back_outputFilename) ◇

```

Fragment referenced in 32.

This is the `processFunction` for this pipeline step

```

⟨ image conversion process 32 ⟩ ≡
    function imageConversionProcess(sliceDirectory,
                                   startImage, endImage,
                                   imageDx, imageDy,
                                   imageWidth, imageHeight,
                                   outputDirectory,
                                   centroids, boundaryMat)
    """
    Support function for converting a stack of image on a single
    independent process
    """

    ⟨ image read and centroids sort 29a ⟩

    ⟨ block iteration 29b ⟩

```

```

    < get image slice 30 >

    if(length(chains3D) != 0)
        # Computing boundary chain
        debug("chains3d = ", chains3D)
        debug("Computing boundary chain")
        objectBoundaryChain = Lar2Julia.larBoundaryChain(boundaryMat, chains3D)
        debug("Converting models into obj")
        try
            mkdir(string(outputDirectory, "MODELS"))
        catch
        end
        < get inner model and boundaries 31a >

        < write block models to file 31b >
    else
        debug("Model is empty")
    end
end
end
end <

```

Fragment referenced in 83b.

This is the code for starting this pipeline step:

```

< pixels to voxels conversion step 33 > ≡
    @time iterateOnBlocks(sliceDirectory,
        imageHeight, imageWidth, imageDepth,
        imageDx, imageDy, imageDz,
        imageConversionProcess, outputDirectory,
        centroidsCalc, boundaryMat) <

```

Fragment referenced in 27b.

5.4.2 Boundaries merge step

Next step of our pipeline consists in *boundaries merge*. In fact, we have already seen that for every non-empty cell we create files for the inner parts and for the boundaries of the block. So if we want a final model without boundaries between internal blocks, we need to merge them removing duplicated faces on both sides (see Section 8.6 for a better explanation of this step). The following is the `processFunction`:

\langle boundary merge process function 34 $\rangle \equiv$

```
function mergeBoundariesProcess(modelDirectory,
                                startImage, endImage,
                                imageDx, imageDy,
                                imageWidth, imageHeight,
                                outputDirectory = None,
                                centroidsCalc = None, boundaryMat = None)

"""
Helper function for mergeBoundaries.
It is executed on different processes

modelDirectory: Directory containing model files
startImage: Block start image
endImage: Block end image
imageDx, imageDy: x and y sizes of the grid
imageWidth, imageHeight: Width and Height of the image
"""
for xBlock in 0:(imageWidth / imageDx - 1)
  for yBlock in 0:(imageHeight / imageDy - 1)

    # Merging right Boundary
    firstPath = string(modelDirectory, "/right_output_", xBlock, "-", yBlock,
                        "_", startImage, "_", endImage)
    secondPath = string(modelDirectory, "/left_output_", xBlock, "-", yBlock + 1,
                        "_", startImage, "_", endImage)
    mergeBoundariesAndRemoveDuplicates(firstPath, secondPath)

    # Merging top boundary
    firstPath = string(modelDirectory, "/top_output_", xBlock, "-", yBlock,
                        "_", startImage, "_", endImage)
    secondPath = string(modelDirectory, "/bottom_output_", xBlock, "-", yBlock,
                        "_", endImage, "_", endImage + (endImage - startImage))
    mergeBoundariesAndRemoveDuplicates(firstPath, secondPath)

    # Merging front boundary
    firstPath = string(modelDirectory, "/front_output_", xBlock, "-", yBlock,
                        "_", startImage, "_", endImage)
    secondPath = string(modelDirectory, "/back_output_", xBlock + 1, "-", yBlock,
                        "_", startImage, "_", endImage)
    mergeBoundariesAndRemoveDuplicates(firstPath, secondPath)
  end
end
end  $\diamond$ 
```

Fragment referenced in 83b.

For every block we do the following merges:

- right boundary with the left boundary of the next block on the right
- top boundary with the bottom boundary of the next block on the top
- front boundary with the back boundary of the next block on the front




Figure 11: Merging of boundary faces. For a single block we need adjacent blocks on the right, top and front

all merges are executed by the function `mergeBoundariesAndRemoveDuplicates` which does the work calling the `Model2Obj` and `LARUtils` libraries for loading and cleaning of the boundaries models.

```

⟨ merge boundaries utility function 35 ⟩ ≡
function mergeBoundariesAndRemoveDuplicates(firstPath, secondPath)
    """
    Merge two boundary files removing common faces between
    them

    firstPath, secondPath: Prefix of paths to merge
    """

    firstPathV = string(firstPath, "_vtx.stl")
    firstPathFV = string(firstPath, "_faces.stl")

    secondPathV = string(secondPath, "_vtx.stl")
    secondPathFV = string(secondPath, "_faces.stl")

    if(isfile(firstPathV) && isfile(secondPathV))

        V, FV = Model2Obj.getModelsFromFiles([firstPathV, secondPathV],
                                              [firstPathFV, secondPathFV])
        V, FV = LARUtils.removeVerticesAndFacesFromBoundaries(V, FV)

```

```

    # Writing model to file
    rm(firstPathV)
    rm(firstPathFV)
    rm(secondPathV)
    rm(secondPathFV)
    Model2Obj.writeToObj(V, FV, firstPath)
end
end ◇

```

Fragment referenced in 83b.

This is the code used to start this pipeline step:

```

⟨ boundaries merge step 36a ⟩ ≡
    @time iterateOnBlocks(string(outputDirectory, "MODELS"),
        imageHeight, imageWidth, imageDepth,
        imageDx, imageDy, imageDz,
        mergeBoundariesProcess, None,
        None, None) ◇

```

Fragment referenced in 27b.

5.4.3 Block merge step

At this step of the computation, we have files with the inner parts of a single block model and the remaining boundaries. Now we need to merge the blocks removing double vertices and faces, so we can save space and prepare our model to the *smoothing step*. This is the code of the `processFunction`:

```

⟨ Block merge process function 36b ⟩ ≡
    function mergeBlocksProcess(modelDirectory,
        startImage, endImage,
        imageDx, imageDy,
        imageWidth, imageHeight,
        outputDirectory = None,
        centroidsCalc = None, boundaryMat = None)

    """
    Helper function for mergeBlocks.
    It is executed on different processes

```

```

modelDirectory: Directory containing model files
startImage: Block start image
endImage: Block end image
imageDx, imageDy: x and y sizes of the grid
imageWidth, imageHeight: Width and Height of the image
"""
for xBlock in 0:(imageWidth / imageDx - 1)
  for yBlock in 0:(imageHeight / imageDy - 1)

    blockCoordsV = string(xBlock, "-", yBlock, "_", startImage,
                          "_", endImage, "_vtx.stl")
    blockCoordsFV = string(xBlock, "-", yBlock, "_", startImage,
                          "_", endImage, "_faces.stl")

    arrayV = [string(modelDirectory, "/left_output_", blockCoordsV),
              string(modelDirectory, "/right_output_", blockCoordsV),
              string(modelDirectory, "/top_output_", blockCoordsV),
              string(modelDirectory, "/bottom_output_", blockCoordsV),
              string(modelDirectory, "/front_output_", blockCoordsV),
              string(modelDirectory, "/back_output_", blockCoordsV),
              string(modelDirectory, "/model_output_", blockCoordsV)]

    arrayFV = [string(modelDirectory, "/left_output_", blockCoordsFV),
              string(modelDirectory, "/right_output_", blockCoordsFV),
              string(modelDirectory, "/top_output_", blockCoordsFV),
              string(modelDirectory, "/bottom_output_", blockCoordsFV),
              string(modelDirectory, "/front_output_", blockCoordsFV),
              string(modelDirectory, "/back_output_", blockCoordsFV),
              string(modelDirectory, "/model_output_", blockCoordsFV)]

    V, FV = Model2Obj.getModelsFromFiles(arrayV, arrayFV)
    V, FV = LARUtils.removeDoubleVerticesAndFaces(V, FV, 0)
    for i in 1:length(arrayV)
      if(isfile(arrayV[i]))
        rm(arrayV[i])
        rm(arrayFV[i])
      end
    end

    Model2Obj.writeToObj(V, FV, string(modelDirectory, "/model_output_",
                                      xBlock, "-", yBlock, "_", startImage, "_", endImage))
  end
end
end ◇

```

Fragment referenced in 83b.

For a better explanation of the `LARUtils` function that remove duplicated vertices, you can see Section 8.4

This is the code for block merge starting

```
< block merge step 38a > ≡
    @time iterateOnBlocks(string(outputDirectory, "MODELS"),
                          imageHeight, imageWidth, imageDepth,
                          imageDx, imageDy, imageDz,
                          mergeBlocksProcess, None,
                          None, None) ◇
```

Fragment referenced in 27b.

5.4.4 Smoothing step

Now we have obtained models without internal boundaries between blocks and without double vertices and faces in a single block. However this partial model has squared edges, so we need to smooth them. The `processFunction` for this step, is the following:

```
< Smooth block process function 38b > ≡
    function smoothBlocksProcess(modelDirectory,
                                startImage, endImage,
                                imageDx, imageDy,
                                imageWidth, imageHeight,
                                outputDirectory = None,
                                centroidsCalc = None, boundaryMat = None)

    """
    Smoothes a block in a single process

    modelDirectory: Path of the directory containing all blocks
                    that will be smoothed
    startImage, endImage: start and end image for this block
    imageDx, imageDy: sizes of the grid
    imageWidth, imageHeight: sizes of the images
    """

    for xBlock in 0:(imageWidth / imageDx - 1)
        for yBlock in 0:(imageHeight / imageDy - 1)

            # Loading the current block model
            blockFileV = string(modelDirectory, "/model_output_", xBlock, "-", yBlock,
                               "_", startImage, "_", endImage, "_vtx.stl")
            blockFileFV = string(modelDirectory, "/model_output_", xBlock, "-", yBlock,
                                "_", startImage, "_", endImage, "_faces.stl")
```

```

if isfile(blockFileV)
  # Loading only model of the current block
  blockModelV, blockModelFV = Model2Obj.getModelsFromFiles([blockFileV], [blockFileFV])
  blockModelV, blockModelFV = LARUtils.removeDoubleVerticesAndFaces(blockModelV,
                                                                    blockModelFV, 0)

  # Loading a unique model from this block and its adjacents
  modelsFiles = Array(String, 0)
  for x in xBlock - 1:xBlock + 1
    for y in yBlock - 1:yBlock + 1
      for z in range(startImage - (endImage - startImage), (endImage - startImage), 3)
        push!(modelsFiles, string(modelDirectory, "/model_output_",
                                   x, "-", y, "-", z, "-", z + (endImage - startImage)))
      end
    end
  end

  modelsFilesV = map((s) -> string(s, "_vtx.stl"), modelsFiles)
  modelsFilesFV = map((s) -> string(s, "_faces.stl"), modelsFiles)

  modelV, modelFV = Model2Obj.getModelsFromFiles(modelsFilesV, modelsFilesFV)
  modelV, modelFV = LARUtils.removeDoubleVerticesAndFaces(modelV, modelFV, 0)

  # Now I have to save indices of vertices of the current block model
  blockVerticesIndices = Array{Int, 0}
  for i in 1:length(blockModelV)
    for j in 1:length(modelV)
      if blockModelV[i] == modelV[j]
        push!(blockVerticesIndices, j)
      end
    end
  end

  # Now I can apply smoothing on this model
  V_sm, FV_sm = Smoother.smoothModel(modelV, modelFV)

  # Now I have to get only block vertices and save them on the new model
  V_final = Array{Array{Float64}, 0}
  for i in blockVerticesIndices
    push!(V_final, V_sm[i])
  end
  outputFilename = string(modelDirectory, "/smoothed_output_", xBlock, "-",
                          yBlock, "-", startImage, "-", endImage)
  Model2Obj.writeToObj(V_final, blockModelFV, outputFilename)
end
end

```



```

        end
    end
end ◇

```

Fragment referenced in 83b.

An explanation of the smoothing algorithm used there, can be found in Section 9.2. What we need to remember here, is the importance of having the adjacent vertices for every vertex of our block. In fact, according to the chosen smoothing algorithm, every vertex is replaced with a new one with coordinates computed from the mean positions of its adjacent. However, loading of the entire model into memory cannot be done because of its sizes; so we created a simple algorithm which loads only near blocks to the current one. In fact, for every block we want to smooth, we load the twenty six adjacent blocks on all directions and the chosen one. We create a unique model with it (removing double vertices and faces) and then smoothing it with the algorithm in **Smother** module. Finally we save only smoothed vertices for the chosen block and continue with the other blocks. In Figure 12 there is a graphical explanation for the algorithm.




Figure 12: Smoothing of a single block. The red block at the center of the figure is the current one, while the other twenty six colored ones are the blocks that will be part of the model which will be smoothed for this iteration

Moreover, this **processFunction** can only execute a single iteration of the smoothing algorithm, so we need a function that can be able to execute more times the algorithm:

```

⟨ execute smoothing function 40 ⟩ ≡
    function smoothBlocks(modelDirectory,
                          imageHeight, imageWidth, imageDepth,
                          imageDx, imageDy, imageDz)
        ""
    end

```


We can see that after every smoothing iteration on the complete model, we need to rename the output files for the next iterations. In fact, this parallel algorithm works because for every block we do not need the current smoothed vertices for the adjacent blocks but only the old ones. However after first iteration we will have a lot of files with both the new smoothed model and the previous version; as a consequence we need to remove the old model and prepare the smoothed data for the next smoothing iteration. This is the code for starting this step:

```

⟨ smoothing step 42a ⟩ ≡
    @time smoothBlocks(string(outputDirectory, "MODELS"),
                        imageHeight, imageWidth, imageDepth,
                        imageDx, imageDy, imageDz) ◇

```

Fragment referenced in 27b.

5.4.5 Model creation step

At this point of the pipeline, we have a lot of files containing models for a single block; now we can merge them in a unique obj file. As we will see in Section 10, there are two different algorithms for file merging. The first one use a serial merging and it is better for traditional filesystems. The other one use a parallel algorithm which is better on a distributed filesystem. This is the code for invocation of the step:

```

⟨ final file merge 42b ⟩ ≡
    if parallelMerge
        @time Model2Obj.mergeObjParallel(string(outputDirectory, "MODELS"))
    else
        @time Model2Obj.mergeObj(string(outputDirectory, "MODELS")) ◇

```

Fragment referenced in 27b.

6 GenerateBorderMatrix

This module has the responsibility for the generation of the border matrix operator for models boundary computation.

6.1 Module imports

These are modules needed for this part of the package and the public functions exported

```
< modules import GenerateBorderMatrix 43a > ≡  
    import LARUtils  
    using PyCall  
  
    import JSON  
  
    export computeOriented3Border, writeBorder, getOriented3BorderPath, getBorderMatrix  
  
    @pyimport sys  
    # Search for python modules in package folder  
    unshift!(PyVector(pyimport("sys")["path"]), Pkg.dir("ImagesToLARModel/src"))  
    @pyimport larcc # Importing larcc from local folder  
    ◇
```

Fragment referenced in 84.

We can notice some lines for importing `larcc` python library, which will be used in subsection [6.5](#)

6.2 Get border matrix from file

As we have already seen in previous sections, we need to compute boundaries for every block of the model grid. This can be done using the topological boundary operator from LAR package. However, the resulting matrix depends only on grid sizes; so it could be reused for other models. Consequently first time we need a border operator we compute it and then save it on disk for next conversions. This function does that work searching for a file containing the border and, if it does not exist, calculate and save it:

```
< get Border matrix 43b > ≡  
function getOriented3BorderPath(borderPath, nx, ny, nz)  
    """  
    Try reading 3-border matrix from file. If it fails matrix  
    is computed and saved on disk in JSON format  
  
    borderPath: path of border directory  
    nx, ny, nz: image dimensions  
    """  
  
    filename = string(borderPath, "/border_", nx, "-", ny, "-", nz, ".json")
```

```

    if !isfile(filename)
        border = computeOriented3Border(nx, ny, nz)
        writeBorder(border, filename)
    end
    return filename
end ◇

```

Fragment referenced in 84.

6.3 Write border matrix on file

We have already seen that for performance reasons border operator matrix is saved on file; here we will see code used for this scope. Firstly, we have defined a function `writeBorder`, which takes as parameters a `PyObject` containing a matrix (computed in subsection 6.4) and the output file path. When porting of `larcc` library will be completed, code for conversion of python csr matrix into csc julia matrix will not be necessary.

```

⟨ write Border matrix 44 ⟩ ≡
function writeBorder(boundaryMatrix, outputFile)
    """
    Write 3-border matrix on json file

    boundaryMatrix: matrix to write on file
    outputFile: path of the outputFile
    """

    fullBorder = pycall(boundaryMatrix["toarray"], PyAny)
    cscBorder = sparse(fullBorder)
    row = findn(cscBorder)[1]
    col = findn(cscBorder)[2]
    data = nonzeros(cscBorder)

    matrixObj = MatrixObject(0, 0, row, col, data)

    outfile = open(string(outputFile), "w")
    JSON.print(outfile, matrixObj)
    close(outfile)
end ◇

```

Fragment referenced in 84.

We can see that, in final JSON file, we write an object called `MatrixObject` which has the following definition:

```

⟨ Matrix object for JSON file 45a ⟩ ≡
    type MatrixObject
        ROWCOUNT
        COLCOUNT
        ROW
        COL
        DATA
    end ◇

```

Fragment referenced in 84.

The most important fields of this object are the last three ones; the first two contain all coordinates of the non-zero elements, the last contains all non-zero elements of the sparse matrix. So considering the full matrix V we will have that $S[ROW[k], COL[k]] = V[k]$.

6.4 Compute border matrix

Here we can see code used for computation of the border operator. As we can see, we call the python `larcc` module, from the `LAR` module, which returns a `PyObject` containing a *sparse csr matrix*. In next versions this function will be probably changed and the code for boundary computation will be moved in `LAR2Julia` module (also transforming all `csr` matrix in `csc` matrix) avoiding python calls.

```

⟨ compute border matrix 45b ⟩ ≡
    # Compute the 3-border operator
    function computeOriented3Border(nx, ny, nz)
        """
        Compute the 3-border matrix using a modified
        version of larcc
        """
        V, bases = LARUtils.getBases(nx, ny, nz)
        boundaryMat = larcc.signedCellularBoundary(V, bases)
        return boundaryMat
    end ◇

```

Fragment referenced in 84.

6.5 Transform border matrix

Last function we will see, extracts the `MatrixObject` in Section 6.3 converting it into a common Julia csc sparse matrix

```
< transform border matrix in csc format 46 > ≡  
function getBorderMatrix(borderFilename)  
    """  
    Get the border matrix from json file and convert it in  
    CSC format  
    """  
    # Loading borderMatrix from json file  
    borderData = JSON.parsefile(borderFilename)  
  
    # Converting Any arrays into Int arrays  
    row = Array{Int64, length(borderData["ROW"])}  
    col = Array{Int64, length(borderData["COL"])}  
    data = Array{Int64, length(borderData["DATA"])}  
  
    for i in 1: length(borderData["ROW"])  
        row[i] = borderData["ROW"][i]  
    end  
  
    for i in 1: length(borderData["COL"])  
        col[i] = borderData["COL"][i]  
    end  
  
    for i in 1: length(borderData["DATA"])  
        data[i] = borderData["DATA"][i]  
    end  
    return sparse(row, col, data)  
end ◊
```

Fragment referenced in 84.

7 Lar2Julia

This module contains functions used in LAR library which are converted using Julia syntax. Next versions of the software will contain more and more functions from the original LAR library (which is written in python)

7.1 Module imports

These are modules used for `Lar2Julia` and the public functions

```
< modules import Lar2Julia 47a > ≡  
import JSON  
  
using Logging  
  
export larBoundaryChain, cscChainToCellList, relationshipListToCSC ◇
```

Fragment referenced in 85a.

7.2 Get boundary chain from a model

Now we will observe how to compute the boundary chain of a LAR model given the list of non-empty cells and the boundary operator stored as a csc sparse matrix. This algorithm is very simply: firstly we need to convert the list of cells into a sparse array containing the LAR model. So, the resulting array (which will be called `cscChain`) will contain a one for every `cscChain[i][1] $\forall i \in \text{brcCellList}$` . Next, we just have to compute the product between the two sparse matrices and convert all values of the result into one of these: $\{-1; +1; 0\}$ using function `cscBinFilter`.

```
< get boundary chain 47b > ≡  
function larBoundaryChain(cscBoundaryMat, brcCellList)  
    """  
    Compute boundary chains  
    """  
  
    # Computing boundary chains  
    n = size(cscBoundaryMat)[1]  
    m = size(cscBoundaryMat)[2]  
  
    debug("Boundary matrix size: ", n, "\t", m)  
  
    data = ones{Int64, length(brcCellList)}  
  
    i = Array{Int64, length(brcCellList)}  
    for k in 1:length(brcCellList)  
        i[k] = brcCellList[k] + 1  
    end  
  
    j = ones{Int64, length(brcCellList)}
```



```

debug("cscChain rows length: ", length(i))
debug("cscChain columns length: ", length(j))
debug("cscChain data length: ", length(brcCellList))

debug("rows ", i)
debug("columns ", j)
debug("data ", data)

cscChain = sparse(i, j, data, m, 1)
cscmat = cscBoundaryMat * cscChain
out = cscBinFilter(cscmat)
return out
end

function cscBinFilter(CSCm)
    k = 1
    data = nonzeros(CSCm)
    sgArray = copysign(1, data)

    while k <= nnz(CSCm)
        if data[k] % 2 == 1 || data[k] % 2 == -1
            data[k] = 1 * sgArray[k]
        else
            data[k] = 0
        end
        k += 1
    end

    return CSCm
end
◇

```

Fragment referenced in 85a.

7.3 Get oriented cells from a chain

Another operation that could be useful (even if it is not actually used in the package) consists in getting of “+1” oriented cells from a chain. For obtaining this result, it is necessary to get all non-zeros element from the sparse Julia array (remembering that if the user manually write a zero into the array it will be returned from **nonzeros** function anyway) and then returning only indices of cells that have a “+1” in nonzero element array.

$\langle \text{get oriented cells from a chain } 48 \rangle \equiv$

```

function cscChainToCellList(CSCm)
    """
    Get a csc containing a chain and returns
    the cell list of the "+1" oriented faces
    """
    data = nonzeros(CSCm)
    # Now I need to remove zero element (problem with Julia nonzeros)
    nonzeroData = Array{Int64, 0}
    for n in data
        if n != 0
            push!(nonzeroData, n)
        end
    end

    cellList = Array{Int64, 0}
    for (k, theRow) in enumerate(findn(CSCm)[1])
        if nonzeroData[k] == 1
            push!(cellList, theRow)
        end
    end
    return cellList
end

```

Fragment referenced in 85a.

7.4 Transform relationships from arrays of arrays to a sparse matrix

Another function which can be useful for our purposes is conversion between different representations of the LAR relationships. For example we often use a representation based on list of list of int but if we want to apply topological operators (such as the incident operators) we need to convert it into a matrix of values. In Figure 13 we can see an example of a LAR relationship with different representations.

```

⟨ transform relationships to csc 49 ⟩ ≡
function relationshipListToCSC(larRelation)
    """
    Get a LAR relationship
    and convert it into a CSC matrix
    """

    # Build I and J arrays for creation of
    # sparse matrix
    data = Array{Int, 0}

```




Figure 13: Different representations for faces of a simple LAR model. the first one is based on a list of list of int, while the other is a simple matrix where for every value we have $FV[i][j] = 1 \iff \text{face } i \text{ contains the vertex } j$

```

I = Array(Int, 0)
J = Array(Int, 0)
for (k,row) in enumerate(larRelation)
  for col in row
    push!(I, k)
    push!(J, col)
    push!(data, 1)
  end
end

return sparse(I, J, data)
end ◇

```

Fragment referenced in 85a.

8 LARUtils

This module contains functions used for manipulation of LAR models

8.1 Module imports

These are modules used in `LARUtils` and the functions exported

$\langle \text{modules import LARUtils } 50 \rangle \equiv$

```

using Logging

export ind, invertIndex, getBases, removeDoubleVerticesAndFaces,
      computeModelAndBoundaries
◇

```

Fragment referenced in 85b.

8.2 Transformation from matrix to array

First utility functions we will see, transform a matrix into an array and vice versa. We have already seen in section 5.4.1 uses of this linearized matrices; now we can focus on code for transformation.

```

⟨ conversion from matrix to array 51a ⟩ ≡
function ind(x, y, z, nx, ny)
    """
        Transform coordinates into linearized matrix indexes
    """
    return x + (nx + 1) * (y + (ny + 1) * (z))
end ◇

```

Fragment referenced in 85b.

Here we have defined also the inverse transformation from the array to the matrix, which is useful for obtaining vertices coordinates from a cell

```

⟨ conversion from array to matrix 51b ⟩ ≡
function invertIndex(nx,ny,nz)
    """
        Invert indexes
    """
    nx, ny, nz = nx + 1, ny + 1, nz + 1
    function invertIndex0(offset)
        a0, b0 = trunc(offset / nx), offset % nx
        a1, b1 = trunc(a0 / ny), a0 % ny
        a2, b2 = trunc(a1 / nz), a1 % nz
        return b0, b1, b2
    end
    return invertIndex0
end ◇

```

Fragment referenced in 85b.

8.3 Get bases of a LAR model

For generation of LAR models from an array of non-empty cells, we need to define a function for obtaining a base for every model, which will contain all LAR relationships:

- **V**: the array of vertices of a LAR model
- **VV**: the relationship between a vertex and itself
- **EV**: the relationship between an edge and its vertices
- **FV**: the relationship between a face and its vertices
- **CV**: the relationship between a cell and its vertices

From a geometrical point of view these bases create a chain composed from $nx \times ny \times nz$ square cells (where nx ny and nz are the grid size).




Figure 14: LAR bases geometry for a $2 \times 2 \times 2$ grid

Now we will see in details how to obtain all LAR relationships.
First of all we need to compute vertices for the geometry:

```
< compute vertices 52 >  $\equiv$   
  # Calculating vertex coordinates (nx * ny * nz)  
  V = Array{Int64}[]  
  for z in 0:nz  
    for y in 0:ny  
      for x in 0:nx  
        push!(V, [x,y,z])  
      end  
    end  
  end  
end  $\diamond$ 
```

Fragment referenced in 55.

So we assume that our cube geometry has only integers coordinates that can vary from (0,0,0) to (nx,ny,nz)

Next we have to compute the CV relationship:

```
 $\langle \text{compute CV 53a} \rangle \equiv$   
  # Building CV relationship  
  CV = Array{Int64}[]  
  for z in 0:nz-1  
    for y in 0:ny-1  
      for x in 0:nx-1  
        push!(CV,the3Dcell([x,y,z]))  
      end  
    end  
  end  $\diamond$ 
```

Fragment referenced in 55.

For every coordinate in the space delimited by the grid size, it is called function `the3Dcell`, which get the coordinate values returning a cell in the three-dimensional space:

```
 $\langle \text{compute three-dimensional cells 53b} \rangle \equiv$   
  function the3Dcell(coords)  
    x,y,z = coords  
    return [ind(x,y,z,nx,ny), ind(x+1,y,z,nx,ny), ind(x,y+1,z,nx,ny),  
            ind(x,y,z+1,nx,ny), ind(x+1,y+1,z,nx,ny), ind(x+1,y,z+1,nx,ny),  
            ind(x,y+1,z+1,nx,ny), ind(x+1,y+1,z+1,nx,ny)]  
  end  
   $\diamond$ 
```

Fragment referenced in 55.

Now we have to compute the FV relationship, which will be widely used in this package:

```
 $\langle \text{compute FV 53c} \rangle \equiv$ 
```

```

# Building FV relationship
FV = Array{Int64}[]
v2coords = invertIndex(nx,ny,nz)

for h in 0:(length(V)-1)
    x,y,z = v2coords(h)

    if (x < nx) && (y < ny)
        push!(FV, [h,ind(x+1,y,z,nx,ny),ind(x,y+1,z,nx,ny),ind(x+1,y+1,z,nx,ny)])
    end

    if (x < nx) && (z < nz)
        push!(FV, [h,ind(x+1,y,z,nx,ny),ind(x,y,z+1,nx,ny),ind(x+1,y,z+1,nx,ny)])
    end

    if (y < ny) && (z < nz)
        push!(FV, [h,ind(x,y+1,z,nx,ny),ind(x,y,z+1,nx,ny),ind(x,y+1,z+1,nx,ny)])
    end

end ◇

```

Fragment referenced in 55.

Finally we have the VV relationship (which is trivial)

```

⟨ compute VV 54a ⟩ ≡
    # Building VV relationship
    VV = map((x)->[x], 0:length(V)-1) ◇

```

Fragment referenced in 55.

and the EV relationship

```

⟨ compute EV 54b ⟩ ≡
    # Building EV relationship
    EV = Array{Int64}[]
    for h in 0:length(V)-1
        x,y,z = v2coords(h)
        if (x < nx)
            push!(EV, [h,ind(x+1,y,z,nx,ny)])
        end
        if (y < ny)

```

```

        push!(EV, [h,ind(x,y+1,z,nx,ny)])
    end
    if (z < nz)
        push!(EV, [h,ind(x,y,z+1,nx,ny)])
    end
end ◇

```

Fragment referenced in 55.

This is the complete code for the function `getBases`

```

⟨ get LAR bases 55 ⟩ ≡
function getBases(nx, ny, nz)
    """
    Compute all LAR relations
    """

    ⟨ compute three-dimensional cells 53b ⟩

    ⟨ compute vertices 52 ⟩

    ⟨ compute CV 53a ⟩

    ⟨ compute FV 53c ⟩

    ⟨ compute VV 54a ⟩

    ⟨ compute EV 54b ⟩

    # return all basis
    return V, (VV, EV, FV, CV)
end ◇

```

Fragment referenced in 85b.

8.4 Double vertices and faces removal

Another useful function for our models is *removal of double vertices and faces*. In fact, when we produce a LAR model getting only full cell from the geometry in Figure 14 we could obtain double vertices (and consequently double faces). Figure 15 shows an example of a model with these vertices:




Figure 15: A sample model taken from a $2 \times 2 \times 2$ grid with double vertices between faces in red (remember that we have only the boundaries faces for the model as we have seen in section 5.4.1)

As we can see, for every model there are a lot of double vertices, so we need to remove them for obtaining a compact representation and for next smoothing of the objects. First of all we have to identify double vertices, so it can be useful to define an order between them. Unfortunately Julia does not define a function for order array containing coordinates (which is format used in V array); so we have to define first a custom ordering function:

```

⟨ vertices comparator function 56a ⟩ ≡
    function lessThanVertices(v1, v2)
        """
        Utility function for comparing vertices coordinates
        """

        if v1[1] == v2[1]
            if v1[2] == v2[2]
                return v1[3] < v2[3]
            end
            return v1[2] < v2[2]
        end
        return v1[1] < v2[1]
    end ◇

```

Fragment referenced in 58b.

Now we can remove double vertices from the V array simply ordering them and removing all consecutive equal vertices. This procedure is more complex than a simple call to Julia `unique` function for removal of double elements because we need the new vertices indices for renaming faces (as we can see later)

```

⟨ removal of double vertices 56b ⟩ ≡

```

```

function removeDoubleVertices(V)
    """
    Remove double vertices from a LAR model

    V: Array containing all vertices of the model
    """

    # Sort the vertices list and returns the ordered indices
    orderedIndices = sortperm(V, lt = lessThanVertices, alg=MergeSort)

    orderedVerticesAndIndices = collect(zip(sort(V, lt = lessThanVertices),
                                             orderedIndices))

    newVertices = Array{Array{Float64}, 0}()
    indices = zeros{Int, length(V)}
    prevv = Void
    i = 1
    for (v, ind) in orderedVerticesAndIndices
        if v == prevv
            indices[ind] = i - 1
        else
            push!(newVertices, v)
            indices[ind] = i
            i += 1
            prevv = v
        end
    end
    return newVertices, indices
end ◇

```

Fragment referenced in 58b.

As we can see the algorithm does the following steps:

1. Sort of vertices list
2. Set the current vertex index counter to 1
3. For every couple (*vertex*, *index* into V array) do:
 - (a) If the current *vertex* is equal to the previous one put into the indices array at position *index* the value for the current vertex index count
 - (b) If the current *vertex* is not equal to the previous one save it into a new V array, insert the indices array at position *index* the current index count and increment it by one

So at the end of this function the array *newVertices* will contain all unique vertices, while the *indices* array will contain the correct index for every vertex into *newVertices* and the index corresponding to the saved vertex for every deleted vertex.

Now we can use these informations for renaming all faces.

⟨renaming of faces 58a⟩ \equiv

```
function reindexVerticesInFaces(FV, indices, offset)
    """
    Reindex vertices indices in faces array

    FV: Faces array of the LAR model
    indices: new Indices for faces
    offset: offset for faces indices
    """

    for f in FV
        for i in 1: length(f)
            f[i] = indices[f[i] - offset] + offset
        end
    end
    return FV
end  $\diamond$ 
```

Fragment referenced in 58b.

Here we can observe a *offset* parameter, which is necessary only if we are renaming faces whose indices doesn't start from zero; actually in *ImagesToLARModel* it is always equal to zero.

Finally for removing double faces, we only have to call *unique* function on renamed faces. This is the final code

⟨removal of double vertices and faces 58b⟩ \equiv

⟨vertices comparator function 56a⟩

```
function removeDoubleVerticesAndFaces(V, FV, facesOffset)
    """
    Removes double vertices and faces from a LAR model

    V: Array containing all vertices
    FV: Array containing all faces
    facesOffset: offset for faces indices
    """
```

```

"""

newV, indices = removeDoubleVertices(V)
reindexedFaces = reindexVerticesInFaces(FV, indices, facesOffset)
newFV = unique(FV)

return newV, newFV

end

⟨removal of double vertices 56b⟩

⟨renaming of faces 58a⟩ ◇

```

Fragment referenced in 85b.

8.5 Creation of a LAR model

Now we can see code used for creation of a LAR model given the sparse array containing full cells of our block (**objectBoundaryChain** as we had seen in Section 7.2). We also need the following parameters:

- **imageDx, imageDy, imageDz**: The grid size
- **xStart, yStart, zStart**: The coordinate offsets for the current block vertices
- **facesOffset**: The offset for faces of this block

First thing to do is define models that will be returned from the function:

```

⟨models definition 59⟩ ≡
V_model = Array(Array{Int}, 0)
FV_model = Array(Array{Int}, 0)

V_left = Array(Array{Int},0)
FV_left = Array(Array{Int},0)

V_right = Array(Array{Int},0)
FV_right = Array(Array{Int},0)

V_top = Array(Array{Int},0)
FV_top = Array(Array{Int},0)

V_bottom = Array(Array{Int},0)

```

```

FV_bottom = Array(Array{Int},0)

V_front = Array(Array{Int},0)
FV_front = Array(Array{Int},0)

V_back = Array(Array{Int},0)
FV_back = Array(Array{Int},0) ◇

```

Fragment referenced in 63b.

We can see from Figure 16 that our grid is divided into seven parts.




Figure 16: Decomposition of a LAR model into seven parts: the inside model (brown), the left boundary (green), the right boundary (light blue), the top boundary (purple), the bottom boundary (light green), the front boundary (blue), the back boundary (red)

We need this decomposition because we are interested in boundaries of the entire model, while we currently have boundaries only for blocks. So we need to split the inner parts of a single block model, as we need to freely merge boundaries between adjacent blocks removing the common faces. Function for boundaries merging are shown in subsection 8.6.

After model definition we have to get the cells indices from the block boundary chain and for every non-empty cell we have found, choose the correct model for it. We can observe that every boundary face has a fixed coordinate; for example all faces on the top boundary have the maximum z-coordinate, or faces on right boundary have the maximum y-coordinate (as shown in Figure 17)

So we can define a series of functions for checking the membership of a given face to a boundary exploiting these fixed coordinates:

⟨ check membership of a face to a boundary 60 ⟩ ≡




Figure 17: Boundaries coordinates for top and right boundaries of a $2 \times 2 \times 2$ grid. We can observe that every boundary has a fixed coordinate

```
function isOnLeft(face, V, nx, ny, nz)
    """
    Check if face is on left boundary
    """

    for(vtx in face)
        if(V[vtx + 1][2] != 0)
            return false
        end
    end
    return true

end

function isOnRight(face, V, nx, ny, nz)
    """
    Check if face is on right boundary
    """

    for(vtx in face)
        if(V[vtx + 1][2] != ny)
            return false
        end
    end
    return true

end

function isOnTop(face, V, nx, ny, nz)
```

```

"""
Check if face is on top boundary
"""

for(vtx in face)
  if(V[vtx + 1][3] != nz)
    return false
  end
end
return true
end

function isOnBottom(face, V, nx, ny, nz)
"""
Check if face is on bottom boundary
"""

for(vtx in face)
  if(V[vtx + 1][3] != 0)
    return false
  end
end
return true
end

function isOnFront(face, V, nx, ny, nz)
"""
Check if face is on front boundary
"""

for(vtx in face)
  if(V[vtx + 1][1] != nx)
    return false
  end
end
return true
end

function isOnBack(face, V, nx, ny, nz)
"""
Check if face is on back boundary
"""

for(vtx in face)
  if(V[vtx + 1][1] != 0)
    return false
  end
end
return true
end

```

```

        end
    end
    return true
end ◇

```

Fragment referenced in 63b.

After choosing of the right model, we have to insert our face into it. We can do it with the following function, which takes vertices and faces of the base and the model, the face, and the offset of the current face for the model chosen:

```

⟨ add a face to a model 63a ⟩ ≡
function addFaceToModel(V_base, FV_base, V, FV, face, vertex_count)
    """
    Insert a face into a LAR model

    V_base, FV_base: LAR model of the base
    V, FV: LAR model
    face: Face that will be added to the model
    vertex_count: Indices for faces vertices
    """

    new_vertex_count = vertex_count
    for vtx in FV_base[face]
        push!(V, [convert(Int, V_base[vtx + 1][1] + xStart),
                  convert(Int, V_base[vtx + 1][2] + yStart),
                  convert(Int, V_base[vtx + 1][3] + zStart)])
        new_vertex_count += 1
    end
    push!(FV, [vertex_count, vertex_count + 1, vertex_count + 3])
    push!(FV, [vertex_count, vertex_count + 3, vertex_count + 2])

    return new_vertex_count
end ◇

```

Fragment referenced in 63b.

As we can see, for every face we put into the model FV array two faces, in fact our final representation is not based on square faces but on triangular faces.

This is the complete code for creation of a model

```

⟨ LAR model creation 63b ⟩ ≡

```





Figure 18: Triangulation of a single face

⟨ check membership of a face to a boundary 60 ⟩

```
function computeModelAndBoundaries(imageDx, imageDy, imageDz,
                                   xStart, yStart, zStart,
                                   objectBoundaryChain)
    """
    Takes the boundary chain of a part of the entire model
    and returns a LAR model splitting the boundaries

    imageDx, imageDy, imageDz: Boundary dimensions
    xStart, yStart, zStart: Offset of this part of the model
    objectBoundaryChain: Sparse csc matrix containing the cells
    """
```

⟨ add a face to a model 63a ⟩

⟨ models definition 59 ⟩

```
V, bases = getBases(imageDx, imageDy, imageDz)
FV = bases[3]

vertex_count_model = 1
vertex_count_left = 1
vertex_count_right = 1
vertex_count_top = 1
vertex_count_bottom = 1
vertex_count_front = 1
vertex_count_back = 1

# Get all cells (independently from orientation)
b2cells = findn(objectBoundaryChain)[1]

debug("b2cells = ", b2cells)

for f in b2cells
    old_vertex_count_model = vertex_count_model
```

```

old_vertex_count_left = vertex_count_left
old_vertex_count_right = vertex_count_right
old_vertex_count_top = vertex_count_top
old_vertex_count_bottom = vertex_count_bottom
old_vertex_count_front = vertex_count_front
old_vertex_count_back = vertex_count_back

# Choosing the right model for vertex
if(isOnLeft(FV[f], V, imageDx, imageDy, imageDz))
    vertex_count_left = addFaceToModel(V, FV, V_left, FV_left,
                                        f, old_vertex_count_left)
elseif(isOnRight(FV[f], V, imageDx, imageDy, imageDz))
    vertex_count_right = addFaceToModel(V, FV, V_right, FV_right,
                                        f, old_vertex_count_right)
elseif(isOnTop(FV[f], V, imageDx, imageDy, imageDz))
    vertex_count_top = addFaceToModel(V, FV, V_top, FV_top,
                                        f, old_vertex_count_top)
elseif(isOnBottom(FV[f], V, imageDx, imageDy, imageDz))
    vertex_count_bottom = addFaceToModel(V, FV, V_bottom, FV_bottom,
                                        f, old_vertex_count_bottom)
elseif(isOnFront(FV[f], V, imageDx, imageDy, imageDz))
    vertex_count_front = addFaceToModel(V, FV, V_front, FV_front,
                                        f, old_vertex_count_front)
elseif(isOnBack(FV[f], V, imageDx, imageDy, imageDz))
    vertex_count_back = addFaceToModel(V, FV, V_back, FV_back,
                                        f, old_vertex_count_back)
else
    vertex_count_model = addFaceToModel(V, FV, V_model, FV_model,
                                        f, old_vertex_count_model)
end

end

# Removing double vertices
return [removeDoubleVerticesAndFaces(V_model, FV_model, 0)],
[removeDoubleVerticesAndFaces(V_left, FV_left, 0)],
[removeDoubleVerticesAndFaces(V_right, FV_right, 0)],
[removeDoubleVerticesAndFaces(V_top, FV_top, 0)],
[removeDoubleVerticesAndFaces(V_bottom, FV_bottom, 0)],
[removeDoubleVerticesAndFaces(V_front, FV_front, 0)],
[removeDoubleVerticesAndFaces(V_back, FV_back, 0)]
end ◇

```

Fragment referenced in 85b.



Figure 19: Creation of a sample model. (a) The original image (b) The three-dimensional model (c) The three-dimensional model (detail with triangular faces)

8.6 Removing double faces and vertices from boundaries

In previous section, we have seen how to create a LAR model from the chain list. However this model contains all borders between blocks, while we are only interested in borders for the entire image. So, we will see functions for boundaries merging with removal of double faces and vertices from both sides.




Figure 20: Removal of double faces from boundaries. (a) Two adjacent blocks (b) The same blocks exploded on x axis (c) Result of the removal on the exploded blocks

The algorithm for the removal is very simply. First of all we need to remove double vertices from models in the usual way using `removeDoubleVertices` function and re-indexing all faces. Next we count all elements in re-indexed faces array removing elements with more than one occurrence and create an array of faces with an explicit representation of vertices (*FV_vertices*). Now we can safely remove double vertices on the other side of the boundary without losing the correct indexing in the faces. Finally we can create the final faces array with only remaining vertices comparing coordinates in *FV_vertices* with the ones in the last vertices array.

Code for this function is the following:




Figure 21: Same as Figure 20 with another model

```

⟨ Removal of double vertices and faces from boundaries 67 ⟩ ≡
function removeVerticesAndFacesFromBoundaries(V, FV)
  """
  Remove vertices and faces duplicates on
  boundaries models

  V,FV: lar model of two merged boundaries
  """

  newV, indices = removeDoubleVertices(V)
  uniqueIndices = unique(indices)

  # Removing double faces on both boundaries
  FV_reindexed = reindexVerticesInFaces(FV, indices, 0)
  FV_unique = unique(FV_reindexed)

  FV_cleaned = Array{Array{Int}, 0}
  for f in FV_unique
    if(count((x) -> x == f, FV_reindexed) == 1)
      push!(FV_cleaned, f)
    end
  end

  # Creating an array of faces with explicit vertices
  FV_vertices = Array{Array{Array{Float64}}, 0}

  for i in 1 : length(FV_cleaned)
    push!(FV_vertices, Array{Array{Float64}, 0})
    for vtx in FV_cleaned[i]
      push!(FV_vertices[i], newV[vtx])
    end
  end
end

```

```

V_final = Array(Array{Float64}, 0)
FV_final = Array(Array{Int}, 0)

# Saving only used vertices
for face in FV_vertices
    for vtx in face
        push!(V_final, vtx)
    end
end

V_final = unique(V_final)

# Renumbering FV
for face in FV_vertices
    tmp = Array{Int, 0}
    for vtx in face
        ind = findfirst(V_final, vtx)
        push!(tmp, ind)
    end
    push!(FV_final, tmp)
end

return V_final, FV_final
end ◇

```

Fragment referenced in 85b.

9 Smoother

This module contains functions used for smoothing LAR models

9.1 Get adjacent vertices

As we will see in next subsection, for executing a smoothing algorithm we need to know adjacent vertices to a given one. So we need a *VV relationship*, where for every vertex index i , we have a list of adjacent vertices.

Algorithm is very simple and exploit the following property: *for triangular faces all vertices are linked together*. So we just need to search for every vertex i all faces that contain it and add all their vertices to a list. *VV* will contain a concatenation of all these lists

$\langle \text{get adjacent vertices } 68 \rangle \equiv$




Figure 22: *VV relationship* for a simple model

```
function adjVerts(V, FV)
    """
    Compute the adjacency graph of vertices
    of a LAR model

    V, FV: LAR model

    Returns the list of indices of vertices adjacent
    to a vertex
    """
    VV = Array{Int}[]
    for i in 1:length(V)
        row = Array{Int, 0}
        for face in FV
            if i in face
                for v in face
                    push!(row, v)
                end
            end
        end
        if length(row) == 0
            push!(row, i)
        end
        push!(VV, collect(unique(row)))
    end
    return VV
end ◇
```

Fragment referenced in 87a.

9.2 Laplacian smoothing

There are many different algorithms for mesh smoothing. The simpler and the one we used in this library is **laplacian smoothing**. For each vertex in a mesh, a new position is chosen according to local information (such as the coordinates of neighbors) and the vertex is moved there. If that mesh is topologically a rectangular grid (so each internal vertex is connected to four neighbors) then this operation produces the *Laplacian* of the mesh.




Figure 23: Laplacian smoothing (picture taken from the *Geometry Processing Algorithms* course at Stanford University)

As we can see from Figure 23, with substitution of every vertex position with the mean of the neighbors positions, we can obtain a curve with smoothed edges. This procedure can be repeated many times, so we can obtain a smoother model. For example, in Figure 25, we can see this algorithm applied on a sample mesh with three iterations.




Figure 24: Laplacian smoothing for a sample mesh. (a) Original mesh (b) Mesh after three iterations of the smoothing algorithm (picture taken from a *Digital Geometry Processing* course at IMPA)

This is the code for the smoothing function; it takes a single LAR model and returns the smoothed model.

$\langle \text{laplacian smoothing } 70 \rangle \equiv$

```

function smoothModel(V, FV)
  """
  Execute a Laplacian smoothing on a LAR model returning
  the new smoothed model

  V, FV: LAR model
  """

  VV = adjVerts(V, FV)
  newV = Array(Array{Float64},0)
  V_temp = Array(Array{Float64},0)

  for i in 1:length(VV)
    adjs = VV[i]
    # Get all coordinates for adjacent vertices
    coords = Array(Array{Float64}, 0)
    for v in adjs
      push!(coords, V[v])
    end

    # Computing sum of all vectors
    sum = [0.0, 0.0, 0.0]
    for v in coords
      sum += v
    end

    # Computing convex combination of vertices
    push!(newV, sum/length(adjs))

  end

  return newV, FV
end ◇

```

Fragment referenced in 87a.

10 Model2Obj

This module contains functions used for reading/writing LAR models into obj files on disk




Figure 25: Smoothing of a sample model made with ImagesToLARModel

10.1 Writing models to file

Up to now we have seen how to manipulate LAR models obtaining a three-dimensional representation for our stack of images. However we have not seen how to visualize them using external software yet. We have chosen the *wavefront obj file format* for external visualization, which is very simple and common. The syntax used is the following:

- All vertices are described with their coordinates and written on a single row according to the following syntax: `v xCoord yCoord zCoord`
- All faces are described with their vertex index (calculated from their row) according to the following syntax: `f vertex1 vertex2 ...vertexn`

In Figure 26 there is an example of an obj file




Figure 26: Obj sample file

We can see that this kind of representation is very similar to the LAR representation schema, so we just have to read every element of V and FV arrays and write them on disk.

Because of we will use these informations a lot, it is more convenient to save the vertices and the faces on different files, so they can be loaded with less efforts. This is code used by the library:

```

< write obj files 73 > ≡
function writeToObj(V, FV, outputFilename)
    """
    Take a LAR model and write it on obj file

    V: array containing vertices coordinates
    FV: array containing faces
    outputFilename: prefix for the output files
    """

    if (length(V) != 0)
        outputVtx = string(outputFilename, "_vtx.stl")
        outputFaces = string(outputFilename, "_faces.stl")

        fileVertex = open(outputVtx, "w")
        fileFaces = open(outputFaces, "w")

        for v in V
            write(fileVertex, "v ")
            write(fileVertex, string(v[1], " "))
            write(fileVertex, string(v[2], " "))
            write(fileVertex, string(v[3], "\n"))
        end

        for f in FV

            write(fileFaces, "f ")
            write(fileFaces, string(f[1], " "))
            write(fileFaces, string(f[2], " "))
            write(fileFaces, string(f[3], "\n"))
        end

        close(fileVertex)
        close(fileFaces)

    end

end ◇

```

Fragment referenced in 85c.

10.2 Merging block models

Now we have seen how to write on disk a LAR model using the *wavefront obj file format*, however, as we have already seen, we have a lot of models from every block; so we need a function for the creation of the final merged model. The code which executes this task is very simple; this is the function:

```
< serial file merge 74 > ≡  
function mergeObj(modelDirectory)  
  ""  
  Merge stl files in a single obj file  
  
  modelDirectory: directory containing models  
  ""  
  
  files = readdir(modelDirectory)  
  vertices_files = files[find(s -> contains(s, string("_vtx.stl")), files)]  
  faces_files = files[find(s -> contains(s, string("_faces.stl")), files)]  
  obj_file = open(string(modelDirectory, "/", "model.obj"), "w") # Output file  
  
  vertices_counts = Array{Int64, length(vertices_files)}  
  number_of_vertices = 0  
  for i in 1:length(vertices_files)  
    vtx_file = vertices_files[i]  
    f = open(string(modelDirectory, "/", vtx_file))  
  
    # Writing vertices on the obj file  
    for ln in eachline(f)  
      splitted = split(ln)  
      write(obj_file, "v ")  
      write(obj_file, string(convert{Int, round(parse(splitted[2]) * 10)}, " "))  
      write(obj_file, string(convert{Int, round(parse(splitted[3]) * 10)}, " "))  
      write(obj_file, string(convert{Int, round(parse(splitted[4]) * 10)}, "\n"))  
      number_of_vertices += 1  
    end  
    # Saving number of vertices  
    vertices_counts[i] = number_of_vertices  
    close(f)  
  end  
  
  for i in 1 : length(faces_files)  
    faces_file = faces_files[i]  
    f = open(string(modelDirectory, "/", faces_file))  
    for ln in eachline(f)  
      splitted = split(ln)  
      write(obj_file, "f ")
```

```

        if i > 1
            write(obj_file, string(parse(splitted[2]) + vertices_counts[i - 1], " "))
            write(obj_file, string(parse(splitted[3]) + vertices_counts[i - 1], " "))
            write(obj_file, string(parse(splitted[4]) + vertices_counts[i - 1]))
        else
            write(obj_file, string(splitted[2], " "))
            write(obj_file, string(splitted[3], " "))
            write(obj_file, splitted[4])
        end
        write(obj_file, "\n")
    end
    close(f)
end
close(obj_file)

# Removing all tmp files
for vtx_file in vertices_files
    rm(string(modelDirectory, "/", vtx_file))
end

for fcs_file in faces_files
    rm(string(modelDirectory, "/", fcs_file))
end

end ◇

```

Fragment referenced in 85c.

As we can see, we take all files contained into the model folder (distinguishing between files containing vertices from those containing faces) and write all their lines into the final model file. However this is simply for vertices files, while it is a bit complicated for faces, because it is necessary to change their indexes according to the current vertices positions into the file. So we need to memorize the offset for every file counting the number of vertices added at every time we open a new file containing vertices. Moreover we can see that we convert vertices coordinates into integer values; this is useful because some softwares do not read float vertices coordinates, so we first make the model ten times bigger (so we still have the first decimal number) and then round it.

The creation of this final model is quite slow, so we can try to speedup the entire software parallelizing it. In the next part we will see how this can be done.

10.2.1 Parallel merging of obj files

Now we will see how to parallelize the final file merging. However this is useful only for certain conditions; in fact in traditional filesystems the disk can be accessed from only one process at the same time, so parallelizing this task is totally useless. However for parallel filesystems it is a different matter because we can have parallel writes on storage.

The first simple algorithm we can think for parallel file merging, takes two files for every process and merge them creating a unique file. Then, this process can be repeated until we have only one final file. In Figure 27 there is a simple schema for this algorithm.




Figure 27: The first parallel algorithm for file merge. Black circles represent the original files, while circles with the cross, represent merged files

How we can see in that figure, if we have a process for every merge operation and sixteen files, we will have eight processes for the first merge, four processes for the second merge steps, two processes for the third step and one process for the final merge. Speaking in a general way, told n the number of files we want to merge, we will use $\lfloor n/2 \rfloor$ processes for every step. Probably if we would not have a balanced tree we could use the number of processes in a more efficient way for all our steps. In Figure 28 there is a non-balanced tree where the number of processes for every merge step is maximized.




Figure 28: A better algorithm for file merge

Now we can examine the code used for obtaining this result. First of all we need a function for assigning files to the right process creating the tree in Figure 28:

```

< assign tasks 77a > ≡
function assignTasks(startInd, endInd, taskArray)
    """
    This function choose the first files to merge
    creating a tree where number of processes is maximized

    startInd: starting index for array subdivision
    endInd: end index for array subdivision
    taskArray: array containing indices of files to merge for first
    """
    if (endInd - startInd == 2)
        push!(taskArray, startInd)
    elseif (endInd - startInd < 2)
        if (endInd % 4 != 0 && startInd != endInd)
            # Stop recursion on this branch
            push!(taskArray, startInd)
        end
        # Stop recursion doing nothing
    else
        assignTasks(startInd, startInd + trunc((endInd - startInd) / 2), taskArray)
        assignTasks(startInd + trunc((endInd - startInd) / 2) + 1, endInd, taskArray)
    end
end ◇

```

Fragment referenced in 85c.

Now we need some functions for merging files; in particular we have to merge vertices files (contemporary counting the offsets for the faces) and faces files. This is the code for the first function:

```

< merge vertices file 77b > ≡
function mergeVerticesFiles(file1, file2, startOffset)
    """
    Support function for merging two vertices files.
    Returns the number of vertices of the merged file

    file1: path of the first file
    file2: path of the second file
    startOffset: starting face offset for second file
    """

    f1 = open(file1, "a")

    f2 = open(file2)

```

```

debug("Merging ", file2)
number_of_vertices = startOffset
for ln in eachline(f2)
    write(f1, ln)
    number_of_vertices += 1
end
close(f2)

close(f1)

return number_of_vertices
end ◇

```

Fragment referenced in 85c.

As we can see the algorithm is very simple; what we do is appending the content of the second file into the first one and returns the number of appended vertices, which will be used as offsets for faces. This is the code for concatenation of faces files:

```

⟨ merge faces file 78 ⟩ ≡
function mergeFacesFiles(file1, file2, facesOffset)
    """
    Support function for merging two faces files

    file1: path of the first file
    file2: path of the second file
    facesOffset: offset for faces
    """

    f1 = open(file1, "a")

    f2 = open(file2)
    for ln in eachline(f2)
        splitted = split(ln)
        write(f1, "f ")
        write(f1, string(parse(splitted[2]) + facesOffset, " "))
        write(f1, string(parse(splitted[3]) + facesOffset, " "))
        write(f1, string(parse(splitted[4]) + facesOffset, "\n"))
    end
    close(f2)

    close(f1)
end ◇

```

Fragment referenced in 85c.

These concatenation functions, are called by the `mergeObjProcesses`, which is executed by a single Julia process:

⟨parallel merge obj process function 79⟩ \equiv

```
function mergeObjProcesses(fileArray, facesOffset = Nothing)
    """
    Merge files on a single process

    fileArray: Array containing files that will be merged
    facesOffset (optional): if merging faces files, this array contains
        offsets for every file

    if it is merging vertices files it returns the offset
    for the corresponding faces
    """

    if(contains(fileArray[1], string("_vtx.stl")))
        # Merging vertices files
        offsets = Array{Int, 1}(0)
        push!(offsets, countlines(fileArray[1]))
        vertices_count = mergeVerticesFiles(fileArray[1], fileArray[2], countlines(fileArray[1]))
        rm(fileArray[2]) # Removing merged file
        push!(offsets, vertices_count)
        for i in 3 : length(fileArray)
            vertices_count = mergeVerticesFiles(fileArray[1], fileArray[i], vertices_count)
            rm(fileArray[i]) # Removing merged file
            push!(offsets, vertices_count)
        end
        return offsets
    else
        # Merging faces files
        mergeFacesFiles(fileArray[1], fileArray[2], facesOffset[1])
        rm(fileArray[2]) # Removing merged file
        for i in 3 : length(fileArray)
            mergeFacesFiles(fileArray[1], fileArray[i], facesOffset[i - 1])
            rm(fileArray[i]) # Removing merged file
        end
    end
end
end ◇
```

Fragment referenced in 85c.

The function can be called for both faces and vertices files; for the last case, however, we need to specify the *facesOffset* parameter.

Now we can put together the above functions with the following code:

```

⟨ merge obj helper function 80 ⟩ ≡
function mergeObjHelper(vertices_files, faces_files)
  """
    Support function for mergeObj. It takes vertices and faces files
    and executes a single merging step

    vertices_files: Array containing vertices files
    faces_files: Array containing faces files
  """
  numberOfImages = length(vertices_files)
  taskArray = Array{Int, 0}()
  assignTasks(1, numberOfImages, taskArray)

  # Now taskArray contains first files to merge
  numberOfVertices = Array{Int, 0}()
  tasks = Array{RemoteRef, 0}()
  for i in 1 : length(taskArray) - 1
    task = @spawn mergeObjProcesses(vertices_files[taskArray[i] : (taskArray[i + 1] - 1)])
    push!(tasks, task)
  end

  # Merging last vertices files
  task = @spawn mergeObjProcesses(vertices_files[taskArray[length(taskArray)] : end])
  push!(tasks, task)

  for task in tasks
    append!(numberOfVertices, fetch(task))
  end

  debug("NumberOfVertices = ", numberOfVertices)

  # Merging faces files
  tasks = Array{RemoteRef, 0}()
  for i in 1 : length(taskArray) - 1

    task = @spawn mergeObjProcesses(faces_files[taskArray[i] : (taskArray[i + 1] - 1)],
                                   numberOfVertices[taskArray[i] : (taskArray[i + 1] - 1)])
    push!(tasks, task)
  end

  #Merging last faces files
  task = @spawn mergeObjProcesses(faces_files[taskArray[length(taskArray)] : end],

```

```

                                numberOfVertices[taskArray[length(taskArray)] : end])

    push!(tasks, task)

    for task in tasks
        wait(task)
    end

end ◇

```

Fragment referenced in 85c.

As we can see, this is the code for distribution of our work among all processes. We have chosen to spawn a new process following the tree in Figure 28, passing to the `mergeObjProcesses` function the files given to the task with the function `assignTasks`.

Finally we just have to define the main function for parallel merging

```

⟨ merge obj parallel 81 ⟩ ≡
function mergeObjParallel(modelDirectory)
    """
    Merge stl files in a single obj file using a parallel
    approach. Files will be recursively merged two by two
    generating a tree where number of processes for every
    step is maximized
    Actually use of this function is discouraged. In fact
    speedup is influenced by disk speed. It could work on
    particular systems with parallel accesses on disks

    modelDirectory: directory containing models
    """

    files = readdir(modelDirectory)

    # Appending directory path to every file
    files = map((s) -> string(modelDirectory, "/", s), files)

    # While we have more than one vtx file and one faces file
    while(length(files) != 2)
        vertices_files = files[find(s -> contains(s,string("_vtx.stl")), files)]
        faces_files = files[find(s -> contains(s,string("_faces.stl")), files)]

        # Merging files
        mergeObjHelper(vertices_files, faces_files)
    end
end

```

```

    files = readdir(modelDirectory)
    files = map((s) -> string(modelDirectory, "/", s), files)
end

mergeVerticesFiles(files[2], files[1], 0)
mv(files[2], string(modelDirectory, "/model.obj"))
rm(files[1])

end ◇

```

Fragment referenced in 85c.

10.3 Load models from files

Another important functionality for our library, consists in model loading from our faces and vertices files. This is useful when passing from a pipeline step to another one. For simplicity, we offer a unique function that loads an array of vertices files (with the corresponding array of faces files), merge the values into a unique model and returns it.

⟨ Load models from file 82 ⟩ ≡

```

function getModelsFromFiles(arrayV, arrayFV)
    ""
    Get a LAR models for two arrays of vertices
    and faces files

    arrayV: Array containing all vertices files
    arrayFV: Array containing all faces files
    ""

    V = Array(Array{Float64}, 0)
    FV = Array(Array{Int}, 0)
    offset = 0

    for i in 1:length(arrayV)
        if isfile(arrayFV[i])
            f_FV = open(arrayFV[i])

            for ln in eachline(f_FV)
                splitted = split(ln)
                push!(FV, [parse(splitted[2]) + offset, parse(splitted[3]) +
                    offset, parse(splitted[4]) + offset])
            end
            close(f_FV)
        end
    end
end

```

```

        f_V = open(arrayV[i])
        for ln in eachline(f_V)
            splitted = split(ln)
            push!(V, [parse(splitted[2]), parse(splitted[3]),
                    parse(splitted[4])])
            offset += 1
        end
        close(f_V)
    end
end
return V, FV
end ◇

```

Fragment referenced in 85c.

11 Exporting the library

ImagesToLARModel

```

"src/ImagesToLARModel.jl" 83a≡
    module ImagesToLARModel

        < update load path 6 >

        < modules import ImagesToLARModel 7 >
        < load JSON configuration 8 >
        < Start conversion from JSON file 10a >
        < Start manual conversion 10b >
    end
    ◇

```

ImagesConversion

```

"src/ImagesConversion.jl" 83b≡
    module ImagesConversion

        < modules import ImagesConversion 23 >

        < main function for ImagesConversion 24 >
    end

```

```

    < parallel block iteration 26 >

    < start conversion of images 28 >

    < image conversion process 32 >

    < boundary merge process function 34 >

    < merge boundaries utility function 35 >

    < Block merge process function 36b >

    < Smooth block process function 38b >

    < execute smoothing function 40 >

end
◇

```

GenerateBorderMatrix

```

"src/GenerateBorderMatrix.jl" 84≡
    module GenerateBorderMatrix

        < Matrix object for JSON file 45a >

        < modules import GenerateBorderMatrix 43a >

        < compute border matrix 45b >

        < write Border matrix 44 >

        < get Border matrix 43b >

        < transform border matrix in csc format 46 >
    end
    ◇

```

Lar2Julia

```
"src/Lar2Julia.jl" 85a≡  
module Lar2Julia  
  
  ⟨ modules import Lar2Julia 47a ⟩  
  
  ⟨ get boundary chain 47b ⟩  
  
  ⟨ get oriented cells from a chain 48 ⟩  
  
  ⟨ transform relationships to csc 49 ⟩  
end  
◇
```

LARUtils

```
"src/LARUtils.jl" 85b≡  
module LARUtils  
  
  ⟨ modules import LARUtils 50 ⟩  
  
  ⟨ conversion from matrix to array 51a ⟩  
  
  ⟨ conversion from array to matrix 51b ⟩  
  
  ⟨ get LAR bases 55 ⟩  
  
  ⟨ removal of double vertices and faces 58b ⟩  
  
  ⟨ Removal of double vertices and faces from boundaries 67 ⟩  
  
  ⟨ LAR model creation 63b ⟩  
end  
◇
```

Model2Obj

```
"src/Model2Obj.jl" 85c≡
```

```

module Model2Obj

using Logging

export writeToObj, mergeObj, mergeObjParallel

< write obj files 73 >

< serial file merge 74 >

< assign tasks 77a >

< merge vertices file 77b >

< merge faces file 78 >

< parallel merge obj process function 79 >

< merge obj helper function 80 >

< merge obj parallel 81 >

< Load models from file 82 >
end
◇

```

PngStack2Array3dJulia

```

"src/PngStack2Array3dJulia.jl" 86≡
module PngStack2Array3dJulia

< modules import PngStack2Array3dJulia 11 >
< Convert to png 14b >
< Get image data 16 >
< Centroid computation 17 >
< Pixel transformation 20 >
end
◇

```

Smoother

```
"src/Smoother.jl" 87a≡  
    module Smoother  
        export smoothModel  
  
        ⟨ get adjacent vertices 68 ⟩  
  
        ⟨ laplacian smoothing 70 ⟩  
    end  
    ◇
```

11.1 Installing the library

12 Conclusions

12.1 Results

12.2 Further improvements

References

- [CL13] CVD-Lab, *Linear Algebraic Representation*, Tech. Report 13-00, Roma Tre University, October 2013.
- [PDFJ15] Alberto Paoluzzi, Antonio DiCarlo, Francesco Furiani, and Miroslav Jirik, *CAD models from medical images using LAR*, Computer-Aided Design and Applications **13** (2015), To appear.
- [W3C] W3C, *Portable Network Graphics (PNG) Specification (Second Edition)*, Tech. report.

A Utility functions

B Tests

Generation of the border matrix

```
"test/generateBorderMatrix.jl" 87b≡
```


[illegible]

```

end

function executeAllTests()
    @time testComputeOriented3Border()
    @time testWriteBorder()
    println("Tests completed.")
end

executeAllTests()

◇

```

Conversion of a png stack to a 3D array

```

"test/pngStack2Array3dJulia.jl" 89≡
push!(LOAD_PATH, "../..")
import PngStack2Array3dJulia
using Base.Test

function testGetImageData()
    """
    Test function for getImageData
    """

    width, height = PngStack2Array3dJulia.getImageData("images/0.png")

    @test width == 50
    @test height == 50

end

function testCalculateClusterCentroids()
    """
    Test function for calculateClusterCentroids
    """

    path = "images/"
    image = 0
    centroids = PngStack2Array3dJulia.calculateClusterCentroids(path, image, 2)

    expected = [0, 253]
    centroids = vec(reshape(centroids, 1, 2))

    @test sort(centroids) == expected

```

```

end

function testPngstack2array3d()
    """
    Test function for pngstack2array3d
    """
    path = "images/"
    minSlice = 0
    maxSlice = 4
    centroids = PngStack2Array3dJulia.calculateClusterCentroids(path, 0, 2)
    image3d = PngStack2Array3dJulia.pngstack2array3d(path, minSlice, maxSlice, centroids)

    @test size(image3d)[1] == 5
    @test size(image3d[1])[1] == 50
    @test size(image3d[1])[2] == 200

end

function executeAllTests()
    @time testCalculateClusterCentroids()
    @time testPngstack2array3d()
    @time testGetImageData()
    println("Tests completed.")
end

executeAllTests()

◇

```

Test for LAR utilities

```

"test/LARUtils.jl" 90≡
push!(LOAD_PATH, "../..")
import LARUtils
using Base.Test

function testInd()
    """
    Test function for ind
    """

    nx = 2
    ny = 2

```

```

    @test LARUtils.ind(0, 0, 0, nx, ny) == 0
    @test LARUtils.ind(1, 1, 1, nx, ny) == 13
    @test LARUtils.ind(2, 5, 4, nx, ny) == 53
    @test LARUtils.ind(1, 1, 1, nx, ny) == 13
    @test LARUtils.ind(2, 7, 1, nx, ny) == 32
    @test LARUtils.ind(1, 0, 3, nx, ny) == 28
end

function executeAllTests()
    @time testInd()
    println("Tests completed.")
end

executeAllTests()

◇

```