Network Catalogue

Network Centrality and PageRank Using Matrices in Python

Linear Algebra and Computer Programming I
Bachelor in Applied Mathematics, IE University
Fall 2026–2027

1 How the networks are assigned

Each group works on its own network, and no two groups can use the same one. Networks are assigned **first come, first served**: the first group to claim a network gets it, and once a network is taken it is no longer available to anyone else. Read this catalogue, agree on a first and second choice within your group, and claim a network as soon as you decide.

- **How to claim:** fill in the **Blackboard form** in your **Computer Programming I** course. Enter your group name, your members, and the folder name of the network (for example `wikispeedia`).
- The claim is final. Please do not swap networks once the claim is registered.
- The data are in the course GitHub repository: https://github.com/daniprec/BAM-CPI-LA-Networks. You only need the folder of your own network.

The project tasks, deliverables, assessment, and deadlines are in the project description. This document only describes the networks.

2 The data format

Every network has been prepared by the teaching team in **the same format**, so the code you write for your network is the same code you would write for any other. You do not need to download anything from the original source.

`nodes.csv`	`node_id,label,group,x,y`
`edges.csv`	`source,target`
`README.md`	`description, meaning of an arrow, preparation, source, limitations`

- `nodes.csv`: one row per node. `node_id` runs from 0 to $n-1$ in order, so it can be used directly as a matrix index. `label` is a human-readable name, `group` is a category when one exists, and `x`, `y` are coordinates only where the original data had them (otherwise blank).
- `edges.csv`: one row per arrow, from `source` to `target`, using `node_id` values.
- **Edges are binary.** There are no repeated rows, so each ordered pair appears at most once. Any weights, ratings or counts present in the original data were dropped, as explained under each network.

- **Self-loops.** A self-loop is a row with `source` equal to `target`. They were removed from all networks except `email_eu_core`, which keeps its 642 self-loops because they belong to the released data. State how you treated them in your report.
- **Blank metadata stay blank.** Missing groups or coordinates are not filled in.

Original sources and citations

The data were collected by other people. **Your report must cite the original source of your network** (listed below under each network and in the references) **and say that the teaching team prepared the data in the format above.** Follow the citation style requested in the project description. Citing only this catalogue is not enough.

All data are provided for this course only. Do not redistribute the files, and do not try to identify individual people from anonymised data.

3 Overview

Folder	Nodes	Edges	Domain
`email_eu_core`	1,005	25,571	Emails inside a research institution
`political_blogs`	1,490	19,022	Links between US political blogs
`florida_bay`	128	2,106	Carbon flow in a food web
`celegans_frontal`	131	764	Synapses between neurons
`collegemsg`	1,899	20,296	Private messages between students
`wikispeedia`	4,604	119,772	Links between Wikipedia articles
`bitcoin_alpha`	3,783	22,650	Trust ratings between traders
`atp_tennis`	1,191	19,986	Tennis match results
`football_transfers`	519	4,755	Football player transfers
`lichess_chess`	1,780	2,891	Online chess results
`foodcom_recipes`	1,500	13,893	Order in which users review recipes
`foodcom_cooks`	2,121	62,068	Users reviewing other users' recipes

A note on size. The two largest networks, `wikispeedia` and `bitcoin_alpha`, produce dense matrices with more than 10^7 entries. They need more memory and time for tasks such as computing all eigenvalues. Everything requested in the project is possible, but plan your computations and think about efficient ways of storing and multiplying the matrices. The other networks are comfortable with dense matrices.

4 The networks

4.1 Email-Eu-core

Folder	`email_eu_core`
Size	1,005 nodes, 25,571 directed edges
An arrow $i \to j$ means	member i sent at least one email to member j.

What it is. Email traffic between members of a large European research institution. Each node is an anonymous member and has a department label (42 departments). Only messages between members of the institution are included.

Original source. Stanford Network Analysis Project (SNAP), https://snap.stanford.edu/data/email-Eu-core.html. Cited as Yin et al. and Leskovec et al. in the references.

What we did to the data. The official file was used unchanged: all 1,005 nodes and 25,571 edges. The 642 self-loops (emails to oneself) are kept. The group is the department number.

Keep in mind. The graph says that a message was sent, not how many, when, or what they said. Do not attempt to identify any person.

4.2 Political blogs

Folder	`political_blogs`
Size	1,490 nodes, 19,022 directed edges
An arrow $i \to j$ means	blog i linked to blog j in a February 2005 crawl of the blogs' front pages.

What it is. US political weblogs around the 2004 presidential election. Each blog is labelled liberal or conservative.

Original source. Mark Newman's network data page, https://websites.umich.edu/~mejn/netdata/. Cited as Adamic and Glance in the references.

What we did to the data. The original file has 19,090 link rows. We collapsed 65 repeated links and removed 3 self-loops, which gives 19,022 binary edges. Blog addresses are kept as labels. The group is the political side.

Keep in mind. The source warns that the political labels were assigned partly from directories and partly by hand, so some may be wrong. A link is not necessarily an endorsement.

4.3 Florida Bay food web

Folder	`florida_bay`
Size	128 nodes, 2,106 directed edges
An arrow $i \to j$ means	carbon is transferred from compartment i to compartment j (often j eats i).

What it is. The carbon flows of the Florida Bay ecosystem. Nodes are compartments: species or groups of organisms, plus special nodes such as Input, Output and Respiration.

Original source. SNAP, https://snap.stanford.edu/data/Florida-bay.html, based on the ecological study cited as Ulanowicz et al. in the references; group metadata from Benson et al.

What we did to the data. The official binary edge set was kept as it is. There are no repeated rows or self-loops. Only 62 of the 128 compartments have a recorded ecological group; the others are left blank.

Keep in mind. A random walk along carbon flow is a model, not the movement of animals. A high score does not mean ecological importance in general.

4.4 *C. elegans* neural network

Folder	`celegans_frontal`
Size	131 nodes, 764 directed edges
An arrow $i \to j$ means	there is a synaptic connection from neuron i to neuron j.

What it is. The wiring of the frontal part of the nervous system of the roundworm *C. elegans*. Nodes are neurons, labelled by name, and two-dimensional coordinates are given so that the network can be drawn as it sits in the worm.

Original source. SNAP, https://snap.stanford.edu/data/C-elegans-frontal.html. Cited as Kaiser and Hilgetag in the references.

What we did to the data. All 131 neurons and 764 edges are kept, with no repeated rows or self-loops. Names and coordinates are copied from the original.

Keep in mind. The graph is anatomical connectivity, not recorded activity. A synapse by itself does not show that one neuron drives another in an experiment.

4.5 CollegeMsg: private messages

Folder	`collegemsg`
Size	1,899 nodes, 20,296 directed edges
An arrow $i \to j$ means	user i sent at least one private message to user j.

What it is. Private messages exchanged on an online social network at the University of California, Irvine, over about 193 days. A message does not imply a reply.

Original source. SNAP, https://snap.stanford.edu/data/CollegeMsg.html. Cited as Panzarasa et al. in the references.

What we did to the data. The original file lists 59,835 timestamped messages. We kept only the sender and the receiver, collapsed repeated messages between the same ordered pair, and removed messages to oneself. Timestamps and message counts are not in the files. Users are anonymous numbers.

Keep in mind. The graph records who wrote to whom, not what was said or whether the person answered. Do not attempt to identify any person.

4.6 Wikispeedia: Wikipedia articles

Folder	`wikispeedia`
Size	4,604 nodes, 119,772 directed edges
An arrow $i \to j$ means	article i contains a hyperlink to article j.

What it is. A small snapshot of Wikipedia: the 4,604 articles of the *Wikipedia Selection for Schools*, used in the Wikispeedia navigation game. Each article has a subject (Science, Geography, Art, History, and so on).

Original source. SNAP, https://snap.stanford.edu/data/wikispeedia.html. Cited as West and Leskovec and as West et al. in the references. Wikipedia text is available under CC BY-SA.

What we did to the data. We used the article list and the link list of the original download. Repeated links and self-links were removed. The label is the article title and the group is the subject of its first listed category. The game's navigation paths are not part of the data.

Keep in mind. This is a 2007 school subset, so only links between these articles exist.

4.7 Bitcoin Alpha: web of trust

Folder	`bitcoin_alpha`
Size	3,783 nodes, 22,650 directed edges
An arrow $i \to j$ means	user i gave user j a positive trust rating (from +1 to +10).

What it is. Traders on the Bitcoin Alpha platform rate each other from −10 (total distrust) to +10 (total trust) to reduce fraud. The original network is signed and weighted; this one keeps only the positive trust ratings.

Original source. SNAP, https://snap.stanford.edu/data/soc-sign-bitcoin-alpha.html. Cited as Kumar et al. in the references.

What we did to the data. Ratings of 0 or below do not create edges, and the rating values are dropped. If a user rated the same person more than once, the pair counts as one edge if any rating was positive. All 3,783 users stay as nodes even if they have no positive ratings.

Keep in mind. About 7% of the original ratings were negative, so the graph is a partial picture of the community. A high score means many positive ratings, not proven honesty.

4.8 ATP tennis: who lost to whom

Folder	`atp_tennis`
Size	1,191 nodes, 19,986 directed edges
An arrow $i \to j$ means	player i lost at least once to player j in a tour-level match.

What it is. Men's professional tennis, seasons 2016–2025. Every player is a node. A win is an arrow *from the loser to the winner*, so a random walker moves from a defeated player to the player who beat him.

Original source. Jeff Sackmann / Tennis Abstract, https://github.com/JeffSackmann/tennis_atp (CC BY-NC-SA 4.0: attribution, non-commercial). Cited as Sackmann in the references.

What we did to the data. We read one match file per season, turned each match into one arrow from loser to winner, and collapsed repeated pairs into one edge. The label is the player name and the group is the country code most often listed for the player.

Keep in mind. Only the pairs that met in these seasons are connected, and the number of meetings, the score and the surface are ignored. You can compare your results with the official rankings, but they measure different things.

4.9 Football transfers

Folder	`football_transfers`
Size	519 nodes, 4,755 directed edges
An arrow $i \to j$ means	at least one permanent player transfer went from club i (seller) to club j (buyer).

What it is. The football transfer market around the English Premier League. Nodes are the Premier League clubs of the data and the clubs they bought players from or sold players to. The group tells you whether a club is a league club or another club.

Original source. Transfermarkt data as collected in https://github.com/ewenme/transfers. Cited as Menezes in the references.

What we did to the data. Each transfer gives an arrow from the selling club to the buying club. Loans, youth-team promotions and transfers without a clear fee were left out. Club names were cleaned automatically and merged when they plainly referred to the same club; a few clubs may still be split or merged wrongly. Clubs outside the league with very few trading partners were removed.

Keep in mind. Transfers between two clubs that are both outside the league are missing, so the outer clubs exist in this graph only because of their trade with league clubs. The data were scraped and may have errors, especially for older seasons.

4.10 Lichess chess: who lost to whom

Folder	`lichess_chess`
Size	1,780 nodes, 2,891 directed edges
An arrow $i \to j$ means	player i lost at least one decisive game to player j.

What it is. Online games played on the Lichess chess server and collected in a public dataset of about 20,000 games. A decisive game is an arrow from the loser to the winner. Players are grouped by their average rating.

Original source. Chess Game Dataset (Lichess), https://github.com/arthur9916/Chess-Game-Dataset-Lichess-. Game data from Lichess, https://lichess.org. Cited as the dataset authors in the references.

What we did to the data. Draws were left out because they have no direction. Repeated results between the same pair give one edge. Players with only a few distinct opponents were removed repeatedly so that a core of players remains. The label is the Lichess username.

Keep in mind. This network is sparse, since most players face few opponents. It is not a random sample of Lichess players. It may behave very differently from the other networks.

4.11 Food.com: what people cook next

Folder	`foodcom_recipes`
Size	1,500 nodes, 13,893 directed edges
An arrow $i \to j$ means	some user reviewed recipe i and, on a later day, reviewed recipe j as their next review.

What it is. A recipe-to-recipe network built from the order in which users review recipes on the website Food.com. If a user reviewed a cake and later a lasagna, the cake points to the lasagna. A random walker behaves like a typical user moving from recipe to recipe. Nodes are the 1,500 most-reviewed recipes, grouped by dish type.

Original source. Food.com Recipes and Interactions, as used in Majumder et al., shared by the teaching team. Cited as Majumder et al. in the references.

What we did to the data. For each user we sorted their reviews by date and linked each recipe to the next different recipe reviewed on a later day. Reviews on the same day were not ordered, so they give no edge. Only recipes with names and enough reviews were kept. Review texts and ratings are not included.

Keep in mind. Reviews are written when users choose to post them, not necessarily when they cook. Only the most popular recipes are present.

4.12 Food.com: cooks reviewing cooks

Folder	`foodcom_cooks`
Size	2,121 nodes, 62,068 directed edges
An arrow $i \to j$ means	user i reviewed at least one recipe published by user j.

What it is. A reputation network on Food.com. Users publish recipes and review the recipes of others; an arrow goes from the reviewer to the author. To keep the network manageable, we kept its dense core: users that remain after repeatedly removing everyone with fewer than 10 connections. The group tells how many recipes the user has published.

Original source. Same data as the previous network, Food.com Recipes and Interactions (Majumder et al.).

What we did to the data. Reviews were joined to the recipes' authors, reviews of one's own recipes were removed, and repeated pairs collapsed to one edge. Users are anonymous numbers. Review texts, ratings and dates are not included.

Keep in mind. The core is only a small part of the site, so your conclusions apply to this group of users. Do not attempt to identify any person.

5 References

The references below follow the MLA style. Add the access date or version your group used if your style guide asks for it.

Adamic, Lada A., and Natalie Glance. "The Political Blogosphere and the 2004 U.S. Election: Divided They Blog." *Proceedings of the WWW-2005 Workshop on the Weblogging Ecosystem*, 2005.

Benson, Austin R., David F. Gleich, and Jure Leskovec. "Higher-Order Organization of Complex Networks." *Science*, vol. 353, no. 6295, 2016, pp. 163–166.

Chess Game Dataset (Lichess). GitHub repository, https://github.com/arthur9916/Chess-Game-Dataset-Lichess-. Game data from Lichess, https://lichess.org.

Kaiser, Marcus, and Claus C. Hilgetag. "Nonoptimal Component Placement, but Short Processing Paths, due to Long-Distance Projections in Neural Systems." *PLoS Computational Biology*, vol. 2, no. 7, 2006, e95.

Kumar, Srijan, et al. "Edge Weight Prediction in Weighted Signed Networks." *IEEE International Conference on Data Mining (ICDM)*, 2016, pp. 221–230.

Leskovec, Jure, Jon Kleinberg, and Christos Faloutsos. "Graph Evolution: Densification and Shrinking Diameters." *ACM Transactions on Knowledge Discovery from Data*, vol. 1, no. 1, 2007.

Leskovec, Jure, and Andrej Krevl. *SNAP Datasets: Stanford Large Network Dataset Collection*. 2014, https://snap.stanford.edu/data/.

Majumder, Bodhisattwa Prasad, et al. "Generating Personalized Recipe from Historical User Preference." *Proceedings of EMNLP*, 2019. Data: Food.com Recipes and Interactions.

Menezes, Ewen. *transfers*. GitHub repository, https://github.com/ewenme/transfers. Data from Transfermarkt.

Newman, Mark E. J. Network data. https://websites.umich.edu/~mejn/netdata/.

Panzarasa, Pietro, Tore Opsahl, and Kathleen M. Carley. "Patterns and Dynamics of Users' Behavior and Interaction: Network Analysis of an Online Community." *Journal of the American Society for Information Science and Technology*, vol. 60, no. 5, 2009, pp. 911–932.

Sackmann, Jeff. *Tennis ATP Match Data.* Tennis Abstract, https://github.com/JeffSackmann/tennis_atp. CC BY-NC-SA 4.0.

Ulanowicz, Robert E., Cristina Bondavalli, and Michael S. Egnotovich. "Network Analysis of Trophic Dynamics in South Florida Ecosystems: The Florida Bay Ecosystem." Annual Report to the U.S. Geological Survey, Biological Resources Division, 1997.

West, Robert, and Jure Leskovec. "Human Wayfinding in Information Networks." *Proceedings of the 21st International Conference on World Wide Web (WWW)*, 2012.

West, Robert, Joelle Pineau, and Doina Precup. "Wikispeedia: An Online Game for Inferring Semantic Distances between Concepts." *Proceedings of IJCAI*, 2009.

Yin, Hao, et al. "Local Higher-Order Graph Clustering." *Proceedings of the ACM SIGKDD Conference*, 2017.