

Sabre® Web Services

SOAP Field Size Overview

February 09, 2009

Field Size Quick Reference

All service providers, including TPFC, will support the fields shown in the following table:

For more information about the SOAP message formats, see *Sabre Web Services: Guide to Accessing and Using Services*. For service-specific SOAP envelope values, consult the documentation related to each Web service.

Field Size Reference Table

SOAP Field Name	Definition	Maximum Field Size
eb:ConversationId	Identifies the set of related messages that make up a connection and its associated session	255
eb:CPAId	Identifies the point of sale location participating in the connection	20
eb:MessageId	A globally unique identifier for each message	255
eb:RefToMessageId	RefToMessageId has a cardinality of zero or one, and when present, it MUST contain the MessageId value of an earlier ebXML message to which this message relates	255
eb:PartyId	Identifies the party that originated the message	255
eb:PartyId eb:type=	Attribute type in the element <eb:PartyId>	255
eb:Service	Identifies the <i>service</i> that acts on the message	128
eb:Service eb:type=	Attribute type in the element <eb:Service >	255
eb:Timestamp	Represents the time that the message header was created conforming to a date-time	30

eb:TimeToLive	<p>The time, expressed as UTC, by which a message should be delivered.</p> <p>This is not supported.</p> <p>It is mutually exclusive with eb:Timeout.</p>	25
eb:Timeout	<p>The time-out value, expressed in seconds (must be less than 60 seconds)</p> <p>Applies to TPFC Sabre Web Services.</p> <p>It is mutually exclusive with eb:TimeToLive.</p>	6
eb:Action	Identifies the <i>action</i> that acts on the <i>service</i>	48
wsse:Username	Specifies a username	20
wsse:Password	Specifies the password associated with the particular username	30
wsse:NewPassword	NewPassword is not currently supported, but upon implementation it will allow for passing a new password into the system	30
Organization	A Sabre extension that specifies the point of sale location associated with the particular username and password	20
Domain	A Sabre extension that specifies a domain location (Sabre partition) that is associated with the particular username, password, and organization	20
wsse:BinarySecurityToken	The security token that is used in conjunction with the eb:ConversationId to allow messages to be exchanged	200