

L^AT_EX 2_ε Cheat Sheet

www.github.com/danish-puri/LaTeX

Document classes

book Default is two-sided.
report No `\part` divisions.
article No `\part` or `\chapter` divisions.
letter Letter (?).
slides Large sans-serif font.

Used at the very beginning of a document:

`\documentclass{class}`. Use `\begin{document}` to start contents and `\end{document}` to end the document.

Common documentclass options

10pt/11pt/12pt Font size.
letterpaper/a4paper Paper size.
twocolumn Use two columns.
twoside Set margins for two-sided.
landscape Landscape orientation. Must use `dvips` -t landscape.
draft Double-space lines.
Usage: `\documentclass[opt,opt]{class}`.

Packages

fullpage Use 1 inch margins.
anysize Set margins: `\marginwidth{l}{r}{t}{b}`.
multicol Use n columns: `\begin{multicols}{n}`.
latexsym Use L^AT_EX symbol font.
graphicx Show image: `\includegraphics[width=x]{file}`.
url Insert URL: `\url{http://...}`.
Use before `\begin{document}`. Usage: `\usepackage{package}`

Title

`\author{text}` Author of document.
`\title{text}` Title of document.
`\date{text}` Date.

These commands go before `\begin{document}`. The declaration `\maketitle` goes at the top of the document.

Miscellaneous

`\pagestyle{empty}` Empty header, footer and no page numbers.
`\tableofcontents` Add a table of contents here.

Document structure

`\part{title}` `\subsubsection{title}`
`\chapter{title}` `\paragraph{title}`
`\section{title}` `\subparagraph{title}`
`\subsection{title}`

Use `\setcounter{secnumdepth}{x}` suppresses heading numbers of depth $> x$, where `chapter` has depth 0. Use a `*`, as in `\section*{title}`, to not number a particular item—these items will also not appear in the table of contents.

Text environments

`\begin{comment}` Comment (not printed). Requires `verbatim` package.
`\begin{quote}` Indented quotation block.
`\begin{quotation}` Like `quote` with indented paragraphs.

Lists

`\begin{enumerate}` Numbered list.
`\begin{itemize}` Bulleted list.
`\begin{description}` Description list.
`\item text` Add an item.
`\item[x] text` Use x instead of normal bullet or number. Required for descriptions.

References

`\label{marker}` Set a marker for cross-reference, often of the form `\label{sec:item}`.
`\ref{marker}` Give section/body number of marker.
`\pageref{marker}` Give page number of marker.
`\footnote{text}` Print footnote at bottom of page.

Floating bodies

`\begin{table}[place]` Add numbered table.
`\begin{figure}[place]` Add numbered figure.
`\begin{equation}[place]` Add numbered equation.
`\caption{text}` Caption for the body.
The *place* is a list valid placements for the body. t=top, h=here, b=bottom, p=separate page, !=place even if ugly.
Captions and label markers should be within the environment.

Text properties

Font face

Command	Declaration	Effect
<code>\textrm{text}</code>	<code>\rmfamily text</code>	Roman family
<code>\textsf{text}</code>	<code>\sffamily text</code>	Sans serif family
<code>\texttt{text}</code>	<code>\ttfamily text</code>	Typewriter family
<code>\textmd{text}</code>	<code>\mdseries text</code>	Medium series
<code>\textbf{text}</code>	<code>\bfseries text</code>	Bold series
<code>\textup{text}</code>	<code>\upshape text</code>	Upright shape
<code>\textit{text}</code>	<code>\itshape text</code>	<i>Italic shape</i>
<code>\textsl{text}</code>	<code>\slshape text</code>	<i>Slanted shape</i>
<code>\textsc{text}</code>	<code>\scshape text</code>	SMALL CAPS SHAPE
<code>\emph{text}</code>	<code>\em text</code>	<i>Emphasized</i>
<code>\textnormal{text}</code>	<code>\normalfont text</code>	Document font
<code>\underline{text}</code>		<u>Underline</u>

The command (tttt) form handles spacing better than the declaration (ttt) form.

Font size

<code>\tiny</code>	tiny	<code>\Large</code>	Large
<code>\scriptsize</code>	scriptsize	<code>\LARGE</code>	LARGE
<code>\footnotesize</code>	footnotesize	<code>\huge</code>	huge
<code>\small</code>	small	<code>\Huge</code>	Huge
<code>\normalsize</code>	normalsize		
<code>\large</code>	large		

These are declarations and should be used in the form `\small ...`, or without braces to affect the entire document.

Verbatim text

`\begin{verbatim}` Verbatim environment.
`\begin{verbatim*}` Spaces are shown as `␣`.
`\verb!text!` Text between the delimiting characters (in

Justification

Environment	Declaration
<code>\begin{center}</code>	<code>\centering</code>
<code>\begin{flushleft}</code>	<code>\raggedright</code>
<code>\begin{flushright}</code>	<code>\raggedleft</code>

Miscellaneous

`\linespread{x}` changes the line spacing by the multiplier x .

Text-mode symbols

Symbols

<code>&</code>	<code>\&</code>	<code>-</code>	<code>_</code>	<code>...</code>	<code>\ldots</code>	<code>•</code>	<code>\textbullet</code>
<code>\$</code>	<code>\\$</code>	<code>^</code>	<code>\^{}{}</code>	<code> </code>	<code>\textbar</code>	<code>\</code>	<code>\textbackslash</code>
<code>%</code>	<code>\%</code>	<code>~</code>	<code>\~{}{}</code>	<code>#</code>	<code>\#</code>	<code>§</code>	<code>\S</code>

Math mode

For inline math, use `\(...\)` or `$...$`. For displayed math, use `\[...]` or `\begin{equation}`.

Superscript x	<code>\^{}{x}</code>	Subscript x	<code>_{}{x}</code>
$\frac{x}{y}$	<code>\frac{x}{y}</code>	$\sum_{k=1}^n$	<code>\sum_{k=1}^n</code>
$\sqrt[n]{x}$	<code>\sqrt[n]{x}</code>	$\prod_{k=1}^n$	<code>\prod_{k=1}^n</code>

Sample L^AT_EX document

```
\documentclass[11pt]{article}
\usepackage{fullpage}
\title{Template}
\author{Name}
\begin{document}
\maketitle

\section{section}
\subsection*{subsection without number}
text \textbf{bold text} text. Some math:  $2+2=5$ 
\subsection{subsection}
text \emph{emphasized text} text. \cite{WC:1953}
discovered the structure of DNA.
```

A table:

```
\begin{table}[!th]
\begin{tabular}{|l|c|r|}
\hline
first & row & data \\
second & row & data \\
\hline
\end{tabular}
\caption{This is the caption}
\label{ex:table}
\end{table}
```

The table is numbered `\ref{ex:table}`.
`\end{document}`