M.S. Ramaiah Institute of Technology
(Autonomous Institute, Affiliated to VTU)
Department of Computer Science and Engineering

Subject Name: Data Communication & Networking

Subject Code: CS44

Credits: 4:0:0

Addressing

	MAC Address	IP Address	Port Numbers
Layer	Data Link	Network Layer	Transport Layer
Bits	EUI-48 bits EUI-64 bits	IPv4- 32bits IPv6- 128 bits	16 bits
Representation	Hexadecimal Ex:- E8-D8-D1-E9-49-5B	Dotted Decimal Notation 103.109.109.98	Decimal 52751
Uniqueness	Universally Unique	Universally Unique	Unique within host
Address Change from network to network	No	Yes	N/A
Allotment of Address	NIC Manufacturer (IEEE)	Internet Service Provider (IANA –Internet Assigned Numbers Authority)	Operating System
		Private IP and Public IP	Standard Port Numbers

RAMAIAH Institute of Technology

Chapter 3
Transport Layer



Computer Networking: A Top-Down Approach
8th edition
Jim Kurose, Keith Ross
Pearson, 2020

Transport layer: overview

- understand principles behind transport layer services:
  - multiplexing, demultiplexing
  - reliable data transfer
  - flow control
  - congestion control

- learn about Internet transport layer protocols:
  - UDP: connectionless transport
  - TCP: connection-oriented reliable transport
  - TCP congestion control

Transport layer: roadmap

- Transport-layer services
- Multiplexing and demultiplexing
- Connectionless transport: UDP
- Connection-oriented transport: TCP
- TCP congestion control

Transport services and protocols

- provide *logical communication* between application processes running on different hosts
- transport protocols actions in end systems:
  - sender: breaks application messages into *segments*, passes to network layer
  - receiver: reassembles segments into messages, passes to application layer
- two transport protocols available to Internet applications
  - TCP, UDP



Transport Layer Actions



Sender:

- passes an application-layer message
- determines segment header fields values
- creates segment
- passes segment to IP



Transport Layer Actions



Receiver:

- receives segment from IP
- checks header values
- extracts application-layer message
- demultiplexes message up to application via socket



Two principal Internet transport protocols

- **TCP:** Transmission Control Protocol
  - reliable, in-order delivery
  - congestion control
  - flow control
  - connection setup
- **UDP:** User Datagram Protocol
  - unreliable, unordered delivery
  - no-frills extension of "best-effort" IP
- services not available:
  - delay guarantees
  - bandwidth guarantees



Chapter 3: roadmap

Transport-layer services

Multiplexing and demultiplexing

Connectionless transport: UDP

Connection-oriented transport: TCP

TCP congestion control


HTTP server
client
application
NETFLIX
transport
network
link
physical
APACHE
HTTP SERVER
HTTP msg
transport
network
link
physical
application
transport
network
link
physical

HTTP server


client
application
NETFLIX
transport
network
link
physical
APACHE
HTTP SERVER
HTTP msg
H_t HTTP msg
network
link
physical
application
transport
network
link
physical


HTTP server
client
APACHE
HTTP SERVER
HTTP msg
application
NETFLIX
transport
network
link
physical
H_t HTTP msg
$H_n H_t$ HTTP msg
link
physical
application
transport
network
link
physical


HTTP server
client
application
NETFLIX
transport
network
link
physical
APACHE
HTTP SERVER
transport
network
link
physical
application
transport
network
link
physical
$H_n H_t$ HTTP msg


HTTP server
client$_1$
application
NETFLIX
transport
network
link
physical
P-client$_1$
P-client$_2$
transport
network
link
physical
client$_2$
application
transport
network
link
physical

Multiplexing/demultiplexing

multiplexing at sender:

handle data from multiple sockets, add transport header (later used for demultiplexing)

demultiplexing at receiver:

use header info to deliver received segments to correct socket



How demultiplexing works

- host receives IP datagrams
  - each datagram has source IP address, destination IP address
  - each datagram carries one transport-layer segment
  - each segment has source, destination port number
- host uses *IP addresses & port numbers* to direct segment to appropriate socket



TCP/UDP segment format

Connectionless demultiplexing

Recall:

- when creating socket, must specify *host-local* port #:

```
DatagramSocket mySocket1
  = new DatagramSocket(12534);
```

- when creating datagram to send into UDP socket, must specify
  - destination IP address
  - destination port #

when receiving host receives *UDP* segment:

- checks destination port # in segment
- directs UDP segment to socket with that port #

IP/UDP datagrams with *same dest. port #,* but different source IP addresses and/or source port numbers will be directed to *same socket* at receiving host

Connectionless demultiplexing: an example



Connection-oriented demultiplexing

- TCP socket identified by 4-tuple:
  - source IP address
  - source port number
  - dest IP address
  - dest port number
- demux: receiver uses *all four values* *(4-tuple)* to direct segment to appropriate socket
- server may support many simultaneous TCP sockets:
  - each socket identified by its own 4-tuple
  - each socket associated with a different connecting client

Connection-oriented demultiplexing: example



Three segments, all destined to IP address: B,
dest port: 80 are demultiplexed to *different* sockets

Summary

- Multiplexing, demultiplexing: based on segment, datagram header field values
- **UDP:** demultiplexing using destination port number (only)
- **TCP:** demultiplexing using 4-tuple: source and destination IP addresses, and port numbers
- Multiplexing/demultiplexing happen at *all* layers

Chapter 3: roadmap

- Transport-layer services
- Multiplexing and demultiplexing
- Connectionless transport: UDP
- Connection-oriented transport: TCP
- TCP congestion control

UDP: User Datagram Protocol

- “no frills,” “bare bones” Internet transport protocol
- “best effort” service, UDP segments may be:
  - lost
  - delivered out-of-order to app
- *connectionless:*
  - no handshaking between UDP sender, receiver
  - each UDP segment handled independently of others

Why is there a UDP?

- no connection establishment (which can add RTT delay)
- simple: no connection state at sender, receiver
- small header size
- no congestion control
  - UDP can blast away as fast as desired!
  - can function in the face of congestion

UDP: User Datagram Protocol

- UDP use:
  - streaming multimedia apps (loss tolerant, rate sensitive)
  - DNS
  - SNMP
- if reliable transfer needed over UDP:
  - add needed reliability at application layer
  - add congestion control at application layer

UDP: User Datagram Protocol [RFC 768]

INTERNET STANDARD

RFC 768 J. Postel
ISI
28 August 1980

User Datagram Protocol

Introduction

This User Datagram Protocol (UDP) is defined to make available a datagram mode of packet-switched computer communication in the environment of an interconnected set of computer networks. This protocol assumes that the Internet Protocol (IP) [1] is used as the underlying protocol.

This protocol provides a procedure for application programs to send messages to other programs with a minimum of protocol mechanism. The protocol is transaction oriented, and delivery and duplicate protection are not guaranteed. Applications requiring ordered reliable delivery of streams of data should use the Transmission Control Protocol (TCP) [2].

Format

```
 0      7 8     15 16    23 24    31
+--------+--------+--------+--------+
|     Source      |   Destination   |
|      Port       |      Port       |
+--------+--------+--------+--------+
|                 |                 |
|     Length      |    Checksum     |
+--------+--------+--------+--------+
|
|          data octets ...
+---------------- ...
```

UDP: Transport Layer Actions



UDP: Transport Layer Actions



UDP sender actions:

- passes an application-layer message
- determines UDP segment header fields values
- creates UDP segment
- passes segment to IP

UDP: Transport Layer Actions



UDP receiver actions:

- receives segment from IP
- checks UDP checksum header value
- extracts application-layer message
- demultiplexes message up to application via socket



UDP segment header



UDP segment format

UDP checksum

Goal: detect errors (*i.e.,* flipped bits) in transmitted segment

	1st number	2nd number	sum
Transmitted:	5	6	11
Received:	4	6	11

receiver-computed checksum ≠ sender-computed checksum (as received)

UDP checksum

Goal: detect errors (*i.e.*, flipped bits) in transmitted segment

sender:

- treat contents of UDP segment (including UDP header fields and IP addresses) as sequence of 16-bit integers
- checksum: addition (one's complement sum) of segment content
- checksum value put into UDP checksum field

receiver:

- compute checksum of received segment
- check if computed checksum equals checksum field value:
  - Not equal - error detected
  - Equal - no error detected. *But maybe errors nonetheless?* More later ….

Internet checksum: an example

example: add two 16-bit integers

	1 1 1 0 0 1 1 0 0 1 1 0 0 1 1 0
	1 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1
wraparound	1 1 0 1 1 1 0 1 1 1 0 1 1 1 0 1 1
sum	1 0 1 1 1 0 1 1 1 0 1 1 1 1 0 0
checksum	0 1 0 0 0 1 0 0 0 1 0 0 0 0 1 1

Note: when adding numbers, a carryout from the most significant bit needs to be added to the result

* Check out the online interactive exercises for more examples: http://gaia.cs.umass.edu/kurose_ross/interactive/

Checksum simple example:

Sender:

00
01
10
11 - sum
00 - check sum

Receiver:

00
01
10
00
11 - sum No Error

11
01
11
01
01
1 - wrap around
10 - sum
01 - checksum

1 10
01
11
01
01
1 0
1 -wrap around
1 1

RAMAIAH
Institute of Technology

Internet checksum: weak protection!

example: add two 16-bit integers

		1	1	1	0	0	1	1	0	0	1	1	0	0	1	1	0
		1	1	0	1	0	1	0	1	0	1	0	1	0	1	0	1
wraparound	1	1	0	1	1	1	0	1	1	1	0	1	1	1	0	1	1
sum		1	0	1	1	1	0	1	1	1	0	1	1	1	1	0	0
checksum		0	1	0	0	0	1	0	0	0	1	0	0	0	0	1	1

0 1
1 0

Even though numbers have changed (bit flips), *no* change in checksum!

Problems on Checksum

P3. UDP and TCP use 1s complement for their checksums. Suppose you have the following three 8-bit bytes: 01010011, 01100110, 01110100. What is the 1s complement of the sum of these 8-bit bytes? (Note that although UDP and TCP use 16-bit words in computing the checksum, for this problem you are being asked to consider 8-bit sums.) Show all work. Why is it that UDP takes the 1s complement of the sum; that is, why not just use the sum? With the 1s complement scheme, how does the receiver detect errors? Is it possible that a 1-bit error will go undetected? How about a 2-bit error?

Problems on Checksum (contd.)

P4. a. Suppose you have the following 2 bytes: 01011100 and 01100101. What is the 1s complement of the sum of these 2 bytes?

b. Suppose you have the following 2 bytes: 11011010 and 01100101. What is the 1s complement of the sum of these 2 bytes?

c. For the bytes in part (a), give an example where one bit is flipped in each of the 2 bytes and yet the 1s complement doesn't change.

Summary: UDP

- "no frills" protocol:
  - segments may be lost, delivered out of order
  - best effort service: "send and hope for the best"
- UDP has its plusses:
  - no setup/handshaking needed (no RTT incurred)
  - can function when network service is compromised
- build additional functionality on top of UDP in application layer (e.g., HTTP/3)

RAMAIAH
Institute of Technology

Chapter 3: roadmap

Transport-layer services

Multiplexing and demultiplexing

Connectionless transport: UDP

Connection-oriented transport: TCP

- segment structure
- Reliable Data Transfer
- flow control
- connection management

TCP congestion control

TCP: overview RFCs: 793,1122, 2018, 5681, 7323

- point-to-point:
  - one sender, one receiver
- reliable, in-order *byte steam:*
  - no “message boundaries"
- full duplex data:
  - bi-directional data flow in same connection
  - MSS: maximum segment size
- cumulative ACKs
- pipelining:
  - TCP congestion and flow control set window size
- connection-oriented:
  - handshaking (exchange of control messages) initializes sender, receiver state before data exchange
- flow controlled:
  - sender will not overwhelm receiver

Go-Back-N: sender

- sender: "window" of up to N, consecutive transmitted but unACKed pkts
  - k-bit seq # in pkt header



- *cumulative ACK:* ACK(*n*): ACKs all packets up to, including seq # *n*
  - on receiving ACK(*n*): move window forward to begin at *n+1*
- timer for oldest in-flight packet
- *timeout(n):* retransmit packet n and all higher seq # packets in window

Go-Back-N: receiver

- ACK-only: always send ACK for correctly-received packet so far, with highest *in-order* seq #
  - may generate duplicate ACKs
  - need only remember `rcv_base`
- on receipt of out-of-order packet:
  - can discard (don't buffer) or buffer: an implementation decision
  - re-ACK pkt with highest in-order seq #

Receiver view of sequence number space:





RAMAIAH
Institute of Technology

Go-Back-N in action



RAMAIAH Institute of Technology

Selective repeat

- receiver *individually* acknowledges all correctly received packets
  - buffers packets, as needed, for eventual in-order delivery to upper layer
- sender times-out/retransmits individually for unACKed packets
  - sender maintains timer for each unACKed pkt
- sender window
  - *N* consecutive seq #s
  - limits seq #s of sent, unACKed packets

Selective repeat: sender, receiver windows



RAMAIAH Institute of Technology

Selective repeat: sender and receiver

sender

data from above:

- if next available seq # in window, send packet

timeout(*n*):

- resend packet *n*, restart timer

ACK(*n*) in [sendbase,sendbase+N]:

- mark packet *n* as received
- if n smallest unACKed packet, advance window base to next unACKed seq #

receiver

packet *n* in [rcvbase, rcvbase+N-1]

- send ACK(*n*)
- out-of-order: buffer
- in-order: deliver (also deliver buffered, in-order packets), advance window to next not-yet-received packet

packet *n* in [rcvbase-N,rcvbase-1]

- ACK(*n*)

otherwise:

- ignore

Selective Repeat in action



Selective repeat: a dilemma!

example:

- seq #s: 0, 1, 2, 3 (base 4 counting)
- window size=3



Selective repeat: a dilemma!

example:

- seq #s: 0, 1, 2, 3 (base 4 counting)
- window size=3

sender window (after receipt)

receiver window (after receipt)



- *receiver can't see sender side*
- *receiver behavior identical in both cases!*
- *something's (very) wrong!*



Q: what relationship is needed between sequence # size and window size to avoid problem in scenario (b)?

TCP segment structure



TCP sequence numbers, ACKs

Sequence numbers:

- byte stream "number" of first byte in segment's data

Acknowledgements:

- seq # of next byte expected from other side
- cumulative ACK

Q: how receiver handles out-of-order segments

- *A:* TCP spec doesn't say, - up to implementor



TCP sequence numbers, ACKs



simple telnet scenario

TCP round trip time, timeout

Q: how to set TCP timeout value?

- longer than RTT, but RTT varies!
- *too short:* premature timeout, unnecessary retransmissions
- *too long:* slow reaction to segment loss

Q: how to estimate RTT?

- `SampleRTT`: measured time from segment transmission until ACK receipt
  - ignore retransmissions
- `SampleRTT` will vary, want estimated RTT "smoother"
  - average several *recent* measurements, not just current `SampleRTT`

TCP round trip time, timeout

EstimatedRTT = (1- α)*EstimatedRTT + α*SampleRTT

- exponential weighted moving average (EWMA)
- influence of past sample decreases exponentially fast
- typical value: α = 0.125



TCP round trip time, timeout

- timeout interval: **`EstimatedRTT`** plus “safety margin”
  - large variation in **`EstimatedRTT`**: want a larger safety margin

```
TimeoutInterval = EstimatedRTT + 4*DevRTT
```

estimated RTT   “safety margin”

- **`DevRTT`**: EWMA of **`SampleRTT`** deviation from **`EstimatedRTT`**:

$$\texttt{DevRTT} = (1-\beta)*\texttt{DevRTT} + \beta*|\texttt{SampleRTT-EstimatedRTT}|$$

(typically, β = 0.25)

* Check out the online interactive exercises for more examples: http://gaia.cs.umass.edu/kurose_ross/interactive/

Chapter 3: roadmap

Transport-layer services

Multiplexing and demultiplexing

Connectionless transport: UDP

Connection-oriented transport: TCP

- segment structure
- Reliable Data Transfer
- flow control
- connection management

TCP congestion control

TCP Sender (simplified)

event: data received from application

- create segment with seq #
- seq # is byte-stream number of first data byte in segment
- start timer if not already running
  - think of timer as for oldest unACKed segment
  - expiration interval: **`TimeOutInterval`**

event: timeout

- retransmit segment that caused timeout
- restart timer

event: ACK received

- if ACK acknowledges previously unACKed segments
  - update what is known to be ACKed
  - start timer if there are still unACKed segments

```
/* Assume sender is not constrained by TCP flow or congestion control, that data from above is less
than MSS in size, and that data transfer is in one direction only. */

NextSeqNum=InitialSeqNumber
SendBase=InitialSeqNumber

loop (forever) {
    switch(event)

        event: data received from application above
            create TCP segment with sequence number NextSeqNum
            if (timer currently not running)
                start timer
            pass segment to IP
            NextSeqNum=NextSeqNum+length(data)
            break;

        event: timer timeout
            retransmit not-yet-acknowledged segment with
                smallest sequence number
            start timer
            break;

        event: ACK received, with ACK field value of y
            if (y > SendBase) {
                SendBase=y
                if (there are currently any not-yet-acknowledged segments)
                    start timer
                }
            break;

    } /* end of loop forever */
```

Fig: TCP Simplified Sender

TCP: retransmission scenarios



lost ACK scenario



premature timeout

TCP: retransmission scenarios



cumulative ACK covers for earlier lost ACK

Doubling timeout interval : when the acknowledgment for sent data is not received on time, TCP sender doubles the timeout interval.

TCP Receiver: ACK generation [RFC 5681]

Event at receiver	*TCP receiver action*

TCP fast retransmit

TCP fast retransmit

if sender receives 3 additional ACKs for same data ("triple duplicate ACKs"), resend unACKed segment with smallest seq #

- likely that unACKed segment lost, so don't wait for timeout



Receipt of three duplicate ACKs indicates 3 segments received after a missing segment – lost segment is likely. So retransmit!

```
event: ACK received, with ACK field value of y
            if (y > SendBase) {
                SendBase=y
                if (there are currently any not yet
                            acknowledged segments)
                    start timer
                }
            else { /* a duplicate ACK for already ACKed
                segment */
                increment number of duplicate ACKs
                received for y
                if (number of duplicate ACKS received
                for y==3)
                /* TCP fast retransmit */
                resend segment with sequence number y
                }
            break;
```

Fig: TCP with Fast Retransmit

Chapter 3: roadmap

Transport-layer services

Multiplexing and demultiplexing

Connectionless transport: UDP

Principles of reliable data transfer

Connection-oriented transport: TCP

- segment structure
- Reliable Data Transfer
- flow control
- connection management

Principles of congestion control

TCP congestion control

TCP flow control

- TCP receiver "advertises" free buffer space in **`rwnd`** field in TCP header
  - **`RcvBuffer`** size set via socket options (typical default is 4096 bytes)
  - many operating systems autoadjust **`RcvBuffer`**
- sender limits amount of unACKed ("in-flight") data to received **`rwnd`**
- guarantees receive buffer will not overflow



TCP segment format

TCP Flow Control

receive side of TCP connection has a receive buffer:



- app process may be slow at reading from buffer

flow control

sender won't overflow receiver's buffer by transmitting too much, too fast

speed-matching service: matching the send rate to the receiving app's drain rate

TCP Flow control: how it works



At Sender side:

$$\texttt{LastByteSent} - \texttt{LastByteAcked} \leq \texttt{rwnd}$$

At Receiver side:

Because TCP is not permitted to overflow the allocated buffer, we must have

$$\texttt{LastByteRcvd} - \texttt{LastByteRead} \leq \texttt{RcvBuffer}$$

The receive window, denoted **rwnd** is set to the amount of spare room in the buffer:

$$\texttt{rwnd} = \texttt{RcvBuffer} - [\texttt{LastByteRcvd} - \texttt{LastByteRead}]$$

TCP connection management

before exchanging data, sender/receiver "handshake":

- agree to establish connection (each knowing the other willing to establish connection)
- agree on connection parameters (e.g., starting seq #s)






```
Socket clientSocket =
  newSocket("hostname","port number");
```

```
Socket connectionSocket =
  welcomeSocket.accept();
```

TCP 3-way handshake

Server state

```
serverSocket = socket(AF_INET,SOCK_STREAM)
serverSocket.bind(('',serverPort))
serverSocket.listen(1)
connectionSocket, addr = serverSocket.accept()
```

Client state

```
clientSocket = socket(AF_INET, SOCK_STREAM)
```



TCP Connection Management

Recall: TCP sender, receiver establish "connection" before exchanging data segments

initialize TCP variables:
- seq. #s
- buffers, flow control info (e.g. `RcvWindow`)

client: connection initiator

```
Socket clientSocket = new
Socket("hostname","port
number");
```

server: contacted by client

```
Socket connectionSocket =
welcomeSocket.accept();
```

Three way handshake:

Step 1: client host sends TCP SYN segment to server
- specifies initial seq #
- no data

Step 2: server host receives SYN, replies with SYNACK segment
- server allocates buffers
- specifies server initial seq. #

Step 3: client receives SYNACK, replies with ACK segment, which may contain data

TCP Connection Management (contd.)

Closing a connection:

client closes socket:
`clientSocket.close();`

Step 1: client end system sends TCP FIN control segment to server

Step 2: server receives FIN, replies with ACK. Closes connection, sends FIN.



TCP Connection Management (contd.)

Step 3: client receives FIN, replies with ACK.

- Enters "timed wait" - will respond with ACK to received FINs

Step 4: server, receives ACK. Connection closed.

Note: with small modification, can handle simultaneous FINs.



Closing a TCP connection



Closing a TCP connection

- client, server each close their side of connection
  - send TCP segment with FIN bit = 1
- respond to received FIN with ACK
  - on receiving FIN, ACK can be combined with own FIN
- simultaneous FIN exchanges can be handled

TCP Connection Management (contd.)



TCP client lifecycle

TCP server lifecycle



Chapter 3: roadmap

Transport-layer services

Multiplexing and demultiplexing

Connectionless transport: UDP

Connection-oriented transport: TCP

Principles of congestion control

TCP congestion control

Principles of congestion control

Congestion:

- informally: "too many sources sending too much data too fast for *network* to handle"
- manifestations:
  - long delays (queueing in router buffers)
  - packet loss (buffer overflow at routers)
- different from flow control!

congestion control: too many senders, sending too fast

flow control: one sender too fast for one receiver

TCP congestion control: AIMD

- *approach:* senders can increase sending rate until packet loss (congestion) occurs, then decrease sending rate on loss event

Additive Increase

increase sending rate by 1 maximum segment size every RTT until loss detected

Multiplicative Decrease

cut sending rate in half at each loss event



AIMD sawtooth behavior: *probing* for bandwidth

TCP AIMD: more

Multiplicative decrease detail: sending rate is

- Cut in half on loss detected by triple duplicate ACK (TCP Reno)
- Cut to 1 MSS (maximum segment size) when loss detected by timeout (TCP Tahoe)

Why AIMD?

- AIMD – a distributed, asynchronous algorithm – has been shown to:
  - optimize congested flow rates network wide!
  - have desirable stability properties

TCP congestion control: details



TCP sending behavior:

- *roughly:* send `cwnd` bytes, wait RTT for ACKS, then send more bytes

$$\text{TCP rate} \approx \frac{\texttt{cwnd}}{\text{RTT}} \text{ bytes/sec}$$

- TCP sender limits transmission: `LastByteSent- LastByteAcked ≤ cwnd`
- `cwnd` is dynamically adjusted in response to observed network congestion (implementing TCP congestion control)

TCP slow start

- when connection begins, increase rate exponentially until first loss event:
  - initially **cwnd** = 1 MSS
  - double **cwnd** every RTT
  - done by incrementing **cwnd** for every ACK received
- *summary:* initial rate is slow, but ramps up exponentially fast



TCP: from slow start to congestion avoidance

Q: when should the exponential increase switch to linear?

A: when **cwnd** gets to 1/2 of its value before timeout.



Implementation:

- variable **ssthresh**
- on loss event, **ssthresh** is set to 1/2 of **cwnd** just before loss event



Congestion window (in segments)
16
14
12
10
8
6
4
2
0
ssthresh
TCP Reno
TCP Tahoe
ssthresh
0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15
Transmission round



Figure 3.58 ♦ TCP window size as a function of time

P40. Consider Figure 3.58. Assuming TCP Reno is the protocol experiencing the behavior shown above, answer the following questions. In all cases, you should provide a short discussion justifying your answer.

a. Identify the intervals of time when TCP slow start is operating.

b. Identify the intervals of time when TCP congestion avoidance is operating.

c. After the 16th transmission round, is segment loss detected by a triple duplicate ACK or by a timeout?

d. After the 22nd transmission round, is segment loss detected by a triple duplicate ACK or by a timeout?

e. What is the initial value of `ssthresh` at the first transmission round?
f. What is the value of `ssthresh` at the 18th transmission round?
g. What is the value of `ssthresh` at the 24th transmission round?
h. During what transmission round is the 70th segment sent?
i. Assuming a packet loss is detected after the 26th round by the receipt of a triple duplicate ACK, what will be the values of the congestion window size and of `ssthresh`?
j. Suppose TCP Tahoe is used (instead of TCP Reno), and assume that triple duplicate ACKs are received at the 16th round. What are the `ssthresh` and the congestion window size at the 19th round?
k. Again suppose TCP Tahoe is used, and there is a timeout event at 22nd round. How many packets have been sent out from 17th round till 22nd round, inclusive?

a) TCP slowstart is operating in the intervals [1,6] and [23,26]
b) TCP congestion avoidance is operating in the intervals [6,16] and [17,22]
c) After the 16th transmission round, packet loss is recognized by a triple duplicate ACK. If there was a timeout, the congestion window size would have dropped to 1.
d) After the 22nd transmission round, segment loss is detected due to timeout, and hence the congestion window size is set to 1.
e) The threshold is initially 32, since it is at this window size that slow start stops and congestion avoidance begins.
f) The threshold is set to half the value of the congestion window when packet loss is detected. When loss is detected during transmission round 16, the congestion windows size is 42. Hence the threshold is 21 during the 18th transmission round.
g) The threshold is set to half the value of the congestion window when packet loss is detected. When loss is detected during transmission round 22, the congestion windows size is 29. Hence the threshold is 14 (taking lower floor of 14.5) during the 24th transmission round.

h) During the 1st transmission round, packet 1 is sent; packet 2-3 are sent in the 2nd transmission round; packets 4-7 are sent in the 3rd transmission round; packets 8-15 are sent in the 4th transmission round; packets 16-31 are sent in the 5th transmission round; packets 32-63 are sent in the 6th transmission round; packets 64 – 96 are sent in the 7th transmission round. Thus packet 70 is sent in the 7th transmission round.

i) The threshold will be set to half the current value of the congestion window (8) when the loss occurred and congestion window will be set to the new threshold value + 3 MSS . Thus the new values of the threshold and window will be 4 and 7 respectively.

j) threshold is 21, and congestion window size is 1.

k) round 17, 1 packet; round 18, 2 packets; round 19, 4 packets; round 20, 8 packets; round 21, 16 packets; round 22, 21 packets. So, the total number is 52.

Summary: TCP congestion control



TCP fairness

Fairness goal: if *K* TCP sessions share same bottleneck link of bandwidth *R*, each should have average rate of *R/K*



Q: is TCP Fair?

Example: two competing TCP sessions:

- additive increase gives slope of 1, as throughput increases
- multiplicative decrease decreases throughput proportionally



***Is* TCP fair?**

A: Yes, under idealized assumptions:
- same RTT
- fixed number of sessions only in congestion avoidance

RAMAIAH Institute of Technology

Fairness: must all network apps be “fair”?

Fairness and UDP

- multimedia apps often do not use TCP
  - do not want rate throttled by congestion control
- instead use UDP:
  - send audio/video at constant rate, tolerate packet loss
- there is no “Internet police” policing use of congestion control

Fairness, parallel TCP connections

- application can open *multiple* parallel connections between two hosts
- web browsers do this , e.g., link of rate R with 9 existing connections:
  - new app asks for 1 TCP, gets rate R/10
  - new app asks for 11 TCPs, gets R/2

Chapter 3: summary

- principles behind transport layer services:
  - multiplexing, demultiplexing
  - reliable data transfer
  - flow control
  - congestion control
- instantiation, implementation in the Internet
  - UDP
  - TCP

Up next:

- leaving the network "edge" (application, transport layers)
- into the network "core"
- two network-layer chapters:
  - data plane
  - control plane

Thank you