



SQL Correlated Subqueries



MrinalVerma


Read

Discuss

Courses

Practice

Correlated subqueries are used for row-by-row processing. Each subquery is executed once for every row of the outer query.



A correlated subquery is evaluated once for each row processed by the parent statement. The parent statement can be a **SELECT**, **UPDATE**, or **DELETE** statement.

```
SELECT column1, column2, ....
FROM table1 outer
WHERE column1 operator
      (SELECT column1, column2
       FROM table2
       WHERE expr1 =
           outer.expr2);
```

A correlated subquery is one way of reading every row in a table and comparing values in each row against related data. It is used whenever a subquery must return a different result or set of results for each candidate row considered by the main query. In other words, you can use a correlated subquery to answer a multipart question whose answer depends on the value in each row processed by the parent statement.

Nested Subqueries Versus Correlated Subqueries :



With a normal nested subquery, the inner **SELECT** query runs first and executes once, returning values to be used by the main query. A correlated subquery, however, executes once for each candidate row considered by the outer query. In other words, the inner query is driven by the outer query.

NOTE: You can also use the **ANY** and **ALL** operator in a correlated subquery. **EXAMPLE of Correlated Subqueries :** Find all the employees who earn more than the average salary in their department.

AD

```
SELECT last_name, salary, department_id
FROM employees outer
WHERE salary >
      (SELECT AVG(salary)
       FROM employees
       WHERE department_id =
         outer.department_id group by department_id);
```

Other use of correlation is in **UPDATE** and **DELETE**

CORRELATED UPDATE :

```
UPDATE table1 alias1
SET column = (SELECT expression
              FROM table2 alias2
              WHERE alias1.column =
                  alias2.column);
```

Use a correlated subquery to update rows in one table based on rows from another table.

CORRELATED DELETE :

```
DELETE FROM table1 alias1
WHERE column1 operator
      (SELECT expression
```

```
FROM table2 alias2
WHERE alias1.column = alias2.column);
```

Use a correlated subquery to delete rows in one table based on the rows from another table.

Using the EXISTS Operator :

The EXISTS operator tests for existence of rows in the results set of the subquery. If a subquery row value is found the condition is flagged **TRUE** and the search does not continue in the inner query, and if it is not found then the condition is flagged **FALSE** and the search continues in the inner query.

EXAMPLE of using EXIST operator :

Find employees who have at least one person reporting to them.

```
SELECT employee_id, last_name, job_id, department_id
FROM employees outer
WHERE EXISTS ( SELECT 'X'
FROM employees
WHERE manager_id =
outer.employee_id);
```

OUTPUT :

EMPLOYEE_ID	LAST_NAME	JOB_ID	DEPARTMENT_ID
100	King	AD_PRES	90
101	Kochhar	AD_VP	90
102	De Haan	AD_VP	90
103	Hunold	IT_PROG	60
108	Greenberg	FI_MGR	100
114	Raphaely	PU_MAN	30
120	Weiss	ST_MAN	50
121	Fripp	ST_MAN	50
122	Kaufling	ST_MAN	50
123	Vollman	ST_MAN	50
More than 10 rows available. Increase rows selector to view more rows.			

10 rows returned in 0.05 seconds

[CSV Export](#)

Trending Now DSA Data Structures Algorithms Interview Preparation Data Science Topic-wise Practice J.

```
SELECT department_id, department_name
FROM departments d
WHERE NOT EXISTS (SELECT 'X'
FROM employees
```

```
WHERE department_id  
= d.department_id);
```

OUTPUT :

DEPARTMENT_ID	DEPARTMENT_NAME
120	Treasury
130	Corporate Tax
140	Control And Credit
150	Shareholder Services
160	Benefits
170	Manufacturing
180	Construction
190	Contracting
200	Operations
210	IT Support
More than 10 rows available. Increase rows selector to view more rows.	

10 rows returned in 0.18 seconds

[CSV Export](#)

Last Updated : 11 Dec, 2022

39

Similar Reads

1. Difference between Nested Subquery, Correlated Subquery and Join Operation
2. Difference between Structured Query Language (SQL) and Transact-SQL (T-SQL)
3. Configure SQL Jobs in SQL Server using T-SQL
4. SQL | Procedures in PL/SQL
5. SQL | Difference between functions and stored procedures in PL/SQL
6. SQL SERVER – Input and Output Parameter For Dynamic SQL
7. Difference between SQL and T-SQL
8. SQL Server | Convert tables in T-SQL into XML
9. SQL SERVER | Bulk insert data from csv file using T-SQL command
10. SQL - SELECT from Multiple Tables with MS SQL Server

[Previous](#)[Next](#)