



SQL | LISTAGG

[Read](#)[Discuss](#)[Courses](#)[Practice](#)

LISTAGG function in DBMS is used to aggregate strings from data in columns in a database table.

- It makes it very easy to concatenate strings. It is similar to concatenation but uses grouping.
- The speciality about this function is that, it also allows to order the elements in the concatenated list.

Syntax:

```
LISTAGG (measure_expr [, 'delimiter']) WITHIN GROUP  
(order_by_clause) [OVER query_partition_clause]
```

measure_expr : The column or expression to concatenate the values.

delimiter : Character in between each measure_expr, which is by default a comma (,) .

order_by_clause : Order of the concatenated values.

Let us have a table named Gfg having two columns showing the subject names and subject number that each subject belongs to, as shown below :

```
SQL> select * from Gfg;
```

SUBNO	SUBNAME
D20	Algorithm
D30	DataStructure
D30	C
D20	C++
D30	Python
D30	DBMS
D10	LinkedList
D20	Matrix
D10	String
D30	Graph
D20	Tree

11 rows selected.

Query 1: Write an SQL query using LISTAGG function to output the subject names in a single field with the values comma delimited.

AD

```
SQL> SELECT LISTAGG(SubName, ' , ') WITHIN GROUP (ORDER BY SubName) AS SUBJECTS
2 FROM GfG ;
```

Output:

```
SUBJECTS
-----
--
Algorithm , C , C++ , DBMS , DataStructure , Graph , LinkedList , Matrix , Python
,
String , Tree
```

Query 2: Write an SQL query to group each subject and show each subject in its respective department separated by comma with the help of LISTAGG function.

```
SQL> SELECT SubNo, LISTAGG(SubName, ' , ') WITHIN GROUP (ORDER BY SubName) AS
SUBJECTS
2 FROM GfG
3 GROUP BY SubNo;
```

Output:

```
SUBNO      SUBJECTS
-----
-----
D10        LinkedList , String
D20        Algorithm , C++ , Matrix , Tree
D30        C , DBMS , DataStructure , Graph , Python
```

Query 3: Write an SQL query to show the subjects belonging to each department ordered by the subject number (SUBNO) with the help of LISTAGG function.

```
SQL> SELECT SubNo, LISTAGG(SubName, ',') WITHIN GROUP (ORDER BY SubName) AS
SUBJECTS
2 FROM GfG
3 GROUP BY SubNo
4 ORDER BY SubNo;
```

Output:

SUBNO	SUBJECTS
D10	LinkedList, String
D20	Algorithm, C++, Matrix, Tree
D30	C, DBMS, DataStructure, Graph, Python

This article is contributed by MAZHAR IMAM KHAN. If you like GeeksforGeeks and would like to contribute, you can also write an article using [contribute.geeksforgeeks.org](https://www.geeksforgeeks.org/contribute) or mail your article to contribute@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

Last Updated : 22 Jun, 2018

12

Similar Reads

1. Difference between Structured Query Language (SQL) and Transact-SQL (T-SQL)
2. Configure SQL Jobs in SQL Server using T-SQL
3. SQL | Procedures in PL/SQL
4. SQL | Difference between functions and stored procedures in PL/SQL
5. SQL SERVER – Input and Output Parameter For Dynamic SQL
6. Difference between SQL and T-SQL
7. SQL Server | Convert tables in T-SQL into XML
8. SQL SERVER | Bulk insert data from csv file using T-SQL command
9. SQL - SELECT from Multiple Tables with MS SQL Server