SQL | Join (Cartesian Join & Self Join)

SQL| JOIN(Inner, Left, Right and Full Joins)

In this article, we will discuss about the remaining two JOINS:

- **CARTESIAN JOIN**
- **SELF JOIN**

Consider the two tables below:

Student

ROLL_NO	NAME	ADDRESS	PHONE	Age
1	Ram	Delhi	xxxxxxxxxx	18
2	RAMESH	GURGAON	xxxxxxxxxx	18
3	SUJIT	ROHTAK	xxxxxxxxxx	20
4	SURESH	Delhi	xxxxxxxxxx	18

StudentCourse

COURSE_ID	ROLL_NO
1	1
2	2
2	3
3	4

1. **CARTESIAN JOIN**: The CARTESIAN JOIN is also known as CROSS JOIN. In a CARTESIAN JOIN there is a join for each row of one table to every row of another table. This usually happens when the matching column or WHERE condition is not specified.
   - In the absence of a WHERE condition the CARTESIAN JOIN will behave like a CARTESIAN PRODUCT . i.e., the number of rows in the result-set is the product of the number of rows of the two tables.
   - In the presence of WHERE condition this JOIN will function like a INNER JOIN.
   - Generally speaking, Cross join is similar to an inner join where the join-condition will always evaluate to True

   Syntax:

```
SELECT table1.column1 , table1.column2, table2.column1...
FROM table1
CROSS JOIN table2;
```

   table1: First table.
   table2: Second table

Example Queries(CARTESIAN JOIN):

- In the below query we will select NAME and Age from Student table and COURSE_ID from StudentCourse table. In the output you can see that each row of the table Student is joined with every row of the table StudentCourse. The total rows in the result-set = 4 * 4 = 16.

```
SELECT Student.NAME, Student.AGE, StudentCourse.COURSE_ID
FROM Student
CROSS JOIN StudentCourse;
```

  Output:

NAME	AGE	COURSE_ID
Ram	18	1
Ram	18	2
Ram	18	2
Ram	18	3
RAMESH	18	1
RAMESH	18	2
RAMESH	18	2
RAMESH	18	3
SUJIT	20	1
SUJIT	20	2
SUJIT	20	2
SUJIT	20	3
SURESH	18	1
SURESH	18	2
SURESH	18	2
SURESH	18	3

2. **SELF JOIN**: As the name signifies, in SELF JOIN a table is joined to itself. That is, each row of the table is joined with itself and all other rows depending on some conditions. In other words we can say that it is a join between two copies of the same table.**Syntax:**

```
SELECT a.coulmn1 , b.column2
FROM table_name a, table_name b
WHERE some_condition;
```

table_name: Name of the table.
some_condition: Condition for selecting the rows.

Example Queries(SELF JOIN):

```
SELECT a.ROLL_NO , b.NAME
FROM Student a, Student b
WHERE a.ROLL_NO < b.ROLL_NO;
```

Output:

ROLL_NO	NAME
1	RAMESH
1	SUJIT
2	SUJIT
1	SURESH
2	SURESH
3	SURESH

This article is contributed by **Harsh Agarwal**. If you like GeeksforGeeks and would like to contribute, you can also write an article using contribute.geeksforgeeks.org or mail your article to contribute@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

Last Updated : 09 Nov, 2020

69

Similar Reads

1. Self Join and Cross Join in MS SQL Server
2. SQL Query to Avoid Cartesian Product
3. SQL Full Outer Join Using Left and Right Outer Join and Union Clause
4. Difference between Inner Join and Outer Join in SQL
5. Difference between Natural join and Inner Join in SQL
6. Difference between Natural join and Cross join in SQL
7. Full join and Inner join in MS SQL Server
8. Left join and Right join in MS SQL Server
9. SQL | EQUI Join and NON EQUI JOIN
10. Implicit Join vs Explicit Join in SQL

Previous Next

Article Contributed By :