



Nested Queries in SQL

[Read](#)[Discuss](#)

Prerequisites : [Basics of SQL](#)

In nested queries, a query is written inside a query. The result of inner query is used in execution of outer query. We will use **STUDENT**, **COURSE**, **STUDENT_COURSE** tables for understanding nested queries.

AD

STUDENT

S_ID	S_NAME	S_ADDRESS	S_PHONE	S_AGE
S1	RAM	DELHI	9455123451	18
S2	RAMESH	GURGAON	9652431543	18
S3	SUJIT	ROHTAK	9156253131	20
S4	SURESH	DELHI	9156768971	18

COURSE

C_ID	C_NAME
C1	DSA
C2	Programming
C3	DBMS

STUDENT_COURSE

S_ID	C_ID
S1	C1
S1	C3
S2	C1
S3	C2
S4	C2
S4	C3

There are mainly two types of nested queries:

- **Independent Nested Queries:** In independent nested queries, query execution starts from innermost query to outermost queries. The execution of inner query is independent of outer query, but the result of inner query is used in execution of outer query. Various operators like IN, NOT IN, ANY, ALL etc are used in writing independent nested queries.

IN: If we want to find out **S_ID** who are enrolled in **C_NAME** 'DSA' or 'DBMS', we can write it with the help of independent nested query and IN operator. From **COURSE** table, we can find out **C_ID** for **C_NAME** 'DSA' or DBMS' and we can use these **C_IDs** for finding **S_IDs** from **STUDENT_COURSE** TABLE.

STEP 1: Finding C_ID for C_NAME ='DSA' or 'DBMS'

Select **C_ID** from **COURSE** where **C_NAME** = 'DSA' or **C_NAME** = 'DBMS'

STEP 2: Using **C_ID** of step 1 for finding **S_ID**

Select **S_ID** from **STUDENT_COURSE** where **C_ID** IN
(SELECT **C_ID** from **COURSE** where **C_NAME** = 'DSA' or **C_NAME**='DBMS');

The inner query will return a set with members C1 and C3 and outer query will return those **S_IDs** for which **C_ID** is equal to any member of set (C1 and C3 in this case). So, it will return S1, S2 and S4.

Note: If we want to find out names of **STUDENTs** who have either enrolled in 'DSA' or 'DBMS', it can be done as:

Select **S_NAME** from **STUDENT** where **S_ID** IN
(Select **S_ID** from **STUDENT_COURSE** where **C_ID** IN
(SELECT **C_ID** from **COURSE** where **C_NAME**='DSA' or **C_NAME**='DBMS'));

NOT IN: If we want to find out **S_IDs** of **STUDENTs** who have neither enrolled in 'DSA' nor in 'DBMS', it can be done as:

Select **S_ID** from **STUDENT** where **S_ID** NOT IN
(Select **S_ID** from **STUDENT_COURSE** where **C_ID** IN
(SELECT **C_ID** from **COURSE** where **C_NAME**='DSA' or **C_NAME**='DBMS'));

The innermost query will return a set with members C1 and C3. Second inner query will return those **S_IDs** for which **C_ID** is equal to any member of set (C1 and C3 in this case) which are S1, S2 and S4. The outermost query will return those **S_IDs** where **S_ID** is not a member of set (S1, S2 and S4). So it will return S3.

- **Co-related Nested Queries:** In co-related nested queries, the output of inner query depends on the row which is being currently executed in outer query. e.g.; If we want to find out **S_NAME** of **STUDENTs** who are enrolled in **C_ID** 'C1', it can be done with the help of co-related nested query as:

Select **S_NAME** from **STUDENT** S where EXISTS
(select * from **STUDENT_COURSE** SC where S.**S_ID**=SC.**S_ID** and SC.**C_ID**='C1');

For each row of **STUDENT** S, it will find the rows from **STUDENT_COURSE** where **S.S_ID = SC.S_ID** and **SC.C_ID='C1'**. If for a **S_ID** from **STUDENT** S, atleast a row exists in **STUDENT_COURSE** SC with **C_ID='C1'**, then inner query will return true and corresponding **S_ID** will be returned as output.

This article has been contributed by Sonal Tuteja.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above

Last Updated : 28 Jun, 2021

109

Similar Reads

1. Configure SQL Jobs in SQL Server using T-SQL
2. SQL vs NO SQL vs NEW SQL
3. Decision Making in PL/SQL (if-then , if-then-else, Nested if-then, if-then-elsif-then-else)
4. SQL queries on clustered and non-clustered Indexes
5. SQL queries on FILM Database
6. Production databases in SQL queries
7. SQL Concepts and Queries
8. How to Compare Two Queries in SQL
9. SQL | Difference between functions and stored procedures in PL/SQL
10. Difference between T-SQL and PL-SQL

[Previous](#)

[Next](#)

Article Contributed By :