



SQL | SOME

[Read](#)[Discuss](#)[Courses](#)[Practice](#)

[SQL | ALL and ANY](#)

SOME operator evaluates the condition between the outer and inner tables and evaluates to true if the final result returns **any one** row. If not, then it evaluates to false.

- The SOME and ANY comparison conditions are similar to each other and are completely interchangeable.
- SOME must match at least one row in the subquery and must be preceded by comparison operators.

Syntax:

```
SELECT column_name(s)
FROM table_name
WHERE expression comparison_operator SOME (subquery)
```

Instructor Table:

Name	Department	Salary
Chandra	Computational Biology	1
Visweswaran	Electronics	1.5
Abraham	Computer Science	1.3
John	Electronics	1.2
Samantha	Computer Science	2
Jyoti	Electronics	1.2
Debarka	Computer Science	2

Ganesh	Computational Biology	0.9
--------	-----------------------	-----

Sample Queries and Outputs:

AD

```
select name
from instructor
where Salary > some(select Salary
from instructor
where dept='Computer Science');
```

Output:

Visweswaran
Samantha
Debarka

Explanation

The instructors with salary > (salary of some instructor in the 'Computer Science' department) get returned. The salaries in the 'Computer Science' department are 1.3, 2 and 2. This implies any instructor with a salary greater than 1.3 can be included in the final result.

Exercise: Try to write same query using [ANY](#) clause.

This article is contributed by **Anannya Uberoi**. If you like GeeksforGeeks and would like to contribute, you can also write an article using [contribute.geeksforgeeks.org](https://www.geeksforgeeks.org/contribute) or mail your article to contribute@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

Last Updated : 21 Mar, 2018

16

Similar Reads