SALE!

GeeksforGeeks Courses Upto 25% Off Enroll Now!



Save 25% on Courses DSA Data Structures Algorithms Interview Preparation Data Science T

Catch block and type conversion in C++

Difficulty Level: Medium • Last Updated: 12 Nov, 2021

Read Discuss Courses Practice Video

Predict the output of following C++ program.

C++

```
#include <iostream>
using namespace std;

int main()
{
    try
    {
        throw 'x';
    }
    catch(int x)
    {
        cout << " Caught int " << x;
    }
    catch(...)
    {
        cout << "Default catch block";
    }
}</pre>
```

Output:

Default catch block

In the above program, a character 'x' is thrown and there is a catch block to catch an int. One might think that the int catch block could be matched by considering ASCII value of 'x'. But

such conversions are not performed for catch blocks. Consider the following program as another example where conversion constructor is not called for thrown object.

C++

```
#include <iostream>
using namespace std;
class MyExcept1 {};
class MyExcept2
public:
    // Conversion constructor
    MyExcept2 (const MyExcept1 &e )
        cout << "Conversion constructor called";</pre>
    }
};
int main()
{
    try
    {
        MyExcept1 myexp1;
        throw myexp1;
    }
    catch(MyExcept2 e2)
        cout << "Caught MyExcept2 " << endl;</pre>
    catch(...)
        cout << " Default catch block " << endl;</pre>
    return 0;
}
```

Output:

AD

Default catch block

As a side note, the derived type objects are converted to base type when a derived object is thrown and there is a catch block to catch base type. See <u>this GFact</u> for more details. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

23

Related Articles

- 1. Java Multiple Catch Block
- 2. Difference between Type Casting and Type Conversion
- 3. Conversion of Struct data type to Hex String and vice versa
- 4. Type Conversion in C++
- 5. Implicit Type Conversion in C with Examples
- 6. Type Conversion in C
- 7. Flow control in try catch finally in Java
- 8. Ask(), Wait() and Answer() Block in Scratch Programming
- 9. Where is an object stored if it is created inside a block in C++?
- 10. C++ Program for Block swap algorithm for array rotation

Previous

Article Contributed By:

