



SQL | Join (Inner, Left, Right and Full Joins)

Read

Discuss

Courses

Practice

Video

SQL Join statement is used to combine data or rows from two or more tables based on a common field between them. Different types of Joins are as follows:

- INNER JOIN
- LEFT JOIN
- RIGHT JOIN
- FULL JOIN
- NATURAL JOIN

Consider the two tables below as follows:

Student

ROLL_NO	NAME	ADDRESS	PHONE	Age
1	HARSH	DELHI	XXXXXXXXXX	18
2	PRATIK	BIHAR	XXXXXXXXXX	19
3	RIYANKA	SILIGURI	XXXXXXXXXX	20
4	DEEP	RAMNAGAR	XXXXXXXXXX	18
5	SAPTARHI	KOLKATA	XXXXXXXXXX	19
6	DHANRAJ	BARABAJAR	XXXXXXXXXX	20
7	ROHIT	BALURGHAT	XXXXXXXXXX	18
8	NIRAJ	ALIPUR	XXXXXXXXXX	19

AD

StudentCourse

COURSE_ID	ROLL_NO
1	1
2	2
2	3
3	4
1	5
4	9
5	10
4	11

The simplest Join is INNER JOIN.

A. INNER JOIN

The INNER JOIN keyword selects all rows from both the tables as long as the condition is satisfied. This keyword will create the result-set by combining all rows from both the tables where the condition satisfies i.e value of the common field will be the same.

Syntax:


```
SELECT table1.column1,table1.column2,table2.column1,....  
FROM table1  
INNER JOIN table2  
ON table1.matching_column = table2.matching_column;
```

table1: First table.

table2: Second table

matching_column: Column common to both the tables.

Note: We can also write JOIN instead of INNER JOIN. JOIN is same as INNER JOIN.



Example Queries(INNER JOIN)

This query will show the names and age of students enrolled in different courses.

```
SELECT StudentCourse.COURSE_ID, Student.NAME, Student.AGE FROM Student  
INNER JOIN StudentCourse  
ON Student.ROLL_NO = StudentCourse.ROLL_NO;
```

Output:

COURSE_ID	NAME	Age
1	HARSH	18
2	PRATIK	19
2	RIYANKA	20
3	DEEP	18
1	SAPTARHI	19

B. LEFT JOIN

This join returns all the rows of the table on the left side of the join and matches rows for the table on the right side of the join. For the rows for which there is no matching row on the right side, the result-set will contain *null*. LEFT JOIN is also known as LEFT OUTER JOIN.

Syntax:

```
SELECT table1.column1,table1.column2,table2.column1,....  
FROM table1
```


```
LEFT JOIN table2  
ON table1.matching_column = table2.matching_column;
```

table1: First table.

table2: Second table

matching_column: Column common to both the tables.

Note: We can also use *LEFT OUTER JOIN* instead of *LEFT JOIN*, both are the same.



Example Queries(LEFT JOIN):

```
SELECT Student.NAME, StudentCourse.COURSE_ID  
FROM Student  
LEFT JOIN StudentCourse  
ON StudentCourse.ROLL_NO = Student.ROLL_NO;
```

Output:

NAME	COURSE_ID
HARSH	1
PRATIK	2
RIYANKA	2
DEEP	3
SAPTARHI	1
DHANRAJ	NULL
ROHIT	NULL
NIRAJ	NULL

C. RIGHT JOIN

RIGHT JOIN is similar to LEFT JOIN. This join returns all the rows of the table on the right side of the join and matching rows for the table on the left side of the join. For the rows for which there is no matching row on the left side, the result-set will contain *null*. RIGHT JOIN is also known as RIGHT OUTER JOIN.

Syntax:


```
SELECT table1.column1,table1.column2,table2.column1,...  
FROM table1  
RIGHT JOIN table2  
ON table1.matching_column = table2.matching_column;
```

table1: First table.

table2: Second table

matching_column: Column common to both the tables.

Note: We can also use *RIGHT OUTER JOIN* instead of *RIGHT JOIN*, both are the same.



Example Queries(RIGHT JOIN):


```
SELECT Student.NAME, StudentCourse.COURSE_ID  
FROM Student  
RIGHT JOIN StudentCourse  
ON StudentCourse.ROLL_NO = Student.ROLL_NO;
```

Output:

NAME	COURSE_ID
HARSH	1
PRATIK	2
RIYANKA	2
DEEP	3
SAPTARHI	1
NULL	4
NULL	5
NULL	4

D. FULL JOIN

FULL JOIN creates the result-set by combining results of both LEFT JOIN and RIGHT JOIN. The result-set will contain all the rows from both tables. For the rows for which there is no matching, the result-set will contain *NULL* values.



Syntax:

```
SELECT table1.column1,table1.column2,table2.column1,....  
FROM table1  
FULL JOIN table2  
ON table1.matching_column = table2.matching_column;
```

table1: First table.

table2: Second table

matching_column: Column common to both the tables.

Example Queries(FULL JOIN):

```
SELECT Student.NAME,StudentCourse.COURSE_ID  
FROM Student  
FULL JOIN StudentCourse  
ON StudentCourse.ROLL_NO = Student.ROLL_NO;
```

Output:

NAME	COURSE_ID
HARSH	1
PRATIK	2

NAME	COURSE_ID
RIYANKA	2
DEEP	3
SAPTARHI	1
DHANRAJ	NULL
ROHIT	NULL
NIRAJ	NULL
NULL	4
NULL	5
NULL	4

[Left JOIN \(Video\)](#).

[Right JOIN \(Video\)](#).

[Full JOIN \(Video\)](#).

[SQL | JOIN \(Cartesian Join, Self Join\)](#).

E. Natural join (⋈)

Natural join can join tables based on the common columns in the tables being joined. A natural join returns all rows by matching values in common columns having same name and data type of columns and that column should be present in both tables.

Both table must have at list one common column with same column name and same data type.

The two table are joined using Cross join.

DBMS will look for a common column with same name and data type Tuples having exactly same values in common columns are kept in result.

Example:

Employee		
Emp_id	Emp_name	Dept_id
1	Ram	10
2	Jon	30
3	Bob	50

Department	
Dept_id	Dept_name
10	IT
30	HR
40	TIS

Query: Find all Employees and their respective departments.

Solution: (Employee) \bowtie (Department)

Emp_id	Emp_name	Dept_id	Dept_id	Dept_name
1	Ram	10	10	IT
2	Jon	30	30	HR
Employee data			Department data	

This article is contributed by [Harsh Agarwal](#). If you like GeeksforGeeks and would like to contribute, you can also write an article using write.geeksforgeeks.org or mail your article to review-team@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please write comments if you find anything incorrect, or if you want to share more information about the topic discussed above.

Last Updated : 24 Apr, 2023

324

Similar Reads