



Vu Buddy- CS201P

1. Which of the following is the correct way to initialize all the elements of array with 0?
 - a. `int arr[5]=All_Zero;`
 - b. `int arr[5]={5&0}`
 - c. `int arr[5]={0};`
 - d. `int arr[5]={5(0)};`
2. What will be the output of the following code? `int main(){ char str1[] = "Hello "; char str2[] = "World!"; cout << strcat(str1,str2); }`
 - a. HelloWorld!
 - b. World!
 - c. Hello World!
 - d. Hello
3. Which type of arrays are used while dealing with sentences?
 - a. Floating-point arrays
 - b. Word arrays
 - c. Integer arrays
 - d. Character arrays
4. What will be the output of the following code? `int main(){ char str[] = "Hello World"; cout<<str[4]; return 0; }`
 - a. l
 - b. o
 - c. H
 - d. W
5. In C++, `atoi ()` function is used to convert _____.
 - a. Character string to float
 - b. Character string to long integer
 - c. Character string to double
 - d. Character string to integer

6. What will be the output of the following code snippet? `void func(int arr[]) { arr[0] = 10; }`
`int main() { int arr[5] = {1, 2, 3, 4, 5}; func(arr); cout << arr[0]; return 0; }`
- a. 10
 - b. Undefined
 - c. 1
 - d. 2
7. What will be the output of the following code? `int main() { int x = 5; int * ptr = &x; *ptr + 1; cout << (*ptr)++; }`
- a. 8
 - b. 6
 - c. 5
 - d. 7
8. To create an output file stream, we must declare the stream to be of class.
- a. `cstream`
 - b. `ifstream`
 - c. `ofstream`
 - d. `iostream`
9. A variable declared inside a code block becomes the variable for that block.
- a. Local
 - b. Constant
 - c. Global
 - d. Static
10. In C++, a one-dimensional array inside a one-dimensional array is called _____.
- a. Three-dimensional array
 - b. Multi-casting array
 - c. Two-dimensional array
 - d. One-dimensional array

VU BUDDY - CS201P