Lecture # 9 Course Advance Web Development

Ms. Hafiza Alia (alia@theprotec.com)

JavaScript HTML DOM Elements

Finding HTML Elements

- ▶ There are a couple of ways to do this:
 - Finding HTML elements by id
 - ► Finding HTML elements by tag name
 - ► Finding HTML elements by class name
 - ► Finding HTML elements by CSS selectors

Finding HTML Element by Id

var myElement = document.getElementById("intro");

myElement.innerHTML="ABC";

Finding HTML Elements by Tag Name

- var x = document.getElementsByTagName("p");
- x.innerHTML="ABC";
- ► The following example first select id and then select all the paragarphs inside Id
 - ▶ Example
 - var x = document.getElementById("main"); var y = x.getElementsByTagName("p");

Finding HTML Elements by Tag Name

- var y=document.getElementById('main');
- var z= y.getElementsByTagName('p');
- console.log(z[0],z[1]);

Finding HTML Elements by CSS Selectors

► The following example returns a list of all elements with class="intro".

- var x = document.querySelectorAll("p.intro");
- x[0].innerHTML="";

Note: The querySelectorAll() method does not work in Internet Explorer 8 and earlier versions.

Form elements Collections

- Find no of elements a form have:
 - var x = document.getElementById("myForm").elements.length;
 - var x = document.getElementById("myForm").elements[0].value;
 - var x = document.getElementById("myForm").elements[0].name;

Finding HTML Elements by HTML Object Collections

var x = document.forms["frm1"];

Finding HTML Elements by HTML Object Collections

- <form id="form1">
- ▶ Name <input type="text" name="abc" value="My Name">
- Email <input type="email" name="email" value="My Email">
- Number <input type="text" name="number" value="My Number">
- </form>
- >

Finding HTML Elements by HTML Object Collections

```
Onclick=myfunc();
Function myfunc(){
var form= document.forms.form1;
document.getElementById('output').innerHTML=
```

form.elements[1].name +
 form.elements[1].value+
 form.length;}

JavaScript HTML DOM - Changing CSS

- Syntax
 - document.getElementById(id).style.property = new style

Example

```
Hello World!
<script>
document.getElementById("p2").style.color = "blue";
</script>
```

JavaScript HTML DOM - Changing CSS

<h1 id="id1">My Heading 1</h1>

```
<button type="button"
onclick="document.getElementById('id1').style.color =
'red"'>
Click Me!</button>
```

Changing HTML Attribute

- document.getElementById("p1").innerHTML = "New text!";
- document.getElementById("myImage").src = "landscape.jpg";
- document.getElementById("myImage").height=400";
- document.getElementById("myImage").width=300;

JavaScript End Of Lecture 9